



POWER	
Engine	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled
Displacement	617cc
Bore x Stroke	2.99x2.68 in
Compression Ratio	10:3:1
Maximum Torque	34.7 lb-ft @ 2500 rpm
Fuel System	DFI® with 34mm Mikuni throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	23 amp

CAPABILITY	
Front Suspension / Wheel Travel	MacPherson Strut/3.9 in
Rear Suspension / Wheel Travel	DeDion Axle/2.8 in
Front Tires	23x11.00-10
Rear Tires	23x11.00-10
Park Brake Type	Independent, Mechanical Drum
Steering	Electric Power Steering (EPS)
Front Brakes	Drum
Rear Brakes	Drum
Ground Clearance	6.9 in
Fuel Capacity	6.3 gal
Turning Radius	11.2 ft
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Cargo Bed Capacity	800 lb
Load Capacity	1327 lb
Seating Capacity	2
Towing Capacity	1200 lb
Lighting	(2) Halogen headlights (2) tail/brake lights

DETAILS	
Overall Length	116.7 in
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1433.3 lb**
Wheelbase	73.6 in
Instruments	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet, fuel gauge, hour meter
Wheel Type	Steel
Color Choices	Timberline Green, Dark Royal Red
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

\*\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).