



Bandit

INDUSTRIES, INC.

Jason Morey

6750 Millbrook Road

Remus, MI 49340

USA

989-561-2270 (Phone)

989-561-2273 (Fax)

www.banditchippers.com

QUOTATION

Quote #	Quote Created	Last Updated	Salesperson
113113	August 18, 2020 08:54 AM by Bandit Industries, Inc.	August 18, 2020 08:56 AM by Jason Morey	Jason Morey
CUSTOMER:		BILL TO:	SHIP TO:
Florida Sheriffs Association 2617 Mahan Drive Tallahassee , FL 32308 USA 800-877-2168 (Phone)		Florida Sheriffs Association 2617 Mahan Drive Tallahassee , FL 32308 USA 800-877-2168 (Phone)	Florida Sheriffs Association 2617 Mahan Drive Tallahassee , FL 32308 USA 800-877-2168 (Phone)

INTIMIDATOR 15XPC 15" DRUM STYLE BRUSH BANDIT

Qty	Part #	Description
1	MODEL-15XPC	Intimidator 15XPC - 15" Drum Style Brush Bandit

STANDARD EQUIPMENT

Qty	Part #	Description
1	STANDARD	24" diameter x 18 3/4" wide chipper drum with (4) 5/8" x 5 1/2" x 9" dual edge knives
1	STANDARD	"Drum Shear Bar" spans full width of the drum mounted in the upper portion of the drum housing potentially creating a slicing action of a winch line or climber's rope
1	STANDARD	Patented 'power slot' assists in maximizing chip velocity. The power slot also provides a place for fine material to escape that might tend to lie in the belly of the drum.
1	STANDARD	30 gallon steel fuel tank with magnetic drain plug, lockable filler cap, and aluminum sight gauge
1	STANDARD	12 gallon steel hydraulic tank with magnetic drain plug, lockable filler cap, and aluminum sight gauge
1	STANDARD	Slide box feed system (includes adjustable spring on each side) with (2) horizontal feed wheels 10 5/8" diameter x 18 3/4" wide, driven by (2) 32.3 CID hydraulic motors.
1	STANDARD	Hydraulic lift cylinder - utilizes a hydraulic cylinder to raise or provide down pressure for the top feed wheel (controlled via a handle located on either side of the infeed hopper)
1	STANDARD	Bottom feed wheel clean out door (opens via spring latch pin allowing dirt and debris to fall out extending knife and component life)
1	STANDARD	360 degree HAND crank swivel discharge (height adjustable) with 12" adjustable chip deflector
1	STANDARD	Clean out and inspection door on discharge
1	STANDARD	29" high x 54" wide tapered infeed hopper with 30" fold down infeed hopper tray, heavy-duty taillight covers, and spring lift assists
1	STANDARD	(2) Last chance safety pull cables
1	STANDARD	Control bar - located around top and sides of infeed hopper with 3 control positions (forward / neutral / reverse)
1	STANDARD	Wooden pusher tool with mount on infeed hopper
1	STANDARD	3/16" x 2" x 4" rectangular tubing with a 1/4" x 3" x 6" tubular tongue
1	STANDARD	Frame / Fender supports
1	STANDARD	Lockable aluminum toolbox
1	STANDARD	5/16" (G70) safety chains with spring loaded latch hooks
1	STANDARD	8,000 pound capacity tongue jack with 15" of travel and foot pad
1	STANDARD	12 volt system with rubber mounted LED taillights, 6 prong replaceable coiled power cord & protected heavy-duty wiring with junction box, and LED clearance lights with reflectors.
1	STANDARD	Banded chipper drive belts (adjustable via a sliding engine system)
1	STANDARD	Pressure check kit - Gauge is NOT included
1	STANDARD	Weather resistant manual container

1	STANDARD	Engine disable plug for hood locking pin-preventing engine from operating without pin in place
1	STANDARD	(1) weatherproof machine manual (includes safety, operation and parts sections) also (1) engine and clutch manual is included if applicable
1	STANDARD	Spanish & English combination safety decals

OPTIONS

1	333-32273	Standard Imron Industrial Urethane Bandit Yellow
1	990-RC1537-119	Caterpillar C3.4, 120 horsepower engine without clutch - Tier 4 FINAL (Includes 2 year / 2,000 hour engine warranty)
1	700-6000-02	Murphy PV380 panel with reversing auto feed for Cat 120 horsepower diesel engines (Includes 1,000 CCA battery with box) (Includes enclosure by Bandit) - Panel is mounted off of engine shroud in lockable composite cover
1	700-1000-12	NACD Spring Loaded Clutch
1	990-1017-54	Standard frame and drive system included in base price
1	OPTION-906-5000-06	Palm frond package for feed wheels (15XP and 15XPC) - Includes feed wheel bearing scraper for top and bottom feed wheel, and 30 bottom feed wheel teeth in lieu of 12
1	OPTION-915-5000-	Hydraulic flow control for feed wheel rate adjustment (All-In-One Mount)
1	LOGISTICS-HANDLING	The fee is applied per machine for logistic costs and may be waived if a kit of two sets of knives are purchased alternatively. Only valid at the time of order. No change orders apply.
1	OPTION-906-5000-03	Single 8,000 pound Torflex axle with electric brakes (0 degree down trail) (Will be 4 1/2" shorter than 45 degree down trail)
1	990-100406	(2) 215/75R 17.5" tires mounted on 8-bolt heavy-duty gray rims (8,000 pound axles on up)
1	990-100415	Aluminum bolt on fenders (Approximately 1/8" thick)
1	990-100274	2-1/2" Wallace Forge Pintle Hitch

DIRECT SALE TOTALS

Total Direct Sale Price:

\$ 59505.20