

## -- Standard Features --

## -- Custom Options --



S Series

SVL75-2

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

## FEATURES

Vertical Lift Path Loader Frame  
Standard Front Quick Coupler,  
Float Standard  
Hydraulic Quick Coupler Option  
Loader Boom Lock  
Open ROPS & Air Conditioned  
ROPS/FOPS Cab Models  
High Back, Adjustable, Vinyl,  
Suspension Seat  
2" Retractable Seat Belt and 2-  
Piece Seat Bar  
12V Electric Outlet  
17.4 gpm Auxiliary Hydraulics  
standard, 29.3 gpm Option  
Direct To Tank Return Line  
Rigid Mounted Undercarriage, 4  
Lower Track Rollers  
Rubber Tracks, 12.6" Standard,  
15" Optional  
Two Speed Travel System  
Automatic Wet Disk Parking  
Brake  
Kubota 4 Hydraulic Pump Load  
Sensing System  
2 Gear, 2 Variable  
Displacement Pumps  
Hydraulic Joystick Controls  
ISO Operating Pattern  
Hand And Foot Throttle  
Controls  
Electronic Travel Torque  
Management  
Automatic Glow Plugs  
Key Switch Stop/Start System  
Self Bleed Fuel System  
2 Front and 2 Rear Working  
Lights  
Hour Meter, Engine  
Temperature and Fuel  
Gauges and Warning Lights  
Horn and Backup Alarm  
Lockable Fuel Cap  
Bolt On Grab Handles to enter  
machine

## BASIC UNITS

SVL75-2, 12.6" Rubber Tracks,  
Open ROPS/FOPS Cab  
Mechanical Quick Coupler

## ENGINE

V3307 Kubota CR-TE4, Tier 4  
Diesel Engine  
4 Cylinder, 4 Cycle, Turbo Charged  
74.3 Gross HP @ 2400 rpm

## DIMENSIONS

Cab Height 82.0"  
Width (without attachment) 65.9"  
Width with wide track option  
(without attachment) 68.3"  
Length (without attachment) 109.0"  
Length of Track on Ground 56.5"

## OPERATIONAL

## DIMENSIONS

Operating Weight\*, SVL75H, 12.6"  
Rubber Tracks, Open  
ROPS/FOPS Cab, Mechanical  
Quick Coupler 9,039 lbs.  
Rated Operating Capacity (@ 35%  
of Tipping Load) 2,300 lbs.  
Rated Operating Capacity (ROC)  
@ 35% of Tipping Load complies  
with ISO 14397-1 and SAE J 818  
for crawler loaders  
Rated Operating Capacity (ROC)  
@ 50% of Tipping Load 3,285 lbs.  
Tipping Load 6,570 lbs.  
Auxiliary Hydraulics Flow 17.4  
gpm  
Travel Speed (Low / High) 4.7 / 7.1  
mph  
Reach @ Maximum Height 41.7"  
Height to Hinge Pin 119.1"  
Ground Pressure 5.6 psi.  
Traction Force 9,678 lbf.

\* Includes operator's weight, 175  
lbs.

SVL75-2 Base Price: \$57,060.00

(1) 68" HEAVY DUTY LOW PROFILE LONG \$1,480.00

FLOOR BUCKET (17.9 CU-FT) W/CUTTING EDGE

AP-HD68LLC-68" HEAVY DUTY LOW PROFILE LONG FLOOR

BUCKET (17.9 CU-FT) W/CUTTING EDGE

Suggested List Price w/ Options: \$58,540.00

**\*Taxes, shipping & handling, surcharges, assembly charges, destination, freight and/or delivery charges are not included.**

This MSRP configuration program is for informational purposes only. In all instances, the user of this program must consult with an authorized Kubota Dealer for complete purchase, warranty and safety information. Special pricing and promotions may be available on certain models. See your Kubota Dealer for details and individuals Dealer product pricing. All prices are shown in U.S. Dollars. Quotes are for products sold in the United States only.