

-- Standard Features --

-- Custom Options --



M Series

M5-091HF-1

2WD, HYDRAULIC SHUTTLE TRANSMISSION & ROPS

*** EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS ***

DIESEL ENGINE

Kubota V3800 Direct Injection
3.8L (230 cu. In.) 4 Cyl
EPA Tier 4 Final Compliant
Common Rail Electronic Fuel Injection
Electronic Engine Management
Turbocharged
w/Wastegate and Intercooled
Fuel Tank Capacity: 27.7 Gal
60 Amp Alternator ROPS
80 Amp Alternator Cab
12V 900 CCA Battery
SAE Gross HP: 92.5
Engine Net HP: 85.5
Max. PTO HP: 76
Cab @ 2600 Engine RPM
ROPS @ 2400 Engine RPM

EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)
SCR System
DEF Tank Capacity: 3.2 Gal

HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump
Max. Flow @ Rated Engine Speed: Power Steering:
Impl. Flow ROPS: 15.9 gpm
Impl. Flow Cab: 17.0 gpm
Total Flow: ROPS: 21.3 gpm

REMOTE VALVES

(1) SCD (Self Canceling Detent)
(1) FD (Float Detent)

3 POINT HITCH & DRAWBAR

Cat II 3-point Hitch
8 Speed Models
@ Lift Points: 7055 lbs
(ASAE) @ 24" Behind: 5181 lbs
12/24 Speed Models
@ Lift Points: 8600 lbs
(ASAE) @ 24" Behind: 7275 lbs
2 External Lift Cylinders
Telescoping Lower Links
Stabilizers
Swinging Drawbar - Straight

POWER TAKE OFF (540)

Live-Independent Hyd. PTO
SAE 1 3/8" Six Spline
540 rpm @ 2205 Eng. rpm
540 rpm @ 2035 Eng. rpm 12/24 speed
540E* @ 1519 Eng. rpm
*if equipped 12/24 Standard

LIGHTING

2 Headlights - Tail lights
4 Hazard Flasher Lights w/ Turn Signals
2 Grille Mounted Worklights
2 Front Cab Halogen Worklights
2 Rear Halogen Worklights

SELECTED TIRES

AMR8961A & AMR8531A
FRONT - 7.5-18 F2 Titan Tru Trac TT
REAR - R-TIRE 460/85R30 R1W Goodyear OpTrac

TRANSMISSION

8F/8R Two Range, 4-Speed
12F/12R Two Range, 6-Speed
540/540E
24F/24R Two Range, 6-Speed Hi/Lo
540/540E
24 speed on M5-111 only
Auto 4WD Function
Electro-Hydraulic Shuttle Shift
Clutch - Multi Plate Wet
Planetary Final Drives
Hydraulic Wet Disc Brakes

FRONT AXLE

Hydrostatic Power Steering
2WD: Tubular Steel Beam Telescoping
4WD: Cast Iron, Bevel Gear 55 deg
Planetary Final Drives
Adj. (Rim) Tread Spacing

FLUID CAPACITY

Cooling System: 11 qts
Crankcase: 11.3 qts
Hydraulics/Trans: 15.85 gal

INSTRUMENTS

LCD readout for MPH and PTO rpm
RPM Memory
Tachometer/Hour meter
Oil Pressure
Fuel Gauge
Coolant Temperature
Gear Speed Digital Light Indicator
Digital Light Indicator F/R Direction

ULTRA GRAND CAB II

4-post, ROPS Certified
RH & LH Doors
Tinted Glass Doors and Windows
In-roof window
Tilt Steering Wheel
Dual Level Air Conditioning & Heater
Front and Wiper/Washer
Front Sun Visor
Retractable Seat belt
LH & RH Side Mirrors
Radio Ready Cab
Steps, Left and Right Side
Interior Dome Light
12V - 30-Amp 2 Wire Coupler
12V - 3 Pin 30-Amp Coupler
12V - Outlet
Cup Holder
Instructor Seat Ready
Hom

SAFETY EQUIPMENT

Flip-Up PTO Shield
Electric Key Shut Off
Parking Brake
Turn Signals
SMV Sign
7-Pin Electrical Trailer Connector

M5-091HF-1 Base Price: \$45,193.00

Suggested List Price w/ Options: \$45,193.00

*Taxes, shipping & handling, surcharges, assembly charges, destination, freight and/or delivery charges are not included.

This MSRP configuration program is for informational purposes only. In all instances, the user of this program must consult with an authorized Kubota Dealer for complete purchase, warranty and safety information. Special pricing and promotions may be available on certain models. See your Kubota Dealer for details and individuals Dealer product pricing. All prices are shown in U.S. Dollars. Quotes are for products sold in the United States only.

