



EQUIPMENT PRICING & ORDER FORM

Phone: 704.966.3300

eFax: 704.919.5350

Sales@LeeBoy.com

Effective:

7 July 2020

Prices in US Dollars

FOB Lincolnton, NC

2020 Model Year Pricing

685D Motor Grader

DEALER: Dobbs Equipment

DATE: 18-Aug-20

P. O. NO: _____

FLOOR PLAN: YES / NO

WITH: _____

NEED BY DATE: _____

STOCK ORDER: YES / NO

CUSTOMER: _____

SHIP VIA: _____

Specification are required with orders linked to bids

CONTACT EMAIL: _____

SHIP TO ADDRESS: _____

SOLD ORDER - CUSTOMER CLASS:

CONTRACTOR

GOV / MUNI

NATIONAL ACCOUNT

SOURCEWELL

MODEL	STYLE	ENGINE	LIST PRICE	ORDER NUMBER	CK
685D	ROPS/FOPS Canopy	130 HP Turbo Cummins	\$ 185,925	685CMN	
685D	ROPS/FOPS Cab	130 HP Turbo Cummins	\$ 193,550	685CMNC	x
685D AWD	ROPS/FOPS Canopy	130 HP Turbo Cummins	\$ 195,950	685CMN6	
685D AWD	ROPS/FOPS Cab	130 HP Turbo Cummins	\$ 203,557	685CMNC6	
STANDARD FEATURES					

All 685D Motor Graders are equipped with: 11-ft x 21-in Sliding/Tilting Moldboard, Moldboard Float Control, Circle Turn Cushion Valve, Front headlights, Front and Rear Turn Signals & LED Working Lights, LED Amber Safety Strobe Light, Vandalism Package, Fail-Safe Park Brake, Dynamic Braking System, Pump De-stroke for Secondary Braking, Back-up Alarm, Tilt Steering Column, Bogie Rear Axle with Robust Gear Drive, Left/Right and Center Rear-View Mirror Package, High Temp/Low Oil Pressure Shutdown, Horn, Defrost Fan, Slow Moving Vehicle Sign, and Full color LCD Display including: Engine RPM, Engine temperature, Hydraulic Oil Temperature, Battery Voltage, Percent Engine Load, DEF Level, Fuel Level, Oil Pressure, Engine Hours, and Engine Diagnostics. Cab Models Add: Heater and Front Wiper.

OPTIONS			
DESCRIPTION	LIST PRICE	ORDER NUMBER	CK
Air Conditioning (Cab model only)	\$ 5,150	1018238	x
Front-mounted V-Bar Scarifier - Includes Float Control	\$ 3,975	1018880	
Rear-mounted Scarifier - Includes 9 ripper shanks w/teeth	\$ 4,125	1018098	x
8' Front Blade - includes blade float control	\$ 5,975	1018831	
Front Blade Mounted Flip-Down 4 Shank Scarifier - Requires 8' Front Blade Option	\$ 975	1018849	
Dead Engine Steering	\$ 2,300	1019630	
Cold Weather Engine Package	\$ 595	1016450	
Rear Wiper and Washer (Cab model only)	\$ 950	1020899	x
12-ft Moldboard	\$ 1,995	1018440	
Circle Side Shift	\$ 2,250	1018648	x
Radio/CD/Bluetooth w/Dual Speakers and Remote	\$ 995	1000705	
Back-up / Reverse camera w/in cab color display	\$ 1,795	1022240	
Topcon Ready **Consult Factory	-	-	
Extended Warranty Program (Contact Factory for Specifics or go to www.leeboy.com and view extended program under the warranty tab of the dealer login home page.)	Call for Pricing	0000	
Total List Price		\$	206,025.00

COMMENTS: _____

SIGNATURE: _____

PHONE: _____

685D Motor Grader

LeeBoy®



Designed with the functionality of a large motor grader, the more compact 685D can be used in many versatile and specialized applications including spreading base materials, ditch/shoulder projects, fine grading, medium cutting or even snow removal. The noticeable power provided by a Cummins engine merged with smooth transition and hydrostatic-controlled drive, makes this motor grader an all-around must have on any job site. Whether you decide a cab or canopy suits your needs, you can rest assured your visibility will remain unobstructed.

Performance Features:

- 130 hp (97 kw) Cummins Tier 4 Final Diesel Engine
- 11' (3.35 m) Moldboard
- Moldboard Shifts 3' (.91 m) left or right
- Hydrostatic Transmission, 2-Speed Tandem Axle
- Tandem Drive
- Electronic Gauge Package
- Fail Safe Braking
- ROPS/FOPS Cab or ROPS/FOPS Canopy
- Cushioned, Fully Adjustable Suspension Seat
- Vandalism Protection Package
- Front or Rear Mounted Scarifier Optional



685D Motor Grader Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 22' 3" (.8 m) - Width: 7' 8" (2.33 m) - Height (w/ cab and beacon): 10' 2" (2.9 m) - Wheel base: 16' 1" (4.9 m) - Base weight: 16,000 lbs. (7,257 kg)
Engine	Cummins turbocharged diesel, Tier 4 Final – 130 hp (97 kw)
Capacities	<ul style="list-style-type: none"> - Fuel: 45 gallons (170 l) - Hydraulic reservoir: 30 gallons (114 l)
Moldboard	<ul style="list-style-type: none"> - 11' x 21" x 5/8" (3.35 m x .533 m x 15.87 mm) - Side shift: 3' (.92 m) left or right - Tilt: 30° - Ground clearance: 13" (.33 m) - Penetration: 1' 2" (.36 m) - Rotation: 64°
Drawbar	- 4" x 6" tube (101 mm x 152 mm)
Articulated Frame	- Steel channel, rectangular tubing, articulated 24° in each direction
Turning Radius	- 22' (6.71 m) from center to outside front tire with frame articulated
Traction Drive	<ul style="list-style-type: none"> - Hydrostatic drive, 2-speed tandem axle - Working range: 0 to 10 mph (0 to 16 kph) - Travel range: 0 to 20 mph (0 to 32 kph) - Tandems oscillate a minimum of +/- 15°
Tires	<ul style="list-style-type: none"> - Six 15 x 19.5, TL, G-2 - 8-ply pneumatic tires
Brakes	<ul style="list-style-type: none"> - Foot operated primary and service brakes - Hydrostatic traction drive system includes secondary brakes - Spring apply, hydraulic release parking brakes automatically apply when ignition is in "off" position or if system pressure is lost

Operator's Station	<ul style="list-style-type: none"> - Fully cushioned, adjustable suspension seat - Choice ROPS/FOPS cab or ROPS/FOPS canopy - Cab includes heat, front wiper, front washer and defroster - Two external convex 7.5" (190 mm) diameter side mirrors, single rear view mirror - Display: coolant and hydraulic oil temperature, fuel level, volt meter, tachometer, hour meter, DEF level, percent engine load, engine diagnostics
Operator's Controls	<ul style="list-style-type: none"> - Industry-standard control levers mounted to an adjustable operator's pedestal - Left and right-hand moldboard lift, front attachment lift, moldboard side shift, circle side shift, moldboard tilt, circle turn, articulation, front wheel lean and rear-mount scarifier control
Rear Hitch	- 15-ton, heavy-duty, forged rear pintle hitch
Lighting	<ul style="list-style-type: none"> - Two rear working lights - Two front moldboard lights - Two front headlights, signals, flashers - Two rear tail lights, signals - Amber strobe beacon
Optional Equipment	<ul style="list-style-type: none"> - All-wheel drive - Air conditioning (cab only) - Front-mounted V-bar scarifier, includes blade float control - Rear-mounted scarifier, 9 ripper shanks w/ teeth - 8' (2.43 m) front blade, includes blade float control - Front blade mounted flip-down 4 shank scarifier - Dead engine steering - Cold weather engine package - Rear wiper and washer (cab only) - 12' (3.65 m) moldboard - Circle side shift - Radio/CD/Bluetooth speakers with remote - Back-up/reverse camera with color display - Topcon ready



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-20016-EN

