



Retail Offer

CUSTOMER INFORMATION:	DEALERSHIP
Florida Sheriffs Assoc. Purchasing Contr 2617 Mahan Drive Tallahassee, FLORIDA 32308 USA	GLADE & GROVE SUPPLY OF BELLE GLADE 1006 S MAIN ST BELLE GLADE, FL 33430 US 561-996-3095 SALESPERSON: Ken Holowecky - (561) 996-3095

Retail Offer Number:	0001086280-1	Retail Offer Valid to:	08/31/2020
----------------------	--------------	------------------------	------------

Description:	CASE IH FARMALL 100C 2WD/ROPS
--------------	----------------------------------

UNITS OFFERED			
Unit # 1 FARMALL 100C PS		List Price	66,850.00
Vehicle / Quote Number:	0701393563	Offered Price	0.00
Sales Order Number:		Physical Damage Ins. (Deductible	
VIN/Serial #:		\$/ months)	

Total	\$0.00
--------------	---------------

Down Payment	\$0.00
---------------------	---------------

Total Offer Value	\$0.00
--------------------------	---------------

FINANCING INFORMATION					
Financed By	N/A	Amount Financed	0.00	Term in Months	
Loan Type		Rate Type		Interest Rate	
Spec #412: Build Sheet- 2WD tractor with open station					

Vehicle Configuration					
Vehicle / Quote Number: 0701393563					
NORMAL	NORMAL OFFER		390411	REAR AXLE	
CIH	CASE IH		8125801	7.50-16 8 PLY HD	549.00
100HP	100 HP		8363801	18.4-30 12PR R1 FLAN	2,661.00
POWER S	POWER SHUT		334991	STD+30AH+ HORN	
ROPS	ROPS		743594	540/1000 RPM PTO	571.00
	Base price	64,196.00	334218	FAS SUPPORT + FHPL READY	
NAFTA	FCP PRICE		743593	LESS FRONT LOADER	
336841	ENG.T4B+HEAT+CRUISE		391035	LESS 3 PT HITCH GROUND CONTROL	
391192	120 AMP_ALTERNATOR		390831	HITCH W/MECH TOP LINK DRAFT CO	
743545	A PILLAR EXHAUST W/GUARD		762164	LESS MMV NEW	
390215	LESS FRONT CARRIER AND WEIGHTS		331156	VINYL SEAT	
743507	30 KPH		743599	REAR FENDERS (30-34)	
330276	12X12 POWER SHUTTLE		390860	LESS FRONT FENDERS	
759176	HAND BRAKE		392315	PLATFORM W/FOLDABLE ROPS	
336858	2WD STANDARD AXLE HEAVY DUTY	-1,127.00	334255	USA ENGLISH CONFIGURATION	
				Total List Price	\$66,850.00

FARMALL C 12 SPEED POWER SHUTTLE US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

MODELS:

Farmall 90C
86 Gross Engine hp
73 PTO hp @ 2300 rpm

*- MODEL
DOWN GRADE*

Farmall 100C
99 Gross Engine hp
85 PTO hp @ 2300 rpm

*BASE
MODEL*

Farmall 110C
107 Gross Engine hp
93 PTO hp @ 2300 rpm

*- MODEL
UPGRADE*

Farmall 120C
117 Gross Engine hp
100 PTO hp @ 2300 rpm

*- MODEL
UPGRADE*

ENGINE:

207 cu in (3.4 L) Displacement
4 Cyl Turbocharged Engine
Tier IVB Emissions Compliant:
(SCR + CEGR)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Dual Element Air Filter
Under Hood Muffler
Vertical Exhaust
30.3 gal Fuel Tank with Guard
2.8 gal DEF Tank

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Synchronized Shuttle
2WD and FWD - 19 mph (30 kph)
Speed varies with tire selection
Park Lock

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes-
Wet disk brakes
Hydraulically assisted

AXLES:

FRONT - 4WD
Limited Slip

For 90C, 100C, and 110C

Electrohydraulic FWD Engagement
Adjustable Tread Width from
56.6 in. to 76.6 in.

For 120C

Heavy Duty Electrohydraulic FWD
Engagement
Adjustable Tread Width from
56.6 in. to 76.6 in.

REAR

For 90C, 100C, and 110C

Flange Type
Adjustable Tread Width 55.5 in.
to 76.2 in.

For 120C

Heavy Duty Flange Type
Adjustable Tread Width 55.5 in.
to 76.2 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (63.9 L)
Steering Pump: 9.7 gpm (37.0 L)
Total Flow: 26.6 gpm (100.8 L)
(2) Open Center Remote Valves with
detent

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

**FARMALL C 12 SPEED POWER SHUTTLE
US PRICE LIST**

**(Ex Works Port of Entry)
Standard Equipment**

PTO:

Fully Independent
Flip-up PTO Shaft Guard
For 90C, 100C, and 110C
540 rpm Hydraulic
For 120C
540/1000 rpm Hydraulic
Electronic engagement
Wet clutch
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
5,620 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
3-pin Power Outlet (30 amp)
Single Pin (8 amp) Accessory Power
outlet
12V power socket
Cab tractors include an additional 12V
power socket

INSTRUMENTATION:

Analog Instrumentation with warning
lights for air cleaner service,
alternator, oil pressure, fuel
sediment/water sensor, PTO
engagement, head light high beam,
low fuel and parking brake,
digital speed readout (cab only)
Gauges for fuel level, engine
temperature, tachometer and hour
meter

LIGHTING:

ROPS
Front: (2) Halogen Headlights
Turn Signals/Flashers/Rear Lights
CAB
Front: (2) Halogen Headlights and
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform
with heat and air conditioning, tinted
windshield, retractable sun screen,
front wiper and washer, two doors
with locks, two external mirrors,
openable side windows, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered with air
suspension and 15 degrees of swivel,
operator's presence sensor,
retractable seat belt and arm rests
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

Case IH Standard Warranty Applies

**FARMALL C 12 SPEED POWER SHUTTLE
US PRICE LIST**

**(Ex Works Port of Entry)
Standard Equipment**

FACTORY INSTALLED LOADER

L620 Front Loader

STANDARD FEATURES:

Quick attach design:

Skid-Steer Style Tool Carrier

4-Bar bucket linkage

Bucket level indicator

Parking stand

Grille guard (included with front
mounting brackets)

SPECIFICATIONS:

See Chart for specifications

L630 Front Loader

STANDARD FEATURES:

Quick attach design:

Skid-Steer Style Tool Carrier

4-Bar bucket linkage

Bucket level indicator

Parking stand

Grille guard (included with front
mounting brackets)

SPECIFICATIONS:

See Chart for specifications