5100M Utility Tractor

Equipment for Base Machine

100 Engine Horsepower @ 2200 rpm* EPA Final Tier 4 Emissions Compliant Turbocharger with Intercooler 4.5L PowerTech Diesel Engine Turbocharger with Intercooler 4 Valve HPCR Dry Type Air Cleaner with Safety Element DEF Tank capacity (3.2 gal) Cold Start Aid - Air Intake Reater Hand and Foot Throttle Key Engine Shut Off Water Separator Bowl TRANSMISSION: EH Differential Lock Hydraulic Oil Cooler Wet Traction Clutch Park Lock Neutral Start Safety Switch Flanged Rear Axle Planetary Final Drives FRONT AXLE: Planetary Final Drives STEERING AND BRAKES: Hydrostatic Power Steering Hydraulic Wet Disk Brakes Self-Equalizing and Self-Adjusting HYDRAULIC: Open Center Hydraulic System Tandem Gear Pump 24.7 gpm (94 lpm) Maximum Total Flow -Steering Pump 6.3 gpm (24 lpm)
Implement Pump 18.4 gpm (70 lpm) POWER TAKE-OFF SHAFT: Independent "Live" 540 rpm Rear PTO Shaft @ 2100 Engine rpm Economy PTO Setting for 540 PTO rpm @ 1645 Engine Electrohydraulic PTO Engagement Wet PTO Clutch Operator Presence Safety Warning - PTO Safety Start Switch Flip Up PTO Shield

ROCKSHAFT, HITCH AND DRAWBAR: 65-mm Lift Cylinder Standard Adjustable Straight Drawbar Telescoping Draft Links with Category II Balls Lower Link Draft Sensing INSTRUMENTATION: Electric Fuel Gauge Flashing Warning Lamp High Beam Indicator Light Service Transmission Indicator PTO Speed Indicator/Roll Mode Neutral Indicator (PR Only) Tachometer/Hour Meter Engine Oil Pressure Hydraulic Temperature Indicator Coolant Temperature Gauge Diesel Exhaust Fluid Guage with low DEF Warning Signal Alternator Indicator Light Air Restriction Indicator Light Exhaust Filter Cleaning Switch Roll Mode for Instrument Cluster PTO Engagement Light (Rear PTO) ELECTRICAL: 12-Volt Electrical System One Battery - 925 CCA** with 180 Minute Reserve Capacity 7-Pin ASAE Outlet Socket LIGHTS: Two Front Halogen Headlights Two Turn/Warning Lights
Dual Tail Lights

* Manufacturer's Rating ** Cold Cranking Amps

Slow-moving Vehicle (SMV) Emblem

MISCELLANEOUS:

Toolbox

and the control of th	. Alt faction flags on a graph seeklithere detailes parantielle er en en externation and a college of	List Price
Attachment		Suggested
Code Identifier Description		Ref. USD (\$)

Select One Code From Each Required Category

BASE MACHINE

253CLV	5100M Utility Tractor	925K0816	65,996.00
	DESTINATION		
0240	DESTINATION American Samoa		No Added Cost
0245	Guam		No Added Cost

Attachr Code Identifi		Ref.	List Price Suggested USD (\$)
0203	DESTINATIONContinued Puerto Rico		No Added Cost
024H	US Minor Outlying Islands		No Added Cost
020A	US Virgin Islands		No Added Cost
0207	Saint Pierre and Miquelon		No Added Cost
0202	North America United States		In Base Price
0184	Canada		No Added Cost
0205	French Quebec		No Added Cost
	OPERATOR'S MANUAL		
0409	ENGLISH		In Base Price
0413	FRENCH		No Added Cost
0437	SPANISH		No Added Cost
	TRANSMISSION		
1362	12F/4R SyncShuttle Plus (30k) Requires Option Code 2010 (Standard OOS) or 2055 (Standard Cab). Requires Option Code 4010 (Mechanical rear hitch)	042K504	-3,252.00
1380	16F/16R PowrReverser		In Base Price
1390	32F/16R PowrReverser Hi-Lo (40k) Requires Option Code 6040 (MFWD). Requires Option Code 4030 (ElectroHydraulic (EH) rear hitch). Not compatible with Option Code 2010 (Standard OOS).	141K372	1,782.00
1394	32F/16R PowrReverser Hi-Lo (40k) with Creeper Requires Option Code 6040 (MFWD). Requires Option Code 4030 (ElectroHydraulic (EH) rear hitch). Not compatible with Option Code 2010 (Standard OOS).	973K511	4,561.00
	OPERATOR'S STATION		
2005	Premium Isolated Open Operator Station Includes all features of Standard Isolated Open Operator Station plus: Fender Extensions with Front Work Lights Requires Option Code 4030 (ElectroHydraulic (EH) rear hitch) 29 U.S. Gallon (111 L) Fuel Tank Capacity	494K13	537.00
2010	Standard Isolated Open Operator Station Isolated Open Operator Station with Flat Floor Standard Floor mat Tilt and Telescoping Steering Column 2-Post Isolated Foldable Roll-Over Protection Structure (ROPS) Plexiglass Debris/Air Deflector with Grab Handles Speedometer Deluxe Seat with Swivel, Armrests, and Retractable Seat Belt Beverage Holder		In Base Price

Attachme Code Identifier		Ref.	List Price Suggested USD (\$)
en en estado en esta	OPERATOR'S STATIONContinued Two Rear Work Lights Flashing Warning Lights Dual Taillights 29 U.S. Gallon (111 L) Fuel Tank Capacity Requires Option Code 4010 (Mechanical rear hitch)		
2055	Standard Cab Deluxe Isolated Cab with Flat Floor Tilt and Telescopic Steering Column Left and Right Side Doors with Steps Air Conditioning and Heater Speedometer Beverage Holder Sunvisor for Front Window 2-Speed Front Windshield Wiper and Washer Two Front/Two Rear Roof-Mounted Work Lights Two Front/Two Rear Roof-Mounted Warning Lights Two Front/Two Rear Roof-Mounted Warning Lights Two Fender-Mounted Taillights Convenience Power Outlet Monitor Mounting Bosses (2 Sets) Swing-Out Rear Window with Two Removable Rear Plugs for Monitor Right-Hand Console Light Radio Preparation (with speakers, wiring) Rear window grab handle Bluetooth Ready 36 U.S. Gallon (139 L) Fuel Tank Capacity 29 U.S. Gallon (111 L) Fuel Tank Capacity (High Crop Cab models) Requires Option Code 3025 (Deluxe Corner Post Exhaust).	059K521	12,365.00
2060	Premium Cab Includes Premium package, all features of Standard Cab plus: Load View Window (Sunroof) with Shade Front Sunshade Factory Installed Radio (Bluetooth and Satellite Capable) Rear Window Wiper Radio Antenna Additional Defrost Louvers Requires PowrReverser Transmission (1380, 1382, 1390 or 1394) Requires Option Code 3025 (Deluxe Corner Post Exhaust). Requires Option Code 4030 (ElectroHydraulic (EH) rear hitch) Requires Option code 6040 (MFWD)	941K0873	14,122.00
2065	Narrow Cab Includes all features and dimensions of Standard Cab with Narrow Fenders, plus High Capacity Fuel Tank 42 U.S. Gallon (161 L) Fuel Tank Capacity Requires Option Code 3025 or 3010 (Deluxe Corner Post Exhaust or Horizontal Side Exhaust)	511K0289	13,363.00
	MIRRORS		
2511	Mirror Telescopic LH & RH Available on Cab Tractors only	402K46	320.00
2500	Less Rear View Mirrors Available on Cab Tractors only		In Base Price
	SEAT		
2100	Mechanical Suspension seat		In Base Price

Attacl Code Identi	hment fier Description	Ref.	List Price Suggested USD (\$)
es Mille te te	SEATContinued	i function of the Country of the second the	***************************************
2120	Air Suspension seat	846K86	892.00
2121	Premium Air Suspension Seat Includes heater and low frequency air suspension. Available on Cab Tractors only.	171K094	1,421.00
	CAB INSTRUCTIONAL SEAT		
2400	Less Instructional Seat		In Base Price
2410	Instructional Seat with Seat-belt Available on Cab Tractors only.	994K51	587.00
	EXHAUST		
3010	Horizontal Side Exhaust	923K81	496.00
3020	Vertical Exhaust Available on Open Operator Station Tractors Only.		In Base Price
3025	Corner Post Deluxe Exhaust Available on Cab Tractors Only.	184K88	634.00
	SELECTIVE CONTROL VALVES		
3325	2 Mechanical Stackable Rear SCV		In Base Price
3326	3 Mechanical Stackable Rear SCV	877K16	931.00
	MID SELECTIVE CONTROL VALVES		
3400	Less Mid SCVs Reguires Code 4010 (Mechanical Rear Hitch Controls)	327K82	-1,016.00
3420	2 Stackable Mid SCVs with Mechanical Joystick control		In Base Price
3430	3 Stackable Mid SCVs with Mechanical Joystick Control	016K26	813.00
	REAR POWER TAKE-OFF (PTO)		
3820	Two Speed PTO - 540/540E		In Base Price
	HITCH CONTROLS		
4010	Mechanical Rear Hitch Control Not compatible with Code 2005 or 2065 (Premium Open Operator Station or Premium Cab)		In Base Price
4030	Electronic Hitch Control with Remote Control on LH Fender Not compatible with Code 2010 (Standard Open Operator Station)	233K84	499.00
	DRAFT LINK		
4110	Telescoping Draft Links with Ball End - Cat.2		In Base Price

	CENTER LINK		
4210	Mechanical Center Link with Ball Ends - Cat. 2		In Base Price
	STABILIZER		
4420	LH & RH Stabilizer Bar		In Base Price
	LIFT LINK		
4160	LH Only Adjustment Lift Link Right Hand side is Fixed.		In Base Price
	FRONT AXLE		
6020	2WD Front Axle Requires Code 1362 or 1380 (12F/4R SyncShuttle Plus or 16F/16R PowrReverser)	795K564	-7,227.00
6040	MFWD Front Axle		In Base Price
	REAR WHEELS AND TIRES		
5103	22.5LL-16.1 In. 6PR R3 (Turf Special) Bias MFWD Requires Code 6123. 2WD Requires Code 6103 or 6113.	621K159	-1,506.00
5121	16.9-30 6PR R1 Bias 2WD Requires Code 6112 or 6113 (Firestone) MFWD Requires Code 6111 (Goodyear)	991K683	-2,187.00
5133	460/85R30 (18.4R30) R1W Radial MFWD Requires Code 6203 (Firestone) 2WD Requires Code 6112 (Firestone)		In Base Price
5141	380/85R38 (15.5R38) 125A8 R1W Radial Reguires Code 6210 (Firestone)	909K77	-1,270.00
5151	230/95R48 134A8 R1W Radial Requires Code 6131 (Kleber) for High Clearance Applications.	791K74	227.00
5155	320/85R36 (12.4R36) R1W Radial Requires Code 6180	876K39	- 831.00
5180	420/85R30 (16.9R30) R1W Radial	766K7	-88-00
5191	460/85R34 (18.4R34) R1W Radial Requires Code 6120	701K61	210.00
5192	19.5L-24 In. 10PR R4 Bias Requires Code 6133 (Goodyear). 2WD Requires Code 6113 (Firestone).	391K699	-2,207.00
5202	420/85R34 (16.9R34) R1W Radial Requires Code 6210	182K6	34.00
5203	480/70R34 R1W Radial	957K19	935.00
5205	23.1-26 8PR R3 MFWD Requires Code 6214 (Titan). 2WD Requires Code 6103 or 6113 (Titan).	466K91	-898.00

Code Ident	ifier Description	Ref.	USD (\$)
	REAR WHEELS AND TIRESContinued		
	REAR TIRE BRAND PREFERENCE		
5999	No Rear Tire Brand Preference		In Base Price
	FRONT WHEELS AND TIRES		
	See Loader Section of the Sales Manual for Front Tire/Loader compatibility information.		
6103	27/12LL-15 In. 6PR R3 (Turf Special) Bias	451K528	-1,985.0
6111	11.2-24 6PR R1 Bias Goodyear Brand	009K24	-1,200.00
6112	11L - 15 in. 8PR F2 Bias Firestone Brand	111K881	-2,443.00
6113	11LL-15 In. 8PR F3 (Truck Type) Bias Firestone Brand	631K862	-2,419.00
6120	380/85R24 - 14.9R24 R1W Radial	536K07	789.00
6123	12LL-16.1 6PR R3 (Turf Special) Bias	461K384	- 1,798.00
6131	230/95R32 126A8 R1W Radial Kleber Brand. Recommended for High Clearance Applications	802K61	340.00
6133	12.5/80-18 In. 12PR R4 Bias Goodyear Brand	791K252	-1,627.00
6180	280/85R24 (11.2R24) R1W Radial	558K8	-115.00
6200	320/85R24 (12.4R24) R1W Radial		No Added Cos
6203	320/85R24 (12.4R24) R1W Radial Firestone Brand		In Base Price
6210	340/85R24 (13.6R24) 125A8 R1W Radial Firestone Brand	724K89	636.00
6211	380/70R24 R1W Radial	957K19	935.00
5214	44X18-20 4PR R3 Bias Titan Brand	725K66	-736.00
	FRONT TIRE BRAND PREFERENCE		
6799	No Front Tire Brand Preference		In Base Price
8280	CAB OPERATOR'S STATION Rear Window Wiper In Base Equipment for R4 Premium Cab. Option applies to Standard Cab Only.	232K30	299.00

Code	Attachment Identifier	Description	Ref.	List Price Suggested USD (\$)
		POWER TAKE-OFF (PTO) CONTROLS		
8386		PTO Remote Control and LH and RH Fenders	055K0	65.00
		HITCH CYLINDERS		
8458		70 mm Hitch lift cylinder	432K76	359.00
		FRONT FENDERS		
8010		Front Fenders - Rigid (Axle Mounted) Front fenders will restrict some front tires	374K47	581.00
8015		Front Fenders - Tumable (Axle Mounted) Front fenders will restrict some front tires	616K87	893.00
8020		Rear Fender Extensions (Cab) Not Compatible with Narrow Cab.	811K94	253.00
		LIGHTING EQUIPMENT		
8725		Beacon Light LH Side mounted - (RH side traffic)	861K67	218.00
		FRONT LOADER PREPARATION PACKAGES		
8910		Loader Preparation Package Compatible with 540M (Previously H260) or H310 Loader. Includes loader mounting frames and hood guard	551K397	1,815.00
		MISCELLANEOUS		
8300		Cold Weather package - Coolant heater Includes Coolant Heater	617K1	93.00
8955		Front Weight Support - (55 kg/121 lbs.)	611K48	193.00
8310		High Capacity Fuel Tank Inner Fuel Tank 29 L/7 gal. additional for Open Station and High Crop Models, 31 L/8 gal. additional for Cab.	551K65	215.00
		* All Narrow Cab and 5115M models have high capacity tank in base equipment		
		ATTACHMENTS FOR FIELD CONVERSION		
	RE574454	Accessories 38.1-mm (1.5-in.) ball mount and socket arm	333K6	54.22
	PF80459	Bracket, Arm, RAM Double Socket	092K0	29.99
	PF80460	Mount - RAM U-Bolt	684K0	60.72
	RE558821	Mounting Ball Stud	161K3	19.64
	AL212683	Mounting Parts - Display Mount RAM	978K4	126.82
	UC17356	RAM Mount Vesa Bracket 1.5	007K7	110.00