

BID SPECIFICATIONS

Mid-Mount ZTR Mower

Lazer Z S-Series Mower

LZS801GKA604A1

SPECIFICATIONS

Engine – Kawasaki® FX801V V-Twin, governed to 3,750 RPM

Carb Compliant – No

Air Filter – Heavy-duty canister air filtration system

Drive System – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12 cc pumps and 14.5 cubic inch motors.

Ground Speed – Infinitely variable speed selection from 0–10.0 mph (16 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

Hydro Fluid – Exmark Premium Hydraulic Oil

Cutting Deck – Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.

Cutting Height – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

Deck Lift Assist – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

Drive Tires – 24 x 12-12, 4 ply Turf Master®

Front Caster Tires – 13 x 6.5-6, smooth-tread, semi-pneumatic.

Steering and Motion Control – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

Curb Weight – 1187 lbs.

Dimensions:

Deck Size - 60"

Width.....72.8 in. (184.9 cm)

Length.....83.1 in. (211.1 cm)

Height..... 70.5 in. (179.1 cm)

Blades – 3 Blades at 20.50" Length

Blade-Tip Speed – Approximately 18,500 fpm.

Blade Spindles – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft and splined blade driver.

Tractor Frame – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

Turning Radius – True zero-turn

Drive-Wheel Release – Allows unit movement without engine running.

Parking Brake – Lever-actuated disc brake.

**Lazer Z S-Series Mower
LZS801GKA604A1**

Seat - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

Fuel Capacity – 12-gallon (45.4-L), single fuel tank with single fill location.

Electrical – 12-volt battery with 15-amp alternator.

PTO Engagement – MagStop electromagnetic 200-ft-lb clutch with spot brake

Standard Features – Engine hour meter and cup holder

Safety Package – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

Available Accessories and Attachments

3-Bushel Bagger	GC3602
12-Volt Adapter	109-9694
Air Ride Suspension Seat	116-8820
Anti-Scalp Kit	116-4614
Equipment Cover - Large	116-1379
Extended Drive Lever	116-1065
Floor Mat	116-6068
Harness Add-On Accessory Kit.....	109-9798
Hitch Kit.....	109-9487
Hydro Maintenance Kit.....	126-8103
Jack.....	127-6666
Jack Mount Receiver.....	127-6665
LED Light Kit (not compatible with TC26).....	135-7320
Micro-Mulch System.....	MK606
Operator Controlled Discharge (Foot)	116-8431
Power Deck Lift	116-2517
Seat Isolation System	116-0941
Sun Shade	126-8077
Tractus Tire	135-2286
Trash Container (Not compatible with 135-7320).....	TC26
Turf Striping Kit	116-6655
UltraVac Collection System, Triple-Bag	LZUV3B
UltraVac, Quick-Disposal, 11-Bushel	LZUVQD11
UltraVac Kit	116-2086