

Ring Power®



Ring Power Corporation
500 World Commerce Parkway
St. Augustine, FL 32092

Prepared For:
Florida Sheriff's Association

8/5/2020

Item #66: (1) NEW CATERPILLAR 316F HYDRAULIC EXCAVATOR

CONTRACT DETAILS

Florida Sheriff's Association
Bid # FSA20-EQU18.0
Item #66: Group: Hydraulic Excavator - 38,000 LB and Options
Contract Dates: October 1, 2020 through September 30, 2023

BID SPECIFICATION:

1. **WEIGHT:** a. Minimum operating weight - 38,000 lbs 2. **ENGINE:** a. Turbocharged diesel engine 113 hp b. Spin on filters c. Two stage air cleaner 3. **TRAVEL SYSTEM:** a. Travel speed of 3.2 mph 4. **HYDRAULIC SYSTEM:** a. Standard auxiliary hydraulic valve b. main hydraulic system flow 72 GPM minimum 5. **UNDERCARRIAGE:** a. Overall track length 12' 10" minimum b. Overall track width 8'5" minimum c. Shoe width 24" 6. **OPERATING STATION:** a. Cab to be air conditioned, heated and pressurized filtration system b. Intermittent windshield wipers c. Opening front windshield d. Vibration dampening cab mount e. Adjustable suspension type operator seat with safety belt f. Work lights

BASE MACHINE

| | |
|----------|----------------------------------|
| 538-9237 | 316F L HEX AM-N BCF1 |
| 427-9701 | 316F L HEX |
| 430-8467 | CONTROL, FINE SWING |
| 432-1340 | AIR CONDITIONER |
| 352-7158 | ACCUMULATOR WITH CRN |
| 488-6543 | SEAT BELT, 51MM (2") RETRACTABLE |
| 360-6166 | ALARM, TRAVEL |
| 372-9524 | CAB-ROPS, 70/30, W/VANDAL-G BOSS |
| 340-6667 | HATCH, OPENABLE ROOF (DUAL) |
| 496-8191 | RADIO, 24V AM/FM |
| 134-8875 | GUARD, SWIVEL |
| 291-7730 | LIGHT, BOOM RIGHT SIDE |
| 453-7538 | SEAT, H-BACK, W/HEATER, S/AIR |
| 319-1179 | LIGHTING, CAB (HALOGEN) |
| 333-3007 | TRAVEL MOTOR, BIO OIL CAPABLE |

| | |
|----------|--------------------------------|
| 342-3202 | BATTERY, COLD WEATHER |
| 342-3636 | WIPER-RADIAL, FRONT 70/30 |
| 346-7396 | WASHER, WINDSHIELD UPPER |
| 369-0145 | PANEL, STD START SWITCH |
| 385-3234 | LINKAGE, BKT W/O LIFT |
| 426-0308 | ENGINE HOOD, HIGH AMBIENT |
| 426-2491 | TANK, FUEL, STANDARD |
| 427-9710 | CAMERA, REAR VIEW, MIRRORS(RH) |
| 447-1667 | FAN, FIXED SPEED |
| 381-8971 | CYLINDER, BKT |
| 457-1770 | REACH BOOM HD PKG |
| 490-8975 | STICK, R 10' 2" HD |
| 430-8472 | AIR CLEANER, STANDARD |
| 340-8211 | TRACK, 28" TG W/ STEP (GLT) |
| 346-7203 | GUARD, TRACK GUIDING, CENTER |
| 510-3658 | JOYSTICK STANDARD STP PKG |
| 502-1373 | LINES, BKT CLOSE PGQC |
| 499-2012 | MACHINE SOFTWARE |
| 426-0304 | GUARD, BOTTOM HD |
| 427-9715 | DECALS, EXTERIOR ANSI |
| 504-9465 | DECALS, CAB ANSI |
| 460-1148 | PRODUCT LINK, CELLULAR PL641 |
| 349-2233 | CHANGER,HAND CTRL 2-WAY (ANSI) |
| 426-2534 | COUNTERWEIGHT, 6,170LBS |
| 0P-3380 | INSTRUCTIONS, ENGLISH |
| 504-1097 | CTRL,CAT PIN GRAB COUPLER ANSI |
| 397-8306 | LINES-QC, REACH 16' 9" BOOM |
| 262-3239 | LINES-QC, REACH 10' 2" STICK |
| 552-8152 | BKT GD 48", 1.19 YD3 315 |
| 380-1204 | SIDE CUTTER, GENERAL PURPOSE |
| 505-4083 | TIP, PENETRATION PLUS ADVANSYS |



Cat[®] 316F L

Hydraulic Excavator

2017

The Cat[®] 316F L is a perfect choice for customers who value versatility, reliability, durability, and maximum efficiency.

Performance

- The C4.4 ACERT™ U.S. EPA Tier 4 Final/EU Stage IV engine is powerful and efficient, and it can run on biodiesel up to B20.
- Advanced control automatically manages pump and engine speed for maximum efficiency.
- Two power modes, high power and eco mode, help you actively manage fuel consumption.
- Engine idle shutdown saves fuel, reduces emissions, and extends service intervals.

Versatility

- Site prep and finishing work are quick and easy with a wide range of Cat work tools.
- Utility work is fast and flawless with a Cat bucket and compactor.
- A coupler lets you swap between attachments in seconds without leaving the cab.
- See the whole more profitable attachment line for your machine at www.cat.com/attachments.

Comfort

- The roll-over protective structure (ROPS) certified cab is quiet and comfortable.
- Automatic climate control helps maintain consistent cab temperature.
- Joystick consoles and armrests are adjustable.
- Seats are adjustable and feature air suspension with an optional heater in Europe, Australia, New Zealand and Pacific Islands.
- The LCD monitor is easy to navigate and programmable in 42 languages.

Serviceability

- Many routine service and maintenance points can be accessed from ground level reducing the time taken to check and service your machine.
- Wide service doors make for easy access.
- Filters are grouped to reduce service time.
- The cooling package is designed to prevent plugging, make blowing off debris easy.

Technology

- Cat Connect technology improves job site efficiency.
- Optional Cat Grade Control helps you create a level base and precise slope with ease.
- Product Link™/VisionLink[®] connects owners to the machine, providing access to location, hours, fuel consumption, idle time, events, and diagnostic codes.

Durability

- The large swing bearing is secured with elongated bolts to help handle the most swing-intensive work.
- Robot welded, Caterpillar designed boom and sticks are built for long service.
- Greased track link between pins and bushings increases undercarriage life and reduces noise.

Safety

- The hydraulic activation lever locks out all hydraulic functions.
- Handrails, anti-skid plating, and countersunk bolts reduce slipping and tripping.
- A ground-level engine shutoff switch shuts down the engine in case of emergency.
- Standard rearview camera and mirrors enhance visibility.
- The side-view camera enhances visibility on the boom side of the machine to help make operators more effective and efficient.



Cat® 316F L Hydraulic Excavator

Engine

| | | |
|--|----------------|---------------|
| Engine Model | Cat C4.4 ACERT | |
| Net Power – SAE J1349/ISO 9249 | 88 kW | 117 hp/118 PS |
| Net Power – ISO 14396 | 91 kW | 122 hp/123 PS |
| Gross Power – SAE J1995 | 91 kW | 122 hp/123 PS |
| Bore | 105 mm | 4.13 in |
| Stroke | 127 mm | 5.00 in |
| Displacement | 4.4 L | 269 in³ |
| • The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO ₂ equivalent of 1.43 metric tonnes. | | |

Hydraulic System

| | | |
|------------------------------------|-----------|-------------|
| Main System – Maximum Flow (total) | 300 L/min | 79 gal |
| Maximum Pressure – Equipment | 35 MPa | 5,076 psi |
| Maximum Pressure – Travel | 35 MPa | 5,076 psi |
| Maximum Pressure – Swing | 25 MPa | 3,626 psi |
| Pilot System – Maximum Flow | 25 L/min | 6.6 gal/min |
| Pilot System – Maximum Pressure | 4120 kPa | 598 psi |

Drive

| | | |
|----------------------|----------|------------|
| Maximum Travel Speed | 5.3 km/h | 3.3 mph |
| Maximum Drawbar Pull | 156 kN | 35,070 lbf |

Machine Weights

| | | |
|--|-----------|-----------|
| Operating Weight* | 17 700 kg | 39,029 lb |
| *5.1 m (16'9") reach boom, 2.6 m (8'6") stick and 700 mm (28") track shoes, with 0.76 m³ (0.99 yd³) GD bucket. | | |

Swing

| | | |
|--------------|-----------|---------------|
| Swing Speed | 8.9 rpm | |
| Swing Torque | 49.6 kN·m | 36,582 lbf-ft |

Service Refill Capacities

| | | |
|-----------------------------------|--------|-----------|
| Fuel Tank Capacity | 290 L | 76.61 gal |
| DEF Tank Capacity | 20.5 L | 5.4 gal |
| Cooling System | 26 L | 6.9 gal |
| Engine Oil (with filter) | 13.5 L | 3.57 gal |
| Swing Drive | 8 L | 2.11 gal |
| Final Drive (each) | 8 L | 2.11 gal |
| Hydraulic System (including tank) | 121 L | 31.96 gal |
| Hydraulic Tank | 106 L | 28.00 gal |

Sound Performance

| | |
|--|-----------|
| ISO 6396 – Operator Sound Pressure Level | 71 dB(A) |
| Exterior Sound Power Level | 102 dB(A) |

Dimensions*

| Reach Boom – 5.1 m (16'9") | | |
|--------------------------------------|---------------|-------|
| R2.6 m (8'6") | | |
| Stick | R2.6 m (8'6") | |
| Shipping Height | 3050 mm | 10'2" |
| Shipping Length | 8570 mm | 28'1" |
| Tail Swing Radius | 2500 mm | 8'2" |
| Length to Center of Rollers | 3170 mm | 10'0" |
| Track Length | 3970 mm | 13'0" |
| Ground Clearance | 440 mm | 1'5" |
| Track Gauge | 1990 mm | 6'6" |
| Transport Width – 700 mm (28") Shoes | 2690 mm | 8'10" |
| Cab Height | 2890 mm | 9'6" |
| Cab Height with Top Guard | 3100 mm | 10'2" |
| Counterweight Clearance | 1010 mm | 3'4" |

Working Ranges*

| Reach Boom – 5.1 m (16'9") | | |
|---|---------------|--------|
| R2.6 m (8'6") | | |
| Stick | R2.6 m (8'6") | |
| Maximum Digging Depth | 6090 mm | 20'0" |
| Maximum Reach at Ground Level | 8780 mm | 28'10" |
| Maximum Cutting Height | 8920 mm | 29'3" |
| Maximum Loading Height | 6280 mm | 20'7" |
| Minimum Loading Height | 2300 mm | 7'6" |
| Maximum Depth Cut for 2440 mm (8'0") Level Bottom | 5870 mm | 19'4" |
| Maximum Vertical Wall Digging Depth | 4960 mm | 16'3" |

Bucket & Stick Forces*

| Reach Boom – 5.1 m (16'9") | | |
|----------------------------|---------------------|------------|
| R2.6 m (8'6") | | |
| Stick | R2.6 m (8'6") | |
| Bucket Type | General Duty Bucket | |
| Bucket Digging Force (SAE) | 98 kN | 22,000 lbf |
| Bucket Digging Force (ISO) | 111 kN | 25,000 lbf |
| Stick Digging Force (SAE) | 77 kN | 17,310 lbf |
| Stick Digging Force (ISO) | 80 kN | 18,000 lbf |

*With a 0.76 m³ (1.00 yd³), 900 mm (41") bucket.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2017 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ1911-01
Replaces AEXQ1911
(AUZ, EU, NACD)



Effective with sales to the first user on or after January 1, 2018

CATERPILLAR LIMITED WARRANTY

Earthmoving, Construction, Material Handling, Forestry and Paving Machines

Worldwide

Caterpillar Inc. or any of its subsidiaries ("Caterpillar") warrants the following new products sold by it to be free from defects in material and workmanship:

- Earthmoving, construction, material handling, forestry and paving machines (except as listed below).
- Attachments/work tools installed on such machines prior to delivery (unless covered by the Cat® Work Tool warranty statement or another manufacturer's warranty). Hammer tool points and compacting plates used on hydraulic hammers are not warranted.

Additional warranties are applicable against breakage for certain Cat Ground Engaging Tools and for wear on all landfill compactor tips. Refer to the applicable warranty statements for coverage detail.

This warranty does not apply to:

- Cat Batteries
- Mobil-trac belts, rubber tracks used on multi terrain loaders, compact track loaders, and mini hydraulic excavators
- Cat Work Tools
- 424 Backhoe Loaders, 216 and 226 Skid Steer Loaders, and 320 Excavators sold in India
- Prentice brand forestry machines
- Longwall mining machines
- 785, 789, 793, 794, 795, 797 Off-Highway Truck models sold in regions other than the Commonwealth of Independent States ("CIS")
- 24 Motor Grader models sold in regions other than the CIS
- 854, 992, 993, 994 Wheel Loader models sold in regions other than CIS
- Cat Utility Vehicles (UTV)
- Compact Construction Equipment including Compact Track & Multi Terrain Loaders, Mini Hydraulic Excavators, and Skid Steer Loaders sold in USA or Canada.

These products are covered by other Caterpillar warranties.

This warranty is subject to the following:

Warranty Period

For new machines and work tools/attachments the warranty period is 12-months/unlimited hours, starting from date of delivery to the first user.

Note:

- For hydraulic line's quick connect/disconnect components sold on compact wheel loaders, mini hydraulic excavators, skid steer loaders, multi terrain loaders, and compact track loader machines, the warranty period is 50 hours starting from the date of delivery to the first user.
- For Draglines, Electric Rope Shovels, Hard Rock Movers, Hard Rock Feeders, Hard Rock Miners, Hard Rock Conveyors, Hard Rock Roof Supports: the warranty period is not to exceed 24 months from shipment of the last major component from the Caterpillar place of manufacture.

Caterpillar Responsibilities

If a defect in material or workmanship is found during the warranty period, Caterpillar will, during normal working hours and at a place of business of a Cat dealer or other source approved by Caterpillar

- Provide (at Caterpillar's choice) new, remanufactured, or Caterpillar approved repaired parts or assembled components needed to correct the defect.

Note: New, remanufactured, or Caterpillar approved replacement parts provided under the terms of this warranty are warranted for the remainder of the warranty period applicable to the product in which installed as if such parts were original components of that product. Items replaced under this warranty become the property of Caterpillar.

- Replace lubricating oil, filters, antifreeze, and other service items made unusable by the defect.
- Provide reasonable and customary labor needed to correct the defect.

User Responsibilities

The user is responsible for:

- Providing proof of delivery date to the first user.
- Labor costs, except as stated under "Caterpillar Responsibilities."
- Transportation costs, except as stated under "Caterpillar Responsibilities."
- Premium or overtime labor costs.
- Parts shipping charges in excess of those that are considered usual and customary.
- Local taxes, if applicable.
- Costs to investigate complaints, unless the problem is caused by a defect in Caterpillar material or workmanship.
- Giving timely notice of a warrantable failure and promptly making the product available for repair.
- Performance of the required maintenance (including use of proper fuel, oil, lubricants, and coolant) and items replaced due to normal wear and tear.
- Allowing Caterpillar access to all electronically stored data.

Limitations

Caterpillar is not responsible for:

- Failures resulting from any use or installation that Caterpillar judges improper.
- Failures resulting from attachments, accessory items, and parts not sold or approved by Caterpillar.
- Failures resulting from abuse, neglect, and/or improper storage or repair.
- Failures resulting from user's delay in making the product available after being notified of a potential product problem.
- Failures resulting from unauthorized repair or adjustments, and unauthorized fuel setting changes.

continued...

This warranty covers every major component of the products. Claims under this warranty should be submitted to a place of business of a Cat dealer or other source approved by Caterpillar. For further information concerning either the location to submit claims or Caterpillar as the issuer of this warranty, write Caterpillar Inc., 100 N. E. Adams St., Peoria, IL USA 61629, telephone 1 (309) 675-1000, or go to URL www.cat.com, Find Your Dealer

Caterpillar's obligations under this Limited Warranty are subject to, and shall not apply in contravention of, the laws, rules, regulations, directives, ordinances, orders, or statutes of the United States, or of any other applicable jurisdiction, without recourse or liability with respect to Caterpillar.

A) For products operating outside of Australia, Fiji, Nauru, New Caledonia, New Zealand, Papua New Guinea, the Solomon Islands, and Tahiti, the following is applicable:

NEITHER THE FOREGOING EXPRESS WARRANTY NOR ANY OTHER WARRANTY BY CATERPILLAR, EXPRESS OR IMPLIED, IS APPLICABLE TO ANY ITEM CATERPILLAR SELLS THAT IS WARRANTED DIRECTLY TO THE USER BY ITS MANUFACTURER.

THIS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, EXCEPT CATERPILLAR EMISSION-RELATED COMPONENTS WARRANTY FOR NEW ENGINES, WHERE APPLICABLE. REMEDIES UNDER THIS WARRANTY ARE LIMITED TO THE PROVISION OF MATERIAL AND SERVICES, AS SPECIFIED HEREIN.

CATERPILLAR IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

CATERPILLAR EXCLUDES ALL LIABILITY FOR OR ARISING FROM ANY NEGLIGENCE ON ITS PART OR ON THE PART OF ANY OF ITS EMPLOYEES, AGENTS, OR REPRESENTATIVES IN RESPECT OF THE MANUFACTURE OR SUPPLY OF GOODS OR THE PROVISION OF SERVICES RELATING TO THE GOODS.

IF OTHERWISE APPLICABLE, THE VIENNA CONVENTION ON CONTRACTS FOR THE INTERNATIONAL SALE OF GOODS IS EXCLUDED IN ITS ENTIRETY.

B) For products operating in Australia, Fiji, Nauru, New Caledonia, New Zealand, Papua New Guinea, the Solomon Islands, and Tahiti, the following is applicable:

THIS WARRANTY IS IN ADDITION TO WARRANTIES AND CONDITIONS IMPLIED BY STATUTE AND OTHER STATUTORY RIGHTS AND OBLIGATIONS THAT BY ANY APPLICABLE LAW CANNOT BE EXCLUDED, RESTRICTED OR MODIFIED ("MANDATORY RIGHTS"). ALL OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED (BY STATUTE OR OTHERWISE), ARE EXCLUDED. WITHOUT LIMITING THE FOREGOING PROVISIONS OF THIS PARAGRAPH, WHERE A PRODUCT IS SUPPLIED FOR BUSINESS PURPOSES, THE CONSUMER GUARANTEES UNDER THE CONSUMER GUARANTEES ACT 1993 (NZ) WILL NOT APPLY.

NEITHER THIS WARRANTY NOR ANY OTHER CONDITION OR WARRANTY BY CATERPILLAR, EXPRESS OR IMPLIED (SUBJECT ONLY TO THE MANDATORY RIGHTS), IS APPLICABLE TO ANY ITEM CATERPILLAR SELLS THAT IS WARRANTED DIRECTLY TO THE USER BY ITS MANUFACTURER.

IF THE MANDATORY RIGHTS MAKE CATERPILLAR LIABLE IN CONNECTION WITH SERVICES OR GOODS, THEN TO THE EXTENT PERMITTED UNDER THE MANDATORY RIGHTS, THAT LIABILITY SHALL BE LIMITED AT CATERPILLAR'S OPTION TO (a) IN THE CASE OF SERVICES, THE SUPPLY OF THE SERVICES AGAIN OR THE PAYMENT OF THE COST OF HAVING THE SERVICES SUPPLIED AGAIN AND (b) IN THE CASE OF GOODS, THE REPAIR OR REPLACEMENT OF THE GOODS, THE SUPPLY OF EQUIVALENT GOODS, THE PAYMENT OF THE COST OF SUCH REPAIR OR REPLACEMENT OR THE ACQUISITION OF EQUIVALENT GOODS.

CATERPILLAR EXCLUDES ALL LIABILITY FOR OR ARISING FROM ANY NEGLIGENCE ON ITS PART OR ON THE PART OF ANY OF ITS EMPLOYEES, AGENTS OR REPRESENTATIVES IN RESPECT OF THE MANUFACTURE OR SUPPLY OF GOODS OR THE PROVISION OF SERVICES RELATING TO THE GOODS.

CATERPILLAR IS NOT LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES UNLESS IMPOSED UNDER MANDATORY RIGHTS.

IF OTHERWISE APPLICABLE, THE VIENNA CONVENTION (CONTRACTS FOR THE INTERNATIONAL SALE OF GOODS) IS EXCLUDED IN ITS ENTIRETY.

C) For products supplied in Australia:

IF THE PRODUCTS TO WHICH THIS WARRANTY APPLIES ARE:

- I. PRODUCTS OF A KIND ORDINARILY ACQUIRED FOR PERSONAL, DOMESTIC OR HOUSEHOLD USE OR CONSUMPTION; OR
- II. PRODUCTS THAT COST AUD 40,000 OR LESS,

WHERE THOSE PRODUCTS WERE NOT ACQUIRED FOR THE PURPOSE OF RE-SUPPLY OR FOR THE PURPOSE OF USING THEM UP OR TRANSFORMING THEM IN THE COURSE OF PRODUCTION OR MANUFACTURE OR IN THE COURSE OF REPAIRING OTHER GOODS OR FIXTURES, THEN THIS SECTION C APPLIES.

THE FOLLOWING MANDATORY TEXT IS INCLUDED PURSUANT TO THE AUSTRALIAN CONSUMER LAW AND INCLUDES REFERENCES TO RIGHTS THE USER MAY HAVE AGAINST THE DIRECT SUPPLIER OF THE PRODUCTS: OUR GOODS COME WITH GUARANTEES THAT CANNOT BE EXCLUDED UNDER THE AUSTRALIAN CONSUMER LAW. YOU ARE ENTITLED TO A REPLACEMENT OR REFUND FOR A MAJOR FAILURE AND COMPENSATION FOR ANY OTHER REASONABLY FORESEEABLE LOSS OR DAMAGE. YOU ARE ALSO ENTITLED TO HAVE THE GOODS REPAIRED OR REPLACED IF THE GOODS FAIL TO BE OF ACCEPTABLE QUALITY AND THE FAILURE DOES NOT AMOUNT TO A MAJOR FAILURE. THE INCLUSION OF THIS TEXT DOES NOT CONSTITUTE ANY REPRESENTATION OR ACCEPTANCE BY CATERPILLAR OF LIABILITY TO THE USER OR ANY OTHER PERSON IN ADDITION TO THAT WHICH CATERPILLAR MAY HAVE UNDER THE AUSTRALIAN CONSUMER LAW.

TO THE EXTENT THE PRODUCTS FALL WITHIN THIS SECTION C BUT ARE NOT OF A KIND ORDINARILY ACQUIRED FOR PERSONAL, DOMESTIC OR HOUSEHOLD USE OR CONSUMPTION, CATERPILLAR LIMITS ITS LIABILITY TO THE EXTENT IT IS PERMITTED TO DO SO UNDER THE AUSTRALIAN CONSUMER LAW TO, AT ITS OPTION, THE REPAIR OR REPLACEMENT OF THE PRODUCTS, THE SUPPLY OF EQUIVALENT PRODUCTS, OR THE PAYMENT OF THE COST OF SUCH REPAIR OR REPLACEMENT OR THE ACQUISITION OF EQUIVALENT PRODUCTS.

THE WARRANTY SET OUT IN THIS DOCUMENT IS GIVEN BY CATERPILLAR INC. OR ANY OF ITS SUBSIDIARIES, 100 N. E. ADAMS ST, PEORIA, IL USA 61629, TELEPHONE 1 309 675 1000. THE USER IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH MAKING A CLAIM UNDER THE WARRANTY SET OUT IN THIS DOCUMENT. EXCEPT AS EXPRESSLY STATED OTHERWISE IN THIS DOCUMENT, AND THE USER IS REFERRED TO THE BALANCE OF THE DOCUMENT TERMS CONCERNING CLAIM PROCEDURES, CATERPILLAR RESPONSIBILITIES AND USER RESPONSIBILITIES.

TO THE EXTENT PERMISSIBLE BY LAW, THE TERMS SET OUT IN THE REMAINDER OF THIS WARRANTY DOCUMENT (INCLUDING SECTION B) CONTINUE TO APPLY TO PRODUCTS TO WHICH THIS SECTION C APPLIES.

©2018 Caterpillar All Rights Reserved.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.