

FSA 2020/2021 Contract - OPTIONS					
Dealer	Brand	Model	Model #	Description	Option \$
GTPB	Exmark	Lazer S	LZS801GKA524A2	Downgrade Option - 52" Deck with 25.5HP Kawasaki Engine	\$ (320)
GTPB	Exmark	Lazer S	LZS749AKC72400	Upgrade Option - 72" Deck with 26.5HP EFI Kohler Engine	\$ 560
GTPB	Exmark	Lazer X	LZX921GKA60600	Upgrade Option - 60" Deck with 31HP Kawasaki Engine	\$ 1,600
GTPB	Exmark	Lazer X	LZX921GKA726C1	Upgrade Option - 72" Deck with 31HP Kawasaki Engine	\$ 2,720
GTPB	Exmark	Lazer X	LZX980EKC96RW0	Upgrade Option - 96" Deck with 38HP EFI Kohler Engine	\$ 16,480
GTPB	Exmark	Lazer Z	LZS88CDYM96RW0	Upgrade Option - 96" Deck with 37HP Yanmar Diesel Engine	\$ 23,680

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower

### Lazer Z S-Series Mower

#### LZS801GKA524A2

## SPECIFICATIONS

**Engine** – Kawasaki® FX801V V-Twin, governed to 3,750 RPM

**Carb Compliant** – No

**Air Filter** – Heavy-duty canister air filtration system

**Drive System** – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12 cc pumps and 14. 5 cubic inch motors.

**Ground Speed** – Infinitely variable speed selection from 0–10.0 mph (16 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

**Hydro Fluid** – Exmark Premium Hydraulic Oil

**Cutting Deck** – Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

**Deck Lift Assist** – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

**Drive Tires** – 23 x 9.5-12, 4 ply Turf Master®

**Front Caster Tires** – 13 x 5.0-6, smooth-tread, semi-pneumatic.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Curb Weight** – 1161 lbs.

## Dimensions:

**Deck Size** - 52"

**Width**.....64.8 in. (164.6 cm)

**Length**.....79.2 in. (201.2 cm)

**Height**..... 70.5 in. (179.1 cm)

**Blades** – 3 Blades at 18.00" Length

**Blade-Tip Speed** – Approximately 18,500 fpm.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft and splined blade driver.

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated disc brake.

**Lazer Z S-Series Mower  
LZS801GKA524A2**

**Seat** - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), single fuel tank with single fill location.

**Electrical** – 12-volt battery with 15-amp alternator.

**PTO Engagement** – MagStop electromagnetic 200-ft-lb clutch with spot brake

**Standard Features** – Engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Available Accessories and Attachments**

3-Bushel Bagger .....	GC3602
12-Volt Adapter .....	109-9694
Air Ride Suspension Seat .....	116-8820
Equipment Cover - Large .....	116-1379
Extended Drive Lever .....	116-1065
Floor Mat .....	116-6068
Harness Add-On Accessory Kit.....	109-9798
Hitch Kit.....	109-9487
Hydro Maintenance Kit.....	126-8103
Jack.....	127-6666
Jack Mount Receiver.....	127-6665
LED Light Kit (not compatible with TC26).....	135-7320
Micro-Mulch System.....	MK526
Operator Controlled Discharge (Foot .....	116-8431
Pedal Adapter Kit .....	135-0100
Power Deck Lift .....	116-2517
Seat Isolation System .....	116-0941
Sun Shade .....	126-8077
Trash Container (Not compatible with 135-7320).....	TC26
Turf Striping Kit (48"/52"/60") .....	116-6655
UltraVac Collection System, Double-Bag .....	LZUV2B
UltraVac, Quick-Disposal, 7-Bushel .....	LZUVQD7
UltraVac Kit .....	116-2085

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower

### Lazer Z S-Series Mower

#### LZS749AKC72400

## SPECIFICATIONS

**Engine** – Kohler® ECV749 Command™ EFI, governed to 3,750 RPM

**Carb Compliant** – Yes

**Air Filter** – Heavy-duty canister air filtration system

**Drive System** – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12 cc pumps and 14.5 cubic inch motors.

**Ground Speed** – Infinitely variable speed selection from 0–10.0 mph (16 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

**Hydro Fluid** – Exmark Premium Hydraulic Oil

**Cutting Deck** – Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

**Deck Lift Assist** – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

**Drive Tires** – 24 x 12-12, 4 ply Turf Master®

**Front Caster Tires** – 13 x 6.5-6, smooth-tread, semi-pneumatic.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Curb Weight** – 1240 lbs.

## Dimensions:

**Deck Size** - 72"

**Width**.....84.9 in. (215.6 cm)

**Length**.....86.1 in. (218.7 cm)

**Height**..... 70.5 in. (179.1 cm)

**Blades** – 3 Blades at 24.50" Length

**Blade-Tip Speed** – Approximately 18,500 fpm.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm(.98") diameter spindle shaft and splined blade driver.

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated disc brake.

**Lazer Z S-Series Mower  
LZS749AKC72400**

**Seat** - Deluxe, two tone, bolstered seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), single fuel tank with single fill location.

**Electrical** – 12-volt battery with 20-amp alternator.

**PTO Engagement** – MagStop electromagnetic 200-ft-lb clutch with spot brake

**Standard Features** – Engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Onboard Intelligence** - Smart Controller

**Available Accessories and Attachments**

12-Volt Adapter .....	109-9694
Air Ride Suspension Seat .....	116-8820
Custom Ride Seat Suspension .....	116-0062
Extended Drive Lever .....	116-1065
Floor Mat .....	116-6068
Full-Suspension Seat .....	116-8912
Harness Add-On Accessory Kit .....	109-9798
Hitch Kit.....	109-9487
Hydro Maintenance Kit.....	126-8103
Jack.....	127-6666
Jack Mount Receiver .....	127-6665
LED Light Kit (not compatible with TC26).....	135-7320
Micro-Mulch System.....	MK726
Operator Controlled Discharge (Foot) .....	116-8431
Power Deck Lift .....	116-2517
Seat Isolation System .....	116-0941
Sun Shade .....	126-8077
Tractus Tire .....	135-2287
Trash Container (Not compatible with 135-7320).....	TC26
Turf Striping Kit .....	116-6656
UltraVac Collection Systems, Triple-Bag .....	LZUV3B
UltraVac, Quick-Disposal, 11-Bushel .....	LZUVQD11
UltraVac Kit .....	116-2087

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower

### Lazer Z X-Series Mower

#### LZX921GKA60600

## SPECIFICATIONS

**Engine** – Kawasaki® FX921V V-Twin, governed to 3,750 RPM

**Carb Compliant** – No

**Air Filter** – Heavy-duty canister air filtration system

**Drive System** – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16 cc pumps and 17.1 cubic inch motors.

**Ground Speed** – Infinitely variable speed selection from 0–11.5 mph (18.5 kmph) forward, 0–7.0 mph (11.3 kmph) reverse

**Hydro Fluid** – Exmark Premium Hydraulic Oil

**Cutting Deck** – Full-floating UltraCut Series 6 with heavy-duty spindle. Side discharge standard with the option to bag or mulch.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

**Deck Lift Assist** – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

**Drive Tires** – 24 x 12.0-12, 4-ply Turf Master®

**Front Caster Tires** – 13 x 6.5-6 smooth tread, semi-pneumatic tires.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Curb Weight** – 1246 lbs.

## Dimensions:

**Deck Size** - 60"

**Width**.....72.8 in. (184.9 cm)

**Length**.....83.1 in. (211.1 cm)

**Height**.....70.5 in. (179.1 cm)

**Blades** – 3 Blades at 20.50" Length

**Blade-Tip Speed** – Approximately 18,500 fpm.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 30mm (1.18") diameter spindle shaft and splined blade driver.

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated disc brake.

**Lazer Z X-Series Mower  
LZX921GKA60600**

**Seat** - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), single fuel tank with single fill location.

**Electrical** – 12-volt battery with 15-amp alternator.

**PTO Engagement** – MagStop Electromagnetic 250-ft-lb clutch with spot brake

**Standard Features** – Engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Available Accessories and Attachments**

12-Volt Power Adapter .....	135-6804
Air Ride Suspension Seat .....	116-8820
Equipment Cover - Large .....	116-1379
Extended Drive Lever Kit .....	116-1065
Floor Mat .....	116-6068
Harness Add-On Accessory Kit.....	109-9798
Hitch Kit .....	109-9487
Hydro Maintenance Kit.....	126-8103
Jack.....	127-6666
Jack Mount Receiver .....	127-6665
LED Light Kit (not compatible with TC26).....	135-7320
Power Deck Lift .....	116-2517
Sun Shade .....	126-8077
Tractus Tire .....	135-2286
Trash Container (Not compatible with 135-7320).....	TC26
3-Bushel Bagger .....	GC3602
Anti-Scalp Kit .....	116-4614
Micro-Mulch System.....	MK606
Operator Controlled Discharge (Foot) .....	116-8431
Turf Striping Kit .....	116-6655
UltraVac Collection Systems, Triple-Bag .....	LZUV3B
UltraVac, Quick-Disposal, 11-Bushel .....	LZUVQD11
UltraVac Kit .....	109-9627

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower

### Lazer Z X-Series Mower

#### LZX921GKA726C1

## SPECIFICATIONS

**Engine** – Kawasaki® FX921V V-Twin, governed to 3,750 RPM

**Carb Compliant** – No

**Air Filter** – Heavy-duty canister air filtration system

**Drive System** – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16 cc pumps and 17.1 cubic inch motors.

**Ground Speed** – Infinitely variable speed selection from 0–11.5 mph (18.5 kmph) forward, 0–7.0 mph (11.3 kmph) reverse

**Hydro Fluid** – Exmark Premium Hydraulic Oil

**Cutting Deck** – Full-floating UltraCut Series 6 with heavy-duty spindle. Side discharge standard with the option to bag or mulch.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

**Deck Lift Assist** – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

**Drive Tires** – 24 x 12.0-12, 4-ply Turf Master®

**Front Caster Tires** – 13 x 6.5-6 smooth tread, semi-pneumatic tires.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Curb Weight** – 1387 lbs.

## Dimensions:

**Deck Size** - 72"

**Width**.....84.9 in. (215.6 cm)

**Length**.....86.1 in. (218.7 cm)

**Height**.....70.5 in. (179.1 cm)

**Blades** – 3 Blades at 24.50" Length

**Blade-Tip Speed** – Approximately 18,500 fpm.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 30mm (1.18")diameter spindle shaft and splined blade driver.

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated disc brake.



**Lazer Z X-Series Mower  
LZX921GKA726C1**

**Seat** - Deluxe, two tone, bolstered seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), single fuel tank with single fill location.

**Electrical** – 12-volt battery with 15-amp alternator.

**PTO Engagement** – MagStop Electromagnetic 250-ft-lb clutch with spot brake

**Standard Features** – Engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Available Accessories and Attachments**

12-Volt Power Adapter .....	135-6804
Harness Add-On Accessory Kit .....	109-9798
Hitch Kit (excludes 96") .....	109-9487
Hydro Maintenance Kit .....	126-8103
Jack .....	127-6666
Jack Mount Receiver (excludes 96") .....	127-6665
LED Light Kit (not compatible with TC26) .....	135-7320
Sun Shade .....	126-8077
Tractus Tire .....	135-2287
Trash Container (Not compatible with 135-7320) .....	TC26
Micro-Mulch System .....	MK726
Operator Controlled Discharge (Foot) (C1 needs 135-0100) .....	116-8431
Pedal Adapter Kit (Suspension Platform) .....	135-0100
Suspension Platform Weight Adapter Kit .....	132-5092
Turf Striping Kit .....	116-6656
UltraVac Collection Systems (C1 needs 132-5092), Triple-Bag .....	LZUV3B
UltraVac, Quick-Disposal, 11-Bushel .....	LZUVQD11
UltraVac Kits .....	109-9629

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower

### Lazer Z X-Series Mower

#### LZX980EKC96RW0

## SPECIFICATIONS

**Engine** – Kohler® ECV980 Command Pro™ EFI, governed to 3,650 RPM

**Carb Compliant** – No

**Air Filter** – Heavy-duty canister air filtration system

**Drive System** – Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16 cc pumps and 18 cubic inch motors.

**Ground Speed** – Infinitely variable speed selection from 0–10.5 mph (18.5 kmph) forward, 0–7.0 mph (11.3 kmph) reverse

**Hydro Fluid** – Exmark Premium Hydraulic Oil

**Cutting Deck** – Full-floating UltraCut Rear Discharge Deck. Rear-discharge standard with finish cut baffles included.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments.

**Deck Lift Assist** – Electric over hydraulic push button control

**Drive Tires** – 24 x 12.0-12, 4-ply Turf Master®

**Front Caster Tires** – 13 x 6.5-6, smooth-tread, semi-pneumatic.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Curb Weight** – 2200 lbs.

## Dimensions:

**Deck Size** - 96"

**Width**.....101.3 in. (257.0 cm), 72.5 in. @ 3 in. HOC when folded

**Length**.....95.8 in. (243.3 cm)

**Height**.....70.5 in. (179.1 cm)

**Blades** – 4 Blades at 24.50" Length

**Blade-Tip Speed** – Approximately 18,100 fpm

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft, double row bearings, top and bottom, and splined blade driver.

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated disc brake.

**Lazer Z X-Series Mower  
LZX980EKC96RW0**

**Seat** - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), single fuel tank with single fill location.

**Electrical** – 12-volt battery with 40-amp alternator.

**PTO Engagement** – MagStop Electromagnetic 250-ft-lb clutch with spot brake

**Standard Features** – engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Onboard Intelligence** - RED Technology

**Available Accessories and Attachments**

12-Volt Power Adapter .....	135-6804
Extended Drive Lever Kit .....	116-1065
Floor Mat .....	116-6068
Harness Add-On Accessory Kit.....	109-9798
Hydro Maintenance Kit.....	126-8103
Jack.....	127-6666
Jack Mount Receiver.....	135-1768
Sun Shade .....	126-8077
LED Light Kit (not compatible with 135-2473) .....	135-7076
Rear Discharge Baffle Kit.....	142-3000
Trash Container (Not compatible with 135-7076).....	135-2473
White Non-Marking Side Bumper (requires 2 per side 3231-7 & 104-8301) .....	126-0854
Black Side Bumper (requires 2 per side 3231-7 & 104-8301) .....	112-1479

# BID SPECIFICATIONS

## Mid-Mount ZTR Mower Lazer Z Diesel Mower LZS88CDYM96RW0

### SPECIFICATIONS

**Engine** – Yanmar 3TNV88C TNV, governed to 3,000 RPM

**Carb Compliant** – Yes

**Air Filter** – Heavy-duty canister air filtration system with electronic vacuum sensor

**Drive System** – Kanzaki KPS-18T Transmission, 16-quart oil capacity, spin-on filter. 18 cc shoe type pumps and 17.84 cubic inch Hydro-Gear HGM-18 motors, hydraulic oil cooler.

**Ground Speed** – Infinitely variable speed selection from 0–12.5 mph (20 kmph) forward, 0–7 mph (11 kmph) reverse.

**Hydro Fluid** – Exmark Ruby Tran.

**Cutting Deck** – Full-floating UltraCut Rear Discharge Deck. Rear-discharge standard with finish cut baffles included.

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments.

**Deck Lift Assist** – Hydraulic

**Drive Tires** – 26 x 12-12, 6ply Multi Trac®

**Front Caster Tires** – 15 x 6.0-6, smooth-tread, semi-pneumatic.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft., also adjustable to 2 height positions. Adjustable dampeners (3 positions) to customize drive responsiveness.

**Curb Weight** – 2650 lbs.

### Dimensions:

**Deck Size** - 96"

**Width**.....101.2 in. (257.0cm), 72.5 in. @ 3 in. HOC when folded

**Length**.....97.2 in. (246.9 cm)

**Height**.....71.8 in. (182.4 cm)

**Blades** – 4 Blades at 24.50" Length

**Blade-Tip Speed** – Approximately 18,500 fpm

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft, double row bearings, top and bottom, and splined blade driver..

**Tractor Frame** – Welded, heavy-duty 1.5" x 3" x 3/16" tubular steel.

**Turning Radius** – True zero-turn

**Drive-Wheel Release** – Allows unit movement without engine running.

**Parking Brake** – Lever-actuated internal wet disc brake.

**Lazer Z Diesel Mower  
LZS88CDYM96RW0**

**Seat** - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Fuel Capacity** – 12-gallon (45.4-L), side fuel tanks

**Electrical** – 12-volt battery with 55-amp alternator.

**PTO Engagement** – Integrated wet clutch system in transmission, connected to right angle gearbox on deck via drive shaft

**Standard Features** – 12-volt plug-in, engine hour meter and cup holder

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Onboard Intelligence** - RED Technology

**Available Accessories and Attachments**

Flasher Kit .....	135-2892
Hitch Kit.....	135-3616
Jack.....	127-6666
Jack Mount Receiver.....	135-1768
LED Light Kit (not compatible with 135-2473) .....	135-7076
Rear Guard and Bumper Kit.....	135-3445
Slow Moving Vehicle Sign Kit.....	135-2891
Sun Shade .....	126-8077
Trash Container (Not compatible with 135-7076).....	135-2473
Finish Cut Baffles .....	135-2449
Anti-Scalp and Side Wear Bar Kit .....	127-6650
White Non-Marking Side Bumper.....	126-0854