



Carryall 1500 4x4 Gasoline

FEATURES & BENEFITS

- Kawasaki® 20.1 rated hp (15 kW), 675 cc air-cooled gas engine
- Exclusive IntelliTrak™ automatic, full-time, 4-wheel drive system
- Certified Roll Over Protective Structure (ROPS), with retractable seat belts
- Rustproof aircraft grade aluminum frame, chassis & cargo box
- 1450 lb (657.7 kg) total vehicle capacity with heavy-duty option
- Heavy-duty steel tilt cargo box with flip-down tailgate
- 4-wheel hydraulic disc brakes
- Automotive Dash features glove box, cup holders, storage spaces and tilt steering wheel
- Bucket or bench seat options
- Industry's Best 2-year Limited Warranty

Engine/Motor Type	Kawasaki® 4-cycle, industrial grade
Controller	NA
Displacement	675 cc
Cylinders	Twin-cylinder
Valving	OHV
Cooling	Air Cooled
Horsepower (Rated)	20.1 hp (15.0 kW) rated @ 3400 RPM per SAE J1349
Max Torque	36.5 ft/lb (49.5 Nm)
Lubrication	Full-pressure, spin-on oil filter
Governor	Automatic ground speed sensing
Transmission	Wide ratio CVT; 3.7:1 low, 0.59:1 high
Front/Rear Differential	IntelliTrak™ Automatic 4-wheel Drive
Gear Selection	Forward/Neutral/Reverse
Gear Ratio	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
Ignition	Transistorized magneto
Battery	12-volt 500 CCA 105 min Reserve
Charger	NA
Headlights	Headlights standard
Fuel Delivery System	Carburetor
Fuel Capacity	6.5 gal (24.6 L)
Steering Mechanism	Rack and pinion with Tilt Steering
Suspension (Front)	Independent double A-arms with coil-over shocks
Suspension (Rear)	Semi-independent 4-link solid axle
Brakes	4-wheel, hydraulic disc
Park Brake	Automotive style
Body (Front & Finish)	GE Geloy high-impact, scratch-resistant, injection molded color, Automotive finish
Body (Frame and Rear)	Tubular aluminum
Tires (Front)	All-terrain, 25 x 10.5-12, 4-ply
Tires (Rear)	All-terrain, 25 x 10.5-12, 4-ply
Wheelbase	88.7 in (225.3 cm)
Overall Height	78.6 in (199.6 cm)
Overall Length	124.6 in (316.5 cm)
Bed L x W x H (Cargo Box)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
Ground Clearance (Differential)	8.2 in (20.8 cm)
Track Width (Front)	48.8 in. (124 cm)
Track Width (Rear)	48.8 in. (124 cm)
Max Width (w/o Mirrors)	58.5 in. (148.5 cm)
Curb Weight	1430 lb (648.6 kg)
Total Vehicle Capacity	1200 lb (544 kg) Standard / 1450 lb (658 kg) with heavy-duty option
Bed Load Capacity	800 lb (363.2 kg)) Standard / 1050 lb (658 kg) with heavy-duty option
Towing Capacity	2000 lb (658 kg)
Combined Gross Vehicle Capacity	1200 lb (544 kg)) Standard / 1450 lb (658 kg) with heavy-duty option
Speed	25 mph (40.2 km/h)
Warranty	2-year/2,000 hour limited