

## SVL75-2

### SVL75-2 Compact Track Loader

#### FEATURES

Vertical Lift Path Loader Frame  
Standard Front Quick Coupler, Float Standard  
Hydraulic Quick Coupler Option  
Loader Arm Self-Leveling  
Loader Boom Lock  
Open ROPS & Air Conditioned ROPS/FOPS Cab Models  
High Back, Adjustable, Vinyl, Suspension Seat  
2" Retractable Seat Belt And 2-Piece Seat Bar  
12V Electric Outlet  
17.4 gpm Auxiliary Hydraulics standard, 28.3 gpm Option  
Direct To Tank Return Line  
Rigid Mounted Undercarriage, 4 Lower Track Rollers  
Rubber Tracks, 12.6" Standard, 15" Optional  
Two Speed Travel System  
Automatic Wet Disk Parking Brake  
Kubota 4 Hydraulic Pump Load Sensing System  
2 Gear, 2 Variable Displacement Pumps  
Hydraulic Joystick Controls, Optional Multi-Function Grips  
ISO Operating Pattern  
Hand And Foot Throttle Controls  
Electronic Travel Torque Management  
Automatic Glow Plugs  
Key Switch Stop System  
Self Bleed Fuel System  
2 Front And 2 Rear Working Lights  
Hour Meter, Engine Temperature And Fuel  
Gauges And Warning Lights  
Horn And Backup Alarm  
Lockable Fuel Cap  
Bolt On Grab Handles to enter machine

#### DIMENSIONS

Cab Height	82.0"
Width (without attachment)	65.9"
Width with wide track option (without attachment)	68.3"
Length (without attachment)	109.0"
Length of Track on Ground	56.5"

#### OPERATIONAL DIMENSIONS

Operating Weight*, SVL75-2H, 12.6" Rubber Tracks, Open ROPS/FOPS Cab, Mechanical Quick Coupler	9,039 lbs.
Rated Operating Capacity (@ 35% of Tipping Load)	2,300 lbs.
Rated Operating Capacity (ROC) @ 50% of Tipping Load	3,285 lbs.
Tipping Load	6,570 lbs.
Auxiliary Hydraulics Flow	17.4 gpm
Travel Speed (Low / High)	4.7 / 7.1 mph
Reach @ Maximum Height	41.7"
Height to Hinge Pin	119.1"
Ground Pressure (Standard Track)	5.6 psi
Ground Pressure (Wide Track)	4.7 psi

\* Includes operator's weight, 175 lbs.

#### BASIC UNITS

SVL75-2, 12.6" Rubber Tracks, Open ROPS/FOPS Cab  
Mechanical Quick Coupler  
SVL75-2F, 12.6" Rubber Tracks, Open ROPS/FOPS Cab  
Mechanical Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2H, 12.6" Rubber Tracks, Open ROPS/FOPS Cab  
Hydraulic Quick Coupler  
SVL75-2HF, 12.6" Rubber Tracks, Open ROPS/FOPS Cab  
Hydraulic Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2W, 15.0" Rubber Tracks, Open ROPS/FOPS Cab  
Mechanical Quick Coupler  
SVL75-2FW, 15.0" Rubber Tracks, Open ROPS/FOPS Cab  
Mechanical Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2HW, 15.0" Rubber Tracks, Open ROPS/FOPS Cab  
Cab Hydraulic Quick Coupler  
SVL75-2HFW, 15.0" Rubber Tracks, Open ROPS/FOPS Cab  
Cab Hydraulic Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2C, 12.6" Rubber Tracks, A/C ROPS/FOPS Cab  
Mechanical Quick Coupler  
SVL75-2FC, 12.6" Rubber Tracks, A/C ROPS/FOPS Cab  
Mechanical Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2HC, 12.6" Rubber Tracks, A/C ROPS/FOPS Cab  
Hydraulic Quick Coupler  
SVL75-2HFC, 12.6" Rubber Tracks, A/C ROPS/FOPS Cab  
Hydraulic Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2WC, 15.0" Rubber Tracks, A/C ROPS/FOPS Cab  
Mechanical Quick Coupler  
SVL75-2FWC, 15.0" Rubber Tracks, A/C ROPS/FOPS Cab  
Mechanical Quick Coupler, High Flow Hydraulics & MF Grips  
SVL75-2HWC, 15.0" Rubber Tracks, A/C ROPS/FOPS Cab  
Cab Hydraulic Quick Coupler  
SVL75-2HFWC, 15.0" Rubber Tracks, A/C ROPS/FOPS Cab  
Cab Hydraulic Quick Coupler, High Flow Hydraulics & MF Grips

#### ENGINE

V3307 Kubota CR-TE4 Tier 4 Final Diesel Engine  
4 Cylinder, 4 Cycle, Turbo Charged  
74.3 Gross HP @ 2400 rpm (SAE J1995)