ISX™ 2200 Zero Turn Mowers

THE LEADER IN SUSPENSION TECHNOLOGY FOR TURF

Featuring the next generation of Ferris suspension technology – ForeFront™ Suspension, a 2-belt iCD™ cutting system, heavy-duty Hydro-Gear® drive system and travel speeds up to 10 mph, the ISX™ 2200 is engineered to increase efficiency and operator comfort.

Starting at \$11,549.00[^]

FIND A DEALER

Menu ▼

OVERVIEW

FEATURES

SPECIFICATIONS

ATTACHMENTS

RELATED PRODUCTS

Feature



Adjustable Cut Height

Foot-operated deck lift, with adjustable pedal, can change cut height in 1/4" increments from 1.5"- 5".

Specifications

5901843

5901845

Model Number

US MSRP *

Engine Brand

Engine Power Rating *

Displacement (cc)

PT0

Cylinders

Fuel Tank Capacity (gal)

Cutting Width (in)

Cutting Height (in)

Spindles

Suspension

•

Drive Axles (in)
Caster Tires (in)

Drive Tires (in)
Ground Speed-Fwd (mph)

Ground Speed-Rev (mph)
Overall Length (in)

Overall Width (in) Deflector Down/Deflector Up

Dry Weight (lbs)

Seat Package

Certified Roll-over Protection System

Controls / Safety Group

Parking Brake / Safety Circuit

Warranty (Engine) †

Warranty (Balance of Machine) †

5901845

\$12,099.00

Vanguard™ 810cc EFI with Oil Guard

28 gross hp

810

Electric

2

11 61

1.5 - 5

Cast Iron Greasable

ForeFront™ Suspension System - Front independent with four control

rods paired with large size adjustable coil over shocks and a rear swing

with large adjustable coilover shocks

1.375

13 x 6.5-6

24 x 12-12

0-10

0-5

83.63

78 / 61.5

1398

Premium high-back Suspension Seat with arm rests, adjustable lumbar

and back recline.

180° foldable

Seat activated engine kill, clutch safety switch, neutral and parking

brake safety circuit/adjustable twin steering controls

Hand operated Internal transaxie brake

3-Year limited manufacturer's warranty

4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coil-over-

shocks and all suspension related components are covered for 5 years

Menu ▼

OVER PER Construction
Transmission Type

FEATURES

Starter

SPECIFICATIONS System

Operator's Manuals

RELATED PRODUCTS

(Manageths) unlimited hours. Coverage on other components varies, please see operator's manual for complete details.

omotion and an adaptitude related components are correct for a years

iCD™ Cutting System, 2-Belt

Dual, commercial Hydro-Gear® ZT-4400™ Transaxles with 8.3" cooling fans

Electric

Standard

Illustrated Parts List - English (/na/en_us/product-catalog/zero-turn-mowers/isx-2200-zero-turn-

mowers/_jcr_content/tab/item_2/specifications.downloadmanual.5901845_II

• Operator's Manual - English (/na/en_us/product-catalog/zero-turn-mowers/isx-2200-zero-turn-

mowers/_jcr_content/tab/item_2/specifications.downloadmanual.5108441_E

Degrator's Manual - Spanish (/na/en_us/product-catalog/zero-turn-mowers/isx-2200-zero-turn-

mowers/_jcr_content/tab/item_2/specifications.downloadmanual.5108442_C

Miring Diagram Schematic - English (/na/en_us/product-catalog/zero-turn-mowers/isx-2200-zero-turn-

mowers/_jcr_content/tab/item_2/specifications.downloadmanual.5105535E(_LO.pdf.html)

† See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty.

Attachments



Fast-Vac® Triple Bag Collection System

The triple bag collection system is simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Available on 61" and 52" models.



^{*} Power rated by engine manufacturer.

^{*} Suggested prices will vary by market. Prices are show in U.S. dollars. Set-up, delivery, documentation and destination fees not included. See dealer for details. Features vary by model. We reserve the right to change specifications, features and pricing without notice.