
RC(M)5715 - 15' Heavy Duty Rotary Cutter

RETURNITOANDEX



Working Width: 15'

Transport Width: 10'3" Normal, 7'3" w/Narrow Option

Overall Width: 16' Overall Length: 16'3"

Hitch: Pull-Type, Self-Leveling Hitch & Clevis

Tongue Jack

Cutting Height*: 1-1/2" - 16"

Cutting Capacity: 5" Deck Height: 12"

Deck Thickness: 10 Gauge Top, 3/16" Bottom

Side Skirt Thickness: 1/4", Removable/Replaceable Gearbox Rating^: 250 HP Divider; 225 HP Center & Wings

Gearbox: 540 rpm or 1000 rpm

Gearbox Input Shaft: 1-3/4" 20 Spline

Gearbox Output Shaft: 3"

Input Driveline: Constant Velocity U-Joint Cat. 6,

Splined 540 or 1000 RPM

Connecting Driveline: Cat. 4 or 5 Slip-Clutch

Forged Diamond Blade Bar

Optional Stump-Jumper: 3/16", Round, Dish Shaped

Optional HD Blade Bar and Dishpans

Blades: 2 per Section, 1/2" x 4" Heat Treated

Free Swinging Alloy Steel with Uplift

Blade Bolt: Keyed with Hardened Flatwasher & Lock Nut

Blade Overlap: 6" Blade Speed:

540 rpm: Center & Wings: 16,400 fpm 1000 rpm: Center: 16,400; Wings: 16,000 fpm

6 or 8 Wheels with Suspension Options Wheel Options: 6" x 21" Laminated Tires 6" x 26" Laminated Tires

29" x 7.75" x 15" Used Aircraft Tires 24" x 7.7-10 Used A/C Foam-Filled Tires 25.5" New, Pneumatic or Foam-Filled

Tapered Roller Bearings & Cast Iron 5-Bolt Hubs

with 1-3/4" Shaft Wing Transport Locks

Wing Hydraulics:3" x 12" Cylinder, Hoses & Fittings Height Adjustments: 3-1/2" x 8" Cylinder, Hose, Fittings

& Flip-over Spacers

Skid Shoes: Wings & Center, Replaceable AR400 Beveled Front and Rear Shielding: Single or Double Chain

Blade Rotation: L-CW, C-CCW, R-CCW

Lights Standard

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	LIST PRICE	
RC5715-02-21-26-32- 40-60-65-70-90	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 6-21" Laminated Tires, HD Single Suspension Center and Wing Axles, CV, Cat 4 Wing, Chains, No Deck Rings, Single Acting Fold Cylinders, Constant Level Clevis Hitch, Diamond Blade Bar	5,104#	\$	24,341
RC5715-17-21-26-32- 40-60-65-75-90	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 6 24" used A/C FF, HD Single Suspension Center and Wing Axles, CV, Cat 4 Wing, Chalns, No Deck Rings, Single Acting Fold Cylinders, Performance Hitch, Diamond Blade Bar	5,421	\$	25,869
RC5715-18-24-29-32- 40-62-67-75-92	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 8-24" FFAC, Parallel Pivot Center and Wing Axles, CV, Cat 4 Wing, Chains, Deck Armor, Independent Fold Cylinders, Performance Hitch, HD Blade Bar/Dishpan	6,328#	\$	29,437
RC5715	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm	3,103#	\$	17,000
RCM5715	15' HEAVY-DUTY ROTARY CUTTER - 1000 rpm	3,103#	\$	17,000
ADD OPTION				
NUMBER	You Must Choose a Tire Option			
-02	21" Laminate, 6 Tires	420#	\$	958
-03	21" Laminate, 8 Tires	560#	\$	1,400
-05	25.5" Aircraft, 6 Tires	522#	\$	2,191
-06	25.5" Aircraft, 8 Tires	696#	\$	3,046
-08	29" Used Aircraft, 6 Tires	432#	\$	1,405
-09	29" Used Aircraft, 8 Tires	576#	\$	1,996
-11	25.5 New Aircraft, Foam-Filled 6 Tires	762#	\$	2,610
-12	25.5 New Aircraft, Foam-Filled 8 Tires	1,016#	\$	3,620
-14	26" Laminate, 6 Tires	520#	\$	1,787
-15	26" Laminate, 8 Tires	694#	\$	2,513
-17	24" Foam-Filled Aircraft, 6 Tires	732#	\$	2,446
-18 *Varies by tire ontion.	24" Foam-Filled Aircraft, 8 Tires	976#	\$	3,404

Varies by tire option.

See pg. 67 for available hitches

Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

^{*}Gearbox HP rating is based on in field use and performance See pg. 60 for optional pricing and color options

RC(M)5715 - 15' Heavy Duty Smooth Top



60-250 HP				
ADD OPTION	You Must Chases a Contra Aula Dation			
NUMBER -21	You Must Choose a Center Axle Option HD Single Suspension Center Axle	363#	ታ	1 070
-22	Independent Suspension Center Axie	459#	\$	1,870
-22 -23	Walking Tandem Center Axie	459# 4 9 7#	\$	2,220
-24	Parallel Pivot Center Axle	497# 443#	\$	2,720
-2-T	You Must Choose a Wing Axle Option	445#	\$	2,370
-26	HD Wing Axles (cannot be sold with option -22)	320#	\$	1,040
-27	Independent Suspension Wing Axles	418#	\$ \$	1,839
-28	Walking Tandem Wing Axles (Must have 8-Tire Option)	359#	\$	1,800
-29	Parallel Pivot Wing Axles (Must have 8-Tire Option)	360#	\$	2,120
	If 540 RPM - You Must Pick a Driveline Package		т	U/ILU
-32	540 CV Main, Cat 4 Wings	78#	\$	1,911
-34	540 CV Main, Cat 5 Wings	78#	\$	2,211
-37	1-3/8" CV Main with Over-Running Clutch, Cat. 4 Wings*	78#	\$	2,072
-38	1-3/8" CV Main with Over-Running Clutch, Cat. 5 Wings*	78#	\$	2,395
	If 1000 RPM - You Must Pick a Driveline Package	70#	4	2,555
-32	1000 1-3/8", CV Main, Cat 4 Wings	78#	.	1 011
-34	1000 1-3/8", CV Main, Cat 4 Wings	78# 78#	\$ \$	1,911 2,211
-35	1000 1-3/4", CV Main, Cat. 4 Wings	78# 78#		2,211
-36	1000 1-3/4", CV Main, Cat. 5 Wing	78#	₽ \$	2,441
-37	1000 1-3/8", CV Main with Over-Running Clutch, Cat 4 Wings*	78#	φ \$	2,072
-38	1000 1-3/8", CV Main with Over-Running Clutch, Cat. 5 Wings*	78#	\$	2,395
50	You Must Choose One Guard	70	4	2,000
-40	Single Chains - Front & Rear	208#	\$	607
-41	Double Chains - Front & Rear	312#	\$	802
42	You May Choose These Options	522	Ψ.	002
-55	Mechanical Winch	44#	\$	425
-56	Tool Box	88#	\$	462
-57	Tow Lugs	20#	\$	57
	You Must Choose a Deck Ring Option		•	
-60	No Deck Rings	0#	\$	0
-61	Deck Rings	195#	\$	700
-62	Deck Armor™	368#	\$	700
	You Must Choose a Fold Option			
-65	Single-acting Fold Cylinders (3") (1 hose)	75#	\$	640
-66	Dual-acting Fold Cylinders (3") for Narrow Transport (2 hoses)	84#	\$	725
-67	Independent Single-acting Fold Cylinders (3") (2 hose)	80#	\$	685
-68	Independent Dual-acting Fold Cylinders (3") for Narrow Transport (4 hoses)	96#	\$	810
	You Must Choose a Hitch Clevis Option			
-70	Constant Level Clevis Hitch	57#	\$	315
-72	Bar-tite Hitch	69#	\$	469
-73	Constant Level Pintle Hitch	71#	\$	460
-74	Ball Hitch 2-5/16"	28#	\$	194
-75	Performance Hitch, Self-leveling	62#	\$	355
	You May Choose a Color Option (No Option=Buckskin)			
-81	Green			N/C
-82	Orange			
-83	Red			
-86	Yellow			
	You Must Choose a Blade Carrier Option			
-90	Diamond Blade Bar	480#	\$	0
-91	Bolt-on Dishpans	605#	\$	206
-92	HD Blade Bar and Dishpans	650#	\$	285
-94	Shredder Kit, Stacked Blades	583#	\$	1,071

*Over-running clutch recommended for tractors with instant off PTO ^Gearbox HP rating is based on in field use and performance Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.