
RC(M)5715 - 15' Heavy Duty Rotary Cutter

RETURN TO INDEX



Working Width: 15'

Transport Width: 10'3" Normal, 7'3" w/Narrow Option

Overall Width: 16' Overall Length: 16'3"

Hitch: Pull-Type, Self-Leveling Hitch & Clevis

Tongue Jack

Cutting Height*: 1-1/2" - 16"

Cutting Capacity: 5" Deck Height: 12"

Deck Thickness: 10 Gauge Top, 3/16" Bottom Side Skirt Thickness: 1/4", Removable/Replaceable Gearbox Rating^: 250 HP Divider; 225 HP Center & Wings

Gearbox Rating**: 250 nr bivider, 225 n Gearbox: 540 rpm or 1000 rpm Gearbox Input Shaft: 1-3/4" 20 Spline

Gearbox Output Shaft: 3"

Input Driveline: Constant Velocity U-Joint Cat. 6,

Splined 540 or 1000 RPM

Connecting Driveline: Cat. 4 or 5 Slip-Clutch

Forged Diamond Blade Bar

Optional Stump-Jumper: 3/16", Round, Dish Shaped

Optional HD Blade Bar and Dishpans

Blades: 2 per Section, 1/2" x 4" Heat Treated

Free Swinging Alloy Steel with Uplift

Blade Bolt: Keyed with Hardened Flatwasher & Lock Nut

Blade Overlap: 6" Blade Speed:

540 rpm: Center & Wings: 16,400 fpm 1000 rpm: Center: 16,400; Wings: 16,000 fpm

6 or 8 Wheels with Suspension Options Wheel Options: 6" x 21" Laminated Tires 6" x 26" Laminated Tires

29" x 7.75" x 15" Used Aircraft Tires 24" x 7.7-10 Used A/C Foam-Filled Tires 25.5" New, Pneumatic or Foam-Filled

Tapered Roller Bearings & Cast Iron 5-Bolt Hubs

with 1-3/4" Shaft Wing Transport Locks

Wing Hydraulics:3" x 12" Cylinder, Hoses & Fittings Height Adjustments: 3-1/2" x 8" Cylinder, Hose, Fittings

& Flip-over Spacers

Skid Shoes: Wings & Center, Replaceable AR400 Beveled Front and Rear Shielding: Single or Double Chain

Blade Rotation: L-CW, C-CCW, R-CCW

Lights Standard

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT		IST RICE
RC5715-02-21-26-32- 40-60-65-70-90	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 6-21" Laminated Tires, HD Single Suspension Center and Wing Axles, CV, Cat 4 Wing, Chains, No Deck Rings, Single Acting Fold Cylinders, Constant Level Clevis Hitch, Diamond Blade Bar	5,104#	\$	24,341
RC5715-17-21-26-32- 40-60-65-75-90	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 6 24" used A/C FF, HD Single Suspension Center and Wing Axles, CV, Cat 4 Wing, Chains, No Deck Rings, Single Acting Fold Cylinders, Performance Hitch, Diamond Blade Bar	5,421	\$	25,869
RC5715-18-24-29-32- 40-62-67-75-92	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm 8-24" FFAC, Parallel Pivot Center and Wing Axles, CV, Cat 4 Wing, Chains, Deck Armor, Independent Fold Cylinders, Performance Hitch, HD Blade Bar/Dishpan	6,328#	\$	29,437
RC5715	15' HEAVY-DUTY ROTARY CUTTER - 540 rpm	3,103#	\$	17,000
RCM5715	15' HEAVY-DUTY ROTARY CUTTER - 1000 rpm	3,103#	\$	17,000
ADD OPTION				
NUMBER	You Must Choose a Tire Option	470.4		050
-02	21" Laminate, 6 Tires	420#	\$	958
-03	21" Laminate, 8 Tires	560# 522#	\$	1,400
-05	25.5" Aircraft, 6 Tires	522# 696#	\$ *	2,191
-06 -08	25.5" Aircraft, 8 Tires 29" Used Aircraft, 6 Tires	696# 432#	\$ \$	3,046 1,405
-09	29" Used Aircraft, 8 Tires	· 576#	э \$	1,996
-11	25.5 New Aircraft, Foam-Filled 6 Tires	; 376# 762#	\$	2,610
-12	25.5 New Aircraft, Foam-Filled 8 Tires	1,016#	\$	3,620
-12 -14	26" Laminate, 6 Tires	520#	\$	1,787
-15	26" Laminate, 8 Tires	694#	\$	2,513
-17	24" Foam-Filled Aircraft, 6 Tires	732#	\$	2,446
-18	24" Foam-Filled Aircraft, 8 Tires	976#	\$	3,404
*Varies by tire ontion.		VARNINGI	<u> </u>	-,,,,,

*Varies by tire option.

^Gearbox HP rating is based on in field use and performance

See pg. 60 for optional pricing and color options

See pg. 67 for available hitches

Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

RC(M)5715 - 15' Heavy Duty Smooth Top

TO RETURN TO INDEX

60-250 HP				
ADD OPTION				
NUMBER	You Must Choose a Center Axle Option			
-21	HD Single Suspension Center Axie	363#	\$	1,870
-22	Independent Suspension Center Axle	459#	\$	2,220
-23	Walking Tandem Center Axle	497#	\$	2,720
-24	Parallel Pivot Center Axle	443#	\$	2,370
	You Must Choose a Wing Axle Option			
-26	HD Wing Axles (cannot be sold with option -22)	320#	\$	1,040
-27	Independent Suspension Wing Axles	418#	\$	1,839
-28	Walking Tandem Wing Axles (Must have 8-Tire Option)	359#	\$	1,800
-29	Parallel Pivot Wing Axles (Must have 8-Tire Option)	360#	\$	2,120
20	If 540 RPM - You Must Pick a Driveline Package	70.4	_	4.044
-32 -34	540 CV Main, Cat 4 Wings	78#	\$	1,911
	540 CV Main, Cat 5 Wings	78#	\$	2,211
-37	1-3/8" CV Main with Over-Running Clutch, Cat. 4 Wings*	78#	\$	2,072
-38	1-3/8" CV Main with Over-Running Clutch, Cat. 5 Wings*	78#	\$	2,395
	If 1000 RPM - You Must Pick a Driveline Package			
-32	1000 1-3/8", CV Main, Cat 4 Wings	78#	\$	1,911
-34	1000 1-3/8", CV Main, Cat 5 Wings	78#	\$	2,211
-35 -36	1000 1-3/4", CV Main, Cat. 4 Wings 1000 1-3/4", CV Main, Cat. 5 Wing	78#	\$	2,148
-37	1000 1-3/4", CV Main, Cat. 5 Willig 1000 1-3/8", CV Main with Over-Running Clutch, Cat 4 Wings*	78# 78#	\$	2,441
-38	1000 1-3/8", CV Main with Over-Running Clutch, Cat. 4 Wings*	78#	\$ \$	2,072 2,395
-36	You Must Choose One Guard	70#	Ψ	2,393
-40	Single Chains - Front & Rear	208#	\$	607
-41	Double Chains - Front & Rear	312#	\$	802
	You May Choose These Options	Jan.	4	002
-55	Mechanical Winch	44#	\$	425
-56	Tool Box	88#	\$	462
-57	Tow Lugs	20#	\$	57
	You Must Choose a Deck Ring Option			
-60	No Deck Rings	0#	\$	0
-61	Deck Rings	195#	\$	700
-62	Deck Armor™	368#	\$	700
	You Must Choose a Fold Option			
-65	Single-acting Fold Cylinders (3") (1 hose)	75#	\$	640
-66	Dual-acting Fold Cylinders (3") for Narrow Transport (2 hoses)	84#	\$	725
-67	Independent Single-acting Fold Cylinders (3") (2 hose)	80#	\$	685
-68	Independent Dual-acting Fold Cylinders (3") for Narrow Transport (4 hoses)	96#	\$	810
-70	You Must Choose a Hitch Clevis Option Constant Level Clevis Hitch	57#		315
-70 -72	Bar-tite Hitch	57# 69#	\$ \$	469
-72 -73	Constant Level Pintle Hitch	71#		460
-74	Ball Hitch 2-5/16"	28#	\$	194
-75	Performance Hitch, Self-leveling	62#	\$	355
	You May Choose a Color Option (No Option=Buckskin)		•	
-81	Green			N/C
-82	Orange			11,0
-83	Red			
-86	Yellow			
	You Must Choose a Blade Carrier Option			
-90	Diamond Blade Bar	480#	\$	0
-91	Bolt-on Dishpans	605#	\$	206
-92	HD Blade Bar and Dishpans	650#	\$	285
-94	Shredder Kit, Stacked Blades	583#	\$	1,071

*Over-running clutch recommended for tractors with instant off PTO

^Gearbox HP rating is based on in field use and performance

Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

ITEM #215 MOWER 15 FT. FLEX WING ROTARY MOWER LANDPRIDE RC5715

UP GRADE / DOWN GRADE OPTIONS

Model	Туре	Sales model & description	PRICE	
RC5715 ,	BASE SPEC	15 FOOT HEAVY DUTY SMOOTH TOP FLEX WING ROTARY CUTTER BASE SPEC	\$	15,750.00
RC5610	DOWN GRADE	10 FOOT FLEX WING OFF SET IN LIEU OF 15 FT	\$	(1,000.00)
RC4715	DOWN GRADE	15 FOOT MEDIUM DUTY SMOOTH TOP FLEX WING WITH SAME SIZE GEAR BOXES AS BASE SPEC	\$	(1,500.00)
RCF3610	DOWN GRADE	10 FOOT PULL TYPE OR 3 POINT HITCH TYPE	\$	(3,850.00)
RC5020	UPGRADE	20 FOOT FLEX WING SMOTH TOP ROTARY CUTTER	\$	5,900.00
	<u> </u>			
				,
1				