

RTV-X900G General Purpose Models

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE
Model Kubota D902
3 Cyl. 54.8 cu in
+21.6 Gross Eng HP
60 Amp Alternator

TRANSMISSION
VHT-X
Variable Hydro Transmission
Forward Speeds:
Low 0 - 15 mph
High 0 - 25 mph
Reverse 0 - 17 mph
Limited-slip Front Differential
Rear differential lock

HYDRAULICS
Hydrostatic Power Steering
Hydraulic Oil Cooler

FLUID CAPACITY
Fuel Tank 7.9 gal
Cooling 6.4 qts
Engine Oil 3.3 qts
Transmission Oil 1.8 gal
Brake Fluid 0.4 qts

TIRES AND WHEELS
ATV Tire 25 x 10 - 12, 6 ply
Turf Tire 25 x 12 - 12, 4 ply
Heavy Duty Worksite 25 x 10 - 12, 6 ply

DIMENSIONS
Width 63.2 in
Height 79.5 in
Length 120.3 in
Wheelbase 80.5 in
Tow Capacity 1300 lbs.
Ground Clearance 10.4 in
Suspension Travel 8 in
Turning Radius 13.1 ft.

CARGO BOX
Width 57.7in
Length 40.5 in
Depth 11.2 in
Load Capacity 1102 lbs.
Vol. Capacity 15.2 cu ft.

KEY FEATURES
Digital Multimeter
Front Independent Adjustable Suspension
Rear Independent Adjustable Suspension
Brakes - Front/Rear Wet Disc
Rear Brake Lights / Front Headlights
2" Hitch Receiver, Front and Rear
Dark gray deluxe 60/40 split bench seats
Open glove box (lid/lock optional)
Front radiator guard (center section only)
Deluxe 60/40 split bench seats
Underseat Storage Compartments

SAFETY EQUIPMENT
SAE J2194 & OSHA 1928 ROPS
Dash-mounted Parking Brake
Horn
Spark Arrestor Muffler
Retractable 2-point Seat Belts
Rear Protective Screen

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
RTV-X900G-A	Utility Vehicle - General Purpose with ATV Tires		1907	\$13,699.00