







7-GAUGE STEEL CUTTING DECK WITH 7-GAUGE TOP AND BOTTOM REINFORCEMENTS

MAINTENANCE-FREE SEALED SPINDLES

KAWASAKI® FX850V 852cc / 27 HP\*\*

DUAL PARKER HTJ 12cc PUMP / 260cc WHEEL MOTOR

3-YEAR, NO-HOUR-LIMIT WARRANTY / 5-YEAR, 1,750 HOUR LIMITED DECK WARRANTY\*

# BUILT IN AMERICA SINCE 1961 Cub Cadet



# **CUTS EVERYTHING, INCLUDING DOWNTIME.**

Every single part of the PRO Z 500 Series is designed to handle the serious rigors of the job. Armed with an efficient engine, larger fuel capacity and an industry-leading commercial cutting deck, this zero-turn lineup allows you to maximize your workday and deliver a flawless cut in a single pass.



### **Optimized Performance**

If you're looking to maximize your workday, look no further. High-torque commercial transmissions are paired with high-horsepower commercial-grade engines to provide optimal and consistent blade tip speed. So you can power through the thickest grass in one pass at maximum speed.



### **Industry-Leading Deck Strength**

Tackle the toughest conditions with the industry's only triple-7-gauge steel cutting deck: a 7-gauge deck shell with 7-gauge top and bottom reinforcements. All backed by a 5-year limited warranty.



### **All-Day Comfort**

Absorb the impact of rough terrain with a front-end construction that features an industry-leading combination of axle, hub and yoke size. Paired with a high-back EVC cushion seat with angle control which adds support for the long haul.



Your Independent Dealer - Expert Service. Locally Owned.

SELECTION GUIDE	PRO Z 554 L/S KW	PRO Z 560 L/S KW
ENGINE AND DRIVE SYSTEM		
Engine/Manufacturer	Kawasaki	FX850v
Horsepower	27 hp**	
Displacement	852cc	
Fuel Capacity	14.9 gal (twin 7.45 gal tanks) with dial gauge	
Transmission	12cc Parker® HTJ pump v	vith hydro release lever
Ground Speed (forward / reverse)	Up to 10 mp	h / 5 mph
MOWER DECK		
Cutting Width	54"	60"
Deck Shell Construction	Floating, fabricated	7 ga (0.187") steel
$\begin{array}{l} \textbf{Reinforcements} \; (\text{top / bottom} - \text{leading} \\ \text{edge}) \end{array}$	7 ga / 7 ga – 1/4"	
Side Reinforcement	5/16" steel	
Wear Guard	3/4" trim-side (polymer)	
Blades / Blade-Tip Speed	3 high-lift Marbain blades	s / 18,500 fpm (approx.)
Spindle Construction	8" sealed cast-aluminum ho	ousing (maintenance-free)
Discharge Chute	High-density, impact-resistant rubber	
Deck Lift System	Foot pedal with spring assist	
Height Positions / Height Range	16 / 1" – 5"	
CHASSIS		
ROPS	2" x 2" quick-latch toolless foldable 3-position	
Rear Bumper	5/16"-thick steel, standard rear hitch (e-coated)	
Additional Bumper Features	Pre-drilled mounts for attachments	
Frame	Fully welded, 3/8" x 5" laser-cut steel full-length (e-coated	
Additional Frame Features	Integrated tie-down slots	
Front Axle	2" x 3" solid steel with sealed ball bearing	
Front Yoke	1/2"-thick steel with sealed ball bearings	
OPERATION		
РТО	Warner PTO clutch (125 ft-lb)	
Steering Control (L/S models)	Lap bar / adjustable tilting steering wheel with electronic power steering (EPS)	
Operator Controls	Low-profile throttle lever with dash guard	
Additional Controls	Sealed key switch / fingertip engagement PTO / resettable maintenance meter	
Parking Brake (L/S models)	Hand operated with hydro-pump release	
Front Tires (L/S models)	Smooth 13" x 6.5" – 6" / turf 15" x 6" – 6"	
Rear Tires (L/S models)	Turf 24" x 12" – 12"	
Seat Type	High-back dial suspension with EVC cushion, seat belt, angle-back adjust and armrests	
DIMENSIONS		
Length	84"	
Width (chute down / up)	56" / 67"	62" / 73"
Height (ROP down / up)	50" /	74"
Weight	1,300 / 1,438 lbs	1,324 / 1,462 lbs
WARRANTY		
Warranty Information*	3-year, no-hour-limit warranty 5-year, 1,750-hour limited deck warranty	

Cub Cadet commercial products are intended for professional use. This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual and on the machine. Models subject to limited availability. Images may not reflect dealer inventory and/or unit specifications. Specifications subject to change without notice.



<sup>\*3-</sup>year unit warranty, unlimited hours. 5-year deck warranty up to 1,750 hours. For full warranty details and exclusions, visit www.cubcadet.com or your local dealer.

\*As required by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International.

\*Built using the highest quality components sourced locally and globally.

\*73-XXXXX | Printed in U.S.A. | © 2020 Cub Cadet









7-GAUGE STEEL CUTTING DECK WITH 7-GAUGE TOP AND BOTTOM REINFORCEMENTS

MAINTENANCE-FREE SEALED SPINDLES

KAWASAKI® FX850V-EFI 852cc / 29.5 HP (60"DECK) KAWASAKI® FX921V 999cc / 31 HP (60"/72" DECK)\*\*

DUAL PARKER HTG 14cc PUMP / 280cc WHEEL MOTOR

3-YEAR, NO-HOUR-LIMIT WARRANTY / 5-YEAR, 1,750 HOUR LIMITED DECK WARRANTY\*





# MAKE EASY WORK OF A HARD DAY.

Every single part of the PRO Z 700 Series is designed to handle the serious rigors of the job. From the thickness of the cutting deck to the all-around heavy-duty construction, this zero-turn lineup will last for the long haul. Step up to greater horsepower, higher top speeds, more comfort, and larger deck options.



# **Optimized Performance**

If you're looking to maximize your workday, look no further. High-torque commercial transmissions are paired with high-horsepower commercial-grade engines to provide optimal and consistent blade tip speed. So you can power through the thickest grass in one pass at maximum speed.



### **Industry-Leading Deck Strength**

Tackle the toughest conditions with the industry's only triple-7-gauge steel cutting deck: a 7-gauge deck shell with 7-gauge top and bottom reinforcements. All backed by a 5-year limited warranty:



### **All-Day Comfort**

Let the PRO Z 700 absorb the punches so your body doesn't have to. Its pivoting front axle with isolation-dampening system mounts allows the front end of the PRO Z to ride across unknown terrain while protecting the quality of the cut.



Your Independent Dealer - Expert Service. Locally Owned.

SELECTION GUIDE	PRO Z 760 L/S KW	PRO Z 772 L KW
ENGINE AND DRIVE SYSTEM		
Engine/Manufacturer	Kawasaki FX921v	
Horsepower	31 hp**	
Displacement	999cc	
Fuel Capacity	14.9 gal (twin 7.45 gal tanks) with electric gauge	
Transmission	14cc Parker HTG pump with hydro release lever	
Ground Speed (forward / reverse)	Up to 12 mph / 6 mph	
MOWER DECK		
Cutting Width	60"	72"
Deck Shell Construction	Floating, fabricated 7 ga (0.187") steel	
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	7 ga / 7 ga – 1/4"	
Side Reinforcement	5/16" steel	
Wear Guard	3/4" trim-side (polymer)	
Blades / Blade-Tip Speed	3 high-lift Marbain blades / 18,500 fpm (approx.)	
Spindle Construction	8" sealed cast-aluminum housing (maintenance-free)	
Discharge Chute	High-density, impa	ct-resistant rubber
Deck Lift System	Foot pedal wit	h spring assist
Height Positions / Height Range	16 / 1" – 5"	
CHASSIS		
ROPS	2" x 2" quick-latch toolless foldable 3-position	
Rear Bumper	5/16"-thick steel, standard rear hitch (e-coated)	
Additional Bumper Features	Pre-drilled mounts for attachments	
Frame	Fully welded, 3/8" x 5" laser-cut steel full-length (e-coated)	
Additional Frame Features	Integrated tie-down slots	
Front Axle	2" x 3" solid steel with sealed ball bearings and isolation-dampening system	
Front Yoke	1/2"-thick steel with sealed ball bearings	
OPERATION		
РТО	Warner PTO clutch (200 ft-lb) with Soft-Start	Warner PTO clutch (225 ft-lb) with Soft-Start
Steering Control (L/S models)	Lap bar / adjustable tilting steering wheel with EPS	
Operator Controls	Low-profile throttle lever with dash guard	
Additional Controls	Sealed key switch / fingertip engagement PTO / resettable maintenance meter	
Parking Brake (L/S models)	Hand operated with hydro-pump release	
Front Tires (L/S models)	Smooth (run flat) 13" x 6.5" – 6" / turf 16" x 6.5" – 8"	
Rear Tires (L/S models)	Turf 24" x 12" – 12"	
Seat Type	High-back dial suspension, EVC cushion, seat belt, angle-back adjust, lumbar support, padded armrests, isolation-dampening system mounted base (lateral suspension)	
DIMENSIONS		
Length	86	6"
Width (chute down / up)	62" / 73"	74" / 85"
Height (ROP down / up)	52" /	/ 74"
Weight	1,424 / 1,562 lbs	1,475 / 1,613 lbs
WARRANTY		
Warranty Information*	3-year, no-hour-limit warranty   5-year, 1,750-hour limited deck warranty	

Cub Cadet commercial products are intended for professional use. This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual and on the machine. Models subject to limited availability. Images may not reflect dealer inventory and/or unit specifications. Specifications subject to change without notice.



<sup>\*3-</sup>year unit warranty, unlimited hours. 5-year deck warranty up to 1,750 hours. For full warranty details and exclusions, visit www.cubcadet.com or your local dealer.

\*As required by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International.

\*Built using the highest quality components sourced locally and globally.

\*73-XXXXX | Printed in U.S.A. | © 2020 Cub Cadet









HIGH BACK AIR-RIDE SUSPENSION SEAT

7-GAUGE STEEL CUTTING DECK WITH 7-GAUGE TOP AND BOTTOM REINFORCEMENTS

MAINTENANCE-FREE SEALED SPINDLES

KAWASAKI® FX1000V 999cc / 35 HP ENGINE\*\*

DUAL PARKER HTG 16cc PUMP / 310cc WHEEL MOTOR

3-YEAR, NO-HOUR-LIMIT WARRANTY / 5-YEAR, 1,750 HOUR LIMITED DECK WARRANTY\*





# A CUT ABOVE THE REST.

Every single part of the PRO Z 900 Series is designed to handle the serious rigors of the job. From the thickness of the cutting deck to the all-around heavy-duty construction, this zero-turn lineup will last for the long haul. Step into best-in-class professional strength and performance while riding in unrivaled comfort.



# **Optimized Performance**

If you're looking to maximize your workday, look no further. High-torque commercial transmissions are paired with high-horsepower commercial-grade engines to provide optimal and consistent blade tip speed. So you can power through the thickest grass in one pass at maximum speed.



### **Industry-Leading Deck Strength**

Tackle the toughest conditions with the industry's only triple-7-gauge steel cutting deck: a 7-gauge deck shell with 7-gauge top and bottom reinforcements. All backed by a 5-year limited warranty:



### Work Hard, Ride Easy

Experience a smooth ride all day long with the PRO Z comfort features. Our exclusive air-ride seat allows riders to adjust seat firmness to their personal preference. The isolation dampening system under the seat reduces vibration, while angle adjustment and lumbar support give a custom feel.



### Your Independent Dealer - Expert Service. Locally Owned.

SELECTION GUIDE	PRO Z 960 L/S KW	PRO Z 972 L/S KW	
ENGINE AND DRIVE SYSTEM	FRO 2 700 L/3 KW	FRO 2 912 L/3 KW	
Engine/Manufacturer	Kawasaki I	FX1000v	
Horsepower	35 h		
Displacement	999		
Fuel Capacity			
Transmission	-	14.9 gal (twin 7.45 gal tanks) with electric gauge 16cc Parker HTG pump with hydro release lever	
Ground Speed (forward / reverse)	Up to 14 mph / 7 mph		
MOWER DECK			
Cutting Width	60"	72"	
Deck Shell Construction	Floating, fabricated	7 ga (0.187") steel	
Reinforcements (top / bottom — leading edge)	7 ga / 7 ga – 1/4"		
Side Reinforcement	5/16" steel		
Wear Guard	3/4" trim-side (polymer)		
Blades / Blade-Tip Speed	3 high-lift Marbain blades	3 high-lift Marbain blades / 18,500 fpm (approx.)	
Spindle Construction	8" sealed cast-aluminum housing (maintenance-free)		
Discharge Chute	High-density, impact-resistant rubber		
Deck Lift System	Foot pedal with	Foot pedal with spring assist	
Height Positions / Height Range	16 / 1"	16 / 1" – 5"	
CHASSIS			
ROPS	2" x 2" quick-latch toolless foldable 3-position		
Rear Bumper	5/16"-thick steel, standard rear hitch (e-coated)		
Additional Bumper Features	Pre-drilled mounts for attachments		
Frame	Fully welded, 3/8" x 5" laser-cut steel full-length (e-coated)		
Additional Frame Features	-	Integrated tie-down slots	
Front Axle		2" x 3" solid steel with sealed ball bearings and isolation-dampening system	
Front Yoke	1/2"-thick steel with s	sealed ball bearings	
OPERATION			
РТО	Warner PTO clutch (200 ft-lb) with Soft-Start	Warner PTO clutch (225 ft-lb) with Soft-Start	
Steering Control (L/S models)	Lap bar / adjustable tilting steering wheel with EPS		
Operator Controls	Low-profile throttle lever with dash guard		
Additional Controls	Sealed key switch / fingertip engagement PTO / resettable maintenance meter		
Parking Brake (L/S models)	Hand operated with hydro-pump release		
Front Tires (L/S models)	Smooth (run flat) 15" x 6" - 6" / turf 16" x 6.5" - 8"		
Rear Tires (L/S models)	Turf 26" x 12" – 12"		
Seat Type	High-back air-ride suspension, EVC cushion, seat belt, angle-back adjust, lumbar support, padded armrests, isolation-dampening system mounted base (lateral suspension)		
DIMENSIONS			
Length	88		
Width (chute down / up)	62" / 73"	74" / 85"	
Height (ROP down / up)	48" / 75"	52" / 75"	
Weight	1,442 / 1,580 lbs	1,591 lbs / 1,631 lbs	
WARRANTY			
Warranty Information*	3-year, no-hour-limit warranty   5-year, 1,750-hour limited deck warranty		

Cub Cadet commercial products are intended for professional use. This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual and on the machine. Models subject to limited availability. Images may not reflect dealer inventory and/or unit specifications. Specifications subject to change without notice.









DUAL REAR WHEELS WITH ULTRA TRACTION CONTROL TREAD

FOUR-WHEEL STEERING WITH EPS (Electronic Power Steering)

7-GAUGE STEEL CUTTING DECK WITH 7-GAUGE TOP AND BOTTOM REINFORCEMENTS

MAINTENANCE-FREE SEALED SPINDLES

ELECTRONIC POWERED DECK LIFT INCLUDED

12-VOLT OUTLET KIT INCLUDED


3-YEAR, NO-HOUR-LIMIT LIMITED COMMERCIAL WARRANTY / 5-YEAR, 1,750 HOUR DECK ASSEMBLY WARRANTY\*





# MADE TO MAKE THE GRADE.

The PRO Z 972 SD and 972 SDL are dual-wheel commercial zero-turn mowers engineered to dominate steep hills up to a 25-degree slope. With unmatched triple-7-gauge deck construction, maintenance-free spindles, superior cutting performance and air-ride seat comfort, these best-in-class mowers are the ultimate mowing solution for municipalities, commercial cutters and properties with varying terrain.



### **Unmatched Hillside Confidence**

Oversized dual rear wheels provide a higher level of stability and precision. The one-of-its-kind drive system with four-wheel steering provides ultimate control, so you can comfortably mow a straight line, execute zero-degree turns and operate on a hillside up to a 25-degree slope.



### **Industry-Leading Deck Strength**

Tackle the toughest conditions with the industry's only triple-7-gauge steel cutting deck: a 7-gauge deck shell with 7-gauge top and bottom reinforcements. All backed by a 5-year limited warranty.



### Work Hard. Ride Easy.

Experience a smooth ride all day long with the PRO Z comfort features. Our exclusive air-ride seat allows riders to adjust seat firmness to their personal preference. The isolation dampening system under the seat reduces vibration, while angle adjustment and lumbar support give a custom feel.



Your Independent Dealer - Expert Service. Locally Owned.



NEW

		NEW
SELECTION GUIDE	PRO Z 972 SD	PRO Z 972 SDL
MOWER DECK		
Cutting Width	72	2"
Deck Construction	Floating, fabricated 7 ga (0.187") steel and adjustable rear striping rollers	
Reinforcements (top/bottom — leading edge)	7 ga / 7 ga — 1/4"	
Side Reinforcement	5/16" steel	
Wear Guard	3/4" trim-side (polymer)	
Blades / Blade-Tip Speed (fpm)	3 high-lift 25" Marbain® blades / Approx. 18,500 fpm blade tip speed	
Spindle Construction	Maintenance-free cast aluminum housing	
Discharge Chute	High-density impact-resistant rubber	
Deck Lift System	Electro-hydraulic as	sist quick-lift design
Height Positions / Height Range	16 / 1*	" — 5"
ENGINE & DRIVE SYSTEM		
Engine/Manufacturer	Kawasaki® FX1000v	
Horsepower	35 hp <sup>†</sup>	
Displacement	999cc	
Fuel Capacity	Twin 7.45 gal tanks (14.9 gal total) with electronic dual gauge read-out	
Electrical / Battery	-	310CCA AGM battery; Relay/Fuse terminal block; 30 AMP voltage regulator
Transmission	Parker® heavy duty HTG 16cc pump / 18.9 cu. ir	n. wheel motors with oversized wheel bearings
Ground Speed (forward/reverse)	Up to 12 m	ph / 6 mph
DIMENSIONS		
Length	88	8"
Width (chute down / up)	74" /	/ 85"
Height (ROP down / up)	49" / 75"	
Weight	1,850 lbs	1,885 lbs
GENERAL		
PTO PTO	Warner PTO clu	utch (225 ft-lbs)
Steering Control	Quick-adjust steering co	olumn w/ power steering
Operator Controls	Low-profile 1	throttle lever
Additional Controls	Sealed key switch / fingertip	engagement PTO / 12v outlet
Parking Brake	Hand-operated / with	n hydro-pump release
ROPS	2" x 2" foldable 3-pos	sition with low profile
Rear Bumper	5/16" thick steel, standard rear hitch	
Additional Bumper Features	Pre-drilled mounts for attachments	
Frame	Fully welded, 3/8" x 5" laser-cut steel	
Additional Frame Features	Integrated tie-down slots	
Safety Lighting	-	6 LED Lights for 360 degrees of lighted visibility; Amber Beacon with three position adjustments
Front Axle/Yolk	2" x 3" solid with Isolation dam	npening system, 1/2" thick steel
Front Tires	Turf 16" x 6.5" – 8" with weighted rim	
Rear Tires	Terra Trac Tread 25" x 9" - 12" Rear dual-wheel design with 18" traction width per side	
Seat Type	High-back air-ride suspension, EVC cushion, seat belt, angle-back adjust, lumbar support, padded armrests, isolation dampening system mounted base (lateral suspension)	
Seat Control Swivel	<del>-</del>	User-controlled lock/unlock swivel seat for operator leveling up to 30-degrees total/15-degrees left or right travel
WARRANTY		
Warranty Information	3-year / no-hour-limit commercial 5-year / 1,750-hour deck construction	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications. Cub Cadet commercial products are intended for professional use.

\*3-year unit warranty, unlimited hours. 5-year deck warranty up to 1,750 hours. For full warranty details and exclusions, visit www.cubcadet.com or your local dealer.

\*4-S required by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International.

\*Built using the highest quality components sourced locally and globally.

\*773-09114 | Printed in U.S.A. | @ 2020 Cub Cadet

