

 $Q \equiv$

OVERVIEW

FEATURES

SPECIFICATIONS

ATTACHMENTS

RELATED PRODUCTS





ISX™ 2200 Zero Turn Mowers

THE LEADER IN SUSPENSION TECHNOLOGY FOR TURF

Featuring the next generation of Ferris suspension technology – ForeFront™ Suspension, a 2-belt iCD™ cutting system, heavy-duty Hydro-Gear® drive system and travel speeds up to 10 mph, the ISX™ 2200 is engineered to increase efficiency and operator comfort.

Starting at \$11,549.00[^]

FIND A DEALER (/na/en_us/support/dealer-locator.html)

Features

Menu **▼**

OVERVIEW

FEATURES

SPECIFICATIONS

ATTACHMENTS

RELATED PRODUCTS



Forefront™ Suspension System (https://youtu.be/N9RqP1sAU7Q)

The system utilizes four upper and lower control rods and mower-specific shocks that ensure the front caster bearing remains vertical through the full range of travel. This controlled motion results in a smoother ride, more precise tracing of the terrain and an improved cut.



Ride-On Mower Warranties

Coil-Over-Shocks and all suspension-related components are covered for 5 years (60 months), for unlimited hours. We are committed to providing performance, productivity and durability.



Menu **▼**

Redesigned Rear Bumper
Feature
The redesigned rear bumper provides

additional ground clearance for moving over curbs and loading trailers. Higher side walls protect the engine while maintaining easy

service access.

OVERVIEW

FEATURES

SPECIFICATIONS

ATTACHMENTS

RELATED PRODUCTS



500 Hour Oil Change

Vanguard™ Engines with Oil Guard System reduce maintenance time and costs by up to 60%.**



Drive System

Dual, commercial Hydro-Gear ZT-4400 transaxles deliver unmatched power and durability.

Menu **▼**

OVERVIEW

FEATURES

SPECIFICATIONS

ATTACHMENTS

RELATED PRODUCTS



Adjustable Cut Height

Foot-operated deck lift, with adjustable pedal, can change cut height in 1/4" increments from 1.5"- 5".

Specifications

5901843



Model Number 5901843 5901845 \$11,549.00 \$12,099.00 US MSRP ^ Vanguard™ 810cc EFI with Oil Vanguard™ 810cc EFI with Oil **Engine Brand** Guard Guard **Engine Power Rating *** 28 gross hp 28 gross hp Displacement (cc) 810 810 Electric Electric PT0 **Cylinders** 2 2 Fuel Tank Capacity (gal) 11 11

Mewiting-Width (in)	52	Feature	61
OVERWhg Height (in)	1.5 - 5		1.5 - 5
FEATURES Spindles SPECIFICATIONS	Cast Iron Greasable		Cast Iron Greasable
Suspension ATTACHMENTS RELATED PRODUCTS	ForeFront™ Suspension System - Front independent with four control rods paired with large size adjustable coil over shocks and a rear swing with large adjustable coilover shocks		ForeFront™ Suspension System - Front independent with four control rods paired with large size adjustable coil over shocks and a rear swing with large adjustable coilover shocks
Drive Axles (in)	1.375		1.375
Caster Tires (in)	13 x 6.5-6		13 x 6.5-6
Drive Tires (in)	24 x 9.5 - 12		24 x 12-12
Ground Speed-Fwd (mph)	0-10		0-10
Ground Speed-Rev (mph)	0-5		0-5
Overall Length (in)	83.63		83.63
Overall Width (in) Deflector Down/Deflector Up	67 / 57		78 / 61.5
Dry Weight (lbs)	1319		1398
Seat Package	Premium high-back Suspension Seat with arm rests , adjustable lumbar and		Premium high-back Suspension Seat with arm rests , adjustable lumbar and

Menu →	back recline.	Feature	back recline.
OVERCHEMITIEN Roll-over Protection System FEATURES	180° foldable		180° foldable
Controls / Safety Group SPECIFICATIONS ATTACHMENTS	Seat activated e clutch safety sw and parking bra	vitch, neutral ke safety	Seat activated engine kill, clutch safety switch, neutral and parking brake safety circuit/adjustable twin steering controls
RELATED PRODUCTS	circuit/adjustab steering control		
Parking Brake / Safety Circuit	Hand operated Internal transaxle brake		Hand operated Internal transaxle brake
Warranty (Engine) †	3-Year limited manufacturer's warranty		3-Year limited manufacturer's warranty
Warranty (Balance of Machine) †	4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coilover-shocks and all suspension related components are covered for 5 years (60 months) unlimited hours. Coverage on other components varies, please see operator's manual for complete details.		4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coilover-shocks and all suspension related components are covered for 5 years (60 months) unlimited hours. Coverage on other components varies, please see operator's manual for complete details.
Deck Construction	iCD™ Cutting System, 2-Belt		iCD™ Cutting System, 2-Belt
Transmission Type	Dual, commercial Hydro- Gear® ZT-4400™ Transaxles with 8.3" cooling fans		Dual, commercial Hydro- Gear® ZT-4400™ Transaxles with 8.3" cooling fans

Menuer Electric Feature Electric

OVERVIEW Standard Standard

FEATURES

* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

† See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty.

SPECIFICATIONS

^ Suggested prices will vary by market. Prices are show in U.S. dollars. Set-up, delivery, documentation and destination fees not included. See dealer for details. Features vary by model. We reserve the right to change specifications, features and pricing without notice.

ATTACHMENTS

RELATED PRODUCTS

Attachments



Fast-Vac® Triple Bag Collection System

The triple bag collection system is simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Available on 61" and 52" models.

