1. ENGINE a. 60 h.p. diesel engine b. Water cooled c. Engine enclosure d. 15 gal. fuel tank 2. HIGH PRESSURE WATER PUMP a. 4000 psi at 18 gpm b. Pressure relief valve c. Triplex type pump d. Low water shutdown e. Multi-flow type system [pressure change without changes to engine rpm] 3. CONTROLS a. Located next to hose reel b. Ignition c. Throttle d. Gauge package [tachometer, hourmeter, oil pressure, volts, and low oil / high temp shutdown] e. Water control valve 4. WATER TANK a. 700 gal capacity b. High density polyethylene with baffles c. Sight gauge d. 2 1/2" overhead tank fill , anti siphon , air gap type e. Strainer f. Tank drain 5. HOSE REEL a. 800 ' capacity of 1/2" high pressure sewer hose b. Hydraulic power in and out 6. HOSE REEL DRIVE HYDRAULIC SYSTEM a. Hydraulic pump 8 gpm b. 15 gal hydraulic reservoir c. Spin on type hydraulic filter 7. TRAILER a. 12000 lb gvw b. 6" x 3/16" frame c. Tandem axle d. 2 5/16" hitch e. Tongue jack f. 235 / 80 r 16" tires g. Fenders h. Breakaway switch i. Lighting as required by Federal and State laws j. Reflective striping k. Toolbox with locking system I. LED directional arrowstick m. Warning beacon [tank mounted] 8. EQUIPMENT FURNISHED a. 500' of 1/2" high pressure sewer hose b. 100' of 1/4" hose and nozzle for small pipe c. Washdown gun and 25 ' of hose with quick dissconnects d. Tiger tail hose protecter e. Nozzles to be furnished, 15 degree, 35 degree, chisel point, grenade flushing type, skid assembly, and rotater nozzle



www.obrienmfg.com toll-free phone: 800-638-1901

7018-SC

Looks Professional. Performs Like One.

This unit is specially designed for the professional day-to-day sewer line cleaner. Municipalities and pumperIcleaner contractors rely on its power and versatility for cleaning a wide range of pipes. The unit has "catwalk" fenders.

Standard unit color is safety yellow or white -customer choice. Can be custom painted to match for add'l cost.

Available Options _100' 1/2" Extra Hose on Main Reel _200' 1/2" Extra Hose on Main Reel Anti-Freeze System (PN OBJ-234) Arrow Board (PN OBJ-144) Auto Level Wind Guide Mounted (PN OBJ-9032-34) Cone Holder Only (PN OBJ-137) Custom Decals (two) 80hp JohnDeere Diesel Engine (PN OBJ-80JDO) _85HP Cummins Diesel Engine (PN OBJ-85CO) _E-Stop Assembly (PN IC-100405-01) Foot Control Swinger (PN OBJ-187A) Garden Hose Reel 1/2" - 50' (PN OBJ-123000L) Garden Hose Reel Electric 100' (PN OBJ-294) Garden Hose Reel Manual 100' (PN OBJ-293) Hose -Reel 42" Weldment (PN J-700-42W) Hydraulic Surge Brakes (PN 7000SB) IntelACount® (PN OBJ-2430E) Level Wind Guide w/Counter (PN OBJ-2430A) Low Water Shutdown (PN OBJ-2424) Paint - Custom (Paint Code Required) STD Paint - Safety Yellow (PN PAINT-1Y) YOUR STD Paint - White Enamel (PN PAINT-3W) CHOICE Pintle Hitch (PN OBJ-1081P) Recirculation System (PN OBJ-3/4"RECIRC) Rotating Beacon-Fixed (PN OBJ-241B) Side Panels (two) - Painted (PN OBJ-2524P) _Spare Tire Holder w/Tire 16" (PN OBJ-9060-16) Tank Shroud Aluminum (PN 7000ADS)

Tank Shroud Steel (PN 7000SS)

Wireless Remote (PN OBJ-101)



Standard Components

700 Gallon Polyethylene Tanks Plate mounted with sump and side baffles

Crowned top & side stabilizers for added strength

12" Manhole with strainer basket

"Swinger" Reel-190° Pivot Makes line cleaning a simple job because it allows for:

- · Easy access to the manhole regardless of how trailer is parked.
- Tethered hand operated reel control.
- Variable-speed control.
- Hydraulic driven

Engine

Std. 65HP Cummins Diesel Engine Murphy safety gauges with auto-shutdown Variable electronic throttle control

Triplex Pump 18 GPM @ 4,000 psi

Available Accessories

-	Artifiery Nozzie Kit (PN 344020AK)	20'
	Cavalry Nozzle Kit (PN 344020CA)	Lev
	Cone Safety Red 18" tall (PN OBJ-71 Fill Hose 25' (PN J-2439)	4) ^{Two} 2" F
	Grit Catcher 6" (PN OB00016A)	
	Grit Catcher 8" (PN OB00018A)	
	Infantry Nozzle Kit (PN 344020IN)	
	Kit - Emergency Hand Crank (PN OBJ	-300)

Root Cutter Kit (PN J-3201)

Lateral Cleaning Kit 150' (PN J-2434) Manhole Cover Hook (PN 015-438)

Nozzle Extension-Finned 3/4" (PN J-40-5)

Nozzle Extension-NonFinned 3/4"(PN J-40-1)

_Rotating Beacon - Magnetic Mount (PN RL650S)

Strobe Light - Magnetic Mount (PN SL650S)

High-Impact Thermoplastic Sewer Hose Easy to keep clean (retains no bacteria-causing residue).

Maintains stiffness and is abrasion resistant. Std. 18/4000 pump = 400' of 1/2" hose Standard 400' hose reaches from manhole to manhole.

Reel capacity is 750' of 1/2" hose.

Tandem-Axle Trailer

Our Trailer Jetter is rated to carry a full tank of water to the job at highway speeds.

- · 6" channel frame
- · A-frame hitch with storage
- 25/16" ball hitch (pintle opt.)
- (2) 6,000 lb. DOT-rated axles
- LT245/75R16
- Electric brakes

Other Standard Components

Two nozzles: penetrator & flusher Toolbox—integrated enclosed tool & battery storage

PVC tank drain valve with stainless steel strainer Direct driven "live" hydraulic system w/17 gal. tnk 17-gallon fuel tank with cap-mounted gauge. Air purge system

20' Leader hose contrasting color Level wind guide

1-714)Two (2) aux 12V power supply outlets 2" PVC fill pipe

_Tiger Tail 3" x 36" (PN J-2203)
_Tiger Tail 3" x 42" (PN J-2205)
Tire & Rim 16" Spare (PN J-16614)
Upstream Pulley Guide (PN J-2401)
Washdown Gun w/Hose (PN 15007-B)

Signature:	Printed Name:	Date:
ices and features subject to change		50 13019550- 1000900-1000-1000-1000-1000-1000-1000

Toll Free Phone: (800)638-1901



MANUFACTURER CERTIFICATION

FSA20-VEL28.0 Pursuit, Administrative & Other Vehicles, FSA20-VEH18.0 Heavy Vehicles
FSA 20-EQU18.0 Heavy Equipment

This is to certify that Pats Pump & Blower					
(Vendor/Res	pondent's Name) or a				
manufacturer's authorized dealer of HiVac Col	poration				
	(Manufacturer/Brand Name)				
in the State of Florida.					
Ву:					
Manufacturer Name: HiVac Corpotation					
Address: 117 Industry Road					
City, State, Zip: Marietta Ohio 45750	The second secon				
Office Phone: 740.374.2306 Mobile Phone:					
E-mail: kparks@hi-vac.com	Providence or an income of the management of the providence of the second of the providence of the pro				
Signature: Hent Parks					
Signature: Tent Varby Title: Inside Sales Ma	inager				
	V				

PLEASE NOTE: This certification form must be executed by an authorized employee of the manufacturer **ONLY.** Dealers/Representatives are not authorized to execute this certification form on behalf of the manufacturer. The manufacturer must execute this certification form even if they are offering their own products. Failure to submit this certification form with your response as required shall result in the disqualification of the response.