

Specification Number	Code	Description	Price - All Zones
423	CT1021HST	Credit - downgrade into the Bobcat® CT1021 Compact Utility Tractor with Hydrostatic Transmission.	7416
423	CT1025HST	Credit - downgrade into the Bobcat® CT1025 Compact Utility Tractor with Hydrostatic Transmission.	6300
423	CT2025MST	Credit - downgrade into the Bobcat® CT1025 Compact Utility Tractor with Manual Transmission.	4410.4
423	CT2025HST	Credit - downgrade into the Bobcat® CT2025 Compact Utility Tractor with Hydrostatic Transmission.	3389.6
423	CT2035MST	Credit - downgrade into the Bobcat® CT2035 Compact Utility Tractor with Manual Transmission.	1049.6
423	CT2040MST	Credit - downgrade into the Bobcat® CT2040 Compact Utility Tractor with Manual Transmission.	631.2
423	CT2040HST	Upgrade to the Bobcat® CT2040 Compact Utility Tractor with Hydrostatic Transmission.	436.8
423	CT4045SST	Upgrade to the Bobcat® CT4045 Compact Utility Tractor with Synco Shift Transmission.	2469.6
423	CT4050SST	Upgrade to the Bobcat® CT4050 Compact Utility Tractor with Synco Shift Transmission.	3446.4
423	CT4045HST	Upgrade to the Bobcat® CT4045 Compact Utility Tractor with Hydrostatic Transmission.	4196.8
423	CT4055SST	Upgrade to the Bobcat® CT4055 Compact Utility Tractor with Synco Shift Transmission.	4424
423	CT4050HST	Upgrade to the Bobcat® CT4050 Compact Utility Tractor with Hydrostatic Transmission.	6998.4
		Upgrade to the Bobcat® CT2535 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Hydrostatic Transmission.	8005.6
423	CT4058HST	Upgrade to the Bobcat® CT4058 Compact Utility Tractor with Hydrostatic Transmission.	8551.2
		Upgrade to the Bobcat® CT2540 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Hydrostatic Transmission.	9246.4
423	CT2540HST	Upgrade to the Bobcat® CT5545 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Electronic Hydrostatic Transmission.	12078.4
423	CT5545E-HST	Upgrade to the Bobcat® CT5550 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Electronic Hydrostatic Transmission.	13549.6
423	CT5550E-HST	Upgrade to the Bobcat® CT5555 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Electronic Hydrostatic Transmission.	15120
423	CT5555E-HST	Upgrade to the Bobcat® CT5558 Compact Utility Tractor with Fully Enclosed Cab with HVAC and Electronic Hydrostatic Transmission.	17428.8
423	CT5558E-HST		
423	Options	20% off MSRP for all Factory Installed Options	0.2
423	Attachments	24% off MSRP for all Attachments and Implements	0.24



Product Quotation

Quotation Number: BDH-00187

Date: 2020-08-20 15:12:52

Description	Part No	Qty	Price Ea.	Total
CT1021 Compact Tractor HST	M1623	1	\$9,221.60	\$9,221.60
Glow Plug Engine Pre-Heat	Four Wheel Drive			
Electric Key Shutoff	Rear Differential Lock			
Horn	Brakes, Wet Multi Disc			
Cupholder	Mid PTO			
Vinyl, w/ retractable seat belt	Rear PTO			
Hydrostatic Power Steering	PTO Shield			
Instrumentation: Hourmeter, tachometer, engine temperature,	Three Point Hitch, Category 1			
fuel gauge, and warning lights	Hydraulic Three-Point Lift Position Control System			
Lights: headlights, tail lights, brake lights, hazard flashers and	Lift rod Turnbuckle			
turn signals	Draw Bar, Fixed			
Safety Interlock System	Tires: Bobcat Industrial Tires			
ROPS two-post, Foldable *	18 x 8.5 10 Front; 26 x 12-12 Rear			
Parking Brake				

Total of Items Quoted	\$9,221.60
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$9,221.60

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: Purchase Order: _____

Authorized Signature:

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00186

Date: 2020-08-20 15:09:25

Description

CT1025 Compact Tractor HST

Bobcat CT1025 HST
Glow Plug Engine Pre-Heat
Electric Key Shutoff
Horn
Cupholder
Vinyl, w/ retractable seat belt
Hydrostatic Power Steering
Instrumentation: Hourmeter, tachometer, engine temperature,
fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and
turn signals
Safety Interlock System
ROPS two-post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1624	1	\$10,337.60	\$10,337.60

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Mid PTO
Rear PTO
PTO Shield
Three-Point Hitch, Category 1
Hydraulic Three-Point Lift Position Control System
Lift rod Turnbuckle
Draw Bar, Fixed
Tires: Bobcat Industrial Tires
18 x 8.5-10 Front; 26 x 12-12 Rear

Total of Items Quoted	\$10,337.60
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$10,337.60

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00184

Date: 2020-08-20 14:54:26

Description

CT2025 Compact Tractor HST

Bobcat CT2025 HST
 Glow Plug Engine Pre Heat
 Electric Key Shutoff
 Horn
 Cupholder
 Vinyl Suspension seat, w/ retractable seat belt
 Hydrostatic Power Steering
 Floor Mat
 Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights
 Lights: headlights, tail lights, brake lights, hazard flashers and turn signals
 Safety Interlock System
 ROPS two post, Foldable *
 Parking Brake

Part No	Qty	Price Ea.	Total
M1603	1	\$13,248.00	\$13,248.00

Four Wheel Drive
 Rear Differential Lock
 Brakes, Wet Multi Disc
 Loader Joystick & Valve
 Fuel Heater (excluded CT2025)
 Rear PTO
 PTO Shield
 Three-Point Hitch, Category 1
 Hydraulic Three Point Lift Position Control System
 Lift rod Turnbuckle
 Draw Bar, Adjustable
 Tires: Bobcat Industrial Tires
 27 x 8.5 15 Front; 15 19.5 Rear

Total of Items Quoted	\$13,248.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$13,248.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: _____ Purchase Order: _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00185

Date: 2020-08-20 15:00:04

Description**CT2025 Compact Tractor MST**

Bobcat CT2025 MST
 Glow Plug Engine Pre-Heat
 Electric Key Shutoff
 Horn
 Cupholder
 Vinyl Suspension seat, w/ retractable seat belt
 Hydrostatic Power Steering
 Floor Mat
 Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights
 Lights: headlights, tail lights, brake lights, hazard flashers and turn signals
 Safety Interlock System
 ROPS two-post, Foldable *
 Parking Brake

Part No	Qty	Price Ea.	Total
M1604	1	\$12,227.20	\$12,227.20

Four Wheel Drive
 Rear Differential Lock
 Brakes, Wet Multi Disc
 Loader Joystick & Valve
 Fuel Heater (excluded CT2025)
 Rear PTO
 PTO Shield
 Three Point Hitch, Category 1
 Hydraulic Three Point Lift Position Control System
 Lift rod Turnbuckle
 Draw Bar, Adjustable
 Tires: Bobcat Industrial Tires
 27 x 8.5 15 Front; 15 19.5 RearCT2025 MST

Total of Items Quoted	\$12,227.20
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$12,227.20

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: Purchase Order: _____

Authorized Signature:

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00183

Date: 2020-08-20 14:49:18

Description**CT2035 Compact Tractor MST**

Bobcat CT2035 MST
 Glow Plug Engine Pre-Heat
 Electric Key Shutoff
 Horn
 Cupholder
 Vinyl Suspension seat, w/ retractable seat belt
 Hydrostatic Power Steering
 Floor Mat
 Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights
 Lights: headlights, tail lights, brake lights, hazard flashers and turn signals
 Safety Interlock System
 ROPS two post, Foldable *
 Parking Brake

Part No	Qty	Price Ea.	Total
M1606	1	\$15,588.00	\$15,588.00

Four Wheel Drive
 Rear Differential Lock
 Brakes, Wet Multi Disc
 Loader Joystick & Valve
 Fuel Heater (excluded CT2025)
 Rear PTO
 PTO Shield
 Three Point Hitch, Category 1
 Hydraulic Three Point Lift Position Control System
 Lift rod Turnbuckle
 Draw Bar, Adjustable
 Tires: Bobcat Industrial Tires
 27 x 8.5 15 Front; 15 19.5 Rear

Total of Items Quoted	\$15,588.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$15,588.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: Purchase Order: _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00188

Date: 2020-08-20 15:30:39

Description

CT2040 Compact Tractor HST

Bobcat CT2040 HST
Glow Plug Engine Pre-Heat
Electric Key Shutoff
Horn
Cupholder
Vinyl Suspension seat, w/ retractable seat belt
Hydrostatic Power Steering
Floor Mat
Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and turn signals
Safety Interlock System
ROPS two post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1607	1	\$17,074.40	\$17,074.40

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Loader Joystick & Valve
Fuel Heater (excluded CT2025)
Rear PTO
PTO Shield
Three-Point Hitch, Category 1
Hydraulic Three Point Lift Position Control System
Lift rod Turnbuckle
Draw Bar, Adjustable
Tires: Bobcat Industrial Tires
27 x 8.5 15 Front; 15 19.5 Rear

Total of Items Quoted	\$17,074.40
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$17,074.40

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00182

Date: 2020-08-20 14:48:17

Description	Part No	Qty	Price Ea.	Total
CT2040 Compact Tractor MST	M1608	1	\$16,006.40	\$16,006.40
Bobcat CT2040 MST	Four Wheel Drive			
Glow Plug Engine Pre-Heat	Rear Differential Lock			
Electric Key Shutoff	Brakes, Wet Multi Disc			
Horn	Loader Joystick & Valve			
Cupholder	Fuel Heater (excluded CT2025)			
Vinyl Suspension seat, w/ retractable seat belt	Rear PTO			
Hydrostatic Power Steering	PTO Shield			
Floor Mat	Three Point Hitch, Category 1			
Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights	Hydraulic Three Point Lift Position Control System			
Lights: headlights, tail lights, brake lights, hazard flashers and turn signals	Lift rod Turnbuckle			
Safety Interlock System	Draw Bar, Adjustable			
ROPS two post, Foldable *	Tires: Bobcat Industrial Tires			
Parking Brake	27 x 8.5 15 Front; 15 19.5 Rear			

Total of Items Quoted	\$16,006.40
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$16,006.40

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00196

Date: 2020-08-20 15:59:45

Description	Part No	Qty	Price Ea.	Total
CT2540 Compact Tractor HST	M1611	1	\$25,884.00	\$25,884.00
Bobcat CT2540 HST	Front Work light			
Glow Plug Engine Pre-Heat	Rear work light			
Cab Heat/Air	Safety Interlock System			
Suspension seat	Parking Brake			
Rear window wiper/defrost	Four Wheel Drive			
Dual arm rest	Rear Differential Lock			
Sun-visor	Brakes, Wet Multi Disc			
Cruise control	Loader Joystick & Valve			
Floor-mat	Fuel Heater Kit			
Tool Box	Rear PTO			
Side View Mirror	PTO Shield			
Rear View Mirror	Three Point Hitch, Category 1			
Dual Air Cleaner	Hydraulic Three Point Lift Position Control System			
Electric Key Shutoff	Rear Three Point Hitch Return to Position			
Horn	Telescopic stabilizer & Lower link			
Cupholder	Lift rod Turnbuckle			
Vinyl, w/ retractable seat belt	Dual Remote Valves (4 port)			
Instrumentation: Hourmeter, tachometer, engine temperature,	Draw Bar, Adjustable			
fuel gauge, and warning lights	Tires: Bobcat Industrial Tires			
Lights: headlights, tail lights, brake lights, hazard flashers and	27 x 8.5 15 Front; 15 19.5 Rear			
turn signals				
Hydrostatic Power Steering, Tilt steering				

Total of Items Quoted	\$25,884.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$25,884.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: _____ **Purchase Order:** _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00191

Date: 2020-08-20 15:40:52

Description

CT4045 Compact Tractor HST

Bobcat CT4045 HST
Glow Plug Engine Pre-Heat
Electric Key Shutoff
Horn
Cupholder
Floor Mat
Toolbox
Suspension Seat, Vinyl, Seat Belt, retractable
Hydrostatic Power Steering
Instrumentation: Hourmeter, tachometer, engine temperature,
fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and
turn signals
Safety Interlock System
ROPS two post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1613	1	\$20,834.40	\$20,834.40

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Fuel Heater
Rear PTO
PTO Shield
Three Point Hitch, Category 1
Hydraulic Three Point Lift Position Control System
Single Remote Valve 2port (HST only)
Rear Three Point Hitch Return to Position
Draw Bar, Adjustable
Lift rod Turnbuckle
Tires: Bobcat Industrial Tires
10 16.5 Front; 14.9 24 Rear

Total of Items Quoted	\$20,834.40
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$20,834.40

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00189

Date: 2020-08-20 15:33:58

Description

CT4045 Compact Tractor SST

Bobcat CT4045 SST
Glow Plug Engine Pre Heat
Electric Key Shutoff
Horn
Cupholder
Floor Mat
Toolbox
Suspension Seat, Vinyl, Seat Belt, retractable
Hydrostatic Power Steering
Instrumentation: Hourmeter, tachometer, engine temperature,
fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and
turn signals
Safety Interlock System
ROPS two post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1614	1	\$19,107.20	\$19,107.20

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Fuel Heater
Rear PTO
PTO Shield
Three Point Hitch, Category 1
Hydraulic Three Point Lift Position Control System
Single Remote Valve 2port (HST only)
Rear Three Point Hitch Return to Position
Draw Bar, Adjustable
Lift rod Turnbuckle
Tires: Bobcat Industrial Tires
10 16.5 Front; 14.9 24 Rear

Total of Items Quoted	\$19,107.20
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$19,107.20

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00193

Date: 2020-08-20 15:49:46

Description	Part No	Qty	Price Ea.	Total
CT4050 Compact Tractor HST	M1615	1	\$23,636.00	\$23,636.00
Bobcat CT4050 HST	Four Wheel Drive			
Glow Plug Engine Pre Heat	Rear Differential Lock			
Electric Key Shutoff	Brakes, Wet Multi Disc			
Horn	Fuel Heater			
Cupholder	Rear PTO			
Floor Mat	PTO Shield			
Toolbox	Three Point Hitch, Category 1			
Suspension Seat, Vinyl, Seat Belt, retractable	Hydraulic Three Point Lift Position Control System			
Hydrostatic Power Steering	Single Remote Valve 2port (HST only)			
Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights	Rear Three Point Hitch Return to Position			
Lights: headlights, tail lights, brake lights, hazard flashers and turn signals	Draw Bar, Adjustable			
Safety Interlock System	Lift rod Turnbuckle			
ROPS two post, Foldable *	Tires: Bobcat Industrial Tires			
Parking Brake	10 16.5 Front; 14.9 24 Rear			

Total of Items Quoted	\$23,636.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$23,636.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00190

Date: 2020-08-20 15:36:41

Description

CT4050 Compact Tractor SST

"Bobcat CT4050 SST
Glow Plug Engine Pre Heat
Electric Key Shutoff
Horn
Cupholder
Floor Mat
Toolbox
Suspension Seat, Vinyl, Seat Belt, retractable
Hydrostatic Power Steering
Instrumentation: Hourmeter, tachometer, engine temperature,
fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and
turn signals
Safety Interlock System
ROPS two post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1616	1	\$20,084.00	\$20,084.00

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Fuel Heater
Rear PTO
PTO Shield
Three Point Hitch, Category 1
Hydraulic Three Point Lift Position Control System
Single Remote Valve 2port (HST only)
Rear Three Point Hitch Return to Position
Draw Bar, Adjustable
Lift rod Turnbuckle
Tires: Bobcat Industrial Tires
10 16.5 Front; 14.9 24 Rear

Total of Items Quoted	\$20,084.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$20,084.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00192

Date: 2020-08-20 15:46:30

Description

CT4055 Compact Tractor SST

Bobcat CT4055 SST
Glow Plug Engine Pre Heat
Electric Key Shutoff
Horn
Cupholder
Floor Mat
Toolbox
Suspension Seat, Vinyl, Seat Belt, retractable
Hydrostatic Power Steering
Instrumentation: Hourmeter, tachometer, engine temperature,
fuel gauge, and warning lights
Lights: headlights, tail lights, brake lights, hazard flashers and
turn signals
Safety Interlock System
ROPS two post, Foldable *
Parking Brake

Part No	Qty	Price Ea.	Total
M1617	1	\$21,061.60	\$21,061.60

Four Wheel Drive
Rear Differential Lock
Brakes, Wet Multi Disc
Fuel Heater
Rear PTO
PTO Shield
Three Point Hitch, Category 1
Hydraulic Three Point Lift Position Control System
Single Remote Valve 2port (HST only)
Rear Three Point Hitch Return to Position
Draw Bar, Adjustable
Lift rod Turnbuckle
Tires: Bobcat Industrial Tires
10 16.5 Front; 14.9 24 Rear

Total of Items Quoted	\$21,061.60
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$21,061.60

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00195

Date: 2020-08-20 15:57:22

Description	Part No	Qty	Price Ea.	Total
CT4058 Compact Tractor HST	M1618	1	\$25,188.80	\$25,188.80
Bobcat CT4058 HST	Four Wheel Drive			
Glow Plug Engine Pre Heat	Rear Differential Lock			
Electric Key Shutoff	Brakes, Wet Multi Disc			
Horn	Fuel Heater			
Cupholder	Rear PTO			
Floor Mat	PTO Shield			
Toolbox	Three Point Hitch, Category 1			
Suspension Seat, Vinyl, Seat Belt, retractable	Hydraulic Three Point Lift Position Control System			
Hydrostatic Power Steering	Single Remote Valve 2port (HST only)			
Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights	Rear Three Point Hitch Return to Position			
Lights: headlights, tail lights, brake lights, hazard flashers and turn signals	Draw Bar, Adjustable			
Safety Interlock System	Lift rod Turnbuckle			
ROPS two post, Foldable *	Tires: Bobcat Industrial Tires			
Parking Brake	10 16.5 Front; 14.9 24 Rear			

Total of Items Quoted	\$25,188.80
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$25,188.80

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:	Purchase Order: _____
Authorized Signature:	
Print: _____	Sign: _____ Date: _____



Product Quotation

Quotation Number: BDH-00197

Date: 2020-08-20 16:02:24

Description	Part No	Qty	Price Ea.	Total
CT5545 Compact Tractor eHST	M1619	1	\$28,716.00	\$28,716.00
Bobcat CT5545 E HST	Parking Brake			
Glow Plug Engine Pre Heat	Four Wheel Drive			
Cab Heat/Air	Rear Differential Lock			
Right arm rest	Brakes, Wet Multi Disc			
Sunshade	Loader Joystick & Valve			
Cruise control	Fuel Heater			
Linked pedal	Rear PTO			
Floor mat	PTO Shield			
Tool Box	PTO Cruise			
Side View Mirror	Three Point Hitch, Category 1			
Electric Key Shutoff	Hydraulic Three Point Lift Position Control System			
Horn	Rear Three Point Hitch Return to Position			
Cupholder	Telescopic stabilizer and lower link			
Suspension seat, w/ retractable seat belt	7 pin Socket			
Hydrostatic Power Steering	Lifting rod Beveled Gear Type			
Instrumentation: Hourmeter, tachometer, engine temperature,	Tires: Bobcat Industrial Tires			
fuel gauge, and warning lights	10 16.5 Front; 14.9 24 Rear			
Lights: headlights, tail lights, brake lights, hazard flashers and				
turn signals				
Safety Interlock System				

Total of Items Quoted	\$28,716.00
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$28,716.00

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: _____ **Purchase Order:** _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00198

Date: 2020-08-20 16:05:58

Description	Part No	Qty	Price Ea.	Total
CT5550 Compact Tractor eHST	M1620	1	\$30,187.20	\$30,187.20
Bobcat CT5550 E HST	Parking Brake			
Glow Plug Engine Pre Heat	Four Wheel Drive			
Cab Heat/Air	Rear Differential Lock			
Right arm rest	Brakes, Wet Multi Disc			
Sunshade	Loader Joystick & Valve			
Cruise control	Fuel Heater			
Linked pedal	Rear PTO			
Floor mat	PTO Shield			
Tool Box	PTO Cruise			
Side View Mirror	Three Point Hitch, Category 1			
Electric Key Shutoff	Hydraulic Three Point Lift Position Control System			
Horn	Rear Three Point Hitch Return to Position			
Cupholder	Telescopic stabilizer and lower link			
Suspension seat, w/ retractable seat belt	7 pin Socket			
Hydrostatic Power Steering	Lifting rod Beveled Gear Type			
Instrumentation: Hourmeter, tachometer, engine temperature,	Tires: Bobcat Industrial Tires			
fuel gauge, and warning lights	10 16.5 Front; 14.9 24 Rear			
Lights: headlights, tail lights, brake lights, hazard flashers and				
turn signals				
Safety Interlock System				

Total of Items Quoted	\$30,187.20
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$30,187.20

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: _____ **Purchase Order:** _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00199

Date: 2020-08-20 16:09:09

Description	Part No	Qty	Price Ea.	Total
CT5555 Compact Tractor eHST	M1621	1	\$31,757.60	\$31,757.60
Bobcat CT5555 E HST	Parking Brake			
Glow Plug Engine Pre Heat	Four Wheel Drive			
Cab Heat/Air	Rear Differential Lock			
Right arm rest	Brakes, Wet Multi Disc			
Sunshade	Loader Joystick & Valve			
Cruise control	Fuel Heater			
Linked pedal	Rear PTO			
Floor mat	PTO Shield			
Tool Box	PTO Cruise			
Side View Mirror	Three Point Hitch, Category 1			
Electric Key Shutoff	Hydraulic Three Point Lift Position Control System			
Horn	Rear Three Point Hitch Return to Position			
Cupholder	Telescopic stabilizer and lower link			
Suspension seat, w/ retractable seat belt	7 pin Socket			
Hydrostatic Power Steering	Lifting rod Beveled Gear Type			
Instrumentation: Hourmeter, tachometer, engine temperature,	Tires: Bobcat Industrial Tires			
fuel gauge, and warning lights	10 16.5 Front; 14.9 24 Rear			
Lights: headlights, tail lights, brake lights, hazard flashers and				
turn signals				
Safety Interlock System				

Total of Items Quoted	\$31,757.60
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$31,757.60

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance: _____ **Purchase Order:** _____

Authorized Signature: _____

Print: _____ **Sign:** _____ **Date:** _____



Product Quotation

Quotation Number: BDH-00200

Date: 2020-08-20 16:11:40

Description	Part No	Qty	Price Ea.	Total
CT5558 Compact Tractor eHST	M1622	1	\$34,066.40	\$34,066.40
Bobcat CT5558 E HST	Parking Brake			
Glow Plug Engine Pre Heat	Four Wheel Drive			
Cab Heat/Air	Rear Differential Lock			
Right arm rest	Brakes, Wet Multi Disc			
Sunshade	Loader Joystick & Valve			
Cruise control	Fuel Heater			
Linked pedal	Rear PTO			
Floor mat	PTO Shield			
Tool Box	PTO Cruise			
Side View Mirror	Three Point Hitch, Category 1			
Electric Key Shutoff	Hydraulic Three Point Lift Position Control System			
Horn	Rear Three Point Hitch Return to Position			
Cupholder	Telescopic stabilizer and lower link			
Suspension seat, w/ retractable seat belt	7 pin Socket			
Hydrostatic Power Steering	Lifting rod Beveled Gear Type			
Instrumentation: Hourmeter, tachometer, engine temperature, fuel gauge, and warning lights	Tires: Bobcat Industrial Tires			
Lights: headlights, tail lights, brake lights, hazard flashers and turn signals	10 16.5 Front; 14.9 24 Rear			
Safety Interlock System				

Total of Items Quoted	\$34,066.40
Dealer Assembly Charges	\$0.00
Quote Total - US dollars	\$34,066.40

Notes:

All prices subject to change without prior notice or obligation. This price quote supersedes all preceding price quotes.

Customer Acceptance:

Purchase Order: _____

Authorized Signature:

Print: _____ Sign: _____ Date: _____

Specifications



Model	CT1021	CT1025	CT2025	CT2035	CT2535	CT2040	CT2540	CT4045	CT4050	CT4055
Engine	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Gross Horsepower	21 hp (15.7 kW)	24.5 hp (18.3 kW)	24.5 hp (18.2 kW)	34.9 hp (26 kW)	34.9 hp (26 kW)	39.6 hp (29.5 kW)	39.6 hp (29.5 kW)	44.9 hp (33.5 kW)	50 hp (37.3 kW)	55 hp (41 kW)
No. of Cylinders	3	3	3	3	3	3	3	3	3	3
Total Displacement	69 cu. in. (1131 cc)	69 cu. in. (1131 cc)	100.5 cu. in. (1647 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)
Fuel Tank Capacity (gallons)	6.7 gal. (25.5 L)	6.7 gal. (25.5 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	11.9 gal. (45 L)	11.9 gal. (45 L)	11.9 gal. (45 L)
3-Point, PTO & Hydraulics										
PTO Horsepower	18.7 hp (13.9 kW)	19.4 hp (14.4 kW)	22.2 hp (16.6 kW) HST (21.8 hp (16.3 kW))	30.8 hp (23 kW) HST (29.4 hp (21.9 kW))	29.4 hp (21.9 kW)	34.9 hp (26 kW) HST (31.9 hp (23.8 kW))	31.9 hp (23.8 kW)	41.6 hp (31 kW) HST (32.8 hp (24.5 kW))	45.6 hp (34 kW) HST (39.3 hp (29.3 kW))	49.6 hp (37 kW)
3-Point Hitch	Category I	Category I	Category I	Category I	Category I	Category I	Category I	Category I	Category I	Category I
Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System
Lift Capacity at 24" Behind Lift Points (per SAE J283)	700 lb. (318 kg)	700 lb. (318 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	2716 lb. (1232 kg)	2716 lb. (1232 kg)	2716 lb. (1232 kg)
Rear PTO	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Rear PTO System	Independent	Independent	Live	Live	Live	Live	Live	Independent	Independent	Independent
Mid-PTO	Standard: 2200 rpm	Standard: 2200 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm
Total Hydraulic Pump Capacity	6.5 gpm (24.6 L/min.)	6.5 gpm (24.6 L/min.)	11.7 gpm (44.4 L/min.)	11.7 gpm (44.4 L/min.)	11.7 GPM (44.4 L/min.)	11.7 gpm (44.4 L/min.)	11.7 GPM (44.4 L/min.)	14.5 gpm (55.1 L/min.)	14.5 gpm (55.1 L/min.)	14.5 gpm (55.1 L/min.)
Rear Hydraulics (optional)	2 Pairs	2 Pairs	2 Pairs	2 Pairs	2 Pairs	2 Pairs	2 Pairs	2 Pairs (2 ports Standard)	2 Pairs (2 ports standard)	2 pairs
Telescopic Stabilizers	Turnbuckle	Turnbuckle	Turnbuckle	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Lower Links	Rigid	Rigid	Rigid	Rigid	Telescopic	Rigid	Telescopic	Rigid	Rigid	Rigid
Lifting Rod	Turnbuckle	Turnbuckle	Crank	Crank	Crank	Crank	Crank	Crank	Crank	Crank
Drive System										
Standard Transmission	Hydrostatic	Hydrostatic	Manual (9x3)	Manual (9x3)	HST	Manual (9x3)	HST-3	Synchro (8x8)	Synchro (8x8)	Synchro (8x8)
Optional Transmission	N/A	N/A	HST	HST	HST	HST	HST	HST	HST	HST
Speed Ranges	2 Range	2 Range	3 Range	3 Range	3 Range	3 Range	3 Range	3 Range	3 Range	3 Range
Brakes	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc
Rear Differential Lock	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Four-Wheel Drive	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
2WD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Travel Speeds (w/ Ag Tires)										
Forward	0-10.31 mph (0-16.6 km/hr.)	0-10.31 mph (0-16.6 km/hr.)	.94-14.63 mph (0-23.56 km/hr.) HST (0-15.53 mph (0-25 km/hr.))	.94-14.63 mph (0-23.56 km/hr.) HST (0-15.53 mph (0-25 km/hr.))	0-15.16 mph (0-24.4 km/hr.)	.94-14.63 mph (0-23.56 km/hr.) HST (0-15.16 mph (0-24.4 km/hr.))	0-15.16 mph (0-24.4 km/hr.)	1.28-17.3 mph (2.06-27.9 km/hr.) HST (0-18.5mph (29.7 km/hr.))	1.28-17.3 mph (2.06-27.9 km/hr.) (0-18.5mph (29.7 km/hr.))	1.28-17.3 mph (2.06-27.9 km/hr.)
Reverse	0-6.96 mph (0-11.2 km/hr.)	0-6.96 mph (0-11.2 km/hr.)	1.18-9.56 mph (1.9-15.39 km/hr.) HST (0-15.83 mph (0-25.48 km/hr.))	.94-14.63 mph (0-23.56 km/hr.) HST (0-15.83 mph (0-25.48 km/hr.))	0-10.31 mph (0-16.6 km/hr.)	1.18-9.56 mph (1.9-15.39 km/hr.) HST (0-10.31 mph (0-16.6 km/hr.))	0-10.31 mph (0-16.6 km/hr.)	1.25-16.9 mph (2.01-27.2 km/hr.) HST (0-12.9 mph (0-20.8 km/hr.))	1.25-16.9 mph (2.01-27.2 km/hr.) HST (0-12.9 mph (0-20.8 km/hr.))	1.25-16.9 mph (2.01-27.2 km/hr.)
Dimensions										
Overall Length (w/ 3-pt.)	92.1 in. (2493 mm)	92.1 in. (2493 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	124.3 in. (3157 mm) HST (125.5 in. (3189 mm))	124.3 in. (3157 mm) HST (125.5 in. (3189 mm))	124.3 in. (3157 mm)
Overall Width (w/ ag tires)	46.5 in. (1182 mm)	46.5 in. (1182 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)	55.1 in. (1400 mm)
Overall Height (w/ ROPS up)	88 in. (2226 mm)	88 in. (2226 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)	99.2 in. (2520 mm)
Wheelbase	55.1 in. (1400 mm)	55.1 in. (1400 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	71.3 in. (1810 mm)	71.3 in. (1810 mm)	71.3 in. (1810 mm)
Ground Clearance	6.4 in. (162 mm)	6.4 in. (162 mm)	13.4 in. (340 mm)	13.4 in. (340 mm)	13.4 in. (340 mm)	13.4 in. (340 mm)	13.4 in. (340 mm)	14.5 in. (368 mm)	14.5 in. (368 mm)	14.5 in. (368 mm)
Weight	1485 lb. (675 kg)	1485 lb. (675 kg)	2646 lb. (1200 kg)	2679 lb. (1215 kg) HST (3397 lb. (1541 kg))	3397 lb. (1541 kg)	2679 lb. (1215 kg) HST (3397 lb. (1541 kg))	3397 lb. (1541 kg)	3373 lb. (1530 kg) HST (3523 lb. (1598 kg))	3373 lb. (1530 kg) HST (3523 lb. (1598 kg))	3373 lb. (1530 kg)
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Inside Turning Radius	8.2 ft. (2.54 m)	8.2 ft. (2.54 m)	8 ft. (2.4 m)	8 ft. (2.4 m)	8 ft. (2.4 m)	8 ft. (2.4 m)	8 ft. (2.4 m)	8 ft. (2.4 m)	103.2 in. (2600 mm)	103.2 in. (2600 mm)
Tilt Steering Wheel	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Standard	Standard
Safety Equipment										
Safety Interlock System (neutral start-operating)	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Fold Down ROPS (roll-over protective structure)	Std	Std	Std	Std	N/A	Std	N/A	Std	Std	Std
Fully Retractable Seatbelt	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Features										
Suspension Seat							Std	Std	Std	Std
Adjustable Seat			Std	Std	Std					
Cup Holder	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Glow Plug Engine Pre-heat	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Toolbox			Opt	Opt	Opt	Opt	Opt	Std	Std	Std
Head Lights/Tail Lights/Brake Lights	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Cruise Control	Opt	Opt	Opt	Opt	Opt	Opt	Opt			
Spark Arrestor Muffler	Opt	Opt								
Horn/Hazard Flasher/Turn Signals	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Rear Working Lights	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
Side Mirror	Opt	Opt	Opt	Opt	Std	Opt	Std	Opt	Opt	Opt

*Note: Hydraulic 3-pt. lift capacity will vary depending on lift point height.

Specifications



Model	CT4058	CT5545	CT5550	CT5555	CT5558
Engine	Diesel	Diesel	Diesel	Diesel	Diesel
Gross Horsepower	57.7 hp (43 kW)	45 hp (33.5 kW)	50 hp (37.5 kW)	55 hp (41 kW)	57.7 hp (43 kW)
No. of Cylinders	3	3	3	3	3
Total Displacement	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)	111.4 cu. in. (1826 cc)
Fuel Tank Capacity (gallons)	12.7 gal. (48 L)	14.8 gal. (56 L)	14.8 gal. (56 L)	14.8 gal. (56 L)	14.8 gal. (56 L)
3-Point, PTO & Hydraulics					
PTO Horsepower	45.1 hp (33.7 kW)	33.9 hp (25.3 kW)	38.9 hp (29 kW)	43.1 hp (32.1 kW)	48.3 hp (36 kW)
3-Point Hitch		Category I	Category I		
Lift Control Type	Hydraulic Position Control System	Position with Draft Control			
Lift Capacity at 24" Behind Lift Points (per SAE J283)	2716 lb. (1232 kg)	2844 lb. (1290 kg)	2844 lb. (1290 kg)	2908 lb. (1319 kg)	2908 lb. (1319 kg)
Rear PTO	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Rear PTO System	Independent	Independent	Independent	Independent	Independent
Mid-PTO	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm	Optional: 2000 rpm
Total Hydraulic Pump Capacity	16.5 gpm (62.4 L/min.)	17.9 gpm (67.6 L/min.)	17.9 gpm (67.6 L/min.)	17.9 gpm (67.6 L/min.)	17.9 gpm (67.6 L/min.)
Rear Hydraulics (optional)	2 Ports Standard	Single/Dual Remote Hydraulic Valve			
Telescopic Stabilizers	Standard	Standard	Standard	Standard	Standard
Lower Links	Rigid	Telescopic	Telescopic	Telescopic	Telescopic
Lifting Rod	Crank	Draft Control	Draft Control	Draft Control	Draft Control
Drive System					
Standard Transmission	HST	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Optional Transmission					
Speed Ranges	3 Range	3 Range	3 Range	3 Range	3 Range
Brakes	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc	Wet Multi-disc
Rear Differential Lock	Std	Std	Std	Std	Std
Four-Wheel Drive	Std	Std	Std	Std	Std
2WD	N/A	N/A	N/A	N/A	N/A
Travel Speeds (w/ Ag Tires)					
Forward	0-18.5 mph (29.7 km/hr.)	0-17.79 mph (28.63 km/hr.)	0-17.79 mph (28.63 km/hr.)	0-17.79 mph (28.63 km/hr.)	0-17.79 mph (28.63 km/hr.)
Reverse	0-12.9 mph (0-20.8 km/hr.)				
Dimensions					
Overall Length (w/ 3-pt.)	125.5 in. (3189 mm)	139.6 in. (3547 mm)	139.6 in. (3547 mm)	139.6 in. (3547 mm)	139.6 in. (3547 mm)
Overall Width (w/ ag tires)	62.8 in. (1596 mm)	65.6 in. (1665 mm)	65.6 in. (1665 mm)	65.7 in. (1669 mm)	65.7 in. (1669 mm)
Overall Height (w/ ROPS up)	96.8 in. (2458 mm)	95.6 in. (2429 mm)	95.6 in. (2429 mm)	96.5 in. (2452 mm)	96.5 in. (2452 mm)
Wheelbase	71.3 in. (1810 mm)	75.6 in. (1920 mm)	75.6 in. (1920 mm)	75.6 in. (1920 mm)	75.6 in. (1920 mm)
Ground Clearance	14.5 in. (368 mm)	13.1 in. (335 mm)	13.1 in. (335 mm)	13.7 in. (350 mm)	13.7 in. (350 mm)
Weight	3523 lb. (1598 kg)	4315 lb. (1957 kg)	4315 lb. (1957 kg)	4520 lb. (2050.3 kg)	4520 lb. (2050.3 kg)
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Inside Turning Radius	103.2 in. (2600 mm)	118.7 in. (2990 mm)	118.7 in. (2990 mm)	120.7 in. (3040 mm)	120.7 in. (3040 mm)
Tilt Steering Wheel	Standard	Standard	Standard	Standard	Standard
Safety Equipment					
Safety Interlock System (neutral start-operating)	Std	Std	Std	Std	Std
Fold Down ROPS (roll-over protective structure)	Std	N/A	N/A	N/A	N/A
Fully Retractable Seatbelt	Std				
Features					
Suspension Seat	Std	Std	Std	Std	Std
Adjustable Seat					
Cup Holder	Std	Std	Std	Std	Std
Glow Plug Engine Pre-heat	Std	Std	Std	Std	Std
Toolbox	Std	Std	Std	Std	Std
Head Lights/Tail Lights/Brake Lights	Std	Std	Std	Std	Std
Cruise Control		Std	Std	Std	Std
Spark Arrestor Muffler					
Horn/Hazard Flasher/Turn Signals	Std	Std	Std	Std	Std
Rear Working Lights	Opt	Std	Std	Std	Std
Side Mirror	Opt	Std	Std	Std	Std

*Note: Hydraulic 3-pt. lift capacity will vary depending on lift point height.



4 WHEEL DRIVE

3 CYLINDER ENGINES

540 RPM REAR PTO

ATTACHMENTS AND IMPLEMENTS

Without attachments or implements, it just wouldn't be Bobcat equipment. Bobcat attachments and implements are a significant source of versatility and value for customers. With the Bobcat brand reputation as the choice of professionals and homeowners alike, owners can be sure they'll find the right tool for any job.

PRIMARY ATTACHMENTS

BOBCAT	PRIMARY ATTACHMENT MODEL NAME		
	FEL	BHL	MM
CT1021	FL6	BH66	M60
CT1025	FL6	BH66	M60
CT2025	FL7	BH76	M60
CT2035	FL8	BH76	
CT2040	FL8	BH76	
CT2535	FL8	BH76	
CT2540	FL8	BH76	
CT4045	FL9	BH86	
CT4050	FL9	BH86	
CT4055	FL9	BH86	
CT4058	FL9	BH86	
CT5545	FL9-5	BH86	
CT5550	FL9-5	BH86	
CT5555	FL9-5	BH86	
CT5558	FL9-5	BH86	

FRONT END LOADER (FEL)					
SPECIFICATIONS					
MODEL	FL6	FL7	FL8	FL9	FL9-5
MAX. LIFT HEIGHT TO PIVOT PIN	74"	94"	99"	104"	108"
MAX. LIFT HEIGHT UNDER LEVEL BUCKET	65"	88"	93"	94"	103"
CLEARANCE WITH BUCKET DUMPED	51"	72"	74"	75"	83"
REACH AT MAXIMUM LIFT HEIGHT	27"	11.5"	20"	25"	16.5"
MAXIMUM DUMP ANGLE	45	48	50	50	67
REACH WITH BUCKET ON GROUND	52"	62"	62"	67.5"	72"
MAXIMUM ROLLBACK ANGLE	27	32	17	36	29
DIGGING DEPTH	5.25"	5.75"	5.5"	11.5"	8.25"
LIFT CAPACITY AT PIVOT PIN (MAX. HEIGHT) (NOT TESTED)	675 lb.	1376 lb.	1378 lb.	2474 lb.	2760 lb.
BREAKOUT FORCE AT 500 MM	1332 lb. (@Pivot Pin)	1656 lb.	2467 lb.	2758 lb.	2963 lb.
WEIGHT	606 lb.	915 lb.	1070 lb.	1202 lb.	1400 lb.
BUCKET WIDTHS	48"	60"	60"	66"	72"

MID MOUNT MOWER (MM)	
SPECIFICATIONS	
MODEL	M60
CUTTING WIDTH	60 in. (1524 mm)
CUTTING HEIGHT	1" - 4"
TRANSPORT HEIGHT	6"
GEAR TYPE	Spiral Bevel
NUMBER OF BLADES	3
BLADE SPINDLE SPEED	2888 rpm
BLADE TIP VELOCITY	78.2 m/s
BLADE LENGTH	20.4"
DECK THICKNESS	0.13"
TOTAL WIDTH	73.4"
TOTAL LENGTH	37.9"
TOTAL HEIGHT	10.8"
DRIVE TYPE	U-Joint and V-Belt
LIFTING TYPE	3 Point Hitch Links
COMPATIBLE WITH LOADER	Yes
DRIVE OVER DECK	Yes

BACKHOE LOADER (BHL)			
SPECIFICATIONS			
MODEL	BH66	BH76	BH86
DIGGING DEPTH (2' FLAT BOTTOM)	84"	90"	94.5"
REACH FROM CENTER LINE OF SWING PIVOT	114"	125"	136"
LOADING HEIGHT (BUCKET AT 60°)	52"	72"	80"
MAXIMUM LEVELING ANGLE	8 deg.	10 deg.	10 deg.
SWING ARC	150 deg.	180 deg.	180 deg.
TRANSPORT HEIGHT (MAXIMUM)	70.5"	83.5"	93"
BUCKET ROTATION	163 deg.	180 deg.	180 deg.
STABILIZER SPREAD (DOWN POSITION)	88"	69"	69"
STABILIZER SPREAD (UP POSITION)	56"	46.5"	46.5"
BUCKET DIGGING FORCE	2096 lbf.	2818 lbf.	3748 lbf.
DIPPERSTICK DIGGING FORCE	1160 lbf.	2105 lbf.	2205 lbf.
OPERATING PRESSURE	1885 psi	2466 psi	2466 psi
WEIGHT (WITHOUT BUCKET)	657 lb.	880 lb.	1102 lb.



ATTACHMENTS AND IMPLEMENTS

3-POINT ATTACHMENTS

3-POINT ATTACHMENTS									
BOBCAT	TRACTOR WIDTH (INCHES)	BOX BLADE	ANGLE BLADE	RAKE	ROTARY CUTTER	TILLER	SNOW BLOWER	FINISH MOWER	AUGER
CT1021	46.7	48	60	60	48	48	50	555 (60)	160
CT1025	46.7	48	60	60	48	48	50	555 (60)	160
CT2025	55.1	60	60	60	60	60	60	555 (60), 655 (72)	160
CT2035	55.1	60	60	60	60	60	60, 66	555 (60), 655 (72)	160, 205
CT2040	55.1	60	60	60	60	60	60, 66	555 (60), 655 (72)	160, 205
CT2535	54.5	60	60	60	60	60	60, 66	555 (60), 655 (72)	160, 205
CT2540	54.5	60	60	60	60	60	60, 66	555 (60), 655 (72)	160, 205
CT4045	62.8	72	72	72	60, 72	60, 72	66	655 (72)	205
CT4050	62.8	72	72	72	60, 72	60, 72	66, 74	655 (72)	205
CT4055	62.8	72	72	72	60, 72	60, 72	74	655 (72)	205
CT4058	62.8	72	72	72	60, 72	60, 72	66	655 (72)	205
CT5545	65.6	72	72, 84	72, 84	72	72	66, 74	655 (72)	205
CT5550	65.6	72	72, 84	72, 84	72	72	74	655 (72)	205
CT5555	65.7	72	72, 84	72, 84	72	72	74	655 (72)	205
CT5558	65.7	72	72, 84	72, 84	72	74	74	655(72)	205

3-POINT ATTACHMENTS	SIZE (INCHES)
BOX BLADE	48, 60, 72
ANGLE BLADE	60, 72, 84
RAKE	60, 72, 85
ROTARY CUTTER	48, 60, 72
TILLER	48, 60, 72
SNOW BLOWER	50, 60, 66, 74
FINISH MOWER	60, 72
POST HOLE DIGGER (AUGER)	160, 205 (6" - 30" Bits)
REAR BALLAST BOX	
QUICK HITCH	Category I



SNOWBLOWER				
SPECIFICATIONS				
MODEL	500	600	660	740
CUTTING WIDTH	50"	60"	66"	74"
CUTTING HEIGHT	24"	24"	24"	25"
FAN	4-Blade	4-Blade	4-Blade	4-Blade
FAN DIMENSIONS	22" X 7"	22" X 7"	22" X 7"	23" X 7"
DRIVE FAN	540 rpm (Open Gear)			
AUGER DIAMETER	15"	15"	15"	15"
SKID SHOES	Adjustable & Replaceable	Adjustable & Replaceable	Adjustable & Replaceable	Adjustable & Replaceable
HITCH CATEGORY	Category I	Category I	Category I	Category I
TRACTOR REQUIREMENT	15-30 hp	20-40 hp	22-40 hp	40-70 hp
WEIGHT	422 lb.	470 lb.	515 lb.	756 lb.

ROTARY CUTTER			
SPECIFICATIONS			
MODEL	48	60	72
OVERALL WIDTH	51"	63"	75"
CUTTING WIDTH	48"	60"	72"
CUTTING HEIGHT	1.5" to 9"	1.5" to 9"	1.5" to 9"
OVERALL LENGTH	68"	80"	92"
DECK TYPE	Single	Single	Single
DECK THICKNESS	14 ga.	14 ga.	14 ga.
DRIVELINE	Shear Bolt	Shear Bolt	Shear Bolt
TRACTOR REQUIREMENTS (PTO)	18-45 hp (540 rpm)	20-50 hp (540 rpm)	25-65 hp (540 rpm)
HITCH CATEGORY	Category I	Category I	Category I
BLADES (HEAT TREATED SUCTION)	3" x 0.5"	3" x 0.5"	3" x 0.5"
GEAR BOX (HP RATING)	45	45	45
WEIGHT	360 lb.	460 lb.	580 lb.

BOX BLADE			
SPECIFICATIONS			
MODEL	48	60	72
OVERALL WIDTH	49.5"	62"	74"
CUTTING EDGES (2)	48" (Reversible)	60" (Reversible)	72" (Reversible)
HEIGHT	32"	33"	33"
OVERALL LENGTH	28"	31"	31"
TRACTOR REQUIREMENTS	18-25 hp	20-50 hp	35-60 hp
HITCH CATEGORY	Category I	Category I	Category I
DIGGING SHANKS	4 (Adjustable/Replaceable)	5 (Adjustable/Replaceable)	6 (Adjustable/Replaceable)
WEIGHT	270 lb.	395 lb.	445 lb.

ATTACHMENTS AND IMPLEMENTS

ANGLE BLADE			
SPECIFICATIONS			
MODEL	60	72	84
OVERALL WIDTH	60"	72"	84"
CUTTING EDGE	Reversible	Reversible	Reversible
OVERALL HEIGHT	38"	38"	38"
OVERALL LENGTH	40"	40"	40"
BLADE HEIGHT	15"	15"	15"
HITCH CATEGORY	Category I	Category I	Category I
BLADE ANGLING	Manual (5 Pin Positions)	Manual (5 Pin Positions)	Manual (5 Pin Positions)
WEIGHT	197 lb.	213 lb.	232 lb.

LANDSCAPE RAKE			
SPECIFICATIONS			
MODEL	60	72	84
OVERALL WIDTH	60"	72"	84"
TINES (CURVED)	High Carbon (Replaceable)	High Carbon (Replaceable)	High Carbon (Replaceable)
OVERALL HEIGHT	39"	39"	39"
OVERALL LENGTH	42"	42"	42"
HITCH CATEGORY	Category I	Category I	Category I
ANGLING	Manual (360 deg.)	Manual (360 deg.)	Manual (360 deg.)
WEIGHT	195 lb.	215 lb.	238 lb.

FINISH MOWER		
SPECIFICATIONS		
MODEL	60 (555)	72 (655)
CUTTING WIDTH	60"	72"
CUTTING HEIGHT	1.5" to 5.5"	1.5" to 5.5"
BLADES	3	3
BLADE DIMENSIONS	1/4" x 2-1/4" x 21-3/4"	1/4" x 2-1/4" x 25-3/4"
DECK THICKNESS	7 ga.	7 ga.
TIRES	13 / 500 x 6 4-ply	13 / 500 x 6 4-ply
TRACTOR REQUIREMENTS (PTO)	15-55 hp	20-55 hp
HITCH CATEGORY	Category I	Category I
GEAR BOX	Closed (540 rpm)	Closed (540 rpm)
WEIGHT	627 lb.	697 lb.

TILLER			
SPECIFICATIONS			
MODEL	48	60	72
OVERALL WIDTH	55"	64"	79"
TILLING WIDTH	48"	60"	72"
HEIGHT	38"	38"	38"
OVERALL LENGTH	28"	28"	28"
DRIVELINE	Gear Driven-Oil Bath	Gear Driven-Oil Bath	Gear Driven-Oil Bath
TRACTOR REQUIREMENTS (PTO)	18-25 hp (540 RPM)	20-50 hp (540 RPM)	25-50 hp (540 RPM)
HITCH CATEGORY	Category I	Category I	Category I
TINES	Heat Treated/Self Sharp.	Heat Treated/Self Sharp.	Heat Treated/Self Sharp.
ROTATION	Forward or Reverse	Forward or Reverse	Forward or Reverse
DEPTH RUNNERS	1" to 4"	1" to 4"	1" to 4"
WEIGHT	591 lb.	638 lb.	718 lb.

POST HOLE DIGGER		
SPECIFICATIONS		
MODEL	160	205
OUTPUT SHAFT	2"	2"
MAIN FRAME MATERIAL	3" Steel Tubing	3.5" Steel Tubing
DRIVELINE	Shear-bolt Protected	Shear-bolt Protected
AUGER BITS	6" - 30" single & double flighted bits	
TRACTOR REQUIREMENTS (PTO)	20-40 hp	35-60 hp
HITCH CATEGORY	Category I	Category I
WEIGHT	160 lb.	205 lb.

QUICK HITCH	
SPECIFICATIONS	
MODEL	CATEGORY I
INSIDE HOOKS (DISTANCE)	27-1/4"
OUTSIDE HOOKS (DISTANCE)	29-1/2"
WEIGHT	76 lb.

WARRANTY

Bobcat Compact Tractor

Bobcat Company warrants to its authorized dealers and authorized dealers of Bobcat Equipment Ltd., who in turn warrant to the owner, that each new Bobcat Compact Tractor will be free from proven defects in material and workmanship with respect to (i) all components of the product except as otherwise specified herein for twenty four (24) months or 1500 hours (whichever occurs first), (ii) the powertrain components consisting of clutch housing, transmission case, differential and final drive housing and all parts contained therein plus the drive axles and external driveshafts, and the engine components consisting of the crankcase, cylinder head, front gear case, valve cover pans and all parts contained therein but not including fuel, electrical, cooling, intake or exhaust components unless specifically covered under the Emission Control System Warranty for such product, for forty eight months unlimited hours for a tractor sold to a Non-Commercial Customer as specified in the delivery report submitted by the dealer to Bobcat or thirty-six months or 2000 hours (whichever occurs first) for a tractor sold to a Commercial Customer as specified in the delivery report submitted by the dealer to Bobcat, (iii) Bobcat brand tires, for twelve (12) months on a prorated basis based on the remaining depth of the tire at the time any defect is discovered, (iv) Bobcat brand batteries, for twelve (12) months with an additional twelve (12) months provided that Bobcat Company shall only reimburse a fixed portion of the cost of replacing the battery during such additional twelve months and (v) Bobcat accessories that are factory installed for a period of twelve (12) months. The foregoing time periods shall all commence after delivery by the authorized Bobcat dealer to the original buyer.

During the warranty period, the authorized Bobcat dealer shall repair or replace, at Bobcat Company's option, without charge for parts and labor, any part of the Bobcat product except as otherwise specified herein which fails because of defects in material or workmanship. The owner shall provide the authorized Bobcat dealer with prompt written notice of the defect and allow reasonable time for repair or replacement. Bobcat Company may, at its option, require failed parts to be returned to the factory. Travel time of mechanics and transportation of the Bobcat product to the authorized Bobcat dealer for warranty work are the responsibility of the owner. The remedies provided in this warranty are exclusive.

This warranty does not apply to tires (except Bobcat brand tires). The owner shall rely solely on the warranty, if any, of the respective manufacturers thereof. This warranty does not cover replacement of scheduled service items such as oil, filters, tune-up parts, and other high-wear items. This warranty does not cover damages resulting from abuse, accidents, alterations, use of the Bobcat product with any accessory or attachment not approved by Bobcat Company, air flow obstructions, or failure to maintain or use the Bobcat product according to the instructions applicable to it.

THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES AND CONDITIONS, EXCEPT THE WARRANTY OF TITLE AND THE EMISSION CONTROL SYSTEM WARRANTY FOR THE PRODUCT. BOBCAT COMPANY DISCLAIMS ALL OTHER WARRANTIES AND CONDITIONS, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL BOBCAT COMPANY OR THE AUTHORIZED BOBCAT DEALER BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES WHATSOEVER, INCLUDING, BUT NOT LIMITED TO, LOSS OR INTERRUPTION OF BUSINESS, LOST PROFITS, OR LOSS OF MACHINE USE, WHETHER BASED ON CONTRACT, WARRANTY, TORT, NEGLIGENCE, STRICT LIABILITY, STATUTE OR OTHERWISE, EVEN IF BOBCAT COMPANY OR THE AUTHORIZED BOBCAT DEALER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE TOTAL LIABILITY OF BOBCAT COMPANY AND THE AUTHORIZED BOBCAT DEALERS WITH RESPECT TO THE PRODUCT AND SERVICES FURNISHED HEREUNDER SHALL NOT EXCEED THE PURCHASE PRICE OF THE PRODUCT UPON WHICH SUCH LIABILITY IS BASED.

