

## M5 SERIES

## M5-091/M5-111

### \*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

#### DIESEL ENGINE

Kubota V3800 Direct Injection  
3.8L (230 cu. in.) 4 Cyl  
EPA Tier 4 Final Compliant  
Common Rail Electronic Fuel Injection  
Electronic Engine Management  
Turbocharged  
w/Wastegate and Intercooled  
60 Amp Alternator - ROPS  
80 Amp Alternator - Cab  
12V 900 CCA Battery

#### EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)  
SCR System

#### HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
Max. Flow @ Rated Engine Speed  
ROPS: 2400 rpm  
Cab: 2600 rpm  
Power Steering: 5.4 gpm  
Impl. Flow - ROPS: 15.9 gpm  
Impl. Flow - Cab: 17.0 gpm  
total Flow - ROPS: 21.3 gpm  
Total Flow - Cab: 23.1 gpm

#### REMOTE VALVES

(1) SCD (Self Canceling Detent)  
(1) FD (Float Detent) on -1 models (2 Total Standard)

#### 3 Point Hitch & Drawbar

Cat II 3-Point Hitch  
8 Speed Models  
@ Lift Points: 7055 lbs  
(ASAE)@ 24" Behind: 5181 lbs  
12/24 Speed Models  
@ Lift Points: 8600 lbs  
(ASAE)@ 24" Behind: 7275 lbs  
2 External Lift Cylinders  
Telescoping Lower Links  
Stabilizers  
Swinging Drawbar - Straight

#### POWER TAKE OFF

Live-Independent Hyd. PTO  
SAE 1 3/8" Six Spline  
540 RPM @ 2205 Eng. RPM  
540 RPM @ 2035 Eng. RPM - 12/24 speed  
540E\* @ 1519 Eng. RPM

#### Transmission/PTO

8F/8R Two Range, 4-Speed  
12F/12R Two Range, 6-Speed  
540/540E  
24F/24R Two Range, 6-Speed Hi/Lo  
540/540E  
24 speed on M5-111 only  
Electronic 4WD Function  
Electro-Hydraulic Shuttle Shift  
Clutch - Multi-Plate Wet  
Planetary Final Drives  
Hydraulic Wet Disc Brakes

#### FRONT AXLE

Hydrostatic Power Steering  
2WD: Tubular Steel Beam Telescoping  
4WD: Cast Iron, Bevel Gear 55 Deg  
Planetary Final Drives  
Adjustable (Rim) Tread Spacing

#### FLUID CAPACITY

Fuel Tank Capacity: 27.7 gal  
DEF Tank Capacity: 3.2 gal  
Cooling System: 11 qts  
Crankcase: 11.3 qts  
Hydraulics/Trans: 15.85 gal

#### INSTRUMENTS

LCD readout for MPH and PTO rpm  
RPM Memory  
Tachometer/Hour meter  
Oil Pressure  
Fuel Gauge  
Coolant Temperature  
Gear Speed Digital Light Indicator  
Digital Light Indicator F/R Direction

#### TIRES AND WHEELS

Front 12.4-24  
Rear 18.4-30

#### Ultra Grand Cab II

4-Post, ROPS Certified  
RH & LH Doors  
Tinted Glass Doors and Windows  
In-Roof Window  
Tilt Steering Wheel  
Dual Level Air Conditioning & Heater  
Front and Wiper w/ Washer  
Front Sun Visor  
Retractable Seat belt  
LH & RH Side Mirrors  
Radio Ready Cab  
Steps, Left and Right Side  
Interior Dome Light  
12V - 30-Amp 2 Wire Coupler  
12V - 3 Pin 30-Amp Coupler  
12V - Outlet  
Cup Holder  
Instructor Seat Ready  
Horn

#### LIGHTING

2 Headlights - Tail lights  
4 Hazard Flasher Lights w/ Turn Signals  
2 Grill Mounted Worklights  
2 Front Cab Halogen Worklights  
2 Rear Halogen Worklights

#### SAFETY EQUIPMENT

Flip-Up PTO Shield  
Safety Start Switches  
Electric Key Shut Off  
Parking Brake  
Turn Signals  
SMV Sign  
7-Pin Electrical Trailer Connector

\* if equipped 12/24 Standard

Model Specifications			
M5-091		M5-111	
SAE Gross HP:	92.5	SAE Gross HP:	105.6
Engine Net HP:	85.5	Engine Net HP:	100
Max . PTO HP:	76	Max . PTO HP:	89

## M5 SERIES

## M5-091

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
<b>2WD MODELS</b>			
***BASE SPEC STANDARD TRACTOR WITH STANDARD TIRES***			
M5-091HF-1	2WD Utility 2 Post Foldable ROPS Tractor	6482 lbs	See Zone Pricing
M5-091HFC-1	2WD Utility Ultra Grand Cab II Tractor r	6482 lbs	\$12,478.00

M5-091/ M5-111 2WD				
TIRES AND WHEELS <sup>†</sup>				
ORDER CODE	DESCRIPTION	WEIGHT EACH		
STANDARD TIRES				
AMR8961A*	F-TIRE 7.5-18 F2 Titan Tru Trac TT	68 lbs		Add In Base Price
AMR8530B*	R-TIRE 18.4-30 R1W GDYR OPTITRAC	393 lbs		
AMXR8789		75 lbs	M132M80	Less (\$165.00)
AMR8522A		346 lbs		
AG - RADIAL REAR				
AMR8961A		68 lbs	M388M80	Add \$487.00
AMR8531A		429 lbs		
AMR8980B		91 lbs	M537M60	Add \$671.00
AMR8531A		429 lbs		
AMR8961A		68 lbs	K1M275M20	Add \$1,593.00
AMR8514B		1027 lbs		
AMR8980B		91 lbs	K1M424M00	Add \$1,779.00
AMR8514B		1027 lbs		
AMR8980B		91 lbs	M838M40	Add \$1,047.00
AMR8537A		342 lbs		
AMR8980B		91 lbs	K1M742M40	Add \$2,177.00
AMR9258A		910 lbs		
TURF				
AMXR8789		75 lbs	M8M00	Less (\$9.00)
AMR8521		301 lbs		
AMR8545		65 lbs	M153M60	Less (\$191.00)
AMR8546		289 lbs		
INDUSTRIAL				
AMXR8789		75 lbs	M200M00	Less (\$249.00)
AMR8532		304 lbs		

† See Tire Section for Individual Tire Pricing and Information

\* Standard tires

## M5 SERIES

## Model Upgrade M5-091/M5-111

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	ADD TO ZONE PRICE
<b>4WD MODELS</b>			
<b>***STANDARD TRACTOR WITH STANDARD TIRES***</b>			
M5-091HD-1	4WD Utility 2 Post Foldable ROPS Tractor	6900 lbs	\$8,380.00
M5-091HD12-1	4WD Utility 2 Post Foldable ROPS, 12 Speed 540/540E	6900 lbs	\$9,380.00
M5-091HDC-1	4WD Utility Ultra Grand Cab II	6900 lbs	\$16,384.00
M5-091HDC12-1	4WD Utility Ultra Grand Cab II, 12 Speed 540/540E	6900 lbs	\$17,382.00
M5-111HD-1	4WD Utility 2 Post Foldable ROPS Tractor	6900 lbs	\$10,771.00
M5-111HD12-1	4WD Utility 2 Post Foldable ROPS, 12 Speed 540/540E	6900 lbs	\$9,380.00
M5-111HDC-1	4WD Utility Ultra Grand Cab II	6900 lbs	\$18,776.00
M5-111HDC12-1	4WD Utility Ultra Grand Cab II, 12 Speed 540/540E	6900 lbs	\$19,780.00
M5-111HDC24-1	4WD Utility Ultra Grand Cab II, 24 Speed 540/540E	6900 lbs	\$22,388.00

M5-091/ M5-111 4WD		Additional Price With Tire Option	
TIRES AND WHEELS <sup>†</sup>			
ORDER CODE	DESCRIPTION	WEIGHT EACH	
<b>STANDARD TIRES</b>			
AMR8556B*	F-TIRE 12.4-24 R1W GDYR OPTITRAC	193 lbs	
AMR8530B*	R-TIRE 18.4-30 R1W GDYR OPTITRAC	393 lbs	Add In Base Price
<b>AG - BIAS REAR</b>			
AMR8556B*	F-TIRE 12.4-24 R1W GDYR OPTITRAC	193 lbs	
AMR8530B*	R-TIRE 18.4-30 R1W GDYR OPTITRAC	393 lbs	Add \$0.00
AMR8538	F-TIRE 12.5/80-18 Titan Trac Impl 422	147 lbs	
AMR8523A	R-TIRE 16.9-24 R1 Ttn Hi TracLug TL 2.5"	265 lbs	Less (\$923.00)
MR8957	F-TIRE 9.50-22 R1 Farm Svc Lug M 8stud	123 lbs	
AMR8523A	R-TIRE 16.9-24 R1 Ttn Hi TracLug TL 2.5"	265 lbs	Less (\$1,135.00)
AMR8555A	F-TIRE 11.2-24 R1 Firestone (SAT) II WAF	163 lbs	
AMR8933	R-TIRE 16.9-30 R1 DuraTorq 19mm holes	348 lbs	Less (\$249.00)
AMR8555A	F-TIRE 11.2-24 R1 Firestone (SAT) II WAF	163 lbs	
AMR8935D	R-TIRE 16.9-30 R1 Gdyr DuraTorq Cast	618 lbs	Add \$805.00
<b>AG - RADIAL REAR</b>			
AMR8557A	F-TIRE 320/85R24 R1W GDYR OPTRAC	220 lbs	
AMR8531A	R-TIRE 460/85R30 R1W GDYR OPTRAC	429 lbs	Add \$873.00
AMR8557A	F-TIRE 320/85R24 R1W GDYR OPTRAC	220 lbs	
AMR8514B	R-TIRE 460/85R30 R1W GDYR OPTRAC CAST	1027 lbs	Add \$1,981.00
AMR8557A	F-TIRE 320/85R24 R1W GDYR OPTRAC	220 lbs	
AMR8537A	R-TIRE 420/85R34 R1W ALLIANCE 385 RADIAL	342 lbs	Add \$1,249.00
AMR8557A	F-TIRE 320/85R24 R1W GDYR OPTRAC	220 lbs	
AMR9258A	R-TIRE 420/85R34 R1W ALLIANCE 385 CAST	910 lbs	Add \$2,379.00
<b>TURF</b>			
AMR8566	F-TIRE 13.50-16.1 F-STONE ANS R3 TRF	112 lbs	
AMR8521	R-TIRE 18.4-26 R3 (ANS) 19mm holes	301 lbs	Add \$381.00
<b>INDUSTRIAL</b>			
AMR8808	F-TIRE 12.5/80-18 I3 Ttn Contrac 8stud	159 lbs	
AMR8532	R-TIRE 19.5L-24 R4 Titan Ind Trac Lug	304 lbs	Less (\$267.00)
<b>TERRAIN KING</b>			
AMR8557A	F-TIRE 320/85R24 R1W GDYR OPTRAC	220 lbs	
AMR8514B	R-TIRE 460/85R30 R1W GDYR OPTRAC CAST	1027 lbs	Add \$1,981.00

\* Standard tires

Ⓢ Not Compatible for Loader Applications

## M6S SERIES

## M6S-111 Midsize Utility Tractors

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

### DIESEL ENGINE

Kubota V3800 Direct Injection  
3.8L (230 cu. in.) 4 Cyl  
EPA Tier 4 Final Compliant  
Common Rail Electronic Fuel Injection  
Electronic Engine Management  
Turbocharged  
w/Wastegate and Intercooled  
12V 900 CCA Battery  
Charging Output 80 amps Cab

### EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)  
SCR System

### HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
Max. Flow @ Rated Engine Speed  
Cab: 2600 RPM  
Power Steering: 12.9 gpm  
Impl. Flow - Cab: 17.6 gpm  
Total Flow - Cab: 30.5 gpm

### REMOTE VALVES

(1) SCD (Self Canceling Detent)  
(1) FD (Float Detent)

### 3 Point Hitch & Drawbar

Cat II 3-Point Hitch  
@ Lift Points: 4960 lbs  
(ASAE)@ 24" Behind: 3858 lbs  
Telescoping Lower Links  
Telescoping Stabilizers  
Swinging Drawbar

### POWER TAKE OFF

Live-Independent Hyd. PTO  
SAE 1 3/8" Six Spline  
540 RPM @ 2405 Eng. RPM  
SAE 1-38" Twenty-One Spline  
1000 RPM @ 2389 Eng. RPM  
Optional 540/1000 standard on  
2 speed PTO Model

### Transmission

16F/16R or 32F/32R Swing Shift Plus  
Shuttle Shift: Electric Hydraulic  
Main Shift: 8-Speed synchronized  
w/swing shift  
Range Shift: 2-Speed Constant Mesh  
Dual Speed: 2-Speed power shift  
Clutch - Multi-Plate Wet  
Planetary Final Drives  
Hydraulic Wet Dish Brakes

### FRONT AXLE

Hydrostatic Power Steering  
2WD: Steel Adjustable  
4WD: Cast Iron, Bevel Gear 55 Deg  
Mechanical Differential Lock  
Adjustable (Rim) Tread Spacing

### FLUID CAPACITY

Fuel Tank Capacity: 46.2 gal  
DEF Tank Capacity: 3.2 gal  
Cooling System: 2.5 gal  
Crankcase: 2.8 gal  
Hydraulics/Trans: 15.8 gal  
Front Axle case: 1.9 gal  
Bevel Gear case: 0.9 gal

### Cab Features

Tilt Steering Wheel  
Retractable Seat belt  
12V - Outlet  
Cup Holder  
Cloth Suspension Seat  
Side view mirrors  
Front wiper and washer

### LIGHTING

2 Headlights - Tail lights  
4 Hazard Flasher Lights w/ Turn Signals  
2 Grill Mounted Worklights  
2 Cab Mounted Worklights  
2 Rear Cab Mounted Worklights

### SAFETY EQUIPMENT

Flip-Up PTO Shield  
Safety Start Switches  
Electric Key Shut Off  
Parking Brake  
Turn Signals  
SMV Sign  
7-Pin Electrical Trailer Connector

### INSTRUMENTS

LCD Display:  
Shuttle position, DEF gauge,  
Clock, Travel Speed, PTO RPM,  
Hour Meter, Trip Meter,  
Fuel Consumption, PM Level, RPM Memory  
Oil Pressure  
Fuel Gauge  
Coolant Temperature  
Swing Shift H/L Digital Light Indicator  
4WD Indicator  
Water Separator Light

### TIRES AND WHEELS

Front: See following pages for combinations noted as standard  
Rear: See following pages for combinations noted as standard

### Model Specifications

#### M6S-111

SAE Gross HP: 114  
Engine Net HP: 105  
Max . PTO HP: 95

## M6S Series Model Upgrade M6S-111 Midsize Utility Tractors

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	ADD TO ZONE PRICE
***STANDARD TRACTOR WITH STANDARD TIRES***			
M6S-111SHD	4WD Farm Tractor ROPS 540 PTO	8466 lbs	\$20,128.00
M6S-111SDS2	4WD Farm Tractor ROPS 540/1000 PTO With Swing Shift Plus	8466 lbs	\$22,535.00
M6S-111SHDC	4WD Farm Tractor w/Factory Cab (A/C)	9789 lbs	\$26,262.00
M6S-111SHDC2	4WD Farm Tractor w/Factory Cab (A/C) 540/1000 rpm PTO	9789 lbs	\$26,783.00
M6S-111SDSC	4WD Farm Tractor w/Factory Cab (A/C) With Swing Shift Plus	9789 lbs	\$28,220.00
M6S-111SDSC2	4WD Farm Tractor w/Factory Cab (A/C) 540/1000 rpm PTO with Swing Shift Plus	9789 lbs	\$28,659.00
M6S-111 4WD			
TIRES AND WHEELS <sup>1</sup>		Additional Price With Tire Option	
ORDER CODE	DESCRIPTION	WEIGHT EACH	PRICE
STANDARD TIRES			
AMR8559A	F-TIRE 340/85R24 R1W GY OPTITRAC	290 lbs	In Base Price
AMR9254D	R-TIRE 460/85R34 R1W GY OPTITRAC	540 lbs	In Base Price
AG - BIAS REAR			
AMR8558C	F-TIRE 13.6-24 R1 Dyna Torque II TL WAF	206 lbs	Add
AMR9246C	R-TIRE 18.4-34 R1 F-Stone(SAT)II CRC Cst	1000 lbs	\$261.00
AMR8558C	F-TIRE 13.6-24 R1 Dyna Torque II TL WAF	206 lbs	Less
AMR9244D	R-TIRE 18.4-34 R1 8-PLY BIAS SAT II	441 lbs	(\$1,139.00)
AMR8556B	F-TIRE 12.4-24 R1W G DYR OPTITRAC	193 lbs	Less
AMR8530B	R-TIRE 18.4-30 R1W G DYR OPTITRAC	393 lbs	(\$1,639.00)
AG - RADIAL REAR			
AMR8559A	F-TIRE 340/85R24 R1W GY OPTITRAC	290 lbs	Add
AMR9254D	R-TIRE 460/85R34 R1W GY OPTITRAC	540 lbs	\$0.00
AMR8559A	F-TIRE 340/85R24 R1W GY OPTITRAC	290 lbs	Add
AMR9256C	R-TIRE 460/85R34 R1W GY OPTITRAC CAST	1020 lbs	\$1,111.00
AMR8557A	F-TIRE 320/85R24 R1W G DYR OPTRAC	220 lbs	Add
AMR8514B	R-TIRE 460/85R30 R1W G DYR OPTRAC CAST	1027 lbs	\$343.00
AMR8557A	F-TIRE 320/85R24 R1W G DYR OPTRAC	220 lbs	Less
AMR9257B	R-TIRE 420/85R34 R1W ALLIANCE 385 RADIAL	380 lbs	(\$155.00)
AMR8557A	F-TIRE 320/85R24 R1W G DYR OPTRAC	220 lbs	Add
AMR9258A	R-TIRE 420/85R34 R1W ALLIANCE 385 CAST	910 lbs	\$741.00
AG - RADIAL R14 Tires			
AMR9304	F-TIRE LSW 340/70R28 GY R14	290 lbs	Add
AMR9308	R-TIRE LSW 460/75R38 GY R14 CAST	1072 lbs	\$3,177.00
AMR9308	F-TIRE 14-17.5 R4 WITH 0.55" INSET	168 lbs	Add
INDUSTRIAL TIRES	R-TIRE 19.5L-24 R4 Titan Ind Trac Lug	304 lbs	\$1,007.00
TERRAIN KING			
AMR9304	F-TIRE LSW 340/70R28 GY R14	290 lbs	Add
AMR9284TK	R-TIRE LSW 460/75R38 GY R14 CAST TK	1080 lbs	\$3,617.00
AMR8559A	F-TIRE 340/85R24 R1W GY OPTITRAC	290 lbs	Add
AMR9280TKA	R-TIRE 460/85R34 R1W GY OPT CAST TK	1010 lbs	\$761.00

\* Standard Tires

① Recommended for loader applications, increases base weight by approximately 600 lbs.

## M60 SERIES

## Model Downgrade M6060/M7060

### \*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

#### DIESEL ENGINE

Kubota V3307 Direct Injection  
3.3L (203 cu. in.) 4 Cyl  
EPA Tier 4 Emission Certified  
Common Rail Electronic Fuel Injection  
Electronic Engine Management  
Constant RPM Management  
Turbocharged  
45 Amp Alternator - ROPS  
60 Amp Alternator - Cab  
12V 700 CCA Battery

#### EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)

#### HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
Max. Flow @ Rated Engine Speed: 2600 RPM  
Power Steering: 6.1 gpm  
Impl. Flow: 11.0 gpm  
Impl. Flow, 12 Speed: 16.2 gpm  
Total Flow: 17.1 gpm  
Total Flow, 12 Speed: 22.3 gpm

#### REMOTE VALVES

(1) SCD (Self Canceling Detent)

#### 3 POINT HITCH & DRAWBAR

Cat I/II 3-Point Hitch  
@ Lift Points: 4190 lbs  
(ASAE)@24" Behind: 3307 lbs  
Telescoping Lower Links  
Telescoping Stabilizers  
Swinging Drawbar - Straight

#### POWER TAKE OFF

Live-Independent Hyd. PTO  
SAE 1 3/8" Six Spline  
540 RPM @ 2295 Eng. RPM  
540/540E Economy PTO Optional (12 Speed Standard)  
Provides 540 PTO @ 1942 Eng. RPM

#### TRANSMISSION

Fully Synchronized Transmission  
8F/ 8R or 12F / 12R Hydraulic-Shuttle  
Planetary Final Drives  
Rear Differential Lock

#### FRONT AXLE

Hydrostatic Power Steering  
2WD: Tubular Steel Beam Telescoping  
4WD: Cast Iron, Bevel Gear 55 Deg

#### FLUID CAPACITY

Fuel Tank Capacity ROPS: 18.5 gal  
Fuel Tank Capacity Cab: 23.8 gal  
Cooling System: 8.5 qts  
Crankcase: 11.6 qts  
Hydraulics/Trans: 59.2 qts  
Front Axle 4WD: 5.8 qts

#### INSTRUMENTS

Tachometer/Hour meter  
Oil Pressure  
Fuel Gauge  
Coolant Temperature

#### TIRES AND WHEELS

2WD: Front 9.5L x 15 F2  
Rear 16.9 x 28 R1  
4WD: Front 9.5 x 24 R1  
Rear 16.9 x 28 R1

#### OPERATOR PLATFORM

Semi-Flat Deck with Hanging Pedals  
High Back Seat with Adjustable  
Suspension  
Color Coded Controls  
Cup Holder

#### Cab (Ultra Grand Cab)

Integral factory ROPS Certified  
Flat Deck  
Suspension Seat w/ Retractable  
Seat Belt and Armrests  
Dual Level Air Conditioning & Heater  
Front Wiper w/ Washer - 2 Speed  
Radio Ready, includes 2 Speakers  
Antenna and Wiring Harness  
2 Doors, Frameless all glass  
Left & Right Side Steps  
Sun Visor  
Tilt Steering Wheel  
Interior Dome Light  
Accessory Plug 12V -15 Amp  
Cup Holder  
Ashtray  
Horn

#### LIGHTING

2 Headlights - Tail lights  
2 Hazard Flasher Lights w/  
Turn Signals

#### CAB LIGHTING

2 Front Work Lights  
2 Rear Work Lights

#### SAFETY EQUIPMENT

2 Post, ROPS Certified  
Retractable Seat Belt  
Flip-Up PTO Shield  
Safety Start Switches:  
Shuttle Lever Neutral  
PTO - OPC Alarm 10 Sec.  
Electric Key Shut Off  
Parking Brake  
Turn Signals  
SMV Sign

Model Specifications	
<b>M6060</b>	<b>M7060</b>
SAE Gross HP: 66.4	SAE Gross HP: 74.3
Engine Net HP: 64.1	Engine Net HP: 71.9
Max . PTO HP: 56	Max . PTO HP: 64

#### 2WD MODELS

\*\*\*STANDA RD T RACTO R WITH STANDA RD TI RES\*\*\*

CODE	DESC RIPTION	SHIP WT.		P PRICE
M6060HFC	2WD Utility Cab Tractor	5226 lbs	CREDIT	-\$623.00
M7060HFC	2WD Utility Cab Tractor	5248 lbs		\$1,289.00

#### 4WD MODELS

\*\*\*STANDA RD T RACTO R WITH STANDA RD TI RES\*\*\*

M6060HD	4WD Utility 2 Post Foldable ROPS Tractor	5358 lbs	CREDIT	-\$4,446.00
M6060HDC	4WD Utility Cab Tractor	5358 lbs		\$2,337.00
M7060HD	4WD Utility 2 Post Foldable ROPS Tractor	5027 lbs	CREDIT	-\$2,527.00
M7060HDC	4WD Utility Cab Tractor	5380 lbs		\$4,256.00
M7060HD12	4WD Utility 2 Post Foldable ROPS Tractor	5027 lbs	CREDI T	-\$38,158.00
M7060HDC12	4WD Utility Cab Tractor	5380 lbs		\$10,817.00

## M60 Series

## Model Downgrade M7060 - Tire Combinations All Models

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE	
			\$	
			\$	
			\$	
			\$	
M7060 4WD				
TIRES AND WHEELS†		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	PRICE	
STANDARD TIRES				
AMR8955C*	F-TIRE 9.5-24 R1 Goodyear Dura Torque	130 lbs	Add In Base Price	
AMR8932D*	R-TIRE 16.9-30 R1 DuraTorq 17mm holes	341 lbs		
AG - BIAS REAR				
AMR8955C*	F-TIRE 9.5-24 R1 Goodyear Dura Torque	130 lbs	MM0 Add	\$0.00
AMR8932D*	R-TIRE 16.9-30 R1 DuraTorq 17mm holes	341 lbs		
AMR8955C	F-TIRE 9.5-24 R1 Goodyear Dura Torque	130 lbs	Add	\$1,106.00
AMR8935D	①③ R-TIRE 16.9-30 R1 Gdyr DuraTorq Cast	618 lbs		
MR8956	F-TIRE 9.50-20 R1 B-Stone Farm Svc Lug M	98 lbs	Less	(\$662.00)
MR8924B	R-TIRE 16.9-24 R1 Ttn Hi TracLug TL 2.8"	263 lbs		
AG - RADIAL REAR				
AMR8605	⑤ F-TIRE LSW320/70R24 GDYR OPTI R1W	220 lbs	Add	\$366.00
AMR8616	R-TIRE LSW 420/75R34 GDYR OPTI R1W	460 lbs		
AMR8605	F-TIRE LSW320/70R24 GDYR OPTI R1W	220 lbs	Add	\$2,312.00
AMR8640	① R-TIRE LSW 420/75R34 GDYR OPTI R1W CST	949 lbs		
TURF				
AMR8536	F-TIRE 29x12.50-15 R3 Ttn MultiTrac8stud	77 lbs	Less	(\$736.00)
AMR8979	② R-TIRE 21.5L-16.1 R3 Firestone Turf&Fld	245 lbs		
AMR8566	F-TIRE 13.50-16.1 F-STONE ANS R3 TRF	112 lbs	Add	\$ 894. 00
AMR8938	R-TIRE 18.4-26 R3 (ANS) 17mm holes	310 lbs		
MR8954B	F-TIRE 9.50-24 R3 Gdyr All Weather TL	113 lbs	00 Add	
AMR8938	R-TIRE 18.4-26 R3 (ANS) 17mm holes	310 lbs		
AMR8526	④ F-TIRE LSW305-521R3 Grizz LSW Soft Turf	113 lbs	Less	(\$160.00)
AMR8541	R-TIRE LSW570-648 R3 Grizz LSW S.TF 5.75	261 lbs		
INDUSTRIAL				
AMR8797	F-TIRE 14-17.5 R4 WITH 0.55" INSET	168 lbs	Add	\$48.00
ALR8917	R-TIRE 16.9-24 R4 Titan Ind Tractor Lug	267 lbs		
AG/INDUSTRIAL HYBRID				
AMR8040	F-TIRE LSW320/70R24 GDYR R14T	195 lbs	Add	\$570.00
AMR8047	R-TIRE LSW420/75R34 GDYR R14T	422 lbs		

† See Tire Section for Individual Tire Pricing and Information

\* Standard tires.

① Recommended for loader applications, increases base weight by approx. 600-1100 lbs.

② Not approved for Backhoe applications.

③ Requires (16) qty - 3A111-97810 Shoulder Lug Nuts for Field Installation

④ For field installation, requires (16) 04512-60140 Spring Washers from Parts Department.

⑤ Steering Stops must be adjusted if 60° centers are required.

## M60 SERIES

## MODEL DOWNGRADE M5660SUH/M5660SUHD

### \*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

#### DIESEL ENGINE

Kubota V2403 Direct Injection  
2.4L (148.5 cu. in.) 4 Cyl  
EPA Tier 4 Final Compliant  
Common Rail Electronic Fuel Injection  
Electronic Engine Management  
Constant rpm Management  
Turbocharged  
45 Amp Alternator ROPS  
12V 600 CCA Battery

#### EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)

#### HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
Max. Flow @ Rated Engine Speed: 2600 rpm  
Power Steering: 6.1 gpm  
Impl. Flow: 10.6 gpm  
Total Flow: 16.5 gpm

#### REMOTE VALVES

(1) SCD (Self Canceling Detent)

#### 3 POINT HITCH & DRAWBAR

Cat II/I 3-point Hitch  
@ Lift Points: 4189 lbs  
(ASAE)@24" Behind: 3307 lbs  
Telescoping Lower Links  
Telescoping Stabilizers  
Swinging Drawbar - Straight

#### POWER TAKE OFF (540)

Live-Independent Hyd. PTO  
SAE 1 3/8" Six Spline  
540 rpm @ 2295 Eng. rpm  
540/540E Economy PTO Optional  
Provides 540 PTO @ 1942 Eng. rpm

#### TRANSMISSION

Eight Speed  
Fully Synchronized Transmission  
8F/ 8R Hydraulic-Shuttle  
Planetary Final Drives  
Rear Differential Lock

#### FRONT AXLE

Hydrostatic Power Steering  
2WD: Tubular Steel Beam Telescoping  
4WD: Cast Iron, Bevel Gear 55 Deg

#### FLUID CAPACITY

Fuel Tank Capacity: 17.2 gal.  
Cooling System: 8.5 qts.  
Crankcase: 7.6 qts.  
Hydraulics/Trans: 50.7 qts.  
Front Axle 4WD: 6.9 qts.

#### INSTRUMENTS

Tachometer/Hour meter  
Oil Pressure  
Fuel Gauge  
Coolant Temperature

#### TIRES AND WHEELS

2WD: Front 6.50 x 16 F2  
Rear 14.9 x 28 R1  
4WD: Front 8.3 x 24 R1  
Rear 14.9 x 28 R1

#### OPERATOR PLATFORM

Semi-Flat Deck with Hanging Pedals  
High Back Seat with  
Adjustable Suspension  
Color Coded Controls  
Cup Holder

#### LIGHTING

2 Headlights - Tail lights  
2 Hazard Flasher Lights w/  
Turn Signals

#### SAFETY EQUIPMENT

2-post, ROPS Certified  
Retractable Seat belt  
Flip-Up PTO Shield  
Safety Start Switches:  
Shuttle Lever Neutral  
PTO Off  
Electric Key Shut Off  
Parking Brake  
Turn Signals  
SMV Sign

Model Specifications	
M5660SUH 2WD	M5660SUHD 4WD
SAE Gross HP: 57.9	SAE Gross HP: 57.9
Engine Net HP: 56	Engine Net HP: 56
Max. PTO HP: 50	Max. PTO HP: 50

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
***STANDARD TRACTOR WITH STANDARD TIRES***			
M5660SUHD	4WD Utility 2 Post Foldable ROPS Tractor	4387	CREDIT -\$6,349.00
TIRES AND WHEELS†			Additional Price with Tire Option
ORDER CODE	DESCRIPTION	Weight Each	PRICE
STANDARD TIRES			
AMR8553*	F-TIRE 9.50-22 R1 Alliance 324	136 lbs	In Base Price
AMR8901B*	R-TIRE 14.9-28 R1 Firestone (SAT) II	255 lbs	
INDUSTRIAL			
AMR8797	F-TIRE 14-17.5 R4 WITH 0.55" INSET	168 lbs	Add \$454.00
ALR8917	R-TIRE 16.9-24 R4 Titan Ind Tractor Lug	267 lbs	
TURF			
AMR8566	F-TIRE 13.50-16.1 F-STONE ANS R3 TRF	112 lbs	Add \$1,300.00
AMR8938	R-TIRE 18.4-26 R3 (ANS) 17mm holes	310 lbs	
AMR8576	F-TIRE 31X13.5-15 R3 MULTI-TRAC TURF	92 lbs	Add \$362.00
AMR8979	R-TIRE 21.5L-16.1 R3 Firestone Turf&Fld	245 lbs	
AMR8526	F-TIRE LSW305-521R3 Grizz LSW Soft Turf	113 lbs	Add \$246.00
AMR8541	R-TIRE LSW570-648 R3 Grizz LSW S.TF 5.75	261 lbs	

\* Standard Tires

Not approved for Backhoe applications.  
Recommended for loader applications, increases base weight by approx. 600 lbs.  
Requires (16) qty - 3A111-97810 Shoulder Lug Nuts for Field Installation



## MX SERIES

## MODEL DOWNGRADE MX5400/MX6000

### \*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

#### DIESEL ENGINE

Kubota V2403 Direct Injection  
2.4L (148.6 cu. in.) 4 Cyl  
EPA Tier 4 Final Compliant  
Turbo Common Rail Electronic Fuel Injection  
Alternator- 45 Amp ROPS / 60 Amp CAB  
12V 600 (ROPS) / 650 (CAB) CCA Battery

#### EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)

#### HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
Max. Flow @ Rated Engine Speed: 2700 RPM  
Power Steering: 4.9 gpm  
Impl. Flow: 9.5 gpm  
Total Flow: 14.4 gpm

#### REMOTE VALVES

Optional (3) valves Float Detent,  
Double Acting

#### 3 POINT HITCH & DRAWBAR

Cat I / II 3-Point Hitch  
@ Lift Points: 2870 lbs  
(ASAE)@24" Behind: 2310 lbs  
2WD Model - Rigid Lower Links  
4WD Model - Telescoping Lower Links  
2WD Model - Turn Buckle Stabilizers  
4WD Model - Telescoping Stabilizers

#### POWER TAKE OFF

Live-Independent Hyd. PTO  
SAE 1 3/8" Six Spline  
540 RPM @ 2700 Eng. RPM

#### FRONT AXLE

Hydrostatic Power Steering  
2WD: Tubular Steel Telescopic  
4WD: Cast Iron, Bevel Gear

#### TRANSMISSION - F / DT

4-Speed Partially Synchronized  
8F/8R Two Range  
Clutch - Dry  
Mechanical Wet Disc Brakes  
Rear Differential Lock

#### TRANSMISSION - HST

3 Range Low/Med/High  
Cruise Control Standard  
Mechanical Wet Disc Brakes  
Left Side Brake Pedals  
Rear Differential Lock

#### FLUID CAPACITY

Fuel Tank Capacity (ROPS): 13.5 gal  
Fuel Tank Capacity (CAB): 11.9 gal  
Cooling System: 6.9 qts.  
Crankcase w/ Filter: 7.4 qts.  
Hydraulics/Trans: 11.6 gal.

#### INSTRUMENTS

Tachometer/Hour meter  
Fuel Gauge meter  
Coolant Temperature meter  
Warning Symbols

#### TIRES AND WHEELS

2WD: Front 7.5L x 15 R1  
Rear 14.9 x 26 R1  
4WD: Front 9.5L x 16 R1  
Rear 14.9 x 26 R1

#### LIGHTING

2 Headlights - Tail Lights  
2 Hazard Flasher Lights w/ Turn Signals  
2 Front Work Lights -CAB ONLY

#### ROPS OPERATOR PLATFORM

Semi-Flat Deck with Hanging Pedals  
Rubber Floor Mat  
High Back Seat with Adjustable Suspension  
Color Coded Controls  
Stationary PTO Switch  
Cup Holder

#### CAB OPERATOR PLATFORM

Semi-Flat Deck with Hanging Pedals  
Rubber Floor Mat  
High Back Seat with Adjustable Suspension  
Tilt-Steering  
Color Coded Controls  
Stationary PTO Switch  
Cup Holder  
Interior Light  
Internal Rearview Mirror  
Front Wiper w/ Washer  
A/C & Heater  
Speakers & Radio Pre-Wired  
Left & Right-Hand Door  
Left Hand Step  
Horn

#### SAFETY EQUIPMENT

2 Post Foldable ROPS  
ROPS Certified CAB  
Retractable Seat Belt  
Flip-Up PTO Shield  
Safety Start Switches:  
Shuttle Lever Neutral  
PTO Off  
Electric Key Shut Off  
Parking Brake  
Turn Signals  
SMV Sign

Model Specifications		
<u>MX5400 F/DT</u>	<u>MX5400 HST</u>	<u>MX6000</u>
SAE Gross HP: 55.5	SAE Gross HP: 57.0	SAE Gross HP: 63.4
Engine Net HP: 53.0	Engine Net HP: 53.8	Engine Net HP: 59.5
Max. PTO HP: 46.5	Max. PTO HP: 46.5	Max. PTO HP: 51.7

ORDER CODE	DESCRIPTION	APPROX.SHIP WT.	ADD/DELETE TO ZONE	PRICE
4WD MODELS				
*** STANDARD TRACTOR WITH STANDARD TIRES ***				
MX5400DT	4WD Utility 2 Post Foldable ROPS	3716 lbs	Credit	-\$8,766.00
MX5400DTC	4WD Utility Cab Tractor, Gear Transmission	4251 lbs	Credit	-\$2,518.00
MX5400HST	4WD Utility 2 Post Foldable ROPS, HST Transmission	3734 lbs	Credit	-\$7,522.00
MX5400HSTC	4WD Utility Cab Tractor, HST Transmission	4268 lbs	Credit	-\$1,264.00
MX6000HST	4WD Utility 2 Post Foldable ROPS, HST Transmission	3734 lbs	Credit	-\$6,290.00
MX6000HSTC	4WD Utility Cab Tractor, HST Transmission	4268 lbs	Credit	-\$52.00
STANDARD TIRE - BIAS REAR				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdys Dura Torque 6stud		IN BASE PRICE	
AMXR 8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL			
INDUSTRIAL				
AMXR8828	F-TIRE 12-16.5 R4Titan HD2000			\$254.00
AMXR8862A	R-TIRE TITAN 17.5L-24 8 PLY R4			
TURF				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf			\$244.00
ALR6802	R-TIRE 44x18-20 R3 Titan Multi Trac 8 stud			
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430			\$232.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud			

