

K Series U35-4

U35-4

Tight Tail Swing Hydraulic Excavator

FEATURES

Tight Tail Swing
 Half Pitched Rubber Tracks or Steel Tracks
 ROPS/OPG (Top Guard, Level 1) 4 Post Canopy or Air Conditioned & Heated Cab
 Suspension Seat
 Kubota 3 Hydraulic Pump Design
 1 Gear; 2 Variable Displacement Pumps
 All Controls Hydraulic Pilot Controls
 Hydraulic Accumulator
 Two Operating Pattern Selection System
 Digital Control Panel
 Attachment Flow Presets, Service Alerts
 Standard Front Dozer Blade with Float
 Optional Float Angle Blade w/ BOCE
 360 Degree Full Rotation
 71° Left and 45° Right Boom Swing Angle
 15.8 GPM Adjustable Auxiliary Hydraulics Port
 Auxiliary Hydraulic Diverter Valve
 Five Second Quick Preheat System
 Key Switch Stop System
 Self Bleed Fuel System
 Auto-downshift Two Speed Travel System
 Thumb Bracket and Relief Valves
 Swivel Negative Brake
 Travel Negative Brake
 Third Line Return (Hydraulic)

BASIC UNIT

U35-4R1, Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy
 U35-4R1A, Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy, Angle Dozer Blade
 U35-4R3, Rubber Tracks, ROPS/OPG (Top Guard, Level 1) Air Conditioned/Heated Cab
 U35-4R3A, Rubber Tracks, ROPS/OPG (Top Guard, Level 1) Air Conditioning/Heated Cab, Angle Dozer Blade

DIMENSIONS AND OPERATING WEIGHT

U35-4R1, Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy
 Overall Length 15' 7"
 Overall Width 5' 7"
 Overall Height 8' 1.2"
 Operating Weight* 8,129 lbs.
 Ground Clearance 11.34"

U35-4R3, Rubber Tracks, ROPS/OPG (Top Guard, Level 1) Air Conditioned/Heated Cab
 Overall Length 15' 7"
 Overall Width 5' 7"
 Overall Height 8' 1.2"
 Operating Weight* 8,451 lbs.
 Ground Clearance 11.34"

*Includes operator's weight of 175 lbs.

ENGINE

D1703-M Kubota E-TVCS Tier 4 Final Diesel Engine
 3 Cylinder, 4 Cycle
 24.8 Gross HP (SAE J1995) @ 2200 RPM
 23.9 Net HP (SAE J1349) @ 2200 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth	9' 8.9"
Max Digging Radius @ Ground Level	16' 11.3"
Max Vertical Digging Depth	6' 7.3"
Max Dumping Height	11' 0.7"

DOZER BLADE DIMENSIONS

Width	67"
Height	13.5"
Lift Above Ground	14.65"
Drop Below Ground	14.53"

PERFORMANCE

Digging Force @ Bucket (K7875)	7924 lbs.
Digging Force @ Dipper Arm	4451 lbs.
Travel Speed (Low/High)	1.9/2.9 mph
Climbing Ability	36% / 20°
Lift Capacity	3230 lbs.
<ul style="list-style-type: none"> • Over Front • Blade Grounded • 2 Ft. Load Point Height • 8 Ft. Load Radius 	

K Series U35-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	LIST PRICE
PART 1	MODEL U35-4 BASIC UNITS		
U35-4R1 With:	Excavator Basic Unit Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight,	8,478	See Zone Pricing
U35-4R1A With:	Excavator Basic Unit Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Dipper Arm, Counterweight	8,478	+\$4,553.00
U35-4R3 With:	Excavator Basic Unit Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight	8,478	+\$7,736.00
U35-4R3A With:	Excavator Basic Unit Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight	8,478	+\$9,857.00
PART 2	BUCKETS		
	PIN-ON BUCKETS (Order attaching pins from Parts)		
K7792A	12 inch 2.60 cu. ft. 3-Hole Bucket	194	\$1,047.00
K7793	16 inch 2.80 cu. ft. 3-Hole Bucket	220	\$1,125.00
K7794	18 inch 3.20 cu. ft. 3-Hole Bucket	229	\$1,176.00
K7796	24 inch 4.50 cu. ft. 3-Hole Bucket	265	\$1,297.00
	QUICK ATTACH BUCKETS		
K7870A	QUICK COUPLER Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin and hardware.	75	\$946.00
K9807	BUCKET HANGERS Set of 2 bucket ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	49	\$390.00
K7872A	12 inch 2.13 cu. ft. Trenching Bucket	160	\$967.00
K7873A	16 inch 2.83 cu. ft. Trenching Bucket	185	\$1,013.00
K7874A	18 inch 3.19 cu. ft. Trenching Bucket The K7874A bucket has four teeth. The K7910A Thumb tines contact the end of the teeth and do not mesh between the teeth.	190	\$1,091.00
K7874AC	18 inch 3.19 cu. ft. Trenching Bucket This is the same bucket as K7874A WITHOUT shanks for teeth	190	\$1,092.00
K7875A	24 inch 4.25 cu. ft. Trenching Bucket	240	\$1,309.00
K7875AC	24 inch 4.25 cu. ft. Trenching Bucket This is the same bucket as K7875A WITHOUT shanks for teeth	216	\$1,309.00
K7473A	36 inch 3.0 cu. ft. TILT GRADING BUCKET Includes hoses and fittings. Tilts 45° each direction.	305	\$4,448.00
K7474A	BOLT ON CUTTING EDGE For K7473 36" grading bucket	36	\$157.00
K7458	36 inch Grading Blade	270	\$1,638.00
K7546	36" Cemetery Bucket	265	\$1,444.00

K Series U35-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 3	ATTACHMENTS		
K7910A	HYDRAULIC THUMB KIT K7870A Quick Coupler required	195	\$2,681.00
K7461	24 INCH EXCAVATING RAKE, QUICK ATTACH	300	\$2,262.00
K7940	CANOPY WORK LIGHT KIT	6	\$153.00
K7447	BEACON LIGHT KIT (Enclosed Cab Use Only)	4	\$289.00
K9784	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse.	1	\$291.00
K7984	SPARK ARRESTOR MUFFLER KIT Optional kit for use in close proximity with grass, brush, timber and similar cellulose materials with potential for ignition. Requires Heat Insulation Kit. 77700-06495	10	\$499.00
PART 4	ROPS / OPG (Top Guard, Level I)		
K9786	REPLACEMENT 4-POST ROPS / OPG (Top Guard, Level I) CANOPY	240	\$1,624.00
K9787	REPLACEMENT ROPS / OPG (Top Guard, Level I) CAB The K9787 cab is configured as a replacement for damaged factory mounted cabs. It does not include cabin electrical wiring, wiper motor, heater, or defroster. Refer to illustrated parts list to order these components.	558	\$6,921.00
K7479	Cab Mirror Kit Includes two side mirrors, one for each side, one rear mirror, and attaching hardware	11	\$291.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance	3	\$92.00
77700-06495	Heat Insulation Kit for Spark Arrestor Muffler		\$169.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models ONLY)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, Halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$ 47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS and CAB Versions		\$72.00

Model Downgrade K Series U25ST4

U25R1T4

Zero Tail Swing Hydraulic Excavator

FEATURES

Zero Tail Swing
Half Pitch Rubber Tracks
ROPS/OPG (Top Guard, Level 1) 4 Post Canopy
Suspension Seat
Kubota 3 Hydraulic Pump Design
1 Gear; 2 Variable Displacement Pumps
Hydraulic Joystick Controls with Wrist Rests
Two Operating Pattern Selection System
Standard Front Dozer Blade
360 Degree Full Rotation
75° Left and 55° Right Boom Swing Angle
12.7 GPM Auxiliary Hydraulics Port
Five Second Quick Preheat System
Key Switch Stop System
Self Bleed Fuel System
Two Speed Travel
Thumb Bracket and Relief Valves

BASIC UNIT

U25R1T4, Rubber tracks, 4-Post ROPS/OPG
(Top Guard, Level 1) Canopy, Dipper Arm,
Counterweight

DIMENSIONS AND OPERATING WEIGHT

U25R1T4, Rubber tracks, 4-Post ROPS/OPG
(Top Guard, Level 1) Canopy, Dipper Arm,
Counterweight

Overall Length	13' 7"
Overall Width	4' 11"
Overall Height	7' 11"
Operating Weight*	5,625 lbs.
Ground Clearance	11.2"

*Includes operator's weight of 175 lbs.

ENGINE

D1105 Kubota E-TVCS Tier 4 Final Diesel Engine
3 Cylinder, 4 Cycle
20.9 Gross HP (SAE J1995) @ 2400 RPM
19.8 Net HP (SAE J1349) @ 2400 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth	9' 3"
Max Digging Radius @ Ground Level	15' 4"
Max Vertical Digging Depth	6' 5"
Max Dumping Height	10' 6"

DOZER BLADE DIMENSIONS

Width	59"
Height	11.8"
Lift Above Ground	14.0"
Drop Below Ground	13.0"

PERFORMANCE

Digging Force @ Bucket (K7978)	5765 lbs.
Digging Force @ Dipper Arm	2745 lbs.
Travel Speed (Low/High)	1.6/2.9 mph
Climbing Ability	36% / 20°
Ground Pressure	3.7 psi
Lift Capacity	2050 lbs.
<ul style="list-style-type: none">• Over Front• Blade Grounded• 2 Ft. Load Point Height• 8 Ft. Load Radius	

K Series U25ST4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL U25ST4 BASIC UNITS		
U25R1T4	Excavator Basic Unit With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight	5357	CREDIT -\$4,842.00
PART 2	BUCKETS		
	PIN-ON BUCKETS (Order Attaching Pins from Parts)		
K7788	12 inch 1.44 cu. ft. 3-Hole H.D. BUCKET	130	\$953.00
K7789	16 inch 2.12 cu. ft. 3-Hole H.D. BUCKET	150	\$1,013.00
K7790	18 inch 2.40 cu. ft. 3-Hole H.D. BUCKET	164	\$1,030.00
K7791	24 inch 3.40 cu. ft. 3-Hole H.D. BUCKET	193	\$1,100.00
	QUICK ATTACH BUCKETS		
K7974	QUICK COUPLER Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin, and hardware.	39	\$854.00
K9781	BUCKET HANGERS Set of 2 bucket ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	24	\$300.00
K7975	9 inch 1.0 cu. ft. Trenching Bucket	110	\$844.00
K7976	12 inch 1.4 cu. ft. Trenching Bucket	135	\$977.00
K7977	16 inch 1.9 cu. ft. Trenching Bucket	150	\$1,110.00
K7978	18 inch 2.2 cu. ft. Trenching Bucket The K7978 bucket has four teeth. The K7912 Thumb tines contact the end of the teeth and do not mesh between the teeth.	155	\$1,240.00
K7979	24 inch 3.0 cu. ft. Trenching Bucket	180	\$1,372.00
PART 3	ATTACHMENTS		
K7912	HYDRAULIC THUMB KIT K7974 Quick Coupler required.	122	\$2,257.00

K Series U25ST4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 3	ATTACHMENTS (Cont.)		
K9919	CANOPY WORK LIGHT KIT	20	\$129.00
K9962	STEEL CRAWLER KIT Convert tracks from rubber to steel	370	\$3,417.00
K9967	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse	7	\$307.00
		154	\$1,388.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$93.00

Model Down Grade K Series U17VR1

U17VR1

Zero Tail Swing Hydraulic Excavator

FEATURES

Zero Tail Swing
Short Pitch Rubber Tracks
ROPS/OPG (Top Guard, Level 1) 4 Post Canopy
Variable Width Track Frame
Kubota 3 Hydraulic Pump Design
1 Gear, 2 Variable Displacement Pumps
Hydraulic Joystick Controls with Wrist Rests
Two Operating Pattern Selection System
Standard Front Dozer Blade with Extensions
360 Degree Full Rotation
65° Left and 58° Right Boom Swing Angle
7.3 GPM Auxiliary Hydraulics Port
Five Second Quick Preheat System
Key Switch Stop System
Self Bleed Fuel System
Two Speed Travel

BASIC UNIT

U17VR1, Rubber tracks, 4-Post ROPS/OPG
(Top Guard, Level 1)

DIMENSIONS AND OPERATING WEIGHT

U17VR1, Rubber tracks, 4-Post ROPS/OPG
(Top Guard, Level 1)
Overall Length 11' 7"
Overall Width 3'3" ~ 4'1"
Overall Height 7'8"
Operating Weight* 3703 lbs.
Ground Clearance 5.9"

*Includes operator's weight of 175 lbs.

ENGINE

D902 Kubota E-TVCS Tier 4 Final Diesel Engine
3 Cylinder, 4 Cycle
16.1 Gross HP (SAE J1995) @ 2300 RPM
15.1 Net HP (SAE J1349) @ 2300 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth	7' 7"
Max Digging Radius @ Ground Level	12' 7"
Max Vertical Digging Depth	6' 3"
Max Dumping Height	8' 0"

DOZER BLADE DIMENSIONS

Width	3'3"/4'1"
Height	10.3"
Lift Above Ground	11.0"
Drop Below Ground	7.5"

PERFORMANCE

Digging Force @ Bucket (K7970)	3417 lbs.
Digging Force @ Dipper Arm	1918 lbs.
Travel Speed (Low/High)	1.4/2.6 mph
Climbing Ability	36% / 20°
Ground Pressure	3.8 psi
Lift Capacity	1140 lbs.
<ul style="list-style-type: none">• Over End• Blade Grounded• 2 Ft. Load Point Height• 8 Ft. Load Radius	

K Series U17VR1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL U17 BASIC UNITS		
U17VR1	Excavator Basic Unit	3814	CREDIT -\$8,959.00
	With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
PART 2	BUCKETS		
	PIN-ON BUCKETS		
K7779A	9 inch 0.52 cu. ft. 2-Hole H. D. Bucket	57	\$688.00
K7780A	12 inch 0.74 cu. ft. 2-Hole H. D. Bucket	82	\$710.00
K7781	16 inch 0.95 cu. ft. 2-Hole H. D. Bucket	94	\$784.00
K7785	18 inch 1.1 cu. ft. 2-Hole H. D. Bucket	95	\$974.00
	QUICK ATTACH BUCKETS		
K7966A	Quick Coupler	20	\$791.00
	Includes two mounting pins, 1 locking pin, and hardware.		
K7967A	9 inch 0.78 cu. ft. Trenching Bucket	86	\$426.00
K7968A	12 inch 1.0 cu. ft. Trenching Bucket	92	\$550.00
K7969A	16 inch 1.3 cu. ft. Trenching Bucket	108	\$548.00
K7970A	18 inch 1.5 cu. ft. Trenching Bucket	115	\$681.00
K9607	Bucket Hangers	12	\$255.00
	Set of two ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.		
PART 3	ATTACHMENTS		
K9919	Canopy Work Light Kit	4	\$129.00
K9773	Travel Alarm Kit	7	\$338.00
	Emits an audible signal when traveling forward or reverse		
K9943A	RETRACTABLE SEAT BELT OPTION (3")	3	\$93.00
	As required in some states for OSHA compliance.		
Available from Parts			
70000-01602	Screen Type Spark Arrestor		\$149.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687)		\$47.00

Model Downgrade K Series K008-3T4

K008-3T4

Hydraulic Excavator

FEATURES

Rubber Tracks
2-Post Foldable ROPS
Variable Width Track Frame
2 Gear Type Pumps
Two Operating Pattern Selection System
Standard Front Dozer Blade
360 Degree Full Rotation
55° Left and 60° Right Boom Swing Angle
5.5 GPM Auxiliary Hydraulics Port
Five Second Quick Preheat System
Key Switch Stop System
Self Bleed Fuel System
Two Speed Travel

BASIC UNIT

K008-3T4, Rubber tracks, 2-Post Foldable ROPS

DIMENSIONS AND OPERATING WEIGHT

K008-3T4 with K9776 Bucket	
Overall Length	9' 0"
Overall Width	2'4" ~ 2'10"
Overall Height	7'4"
Operating Weight*	2200 lbs.
Ground Clearance	5.9"

*Includes operator's weight of 175 lbs.

ENGINE

D722 Kubota E-TVCS Tier 4 Final Diesel Engine
3 Cylinder, 4 Cycle
10.3 Gross HP (SAE J1995) @ 2050 RPM
10.1 Net HP (SAE J1349) @ 2050 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth	5' 8"
Max Digging Radius @ Ground Level	9' 11"
Max Vertical Digging Depth	4' 6"
Max Dumping Height	6' 8"

DOZER BLADE DIMENSIONS

Width	28"/34"
Height	7.9"
Lift Above Ground	7.9"
Drop Below Ground	7.1"

PERFORMANCE

Digging Force @ Bucket (K9776)	2200 lbs.
Digging Force @ Dipper Arm	1010 lbs.
Travel Speed (Low/High)	1.2/2.5 mph
Climbing Ability	27% / 15°
Ground Pressure	3.5 psi
Lift Capacity	660 lbs.
<ul style="list-style-type: none">• Over End• Blade Grounded• 2 Ft. Load Point Height• 6 Ft. Load Radius	

K Series K008-3T4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL K008T4 BASIC UNIT		
K008T4	Excavator Basic Unit	1885	CREDIT -\$13,928.00
	With: Rubber Tracks, 2-Post Foldable ROPS, Dozer Blade, Dipper Arm, and Counterweight		
PART 2	BUCKETS		
K9775	10 inch 0.49 cu. ft. Bucket (Welded teeth)	36	\$362.00
K9776	14 inch 0.74 cu. ft. Bucket (Welded teeth)	44	\$438.00
K7759	8 inch 0.35 cu. ft. H.D. Bucket (Bolt-on teeth)	45	\$582.00
K7760	10 inch 0.49 cu. ft. H.D. Bucket (Bolt-on teeth)	57	\$591.00
K7768	12 inch 0.63 cu. ft. H.D. Bucket (Bolt-on teeth)	53	\$606.00
K7769	16 inch 0.9 cu. ft. H.D. Bucket (Bolt-on teeth)	70	\$676.00
	ATTACHMENTS		
PART 3	Two Way Service Port Hydraulic Kit		
K7748	The K7748 converts the auxiliary hydraulics from one way to two way flow. Includes manual, hydraulic hoses, and fittings	6	\$300.00
	3" seat belt option		
K9797	As required in some states for OSHA compliance.	3	\$91.00
	Spark Arrestor Muffler Kit		
K7802	Optional kit for use in close proximity with grass, brush, timber and similar material with potential for ignition. Requires K7812 Spark Arrestor Screen	7	\$124.00
	Spark Arrestor Screen		
K7812	Required for K7802 installation.	4	\$34.00

Model Upgrade K Series U55-4

U55-4
Tight Tail Swing Hydraulic Excavator

FEATURES

Eco Plus System
Auto Idler
Rubber Or Steel Track Models
4-Post ROPS/OPG (Top Guard Level I) Canopy or
Air Conditioned Cab
Suspension Seat
Kubota 3 Hydraulic Pump Load Sensing System
1 Gear, 2 Variable Displacement Pumps
All Controls Hydraulic Pilot Controls
Two Operating Pattern Selection System
Accumulator
Digital Control Panel
Attachment Flow Presets, Service Alerts
Standard Front Dozer Blade w/ Float
Optional Float Angle Blade w/ Bolt-on Cutting Edge
360 Degree Full Rotation
70 Degree Left, 55 Degree Right Boom Swing
19.8 gpm Adjustable Auxiliary Hydraulics Port 1
Auxiliary Hydraulics Diverter Valve
9.8 gpm Adjustable Auxiliary Hydraulics Port 2 Option
Thumb Bracket And Relief Valves
Five Second Quick Preheat System
Key Switch Stop System
Half Pitch Rubber Tracks
Self-Bleed Fuel System
Auto-Downshift Two Speed Travel System
Swivel Negative Brake
Travel Negative Brake
Third Line

BASIC UNITS

U55-4R1, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight
U55-4R1P, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight, SP2
U55-4R1A, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Dipper Arm, Counterweight
U55-4R1AP, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Dipper Arm, Counterweight, SP2
U55-4R3, Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight
U05-4R3P, Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight, SP2
U55-4R3A, Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight
U55-4R3AP, Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2
U55-4S3A, Steel Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight
U55-4S3AP, Steel Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2

ENGINE

V2607 Kubota DI CRS Tier 4 Final Diesel Engine
4 Cylinder, 4 Cycle
47.6 Gross HP @ 2200 rpm (SAE J1995)
45.2 Net HP @ 2200 rpm (SAE J1349)

OPERATIONAL DIMENSIONS

Max Digging Depth	11' 10.3"
Max Digging Radius @ Ground Level	19' 6.1"
Max Vertical Digging Depth	4' 11.6"
Max Dumping Height	13' 2.3"

STANDARD DOZER BLADE DIMENSIONS

Width	77.2"
Height	16.1"
Lift Above Ground	17.3"
Drop Below Ground	16.1"

PERFORMANCE

Digging Force @ Bucket (K7919)	11,177 lbs.
Digging Force @ Dipper Arm	6,261 lbs.
Travel Speed (Low/High)	1.8/3.1 mph
Climbing Ability	36% / 20°
Lift Capacity	3,700 lbs.
<ul style="list-style-type: none"> Over Front Blade Grounded 4.0 Ft. Load Point Height 12.0 Ft. Load Radius 	

DIMENSIONS AND OPERATING WEIGHT

U55-4R1, Rubber Tracks, ROPS/OPG (Top Guard Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight

Overall Length	18' 1.3"
Overall Width	6' 5.2"
Overall Height	8' 4.4"
Operating Weight*	11,915 lbs.
Ground Clearance	12' 0.2"

U55-4R3AP, Rubber Tracks, ROPS/OPG (Top Guard Level I) A/C Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2

Overall Length	18' 1.3"
Overall Width	6' 5.2"
Overall Height	8' 4"
Operating Weight*	12,535 lbs.
Ground Clearance	12.0.2"

* Includes operator's weight, 175 lbs.

K Series U55-4

ORDER CODE		DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1		MODEL U55 BASIC UNITS		
U55-4R1		Excavator Basic Unit	12,535	+\$17,067.00
	With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
U55-4R1A		Excavator Basic Unit	12,535	+\$19,795.00
	With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Blade, Dipper Arm, Counterweight		
U55-4R3		Excavator Basic Unit	12,535	+\$22,371.00
	With:	Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight		
U55-4R3A		Excavator Basic Unit	12,535	+ \$24,493.00
	With:	Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Blade, Dipper Arm, Counterweight		

K Series U55-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 2	QUICK ATTACH BUCKETS		
K7915A	Quick Coupler Includes two mounting pins, 1 locking pin and hardware.	96	\$949.00
K7916	Bucket Hangers Set of two ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	97	\$353.00
K7917A	12 inch 3.00 cu. ft. Trenching Bucket	218	\$1,190.00
K7918A	18 inch 4.50 cu. ft. Trenching Bucket The K7918A bucket has four teeth. The K7937A thumb tines contact the end of the teeth and do not mesh between the teeth.	155	\$1,209.00
K7918AC	18 inch 4.50 cu. ft. Trenching Bucket This is the same bucket as K7918A WITHOUT shanks for teeth	240	\$1,209.00
K7919A	24 inch 6.30 cu. ft. Trenching Bucket	180	\$1,209.00
K7919AC	24 inch 6.30 cu. ft. Trenching Bucket This is the same bucket as K7919A WITHOUT shanks for teeth	180	1,209.00
K7920A	30 inch 8.00 cu. ft. Trenching Bucket	180	\$1,384.00
K7921A	36 inch 8.00 cu. ft. Trenching Bucket	180	\$1,939.00
K7926	36 inch 3.48 cu. ft. Cemetery Bucket	265	\$1,445.00
K7922A	36 inch 6.64 cu. ft. Drainage Bucket Pre-drilled for bolt on cutting edge.	270	\$1,193.00
K7474A	Bolt On Cutting Edge for K7922A 36" Drainage Bucket	36	\$156.00
K7924A	48 inch 8.50 cu. ft. Grading Bucket Pre-drilled for bolt on cutting edge. Not authorized for use on models with K7937A thumb.	400	\$1,706.00
K7878A	Bolt On Cutting Edge for K7924 48" Grading Bucket	51	\$209.00
PART 3	ATTACHMENTS		
K7937A	HYDRAULIC THUMB KIT K7915A Quick Coupler required.	195	\$2,251.00
K7932	FROST RIPPER	315	\$1,312.00
K7940	CANOPY WORK LIGHT KIT	6	\$154.00
K7447	BEACON LIGHT KIT (Enclosed Cab Use Only)	4	\$290.00
K7927	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse.	2	\$145.00
K7938	Steel Crawler Kit Converts tracks from rubber to steel	1298	\$5,401.00
K7440	BOLT ON RUBBER PAD KIT (400 mm, 15.7") Machine must be equipped with steel tracks. This kit includes 78 bolt on pads to be <u>installed on the existing steel grousers</u> (Individual pads can be ordered separate through parts if needed for individual replacement) Part # 77700-10394	250	\$4,077.00

K Series U55-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 4	ROPS / OPG (Top Guard, Level I)		
K7479	Cab Mirror Kit Includes two side mirrors, one for each side, one rear mirror, and attaching hardware	11	\$292.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$93.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models ONLY)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, Halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS Versions		\$72.00
