

KELLY TRACTOR Dealer:

XL 80 Power Tail

XL 80 PT CAPACITY: 80,000 LB OVERALL CONCENTRATED: 50,000 LB IN 10' OVERALL LENGTH: 48' OR 53' **OVERALL WIDTH: 102**" GOOSENECK 9' LONG FULL-WIDTH 90° SLOPE **16" KING PIN SETTING 86" SWING CLEARANCE** 49" 5TH WHEEL HEIGHT STEEL TREAD PLATE DECKING (2) D-RINGS PER SIDE 2 SPEED LANDING GEAR WITH HANDLE

ON DRIVER SIDE WET LINE HYDRAULICS TO RUN OFF TRUCK HYDRAULIC LEVERS ON DRIVER SIDE PLANETARY DRIVE 18,000 LB HYDRAULIC WINCH WITH 75' OF 1/2" CABLE & AIR KICK OUT **2 FUNCTION WIRELESS REMOTE** FOR WINCH 2 TOOLBOXES WITH LIDS 9' LONG POP-UP RAMP, DECK TO NECK INTEGRATED FOOT STEP AND GRAB HANDLE, ON BOTH SIDES

MAIN DECK T-1 FLANGE, 80K WEB 48' OAL: 30' 4" LONG 53' OAL: 35' 4" LONG 36" LOADED DECK HEIGHT 1.3/8" RAISED APITONG 1/4" TREAD PLATE COVERED WHEELS 10" & 8" JR. I-BEAM CROSSMEMBERS ON ALTERNATING 12" CENTERS **18" FABRICATED I-BEAM SIDE MEMBERS** (5) D-RINGS PER SIDE STAKE POCKETS AND CHAIN SLOTS **ON ALTERNATING 24" CENTERS, SIDES** CHAIN SLOTS DOWN CENTER OF DECK ON 48" CENTERS

KELLY TRACTOR

TAIL SECTION 13' 8" HYDRAULIC TAIL: 8' 8" PLATFORM 60" FOLD UNDER FLIP TAIL AUTOMATIC FLIP TAIL LOCK TRACTION AIDS STAR TRACTION PLATE

SUSPENSION AIR RIDE 25,000 LB AIR RIDE

AXLES (2) 25,000 LB NOMINAL 49" AXLE SPACING HUB PILOT, OUTBOARD DRUMS 4S2M ABS SPRING BRAKES ON 2 AXLES 12 1/4" X 7 1/2" BRAKES AUTO SLACK ADJUSTERS AIR DUMP ON BOTH AXLES

WHEELS & TIRES 6.75 X 17.5 STEEL RIMS 245 / 70R / 17.5 TIRES

LIGHTING 12V SEALED GROTE HARNESS RUBBER MOUNTED LED LIGHTS **3 TAIL LIGHT PACKAGE** (1) MID-TURN SIGNAL PER SIDE (2) CLEARANCE LIGHT PER SIDE 7 POLE ELECTRICAL SOCKET

XL 80 Power Tail Options

OAL Base Prices

✓ 48' OAL

🗆 53' OAL

Gooseneck

- 13HP Honda power unit (consumes drivers side toolbox)
- No pop-up ramp (deduct)
- □ 30,000 lb winch
- 20,000 lb winch
- 12,000 lb winch (deduct)
- Work-around pulley for winch cable
- □ Bolt-on winch guard
- 8 function wireless remote (for tail & winch, not pop-up ramp)
- □ 10 function wireless remote (for tail, winch & pop-up ramp)
- Registration holder

Main Deck

- Double drop style
- Additional bent D-rings

Pairs

□ Additional clearance lights

Pairs

Amber strobe as third taillight

Tail Section

Steel tread plate decking in lieu of star traction (deduct)

VIN

- Foreign VIN
- Domestic VIN

Notes

Axles/Brakes □ Hubometer

- □ TP Axles (same inner & outer bearings)
- Dust shields
- □ Cat eye systems
- Disc brakes

Wheels/Tires

- □ 255/70R/22.5 tires (deck height + 3")
- □ PSI Tire inflation system
- □ Aluminum mill wheels (inside)
- □ Aluminum mill wheels (outside)
- □ Aluminum polished wheels (outside)
- □ Michelin tires
- □ Customer specified tires Brand
- □ Customer specified mud flaps

Suspension

- □ Liquid filled air gauge
- □ Air weigh digital scale

Paint/Decals

☑ Black

- □ IH Red New Cat Yellow
- Non-standard paint colors
- Non-standard metallic paint

Paint Code



XL POWER TAIL



FEATURES

• Foot hole and grab handle for access to upper deck

- 9' pop-up ramp from deck to neck
- 18,000 lb winch with air kickout
- 25,000 lb tail lifting capacity
- Work light at rear of neck
- 2 function wireless remote
- Star traction or steel tread plate



UNIQUE HYDRAULIC TAIL DESIGN


The tail is comprised of two sections – an 8-foot 8-inch platform ramp and a 60-inch flip tail. Both hinge points stay clean thanks to lug style hinges. These hinges prevent debris from accumulating.

HANDLES HARD-TO-LOAD EQUIPMENT

With a load angle of 10 degrees, the hydraulic tail is equipped to easily handle hard-to-load equipment such as manlifts, rollers, forklifts and paving equipment. The tail features a lifting capacity of 25,000 pounds for loads centered on the main platform.

DESIGNED FOR YOU. BUILT TO LAST.

www.xlspecializedtrailer.com | 877.283.4852



CAPACITY

capacity: 80,000 lb overall concentrated: 50,000 lb in 10'

OVERALL LENGTH & WIDTH

overall length: 48' or 53' overall width: 102"

GOOSENECK

9' long full-width 90° slope 16" king pin setting 86" swing clearance 49" 5th wheel height steel tread plate decking (2) d-rings per side 2 speed landing gear with handle on driver side wet line hydraulics to run off truck hydraulic levers on driver side planetary drive 18,000 lb hydraulic winch with 75' of 1/2" cable & air kick out 2 function wireless remote for winch 2 toolboxes with lids 9' long pop-up ramp, deck to neck integrated foot step and grab

handle, on both sides

GOOSENECK OPTIONS

13HP honda power unit no pop-up ramp 30,000 lb winch 20,000 lb winch 12,000 lb winch work-around pulley for winch cable bolt-on winch guard 8 function wireless remote 10 function wireless remote

MAIN DECK

T-1 flange, 80k web 48' OAL: 30' 4" long 53' OAL: 35' 4" long 36" loaded deck height 1 3/8" Apitong decking - raised 1/4" tread plate covered wheels
18" fabricated i-beams
10" & 8" jr. i-beam cross members on alternating 12" centers
5 d-rings per side
stake pockets and chain slots on alternating 24" centers, sides
chain slots down on 48" centers, center deck
2 pairs of flag holders

MAIN DECK OPTIONS

double drop design additional d-rings

TAIL SECTION

13' 8" hydraulic tail: 8' 8" platform 60" fold under flip tail automatic flip tail lock traction aids star traction plate decking

TAIL SECTION OPTIONS tread plate decking

WHEELS & TIRES

6.75 x 17.5 steel rims 245 / 70R / 17.5 tires

WHEEL & TIRE OPTIONS

255 tires changes rear deck height to 39" aluminum mill wheels aluminum polished wheels customer specified tires customer specified mud flaps Michelin tires PSI tire inflation system

SUSPENSION 25,000 lb air ride

SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale

AXLES

(2) 25,000 lb nominal 49" axle spacing hub pilot, outboard drums 4S2M ABS spring brakes on 2 axles 12 1/4" x 7 1/2" brakes auto slack adjusters air dump on both axles

AXLE OPTIONS

hubometer TP axles (same inner & outer bearings) dust shields cat eye systems disc brakes

LIGHTING

12V sealed grote harness rubber mounted led lights 3 tail light package 1 mid-turn signal per side 2 clearance light per side 7 pole electrical socket

LIGHTING OPTIONS

amber strobe as 3rd tail light extra clearance lights

PAINT

black, IH red, CAT yellow air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY 5 year structural 1 year paint

AVAILABLE MODELS

DESIGNED FOR YOU. BUILT TO LAST.

www.xlspecializedtrailer.com | 877.283.4852