

K Series KX080-4S2

KX080-4S2 Excavator Tight Tail Swing Utility Class Excavator

FEATURES

Auto Idle
Rubber Or Steel Track Models
Air Conditioned ROPS/OPG (Top Guard, Level I) Cab
Cloth Suspension Seat
Kubota 2 Hydraulic Pump Load Sensing System
2 Variable Displacement Pumps
All Controls Hydraulic Pilot Controls
Two Operating Pattern Selection System
Accumulator
Standard Front Dozer Blade w/ Float
Optional Float Angle Blade w/ Bolt-on Cutting Edge
360 Degree Full Rotation
70 Degree Left, 60 Degree Right Boom Swing
26.4 gpm Adjustable Auxiliary Hydraulics Port 1
14.7 gpm Adjustable Auxiliary Hydraulics Port 2
Thumb Bracket and Relief Valves
Five Second Quick Preheat System
Key Switch Stop System
Half Pitch Rubber Tracks
Self-Bleed Fuel System
Auto-Downshift Two Speed Travel System
Swivel Negative Brake
Travel Negative Brake
Third Line

BASIC UNITS

KX080-4S2R3, Rubber Tracks, Air Conditioned
ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade,
Dipper Arm, Counter weight
KX080-4S2R3A, Rubber Tracks, Air Conditioned
ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer
Blade, Dipper Arm, Counter weight
KX080-4S2S3, Steel Tracks, Air Conditioned
ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade,
Dipper Arm, Counter weight
KX080-4S2S3A, Steel Tracks, Air Conditioned
ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer
Blade, Dipper Arm, Counter weight
KX080-4S2W3, 24" Wide Steel Tracks, Air Conditioned
ROPS/OPG (Top Guard, Level I) Cab, Wide Dozer
Blade, Dipper Arm, Counter weight

ENGINE

V3307 Kubota DI CRS Turbo Tier 4 Final Diesel Engine
4 Cylinder, 4 Cycle
66.6 Gross HP @ 2000 rpm (SAE J1995)
62.3 Net HP @ 2200 rpm (SAE J1349)

OPERATIONAL DIMENSIONS

Max Digging Depth	15' 1"
Max Digging Radius @ Ground Level	23' 6.3"
Max Vertical Digging Depth	12' 7.6"
Max Dumping Height	17' 2.7"

DOZER BLADE DIMENSIONS

Width	86.6"
Height	19.7"
Lift Above Ground	19.7"
Drop Below Ground	19.7"

PERFORMANCE

Digging Force @ Bucket (K7427)	14,660 lbs.
Digging Force @ Dipper Arm	8,554 lbs.
Travel Speed (Low / High)	1.7/3.1mph
Climbing Ability	36% / 20°
Lift Capacity	6,500 lbs.
<ul style="list-style-type: none"> Over Front Blade Grounded 4.0 Ft. Load Point Height 12.0 Ft. Load Radius 	

DIMENSIONS AND OPERATING WEIGHT

KX080-4S2R3, Rubber Tracks, Air Cond. ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counter weight	
Overall Length	21' 1.9"
Overall Width	7' 2.6"
Overall Height	8' 4"
Operating Weight*	18,280 lbs.
Ground Clearance	15.4"
KX080-4S2S3, Steel Tracks, Air Cond. ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counter weight	
Overall Length	21' 1.9"
Overall Width	7' 2.6"
Overall Height	8' 4"
Operating Weight*	18,390 lbs.
Ground Clearance	15.4"

* Includes operator's weight, 175 lbs.

K Series KX080-4S2

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL KX080-4S BASIC UNITS		
KX080-4S2R3	EXCAVATOR BASIC UNIT	18,596	See Zone Pricing
With:	Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight		
KX080-4S2R3A	EXCAVATOR BASIC UNIT	19,456	\$9,565.00
With:	Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight		
KX080-4S2SW3	EXCAVATOR BASIC UNIT	18,706	\$7,909.00
With:	Wide Steel Tracks (600 mm, 24"), Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, 92.5" Wide Dozer Blade, Dipper Arm, Counterweight		

K Series KX080-4S2

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 2	BUCKETS		
	PIN-ON BUCKETS (Order Attaching Pins from Parts)		
K7416	18 inch 6.5 cu. ft. TRENCHING BUCKET	405	\$1,995.00
K7417	24 inch 9.4 cu. ft. TRENCHING BUCKET	460	Included
K7418	30 inch 10.8 cu. ft. TRENCHING BUCKET	505	\$2,847.00
K7419	36 inch 12.1 cu. ft. TRENCHING BUCKET	539	\$3,172.00
K7436	48 inch 10.8 cu. ft. GRADING BUCKET	565	\$2,948.00
K7437	54 inch 12.2 cu. ft. GRADING BUCKET	615	\$3,086.00
K7438	60 inch 13.5 cu. ft. GRADING BUCKET	665	\$3,168.00
	QUICK ATTACH BUCKETS		
K7402A	QUICK COUPLER Includes two mounting pins, 1 locking pin, and hardware.	140	\$1,635.00
K7407	BUCKET HANGERS Set of two ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	139	\$516.00
K7426A	18 inch 6.5 cu. ft. TRENCHING BUCKET The K7426 bucket has four teeth. The K7405 thumb tines contact the end of the teeth and do not mesh between the teeth.	393	\$1,814.00
K7427A	24 inch 9.4 cu. ft. TRENCHING BUCKET	448	\$2,168.00
K7428A	30 inch 10.8 cu. ft. TRENCHING BUCKET	493	\$2,354.00
K7429A	36 inch 12.1 cu. ft. TRENCHING BUCKET	527	\$2,628.00
K7441	48 inch 10.8 cu. ft. GRADING BUCKET	553	\$2,883.00
K7441A	48 inch 10.8 cu. ft. GRADING BUCKET	565	\$2,481.00
K7442	54 inch 12.2 cu. ft. GRADING BUCKET K7494 Additional Weight Kit required with K7405A Thumb	603	\$3,018.00
K7442A	54 inch 12.2 cu. ft. GRADING BUCKET K7494 Additional Weight Kit required with K7405A Thumb	615	\$2,596.00
K7444A	54 inch 9.6 cu. ft. TILT GRADING BUCKET Includes hoses and fittings. Tilts 45° each direction K7494 Additional Weight Kit required with K7405 Thumb	850	\$7,651.00
K7443	60 inch 13.5 cu. ft. GRADING BUCKET K7494 Additional Weight Kit required with K7405 Thumb applications	652	\$3,137.00
K7443A	60 inch 13.5 cu. ft. GRADING BUCKET K7494 Additional Weight Kit required with K7405A Thumb	665	\$2,694.00
K7448	60 inch GRADING BLADE	500	\$2,683.00

K Series KX080-4S2

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
K7451	BOLT-ON CUTTING EDGE For K7436 and K7441 48" grading buckets	79	\$192.00
K7451A	BOLT-ON CUTTING EDGE For K7436 and K7441 48" grading buckets	79	\$165.00
K7452	BOLT-ON CUTTING EDGE For K7437, K7442, and K7444 54" grading buckets	89	\$221.00
K7452A	BOLT-ON CUTTING EDGE For K7437, K7442, and K7444 54" grading buckets	89	\$189.00
K7453	BOLT-ON CUTTING EDGE For K7438, and K7443 60" grading buckets	109	\$240.00
K7453A	BOLT-ON CUTTING EDGE For K7438, and K7443 60" grading buckets	109	\$206.00
K7405A	HYDRAULIC THUMB KIT K7402 quick coupler required	370	\$4,280.00
PART 3	ATTACHMENTS (Cont.)		
K7449A	Brush Guard Kit	300	\$3,377.00
K4080	FLAIL BRUSH SHREDDER Quick coupler mount, integrated thumb saddle, hoses, hydraulic	1400	\$18,220.00
K4081	REPLACEMENT BLADE KIT FOR K4080 SHREDDER	91	\$639.00
K7462	EXCAVATING RAKE, 36", Pin-on	533	\$4,677.00
K7463	EXCAVATING RAKE, 36", Quick Attach	555	\$4,481.00
K7464	EXCAVATING RAKE, 48", Pin-on	720	\$5,125.00
K7465	EXCAVATING RAKE, 48", Quick Attach	707	\$4,666.00
K7467	FROST RIPPER, 24", Pin-On	315	\$1,686.00
K7466	FROST RIPPER, 24", Quick Attach	295	\$1,619.00
K7468	SOLID TINE GRAPPLE, 36", Pin-on	1015	\$7,380.00
K7471	COMPACTION WHEEL, 18", Pin-On	980	\$6,693.00
K7472	COMPACTION WHEEL, 18", Quick Attach	960	\$6,693.00

KUBOTA

Cab pre-wired with switch. A new bracket must be created for the installation. See installation instructions.

K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$94.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models ONLY)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, Halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS and CAB Versions		\$72.00

Model Downgrade K Series KX057-4

KX057-4 Hydraulic Excavator

FEATURES

Eco Plus System
Auto Idler
Rubber Or Steel Track Models
4-Post ROPS/OPG (Top Guard, Level I) Canopy or Air
Conditioned Cab
Suspension Seat
Kubota 3 Hydraulic Pump Load Sensing System
1 Gear, 2 Variable Displacement Pumps
All Controls Hydraulic Pilot Controls
Two Operating Pattern Selection System
Accumulator
Digital Control Panel
Attachment Flow Presets, Service Alerts
Standard Front Dozer Blade w/ Float
Optional Float Angle Blade w/ Bolt-on Cutting Edge
360 Degree Full Rotation
70 Degree Left, 55 Degree Right Boom Swing
19.8 gpm Adjustable Auxiliary Hydraulics Port 1
Auxiliary Hydraulics Diverter Valve
9.8 gpm Adjustable Auxiliary Hydraulics Port 2 Option
Thumb Bracket And Relief Valves
Five Second Quick Preheat System
Key Switch Stop System
Half Pitch Rubber Tracks
Self Bleed Fuel System
Auto-Downshift Two Speed Travel System
Swivel Negative Brake
Travel Negative Brake
Third Line

ENGINE

V2607 Kubota DI CRS Tier 4 Final Diesel Engine
4 Cylinder, 4 Cycle
47.6 Gross HP @ 2200 rpm (SAE J1995)
45.2 Net HP @ 2200 rpm (SAE J1349)

OPERATIONAL DIMENSIONS

Max Digging Depth	12' 8.2"
Max Digging Radius @ Ground Level	20' 0.5"
Max Vertical Digging Depth	5' 7.3"
Max Dumping Height	13' 8.6"

STANDARD DOZER BLADE DIMENSIONS

Width	77.2"
Height	16.1"
Lift Above Ground	17.3"
Drop Below Ground	16.1"

PERFORMANCE

Digging Force @ Bucket (K7919)	11,177 lbs.
Digging Force @ Dipper Arm	5,644 lbs.
Travel Speed (Low / High)	1.8/3.1 mph
Climbing Ability	36% / 20°
Lift Capacity	3,410 lbs.
• Over Front	
• Blade Grounded	
• 4.0 Ft. Load Point Height	
• 12.0 Ft. Load Radius	

BASIC UNITS

KX057-4R1, Rubber Tracks, ROPS/OPG (Top Guard, Level I)
Canopy, Dozer Blade, Dipper Arm, Counterweight
KX057-4R1P, Rubber Tracks, ROPS/OPG (Top Guard,
Level I) Canopy, Dozer Blade, Dipper Arm,
Counterweight, SP2
KX057-4R1A, Rubber Tracks, ROPS/OPG (Top Guard,
Level I) Canopy, Angle Dozer Blade, Dipper Arm,
Counterweight
KX057-4R1AP, Rubber Tracks, ROPS/OPG (Top Guard, Level I)
Canopy, Angle Dozer Blade, Dipper Arm, Counterweight, SP2
KX057-4R3, Rubber Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Dozer Blade, Dipper Arm, Counterweight
KX057-4R3P, Rubber Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Dozer Blade, Dipper Arm, Counterweight, SP2
KX057-4R3A, Rubber Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight,
KX057-4R3AP, Rubber Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight,
SP2
KX057-4S3A, Steel Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Angle Dozer Blade, Dipper Arm,
Counterweight
KX057-4S3AP, Steel Tracks, A/C ROPS/OPG (Top Guard,
Level I) Cab, Angle Dozer Blade, Dipper Arm,
Counterweight, SP2

DIMENSIONS AND OPERATING WEIGHT

KX057-4R1, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight	
Overall Length	18' 1.3"
Overall Width	6' 5.2"
Overall Height	8' 4.4"
Operating Weight*	12,200 lbs.
Ground Clearance	12' 0.2"
KX057-4R3AP, Rubber Tracks, ROPS/OPG (Top Guard, A/C Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2	
Overall Length	18' 1.3"
Overall Width	6' 5.2"
Overall Height	8' 4"
Operating Weight*	12,820 lbs.
Ground Clearance	12.0.2"

* Includes operator's weight, 175 lbs.

K Series KX057-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL KX057-4 BASIC UNITS		
KX057-4R1	Excavator Basic Unit	12,048	CREDIT -\$21,299.00
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
KX057-4R1A	Excavator Basic Unit	12,048	CREDIT -\$19,177.00
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Blade, Dipper Arm, Counterweight		
KX057-4R3	Excavator Basic Unit	12,048	CREDIT -\$15,388.00
With:	Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight, SP2		
KX057-4R3A	Excavator Basic Unit	12,048	CREDIT -\$14,479.00
With:	Rubber Tracks, A/C ROPS/OPG (Top Guard, Level I) Cab, Angle Blade, Dipper Arm, Counterweight		

K Series KX057-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 2	QUICK ATTACH BUCKETS		
K7915A	Quick Coupler Includes two mounting pins, 1 locking pin and hardware.	96	\$949.00
K7916	Bucket Hangers Set of two ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	97	\$353.00
K7917A	12 inch 3.00 cu. ft. Trenching Bucket	218	\$1,190.00
K7918A	18 inch 4.50 cu. ft. Trenching Bucket The K7918 bucket has four teeth. The K7937 thumb tines contact the end of the teeth and do not mesh between the teeth.	155	\$1,209.00
K7918AC	18 inch 4.50 cu. ft. Trenching Bucket This is the same bucket as K7918A WITHOUT shanks for teeth	240	\$1,209.00
K7919A	24 inch 6.30 cu. ft. Trenching Bucket	180	\$1,277.00
K7919AC	24 inch 6.30 cu. ft. Trenching Bucket This is the same bucket as K7919A WITHOUT shanks for teeth	180	\$1,277.00
K7920A	30 inch 8.00 cu. ft. Trenching Bucket	180	\$1,384.00
K7921A	36 inch 8.00 cu. ft. Trenching Bucket	180	\$1,940.00
K7926	36 inch 3.48 cu. ft. Cemetery Bucket	265	\$1,445.00
K7922A	36 inch 6.64 cu. ft. Drainage Bucket Pre-drilled for bolt on cutting edge	270	\$1,193.00
K7474A	Bolt On Cutting Edge for K7922 36" Drainage Bucket	36	\$156.00
K7924A	48 inch 8.50 cu. ft. Grading Bucket Pre-drilled for bolt on cutting edge	400	\$1,706.00
K7878A	Bolt On Cutting Edge for K7924A 48" Grading Bucket	51	\$156.00
PART 3	ATTACHMENTS		
K7937A	HYDRAULIC THUMB KIT K7915 Quick Coupler required.	195	\$2,251.00
K7932	FROST RIPPER	315	\$1,312.00
K7940	CANOPY WORK LIGHT KIT	6	\$154.00
K7447	BEACON LIGHT KIT (Enclosed Cab Use Only)	4	\$290.00
K7927	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse.	2	\$145.00
PART 3	ATTACHMENTS (Cont.)		
K7938	Steel Crawler Kit Converts tracks from rubber to steel	1298	\$5,401.00
K7440	BOLT ON RUBBER PAD KIT (400 mm, 15.7") Machine must be equipped with steel tracks. This kit includes 78 bolt on pads to be <u>installed on the existing steel grousers</u> . (Individual pads can be ordered separate through parts if needed for individual replacement) Part # 77700-10394	250	\$4,077.00

K Series KX057-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 4			
K7479	Cab Mirror Kit Includes two side mirrors, one for each side, one rear mirror, and attaching hardware	11	\$293.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$93.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models ONLY)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, Halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS Versions		\$72.00

Model Down Grade K Series KX040-4

KX040-4 Hydraulic Excavator

FEATURES

Eco Plus System
Auto Idler
Rubber Or Steel Track Models
ROPS/OPG (Top Guard, Level I) 4-Post Canopy or Air Conditioning Cab
Suspension Seat
Kubota 1 Hydraulic Pump Load Sensing System
1 Variable Displacement Pump
All Controls Hydraulic Pilot Controls
Two Operating Pattern Selection System
Accumulator
Digital Control Panel
Attachment Flow Presets, Service Alerts
Standard Front Dozer Blade w/ Float
Optional Float Angle Blade w/ Bolt-on Cutting Edge
360 Degree Full Rotation
70 Degree Left, 55 Degree Right Boom Swing
17.2 gpm Adjustable Auxiliary Hydraulics Port 1
Auxiliary Hydraulics Diverter Valve
9.8 gpm Adjustable Auxiliary Hydraulics Port 2 Option
Thumb Bracket and Relief Valves
Five Second Quick Preheat System
Key Switch Stop System
Half Pitch Rubber Tracks
Self-Bleed Fuel System
Auto-Downshift Two Speed Travel System
Swivel Negative Brake
Travel Negative Brake
Third Line

BASIC UNITS

KX040-4R1, Rubber Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Dozer Blade
KX040-4R1A, Rubber Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Angle Dozer Blade
KX040-4R1T, Rubber Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Canopy, 6-in-1 Dozer Blade
KX040-4R1P, Rubber Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I), Canopy, Dozer Blade, SP2
KX040-4R1AP, Rubber Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Angle Dozer Blade, SP2
KX040-4R1TP, Rubber Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, 6-in-1 Dozer Blade, SP2
KX040-4R3, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Dozer Blade
KX040-4R3A, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Angle Dozer Blade
KX040-4R3T, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, 6-in-1 Dozer Blade
KX040-4R3P, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Dozer Blade, SP2
KX040-4R3AP, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I), Cab, Angle Dozer Blade, SP2
KX040-4R3TP, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I), Cab, 6-in-1 Dozer Blade, SP2
KX040-4S1, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Dozer Blade
KX040-4S1A, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Angle Dozer Blade
KX040-4S1T, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, 6-in-1 Dozer Blade
KX040-4S1P, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Dozer Blade, SP2

BASIC UNITS (cont'd)

KX040-4S1P, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Dozer Blade, SP2
KX040-4S1AP, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Angle Dozer Blade, SP2
KX040-4S1TP, Steel Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, 6-in-1 Dozer Blade, SP2
KX040-4S3, Steel Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Dozer Blade
KX040-4S3A, Steel Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Air Conditioned Cab, Angle Dozer Blade
KX040-4S3T, Steel Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Air Conditioned Cab, 6-in-1 Dozer Blade
KX040-4S3P, Steel Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Dozer Blade, SP2
KX040-4S3AP, Steel Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Air Conditioned Cab, Angle Dozer Blade, SP2
KX040-4S3TP, Steel Tracks, ROPS/OPG (TOP GUARD, LEVEL I) Air Conditioned Cab, 6-in-1 Dozer Blade, SP2

DIMENSIONS AND OPERATING WEIGHT

KX040-4R1, Rubber Tracks, 4-Post ROPS/OPG (TOP GUARD, LEVEL I) Canopy, Dozer Blade
Overall Length 16' 8.2"
Overall Width 5' 6.9"
Overall Height 8' 1.8"
Operating Weight* 9,195 lbs.
Ground Clearance 12.9"

KX040-4R3A, Rubber Tracks, Air Conditioned ROPS/OPG (TOP GUARD, LEVEL I) Cab, Angle Dozer Blade

Overall Length 16' 8.1"
Overall Width 5' 6.9"
Overall Height 8' 1.8"
Operating Weight* 9,855 lbs.
Ground Clearance 12.9"

* Includes operator's weight, 175 lbs.

ENGINE

D1803 Kubota DI CRS Turbo Tier 4 Diesel Engine
3 Cylinder, 4 Cycle ; 40.4 Gross HP, 38.9 Net HP
@ 2200 rpm (SAE J1995 & J1349 Respectively)

OPERATIONAL DIMENSIONS

Max Digging Depth 11' 2.7"
Max Digging Radius @ Ground Level 17' 9.0"
Max Vertical Digging Depth 7' 4.8"
Max Dumping Height 12' 9.5"

STANDARD DOZER BLADE DIMENSIONS

Width 66.9"
Height 15.75"
Lift Above Ground 15.17"
Drop Below Ground 15.94"

PERFORMANCE

Digging Force @ Bucket (K7875) 9,535 lbs.
Digging Force @ Dipper Arm 4,112 lbs.
Travel Speed (Low/ High) 1.8/3.1 mph
Climbing Ability 36% / 20°
Lift Capacity 4,080 lbs.
• Over Front, Blade Grounded
• 2.0 ft. Load Point Height, 8.0 ft. Load radius

K Series KX040-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL KX040-4 BASIC UNITS		
KX040-4R1	Excavator Basic Unit	8576	CREDIT -\$33,401.00
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
KX040-4R1A	Excavator Basic Unit	8576	CREDIT -\$31,507.00
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Dipper Arm, Counterweight		
KX040-4R1T	Excavator Basic Unit	8,576	CREDIT -\$28,590.00
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, 6-in-1 Dozer Blade, Dipper Arm, Counterweight		
KX040-4R3	Excavator Basic Unit	9312	CREDIT -\$28,703.00
	Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight		
KX040-4R3A	Excavator Basic Unit	9312	CREDIT -\$26,809.00
	Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, 6-in-1 Dozer Blade, Dipper Arm, Counterweight		
KX040-4R3T	Excavator Basic Unit	8,719	CREDIT -\$23,893.00
	Steel Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		

K Series KX040-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 2	BUCKET OPTIONS		
	PIN-ON BUCKETS (Order attaching pins from Parts)		
K7792A	12 inch 2.6 cu. ft. 3-Hole Bucket	194	\$1,048.00
K7793	16 inch 2.80 cu. ft. 3-Hole Bucket	220	\$1,126.00
K7794	18 inch 3.20 cu. ft. 3-Hole Bucket	229	\$1,177.00
K7796	24 inch 4.50 cu. ft. 3-Hole Bucket	265	\$1,298.00
K7797	30 inch 5.80 cu. ft. 3-Hole Bucket	300	\$1,423.00
K9836A	36 inch 4.17 cu. ft. Drainage Bucket	194	\$1,035.00
	QUICK ATTACH BUCKETS		
	MECHANICAL QUICK ATTACH OPTIONS		
K7870A	QUICK COUPLER Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin and hardware.	75	\$947.00
K9807	BUCKET HANGERS Set of 2 bucket ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	49	\$391.00
K7872A	12 inch 2.13 cu. ft. Trenching Bucket	160	\$968.00
K7873A	16 inch 2.83 cu. ft. Trenching Bucket	185	\$1,014.00
K7874A	18 inch 3.19 cu. ft. Trenching Bucket The K7874 bucket has four teeth. The K7910 Thumb tines contact the end of the teeth and do not mesh between the teeth.	190	\$1,093.00
K7874AC	18 inch 3.19 cu. ft. Trenching Bucket This is the same bucket as K7874A WITHOUT shanks for teeth	190	\$1,093.00
K7875A	24 inch 4.25 cu. ft. Trenching Bucket	240	\$1,310.00
K7875AC	24 inch 4.25 cu. ft. Trenching Bucket This is the same bucket as K7875A WITHOUT shanks for teeth	216	\$1,310.00
K7461	24" Excavating Rake	300	\$2,643.00
K7876A	30 inch 5.31 cu. ft. Trenching Bucket	265	\$1,444.00
K7546	36" Cemetery Bucket	265	\$1,445.00
K7877B	36 inch 6.64 cu. ft. Smooth Grading Bucket If used with thumb, the tines meet below cutting edge	230	\$1,191.00
K7458	36" Grading Blade	270	\$1,639.00
K7473A	36 inch 3.0 cu. ft. TILT GRADING BUCKET Includes hoses and fittings. Tilts 45° each direction.	305	\$4,449.00
K7454	39 inch 4.72 cu. ft. Tilt Grading Bucket Includes hoses and fittings. Tilts 45° each direction	485	\$5,748.00
K7454A	39 inch 4.72 cu. ft. Tilt Grading Bucket Includes hoses and fittings. Tilts 45° each direction	485	\$5,048.00

K Series KX040-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 3	ATTACHMENTS		
K7910A	HYDRAULIC THUMB KIT K7870A Quick Coupler required	195	\$2,682.00
K7474A	36" Bolt On Cutting Edge For K7877B, K7473, K7121, or K7123 36" Buckets	36	\$156.00
K7455A	39" Bolt On Cutting Edge For K7454 or K7124 39" Tilt Grading Bucket	44	\$153.00
K7940	CANOPY WORK LIGHT KIT	6	\$154.00
K7447	BEACON LIGHT KIT (Enclosed Cab Use Only)	4	\$290.00
K9929	STEEL CRAWLER KIT Convert tracks from rubber to steel	439	\$3,945.00
K7927	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse	2	\$145.00
PART 4	ROPS / OPG (Top Guard, Level I)		
K9153	REPLACEMENT 4-POST ROPS / OPG (Top Guard, Level I) CANOPY	250	\$1,940.00
K9152	REPLACEMENT ROPS / OPG (Top Guard, Level I) CAB The K9152 cab is configured as a replacement for damaged factory mounted cabs. It does not include cabin electrical wiring, wiper motor, heater, or defroster. Refer to illustrated parts list to order these components.	390	\$8,547.00
K7479	Cab Mirror Kit Includes two side mirrors, one for each side, one rear mirror, and attaching hardware	11	\$292.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$93.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models only)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$166.00
77700-08687	Rotating Beacon, Class 1, Halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS Versions		\$72.00

Model Downgrade K Series KX033-4

KX033-4 Hydraulic Excavator

FEATURES

Half Pitched Rubber Tracks or (Steel Tracks) ***
 ROPS/OPG (Top Guard, Level 1) 4 Post Canopy or
 Heated Cab with A/C
 Suspension Seat
 Kubota 3 Hydraulic Pump Design
 1 Gear; 2 Variable Displacement Pumps
 Hydraulic Joystick Controls with Wrist Rests
 Hydraulic Accumulator
 Two Operating Pattern Selection System
 Standard Front Dozer Blade
 360 Degree Full Rotation
 70° Left and 48° Right Boom Swing Angle
 15.8 GPM Adjustable Auxiliary Hydraulics Port
 With Diverter Valve
 Five Second Quick Preheat System
 Key Switch Stop System
 Self Bleed Fuel System
 Two Speed Travel
 Auto Idle
 Thumb Bracket and Relief Valves
 Swivel Negative Brake
 Travel Negative Brake
 Third Line Return (Hydraulic)

BASIC UNIT

KX033-4R1 Rubber Tracks, 4-Post ROPS/OPG
 (Top Guard, Level 1) Canopy
 KX033-4R1A, Rubber Tracks, ROPS/OPG (Top
 Guard, Level 1) Canopy, Angle Dozer Blade
 KX033-4R1E***, Rubber Tracks, ROPS/OPG,
 Canopy, Extendable Dipper Arm
 KX033-4R1AE***, Rubber Tracks, ROPS/OPG
 (Top Guard, Level 1) Canopy, Angle Dozer Blade,
 Extendable Dipper Arm
 KX033-4R3, Rubber Tracks, ROPS/OPG (Top
 Guard, Level 1) Heated Cab with A/C
 KX033-4R3A, Rubber Tracks, ROPS/OPG (Top
 Guard, Level 1) Heated Cab with A/C, Angle
 Blade
 KX033-4R3E***, Rubber Tracks, ROPS/OPG (Top
 Guard, Level 1) Heated Cab with A/C,
 Extendable Dipper Arm
 KX033-4R3AE***, Rubber Tracks, ROPS/OPG
 (Top Guard, Level 1) Heated Cab with A/C, Angle
 Dozer blade, Extendable Dipper Arm

DIMENSIONS AND OPERATING WEIGHT

KX033-4R1, Rubber Tracks, 4-Post ROPS/OPG (Top
 Guard, Level 1) Canopy
 Overall Length 15' 6"
 Overall Width 5' 1"
 Overall Height 8' 1"
 Operating Weight* 7420 lbs.
 Ground Clearance 11.4"

KX033-4R3, Rubber Tracks, ROPS/OPG (Top Guard,
 Level 1) Heated Cab with A/C
 Overall Length 15' 6"
 Overall Width 5' 1"
 Overall Height 8' 1"
 Operating Weight* 7,742 lbs.
 Ground Clearance 11.4"

*Includes operator's weight of 175 lbs.

ENGINE

Kubota D1703M-DI-E4
 3 Cylinder, 4 Cycle
 24.8 Gross HP (SAE J1995) @ 2200 RPM
 23.2 Net HP (SAE J1349) @ 2200 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth 10' 6"
 Max Digging Radius @ Ground Level 16' 10"
 Max Vertical Digging Depth 7' 4"
 Max Dumping Height 11' 7"

DOZER BLADE DIMENSIONS

Width 61"
 Height 13.5"/ 15.2" Angle
 Lift Above Ground 14.4"/ 15.9" Angle
 Drop Below Ground 14.8"/ 16.1" Angle

PERFORMANCE

Digging Force @ Bucket 8138 lbs
 Digging Force @ Dipper Arm 3867 lbs
 Travel Speed (Low/High) 1.9/2.9 mph
 Traction Force (Low) 6091 lbs
 Lift Capacity 3230 lbs
 • Over Front
 • Blade Grounded
 • 2 Ft. Load Point Height
 • 8 Ft. Load Radius

K Series KX033-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL KX033-4		
KX033-4R1	Excavator Basic Unit With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight	6,978	CREDIT -\$39,355.00
KX033-4R1A	Excavator Basic Unit With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Dipper Arm, Counterweight	7,198	CREDIT -\$37,271.00
KX033-4R3	Excavator Basic Unit With: Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab, Heat and A/C, Dozer Blade, Dipper Arm, Counterweight	7,198	CREDIT \$34,726.00
KX033-4R3A	Excavator Basic Unit With: Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab, Heat and A/C, Angle Dozer Blade, Dipper Arm, Counterweight	7,199	\$32,648.00
KX033-4R1E	Excavator Basic Unit With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Extendable Dipper Arm, Counterweight	6,978	CREDIT -\$36,939.00
KX033-4R1AE	Excavator Basic Unit With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Angle Dozer Blade, Extendable Dipper Arm, Counterweight	6,978	CREDIT -\$34,854.00
KX033-4R3E	Excavator Basic Unit With: Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab, Heat and A/C, Dozer Blade, Extendable Dipper Arm, Counterweight	7,198	CREDIT -\$32,310.00
KX033-4R3AE	Excavator Basic Unit With: Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab, Heat and A/C, Angle Dozer Blade, Extendable Dipper Arm, Counterweight	7,198	CREDIT -\$30,321.00
PART 2	BUCKETS		
	PIN-ON BUCKETS (Order Attaching Pins from Parts)		
K7792A	12 inch 2.60 cu. ft. 3-Hole Bucket	194	\$1,048.00
K7793	16 inch 2.80 cu. ft. 3-Hole Bucket	220	\$1,126.00
K7794	18 inch 3.20 cu. ft. 3-Hole Bucket	229	\$1,177.00
K7796	24 inch 4.50 cu. ft. 3-Hole Bucket	265	\$1,298.00
	QUICK ATTACH BUCKETS		
K7870A	QUICK COUPLER Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin and hardware.	75	\$947.00
K9807	BUCKET HANGERS Set of 2 bucket ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	49	\$391.00

K Series KX033-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 2	BUCKETS (Cont.)		
K7872A	12 inch 2.13 cu. ft. Trenching Bucket	160	\$968.00
K7873A	16 inch 2.83 cu. ft. Trenching Bucket	185	\$1,014.00
K7874A	18 inch 3.19 cu. ft. Trenching Bucket	190	\$1,093.00
	The K7874 bucket has four teeth. The K7910 Thumb tines contact the end of the teeth and do not mesh between the teeth.		
K7874AC	18 inch 3.19 cu. ft. Trenching Bucket This is the same bucket as K7874A WITHOUT shanks for teeth	190	\$1,093.00
K7875A	24 inch 4.25 cu. ft. Trenching Bucket	240	\$1,310.00
K7875AC	24 inch 4.25 cu. ft. Trenching Bucket This is the same bucket as K7875A WITHOUT shanks for teeth	216	\$1,310.00
K7473A	36 inch 3.0 cu. ft. TILT GRADING BUCKET Includes hoses and fittings. Tilts 45° each direction	305	\$4,449.00
K7474A	BOLT ON CUTTING EDGE For K7473A 36" grading bucket	36	\$156.00
K7458	36" Grading Blade	270	\$1,639.00
K7546	36" Cemetery Bucket	265	\$1,445.00
PART 3	ATTACHMENTS		
K7910A	① HYDRAULIC THUMB KIT K7870A Quick Coupler required	195	\$2,682.00
K7461	① 24 INCH EXCAVATING RAKE, QUICK ATTACH	300	\$2,263.00
K7940	CANOPY WORK LIGHT KIT	6	\$154.00
K9784	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse	1	\$292.00
K7984	SPARK ARRESTOR MUFFLER KIT Optional kit for use in close proximity with grass, brush, timber and similar cellulose material with potential for ignition. Requires Heat Insulation Kit. 77700-06495	10	\$500.00

① Not approved for use with extendible arm.

K Series KX033-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 4	Cab Mirror Kit		
K9786	Includes two side mirrors, one for each side, one rear mirror, and attaching hardware	11	\$292.00
K9787	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	11	\$93.00
77700-04754A	Radio Kit AM/FM/ WB/ AUX/ USB/ iPod/ SAT (for Cab models ONLY)		\$266.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS and CAB Versions		\$72.00

Model Downgrade K Series KX71-3S4

KX71-3S4 Hydraulic Excavator

FEATURES

Half Pitched Rubber Tracks or Steel Tracks
ROPS/OPG (Top Guard, Level 1) 4 Post Canopy
or Heated Cab
Suspension Seat
Kubota 3 Hydraulic Pump Design
1 Gear; 2 Variable Displacement Pumps
Hydraulic Joystick Controls with Wrist Rests
Two Operating Pattern Selection System
Standard Front Dozer Blade
360 Degree Full Rotation
80° Left and 60° Right Boom Swing Angle
13.1 GPM Adjustable Auxiliary Hydraulics Port
Five Second Quick Preheat System
Key Switch Stop System
Self Bleed Fuel System
Two Speed Travel
Thumb Bracket and Relief Valves
Swivel Negative Brake

KX71-3S4R1, Rubber Tracks, 4-Post ROPS/OPG
(Top Guard, Level 1) Canopy
KX71-3S4R2, Rubber Tracks, ROPS/OPG (Top
Guard, Level 1) Heated Cab
KX71-3S4S1, Steel Tracks, 4-Post ROPS/OPG
(Top Guard, Level 1) Canopy
KX71-3S4S2, Steel Tracks, ROPS/OPG (Top
Guard, Level 1) Heated Cab

ENGINE

D1505 Kubota E-TVCS Tier 4 Final Diesel Engine
4 Cylinder, 4 Cycle
24.4 Gross HP (SAE J1995) @ 2300 RPM
23.1 Net HP (SAE J1349) @ 2300 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth	9' 9"
Max Digging Radius @ Ground Level	16' 0"
Max Vertical Digging Depth	6' 5"
Max Dumping Height	10' 5"

DOZER BLADE DIMENSIONS

Width	59"
Height	12.0"
Lift Above Ground	13.0"
Drop Below Ground	12.0"
Digging Force @ Bucket (K7978)	6350 lbs.
Digging Force @ Dipper Arm	3285 lbs.
Travel Speed (Low/High)	1.8/2.9 mph
Climbing Ability	36% / 20°
Ground Pressure (Rubber/Canopy)	3.9 psi
Lift Capacity	1,760 lbs.
<ul style="list-style-type: none"> Over Front Blade Grounded 2 Ft. Load Point Height 8 Ft. Load Radius 	

DIMENSIONS AND OPERATING WEIGHT

KX71-3S4R1, Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy	
Overall Length	14' 11"
Overall Width	4' 11"
Overall Height	8' 0"
Operating Weight*	6,305 lbs.
Ground Clearance	11.0"

KX71-3S4R2, Rubber Tracks, ROPS/OPG (Top Guard, Level 1) Heated Cab	
Overall Length	14' 11"
Overall Width	4' 11"
Overall Height	7' 11"
Operating Weight*	6,550 lbs.
Ground Clearance	11.0"

*Includes operator's weight of 175 lbs.

K Series KX71-3S4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1			
KX71-3S4R1	MODEL KX71-3S4 BASIC UNITS	6550	CREDIT -\$43,601.00
	Excavator Basic Unit		
With:	Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
KX71-3S4R2		6550	CREDIT -\$40,382.00
	Excavator Basic Unit		
With:	Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade, Dipper Arm, Counterweight		
		6746	CREDIT -\$40,173.00
PART 2			
	BUCKETS		
	PIN-ON BUCKETS (Order attaching pins from Parts)		
K7792A	12 inch 2.60 cu. ft. 3-Hole Bucket	194	\$1,048.00
K7793	16 inch 2.80 cu. ft. 3-Hole Bucket	220	\$1,127.00
K7794	18 inch 3.20 cu. ft. 3-Hole Bucket	229	\$1,177.00
K7796	24 inch 4.50 cu. ft. 3-Hole Bucket	265	\$1,298.00
	QUICK ATTACH BUCKETS		
	QUICK COUPLER		
	Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin and hardware.		
K7870A	QUICK COUPLER	75	\$948.00
	Curl hole and power hole built into quick coupler. Includes two mounting pins, 1 locking pin and hardware.		
K9807	BUCKET HANGERS	49	\$391.00
	Set of 2 bucket ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.		
K7872A	12 inch 2.13 cu. ft. Trenching Bucket	160	\$968.00
K7873A	16 inch 2.83 cu. ft. Trenching Bucket	185	\$1,014.00
K7874A	18 inch 3.19 cu. ft. Trenching Bucket	190	\$1,092.00
	The K7874A bucket has four teeth. The K7902 Thumb tines contact the end of the teeth and do not mesh between the teeth.		
K7874AC	18 inch 3.19 cu. ft. Trenching Bucket	190	\$1,093.00
	This is the same bucket as K7874A WITHOUT shanks for teeth		
K7875A	24 inch 4.25 cu. ft. Trenching Bucket	240	\$1,310.00
K7875AC	24 inch 4.25 cu. ft. Trenching Bucket	216	\$1,310.00
	This is the same bucket as K7875A WITHOUT shanks for teeth		
K7473	36 inch 3.0 cu. ft. TILT GRADING BUCKET	305	\$5,066.00
	Includes hoses and fittings. Tilts 45° each direction.		
K7474A	BOLT ON CUTTING EDGE	36	\$156.00
	For K7473 36" grading bucket		
K7458	36 inch Grading Blade	270	\$1,639.00
K7458A	36 inch Grading Blade	270	\$1,395.00
K7546	36" Cemetery Bucket	265	\$1,445.00

K Series KX71-3S4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 3	ATTACHMENTS		
K7902	HYDRAULIC THUMB KIT K7870 Quick Coupler required.	190	\$3,081.00
K7461	24" EXCAVATING RAKE, QUICK ATTACH	300	\$2,263.00
K9919	CANOPY WORK LIGHT KIT	4	\$129.00
K9736	STEEL CRAWLER KIT Convert tracks from rubber to steel	787	\$2,985.00
K9967	TRAVEL ALARM KIT Emits an audible signal when traveling forward or reverse	2	\$307.00
PART 4	ROPS / OPG (Top Guard, Level I)		
K7890	REPLACEMENT 4-POST ROPS/OPG (Top Guard, Level I) CANOPY	180	\$1,204.00
K7899	REPLACEMENT ROPS / OPG (Top Guard, Level I) CAB The K7899 cab is configured as a replacement for damaged factory mounted cabs. It does not include cabin electrical wiring, wiper motor, heater, or defroster. Refer to illustrated parts list to order these components.	400	\$5,856.00
K9943A	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$93.00

Model Downgrade K Series KX018-4

KX018-4

Hydraulic Excavator

FEATURES

Short Pitch Rubber Tracks
ROPS/OPG (Top Guard, Level 1) 4 Post Canopy or Heated Cab
Suspension Seat
Variable Width Track Frame
Kubota 4 Hydraulic Pump Design
2 Gear; 2 Variable Displacement Pumps
Hydraulic Joystick Controls with Wrist Rests
Two Operating Pattern Selection System
Standard Front Dozer Blade with Extensions
360 Degree Full Rotation
75° Left and 60° Right Boom Swing Angle
7.4 GPM Auxiliary Hydraulics Port
Five Second Quick Preheat System
Key Switch Stop System
Self Bleed Fuel System
Auto-downshift Two Speed Travel System

BASIC UNIT

KX018-4R1, Rubber tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy, Dipper Arm, Counterweight
KX018-4R2, Rubber tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Heated Cab, Dipper Arm, Counterweight

DIMENSIONS AND OPERATING WEIGHT

KX018-4R1, Rubber tracks, 4-Post ROPS/OPG (Top Guard, Level 1) Canopy, Dipper Arm, Counterweight
Overall Length 12' 2.1"
Overall Width 3'3" / 4'3.2"
Overall Height 7'7.7"
Operating Weight* 3747 lbs.
Ground Clearance 6.3"

*Includes operator's weight of 175 lbs.

ENGINE

D902 Kubota E-TVCS Tier 4 Final Diesel Engine
3 Cylinder, 4 Cycle
16.1 Gross HP (SAE J1995) @ 2300 RPM
15.5 Net HP (SAE J1349) @ 2300 RPM

OPERATIONAL DIMENSIONS

Max Digging Depth 7' 9.7"
Max Digging Radius @ Ground Level 12' 8"
Max Vertical Digging Depth 6' 7.9"
Max Dumping Height 7' 9.7"

DOZER BLADE DIMENSIONS

Width 3'3" / 4'3.2"
Height 9.1"
Lift Above Ground 9.1"
Drop Below Ground 9.1"

PERFORMANCE

Digging Force @ Bucket (K7970) 3594 lbs.
Digging Force @ Dipper Arm 1852 lbs.
Travel Speed (Low/High) 1.4/2.6 mph
Climbing Ability 27% / 15°
Ground Pressure 3.7 psi
Lift Capacity 910 lbs.
• Over End
• Blade Grounded
• 2 Ft. Load Point Height
• 8 Ft. Load Radius

K Series KX018-4

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	PRICE
PART 1	MODEL KX018-4 BASIC UNITS		
KX018-4R1	Excavator Basic Unit	3747	CREDIT -\$49,519.00
	With: Rubber Tracks, 4-Post ROPS/OPG (Top Guard, Level I) Canopy, Dozer Blade, Dipper Arm, Counterweight		
KX018-4R2	Excavator Basic Unit	3967	CREDIT -\$46,868.00
	With: Rubber Tracks, ROPS/OPG (Top Guard, Level I) Heated Cab, Dozer Blade, Dipper Arm, Counterweight		
PART 2	BUCKETS		
	PIN-ON BUCKETS		
K7779A	9 inch 0.52 cu. ft. 2-Hole H. D. Bucket	57	\$688.00
K7780A	12 inch 0.74 cu. ft. 2-Hole H. D. Bucket	82	\$710.00
K7781	16 inch 0.95 cu. ft. 2-Hole H. D. Bucket	94	\$784.00
K7785	18 inch 1.1 cu. ft. 2-Hole H. D. Bucket	95	\$974.00
	QUICK ATTACH BUCKETS		
K7966A	Quick Coupler Includes two mounting pins, 1 locking pin, and hardware.	20	\$808.00
K7967A	9 inch 0.78 cu. ft. Trenching Bucket	86	\$426.00
K7968A	12 inch 1.0 cu. ft. Trenching Bucket	92	\$550.00
K7969A	16 inch 1.3 cu. ft. Trenching Bucket	108	\$548.00
K7970A	18 inch 1.5 cu. ft. Trenching Bucket	115	\$682.00
K9607	Bucket Hangers Set of two ear blanks. Converts buckets to quick coupler style. Modification to match bucket contour required.	12	\$255.00
PART 3	ATTACHMENTS		
K7420	Travel Pedal Kit	7	\$262.00
K7421	Canopy Work Light Kit	9	\$211.00
K7141	MIRROR KIT **Cab ONLY	11	\$224.00
K7424	Travel Alarm Kit Emits an audible signal when traveling forward or reverse	1	\$211.00
PART 4	ROPS / OPG (Top Guard, Level I)		
K7422	REPLACEMENT 4-POST ROPS / OPG (Top Guard, Level I) CANOPY	143	\$1,362.00
K7423	REPLACEMENT ROPS / OPG (Top Guard, Level I) CAB The K7423 cab is configured as a replacement for damaged factory mounted cabs. It does not include cabin electrical wiring, wiper motor, heater, or defroster. Refer to illustrated parts list to order these components.	375	\$4,824.00
K7425	RETRACTABLE SEAT BELT OPTION (3") As required in some states for OSHA compliance.	3	\$83.00
	Available from Parts		
70000-01602	Screen Type Spark Arrestor		\$169.00
77700-08686	Strobe Light, Class 2, LED, flashing strobe w/ vacuum magnetic mounting		\$161.00
77700-08687	Rotating Beacon, Class 1, halogen (beacon light only) w/ magnetic mounting		\$194.00
77700-10379	Wire harness needed for installation of Strobe (77700-08686) and Beacon (77700-08687) on ROPS machines ONLY		\$ 47.00
RD829-53870	Switch for Strobe (77700-08686) and Beacon (77700-08687) ROPS and CAB Versions		\$72.00