

ST PRO SERIES WEDGE CARGO



Standard Features

Height

- 6'6" Interior Height

Wedge Depth

- 18.5" Ext. Wedge Depth

Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows
- "WideTrac" Full-Width Interior Walls Without Fender Boxes (on 7' wides)

Hitch

- 7-Way Molded Plug
- 2-5/16" Coupler on 7K and 10K
- Adjustable 2-5/16" Coupler on 14K
- 4-Bolt Faceplate Pintle on 16K
- Safety Chains
- Zinc-Plated Setback Jack on 7K
- 7K Setback Jack on 10K & 14K
- HD 12K Setback Jack on 16K

Axle

- ***Torsion Axles**
- All Wheel Brakes

Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)
- Radial Tires on Black Wheels (16K)

Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Engineered Wood Flooring Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/1 Wall Switch
- LED 6" Oval Tail Lights w/Rubber Mounted 3/4" Bullet Marker Lights (All Clear Lens)
- ***Integrated Backup Lights**

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Bright Nose Cap & Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- Seamless Aluminum Roof w/3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 32"x70" RV Side Door w/Aluminum Door Holder
- Heavy-Duty Rear Ramp Door w/Wood Flap or Rear Double Doors w/Aluminum Rear Door Holders
- Ramp Ratings - 7' wide = 2,250 lb.
8.5' wide = 4,100 lb.

Limited 3-Year Warranty

* Denotes New for 2020

SPECIFICATIONS

Model #	12'	7' Wide (7K)	7' Wide (10K)	8.5' Wide (7K)	8.5' Wide (10K)
	14'	STW8412TA	STW8412TA-100	-	-
	16'	STW8414TA	STW8414TA-100	-	-
	18'	STW8416TA	STW8416TA-100	STW10216TA	STW10216TA-100
	20'	STW8418TA	STW8418TA-100	STW10218TA	STW10218TA-100
	24'	-	-	STW10220TA	STW10220TA-100
GVWR (lb. / Axle)		7000	9900	7000	9900
GAWR (lb. / Axle)		3500	5200	3500	5200
Curb Weight	12'	1900	2150	-	-
	14'	2040	2290	-	-
	16'	2120	2400	2880	3350
	18'	2220	2550	3260	3430
	20'	-	-	3610	3760
	24'	-	-	4170	4420
Payload	12'	5100	7750	-	-
	14'	4960	7610	-	-
	16'	4880	7500	4120	6550
	18'	4780	7350	3740	6470
	20'	-	-	3390	6140
	24'	-	-	2830	5480
Frame		6x2 Tube		6x2, 1/8" Tube	
Cross Members		C-Channel (16" On-Center)		C-Channel (16" On-Center)	
Tongue		6x2 Tube		6x2, 1/8" Tube	
Wall Studs		Tube (16" On-Center)		Tube (16" On-Center)	
Roof Bows		Tube (24" On-Center)		Tube (24" On-Center)	
Coupler		2 5/16" Ball		2 5/16" Ball	
Jack		2K Setback	7K Setback	2K Setback	7K Dropleg
Fenders		Aluminum Teardrop		Aluminum Teardrop	
Easy Lube Axles		22.5 Degree Up Torsion		22.5 Degree Up Torsion	
Tires		205/75R 15 LRC	225/75R15 LRD	205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial	15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Wheels		Aluminum		Aluminum	
Flooring		Engineered Wood		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7 Pole RV Molded Flat Blade		7 Pole RV Molded Flat Blade	
Exterior		.030 Aluminum		.030 Aluminum	
Overall Length	12'	198"		-	
	14'	222"		-	
	16'	246"		249"	
	18'	270"		273"	
	20'	-		297"	
	24'	-		345"	
Overall Width		102"		102"	
Overall Height		101"		101"	
Interior Height		78"		78"	
Interior Width		81"		97" (80.5" Between Fender Box)	
Interior Length	12'	153"		-	
	14'	177"		-	
	16'	201"		201"	
	18'	225"		225"	
	20'	-		249"	
	24'	-		297"	
Floor Height		18"		21"	
Rear Door Opening (WxH)		74" x 72.50"		90" x 72.50"	
Ramp Door Capacity (lbs.)		2250		2250	

