

ST HD LOW PROFILE DUMP



Gooseneck Option



16K Models Include

4-Bolt Adj Pintle, HD 12K Jack, 8" Tongue, 6" Cylinder and Thicker Wall Tube Frame.

HD LOW PROFILE DUMP FEATURES

16" Radial Tires (235 80R16 LRE,) 6k & 7K Axle
17.5" Radial Tires (215 75R17.5 LRH) 8K Axle
HD Set-Back Jack
Adjustable Coupler
HD Slipper Spring Axle
Easy Lube Hubs
All-Wheel Brakes
Sealed Brake Connections
Welded Tubular Steel Main Frame
6" Tube Tongue
Reinforced Combo Barn Door Spreader Gate with Cambar

Wider & Heavier HD Ramps (Stored Underneath Bed)
Integrated Side Body Stiffening System
Underbody Secure Tool Storage
10 Gauge Floor
Side Steps
Spare Tire Carrier
Board Holders
Stabilizer Jack Receivers (Jacks Optional)
(5) 1/2" D-Rings (12K & 14K Models)
(5) 5/8" D-Rings (16K Models)
Stake Pockets - 3 Per Side (12' Models)

Stake Pockets - 4 Per Side (14' Models)
Stake Pockets - 5 Per Side (16' Models)
Tongue Mounted HD Control Box with Key Lock
Iron Phosphate Wash Steel Prep
Powder Coat Finish
Integrated Tarp Mount
Tarp Kit (Installed) (NEW)
7-Way RV-Style Electrical Plug
Deep Cycle Marine Grade Battery
Battery Charger, 110V
All LED Lighting

SPECIFICATIONS

		82" x 12 (12K)	82" x 12 (14K)	82" x 14 (14K)	82" x 16 (14K)	82" x 14 (16K)	82" x 16 (16K)
Model	Dual Ram	ST8212DD-B-120	ST8212DD-B-140	ST8214DD-B-140	ST8216DD-B-140	N/A	N/A
	Scissor	ST8212HLOD-B-120	ST8212HLOD-B-140	ST8214HLOD-B-140	ST8216HLOD-B-140	ST8214HLOD-B-160	ST8216HLOD-B-160
	Telescopic	ST8212TLDD-B-120	ST8212TLDD-B-140	ST8214TLDD-B-140	ST8216TLDD-B-140	ST8214TLDD-B-160	ST8216TLDD-B-160
GVWR (lb.)		12000	14000	14000	14000	16000	16000
GAWR (lb.axle)		6000	7000	7000	7000	8000	8000
Curb Weight	Dual Ram	3240	3460	3600	3960	-	-
	Scissor	3400	3620	3800	4160	4040	4360
	Telescopic	3240	3460	3600	4100	4540	5040
Payload	Dual Ram	8760	10540	10400	10040	-	-
	Scissor	8600	10380	10200	9840	11960	11640
	Telescopic	8760	10540	10400	9900	11460	10960
Frame		5 x 2 Tube (Tele - 6x2, 3/16" Tube)	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 1/4" Tube		
Cross Members		4" C-Channel					
Tongue		6 x 2 Tube				8 x 2 Tube	
Sides		24"	24"	24"	24"	24"	24"
Coupler		Adjustable 2-5/16"				Adjustable 4 Bolt Pintle	
Jack		7K Dropleg, Set Back				HD 12K Dropleg, Set Back	
Fenders		Heavy Duty Tread Plate, Double Brake					
Easy Lube Axles		Easy Lube Cambered Brake					
Suspension		Slipper Spring					
Tires		235/80R16 LRE				215/75R17.5 LRH	
Wheels		16", 8 on 6.5, Radial				17.5", 8 on 6.5, Radial	
Decking		10 ga. Smooth Steel					
Lights		All LED Lights					
Electric Plug		7 Pole RV Molded Flat Blade					
Finish		Powder Coated High Gloss Black					
Overall Length		198"	198"	222"	246"	222"	246"
Bed Length Inside		144"	144	168"	192"	168"	192"
Bed Width Inside		82"	82"	82"	82"	82"	82"
Side Wall Height		24"	24"	24"	24"	24"	24"
Deck Height		29"	29"	29"	29"	29"	29"
Coupler Height		Adjustable 19-27"					
Gate		Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Dual Ram	Dual Ram, Power Up, Power Down					
	Scissor	Power Up, Gravity Down					
	Telescopic	Power Up, Gravity Down					
Hydraulic Pump	Dual Ram	2300 PSI	3000 PSI	3000 PSI	2000 PSI	-	-
	Scissor	2500 PSI	2800 PSI	2800 PSI	2500 PSI	2800 PSI	2800 PSI
	Pump	2300 PSI	2300 PSI	2300 PSI	2300 PSI	2500 PSI	2500 PSI
Battery	Dual Ram	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP31	12V Deep Cycle, DP31	12V Deep Cycle, DP31
	Scissor	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP31	12V Deep Cycle, DP31	12V Deep Cycle, DP31
	Telescopic	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP24	12V Deep Cycle, DP31	12V Deep Cycle, DP31	12V Deep Cycle, DP31

