

Item #370

Build Sheet

Vac-Con Sewer Cleaner Model V311HN/1000

Standard Equipment Includes:

Three Stage Centrifugal Compressor Vacuum System, Rated at 3500CFM @ 14.5 inches of mercury

Centrifugal Compressor Diffuser/Muffler

Centrifugal Separator with Cleanout Box

Hydrostatic Vacuum Drive

11 Cubic Yard, 3/16" Corten Steel Debris Tank

Full Opening Rear Door, Hinged at the Top

Hydraulic Rear Door Locks, with Door Grabber and Safety Latch

Internal Polyethylene Float Device with External Indicator

5" Butterfly Drain Valve with 10' Lay Flat Hose

Debris Tank Dumping: Minimum 50 degrees, Hydraulic Scissors Lift - Power Up/Power Down

Automatic Vacuum Breaker and Overfill Protection

Vacuum Relief Valves

8" Vacuum Intake Hose

Boom Transport Cradle

4 Way Hydraulic Boom with Clean Out, 270 Degree Rotation and Joystick Controls

Pendant Control

Front Mounted Hose Reel 800' x 1" Capacity, Hydraulic Power

Hose Reel Speed Control, Hydraulic Locks

400' x 1" 2500 PSI Rated Hose

1,000 Gallon Capacity Polyethylene Water Tanks

Curbside Fill

Sight Gauge to Indicate Water Level

Water Pump: 80 GPM @2,500 PSI

High-Pressure Relief Valves

Hydrostatic Water Pump Drive

Dual Roller Level Wind

Manual Hose Rewind Guide

Flexible Hose Guide (Tiger Tail)

10' x 1" Leader Hose

20 GPM at 600 PSI Wash Down Hand Gun with 25' of Hose, Nozzle & Relief Valve

Hose Storage Rack

Sealed and Locking Tool Box

1) each Sanitary (15 degree) and Penetrator (30 degree) nozzles

20.5' x 8" Aluminum Intake Tubes (1-3', 1-5', 1-6', and 1-6.5' nozzle)

ICC LED lighting

Polyurethane Paint

Vac-Con Manual

12 Month Standard Warranty

5 lb. Fire Extinguisher

1) Set of Triangles