800-782-4134 www.southernsewer.com

## Item #371

## **Build Sheet**

## Vac-Con Sewer Cleaner Model VPD4211SHAE

Standard Equipment Includes: 827 Positive Displacement Blower, Rated at 4200 CFM @ 18 Inches of Mercury Diffuser/Muffler Centrifugal Separator with Cleanout Box Hydrostatic Vacuum Drive 11 Cubic Yard, 3/16" Corten Steel Debris Tank Full Opening Rear Door, Hinged at the Top Hydraulic Rear Door Locks, with Door Grabber and Safety Latch Internal Polyethylene Float Device with External Indicator 5" Butterfly Drain Valve with 10' Lay Flat Hose Debris Tank Dumping: Minimum 50 degrees, Hydraulic Scissors Lift - Power Up/Power Down Automatic Vacuum Breaker and Overfill Protection Vacuum Relief Valves 8" Vacuum Intake Hose **Boom Transport Cradle** 6' Aluminum Telescoping Hydraulic Boom with Clean Out, 270 Degree Rotation and Joystick Controls Pendant Control Front Mounted Articulating Hose Reel 800' x 1" Capacity, Hydraulic Power Hose Reel Speed Control, Hydraulic Locks 400' x 1" 2500 PSI Rated Hose 1,000 Gallon Capacity Polyethylene Water Tanks Curbside Fill Sight Gauge to Indicate Water Level Water Pump: 80 GPM @ 2,500 PSI **High-Pressure Relief Valves** Water Pump Drive: Gas Auxiliary Engine **Dual Roller Level Wind** Manual Hose Rewind Guide Flexible Hose Guide (Tiger Tail) 10' x 1" Leader Hose 20 GPM at 600 PSI Wash Down Hand Gun with 25' of Hose, Nozzle & Relief Valve Hose Storage Rack Sealed and Locking Tool Box 1) each Sanitary (15 degree) and Penetrator (30 degree) nozzles 20.5' x 8" Aluminum Intake Tubes (1-3', 1-5', 1-6', and 1-6.5' nozzle) **ICC LED lighting Polyurethane Paint** Vac-Con Manual 12 Month Standard Warranty 5 lb. Fire Extinguisher 1) Set of Triangles