

S = Standard Equipment A = Available --(dashes) = Not Available D = ADI Available

■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

* Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Model.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CP11003 and CP31003 models. 2 - Available on CP12003 and CP32003 models. 3 - Available on CP13003 and CP33003 models. 4 - Available on CP14003 and CP34003 models. 5 - Available on CP13043 and CP33043 models. 6 - Available on CP14043 and CP34043 models.	Reg. Cab				Crew Cab	
			1WT 109" WB ¹	1WT 132.5" WB ²	1WT 150" WB ³	1WT 176" WB ⁴	1WT 150" WB ⁵	1WT 176" WB ⁶
	C60	Air conditioning , single-zone manual, integral in-dash mounted	S	S	S	S	S	S
	K34	Cruise control , electronic, automatic	S	S	S	S	S	S
		Cup holders	S	S	S	S	S	S
	UIZ	Audio System , AM/FM stereo with CD player, auxiliary jack, USB port and Bluetooth	S	S	S	S	S	S
	UAD	Audio system feature , 2 speakers	S	S	S	S	S	S
	AU3	Door locks , power	S	S	S	S	S	S
	UDH	Driver Information Center	S	S	S	S	S	S
		Floor mats	S	S	S	S	S	S
		Lighting , interior dome	S	S	S	S	S	S
	A1F	Seat , front high back bucket driver and passenger, tricloth covered reclining high back driver seat with single two-occupant fold down passenger seat	S	S	S	S	S	S
	N3R	Steering wheel , urethane	S	S	S	S	S	S
	N33	Steering column , Tilt-Wheel	S	S	S	S	S	S
		Storage , door pockets	S	S	S	S	S	S
		Storage , seatback pockets	S	S	S	S	S	S
	A31	Windows , power	S	S	S	S	S	S
		Windshield washer bottle access , on passenger side dash when passenger-side door is open	S	S	S	S	S	S
		Daytime Running Lamps	S	S	S	S	S	S
		Glass , tinted	S	S	S	S	S	S
	DB5	Mirror , outside left-hand and right-hand dual cab-mounted with integral convex mirror	S	S	S	S	S	S
	E01	Assist steps	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CP11003 and CP31003 models. 2 - Available on CP12003 and CP32003 models. 3 - Available on CP13003 and CP33003 models. 4 - Available on CP14003 and CP34003 models. 5 - Available on CP13043 and CP33043 models. 6 - Available on CP14043 and CP34043 models.	Reg. Cab				Crew Cab	
			1WT 109" WB ¹	1WT 132.5" WB ²	1WT 150" WB ³	1WT 176" WB ⁴	1WT 150" WB ⁵	1WT 176" WB ⁶
	2TA	Tires , front, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season 1 - Standard on 3500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	2TC	Tires , front, 225/70R19.5 G 128/126 L BW HWY VAR1 1 - Standard on 4500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	3TA	Tires , rear, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season 1 - Standard on 3500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	3TC	Tires , rear, 225/70R19.5 G 128/126 L BW HWY VAR1 1 - Standard on 4500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	PWJ	Wheels , 16" x 6, K. steel 1 - Standard on 3500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	PWK	Wheels , 19.5" x 6", K steel 1 - Standard on 4500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	CD7	Windshield wiper , pulse, wet arm	S	S	S	S	S	S
	RQ2	Vehicle Application Truck	S	S	S	S	S	S
	VXT	Incomplete vehicle certification	S	S	S	S	S	S
	K45	Air cleaner , heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.	S	S	S	S	S	S
	TP6	Battery , 750 cold-cranking amps, 12-volt single, maintenance free, frame-mounted battery box	S	S	S	S	S	S
	JE5	Brakes , 4-wheel antilock, front disc, rear drum, dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system.	S	S	S	S	S	S
	J69	Brake , parking, cable actuated, internal expanding drum type, transmission-mounted	S	S	S	S	S	S
	L8T	Engine , 6.6L V8 SIDI, GMPT-V8 8 cylinder V Iron block, four cycle overhead valve water cooled 6.6L SIDI V8 350 hp [261 kW] @ 4500 rpm, 425 lb.-ft of torque [575.8 N-m] @ 3800 rpm. Electronically controlled direct fuel injection. Six bolt main cap design for heavy-duty performance. Engine Control Module (ECM) and Transmission Control Module (TCM) engine control system. Engine cruise control, engine oil cooler, High Idle Mode (1200 rpm).	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CP11003 and CP31003 models. 2 - Available on CP12003 and CP32003 models. 3 - Available on CP13003 and CP33003 models. 4 - Available on CP14003 and CP34003 models. 5 - Available on CP13043 and CP33043 models. 6 - Available on CP14043 and CP34043 models.	Reg. Cab				Crew Cab	
			1WT 109" WB ¹	1WT 132.5" WB ²	1WT 150" WB ³	1WT 176" WB ⁴	1WT 150" WB ⁵	1WT 176" WB ⁶
	N4C	Emissions , 50 state certification	S	S	S	S	S	S
	NB5	Exhaust , single outlet	S	S	S	S	S	S
	NH3	Fuel tank , 38.6 Gallon, (146L), rectangular fuel tank mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	S	S	S	S	S	S
	KG3	Alternator , 145 amps output with integral regulator	S	S	S	S	S	S
	C7L	GVWR , 12,000 lbs. (5443 kg) 1 - Standard on 3500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	C7S	GVWR , 14,500 lbs. (6577 kg) 1 - Standard on 4500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	EB4	Wheelbase , 109" (276.9 cm)	S	--	--	--	--	--
	FNJ	Wheelbase , 132.5" (336.6 cm)	--	S	--	--	--	--
	FWH	Wheelbase , 150" (381.0 cm)	--	--	S	--	S	--
	FNW	Wheelbase , 176" (447.0 cm)	--	--	--	S	--	S
		Frame , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 7.20 cu.in. and RBM 316,800 lb-ft/in per rail.	S	S	S	S	S	S
	FL5	Front axle , 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering. ratio 18.8-20.9:1	S	S	S	S	S	S
	FM2	Front suspension , 8,440 lbs. (3828 kg) tapered leaf, semi-elliptical steel alloy tapered leaf springs. Includes shock absorbers and stabilizer bar.	S	S	S	S	S	S
	HS6	Rear axle , 11,020 lbs. (4998 kg) R050, full-floating single-speed, with oil lubricated rear wheel-bearings	S	S	S	S	S	S
	FU4	Rear suspension , 12,900 lbs. (5851 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers	S	S	S	S	S	S
	066	Rear axle , 4.10 ratio 1 - Standard on 3500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	092	Rear axle , 4.30 ratio 1 - Standard on 4500 model only.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	MYD	Transmission , 6-speed automatic, 6L90-E Hydra-Matic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.852, 0.667, Rev. 3.064:1	S	S	S	S	S	S