

S = Standard Equipment A = Available --(dashes) = Not Available D = ADI Available

■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

* Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Model.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab							
			1WT CT73203 152" WB	1WT CT73903 170" WB	1WT CT74503 188" WB	1WT CT75003 200" WB	1WT CT76003 212" WB	1WT CT76503 224" WB	1WT CT77603 236" WB	1WT CT78803 248" WB
	C60	Air conditioning , single-zone manual, integral in-dash mounted	S	S	S	S	S	S	S	S
	UIZ	Audio System , AM/FM stereo with CD player, auxiliary jack, USB port and Bluetooth	S	S	S	S	S	S	S	S
	UAD	Audio system feature , 2 speakers	S	S	S	S	S	S	S	S
	K34	Cruise control , electronic, automatic	S	S	S	S	S	S	S	S
		Cup holders	S	S	S	S	S	S	S	S
	AU3	Door locks , power	S	S	S	S	S	S	S	S
	UDH	Driver Information Center , Multi-Information Display (MID) (monitors vital functions including diesel exhaust fluid levels (DEF), particulate matter emissions level in the diesel particulate filter (DPF), diesel particulate filter regeneration, service reminders for engine oil, transmission oil, differential oil, power steering fluid, engine oil filter, and fuel filters. The MID provides fuel economy reporting by average, instant, and trip.)	S	S	S	S	S	S	S	S
		Floor mats	S	S	S	S	S	S	S	S
		Lighting , interior dome	S	S	S	S	S	S	S	S
	A1G	Seat , high back driver only air suspension system and fixed passenger seat	S	S	S	S	S	S	S	S
	N3R	Steering wheel , urethane	S	S	S	S	S	S	S	S
	N33	Steering column , Tilt-Wheel and telescoping steering column	S	S	S	S	S	S	S	S
		Storage , door pockets	S	S	S	S	S	S	S	S
		Storage , seatback pockets	S	S	S	S	S	S	S	S
	A31	Windows , power	S	S	S	S	S	S	S	S
		Windshield washer bottle access , underhood	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab							
			1WT CT73203 152" WB	1WT CT73903 170" WB	1WT CT74503 188" WB	1WT CT75003 200" WB	1WT CT76003 212" WB	1WT CT76503 224" WB	1WT CT77603 236" WB	1WT CT78803 248" WB
	E01	Assist steps	S	S	S	S	S	S	S	S
		Daytime Running Lamps	S	S	S	S	S	S	S	S
		Glass, tinted	S	S	S	S	S	S	S	S
		Grille, color-keyed bar and grille surround	S	S	S	S	S	S	S	S
	DB5	Mirror, outside left-hand and right-hand dual cab mounted exterior with convex mirror	S	S	S	S	S	S	S	S
	YCF	Tires, Front, LT255/70R22.5 H BW HWY Continental	S	S	S	S	S	S	S	S
	YCR	Tires Rear, LT255/70R22.5 H BW HWY Continental	S	S	S	S	S	S	S	S
	RTP	Wheels, 22.5 x 8.25 steel, painted white	S	S	S	S	S	S	S	S
	CD7	Windshield wiper, pulse, wet arm	S	S	S	S	S	S	S	S
	RQ2	Vehicle Application Truck	S	S	S	S	S	S	S	S
	VXT	Incomplete vehicle certification	S	S	S	S	S	S	S	S
	K45	Air cleaner, heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.	S	S	S	S	S	S	S	S
	TP7	Battery, dual 750 cold-cranking amps, 12-volt, maintenance free with threaded post	S	S	S	S	S	S	S	S
	JE4	Brakes, dual circuit Air service with 4-wheel anti-lock, brake system is standard with an exhaust brake	S	S	S	S	S	S	S	S
		Park brake, Air, Cable actuated, internal expanding drum type, transmission mounted	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab							
			1WT CT73203 152" WB	1WT CT73903 170" WB	1WT CT74503 188" WB	1WT CT75003 200" WB	1WT CT76003 212" WB	1WT CT76503 224" WB	1WT CT77603 236" WB	1WT CT78803 248" WB
	I1B	Engine , Diesel 5.2L 4 cylinder, 215 hp [160.3 kW] @2500 rpm, 520 lb-ft of torque [705 Nm] @ 1650 rpm (Governed). 16 valve, four cycle, chain-driven dual overhead camshaft valve train, a cast iron cylinder block, and a cast aluminum cylinder head. Turbocharged, inter-cooled, water cooled EGR, direct injection, electronically controlled common rail fuel system and engine cruise control. Oil level check switch and light. Engine warning system with audible warning for low oil pressure, high coolant temperature, and a protection system that will reduce fueling if excessive coolant temperature is detected	S	S	S	S	S	S	S	S
	K40	Exhaust brake	S	S	S	S	S	S	S	S
	N4C	Emissions , 50 state certification	S	S	S	S	S	S	S	S
	NC2	Exhaust , single horizontal outlet	S	S	S	S	S	S	S	S
NL0		Fuel Tank , 50 Gallon, (189L), rectangular steel fuel tank mounted on left hand frame rail. Fuel water separator with indicator light.	S	S	A	A	A	A	--	--
	NNB	Fuel Tank , 100 Gallon, (378L), rectangular steel fuel tank mounted on left hand frame rail. Fuel water separator with indicator light.	--	--	S	S	S	S	S	S
	KG9	Alternator , 140 amps	S	S	S	S	S	S	S	S
	GZI	GVWR , 25,950 lbs. (11,770 kg)	S	S	S	S	S	S	S	S
	EG9	Wheelbase , 152" (386.1 cm)	S	--	--	--	--	--	--	--
	EH8	Wheelbase , 170" (431.8 cm)	--	S	--	--	--	--	--	--
	EK8	Wheelbase , 188" (477.5 cm)	--	--	S	--	--	--	--	--
	EM2	Wheelbase , 200" (508 cm)	--	--	--	S	--	--	--	--
	EL5	Wheelbase , 212" (538.5 cm)	--	--	--	--	S	--	--	--
	EK6	Wheelbase , 224" (569 cm)	--	--	--	--	--	S	--	--
	EG7	Wheelbase , 236" (599.4 cm)	--	--	--	--	--	--	S	--
	ES5	Wheelbase , 248" (629.9 cm)	--	--	--	--	--	--	--	S

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab							
			1WT CT73203 152" WB	1WT CT73903 170" WB	1WT CT74503 188" WB	1WT CT75003 200" WB	1WT CT76003 212" WB	1WT CT76503 224" WB	1WT CT77603 236" WB	1WT CT78803 248" WB
		Frame , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 80,000 psi, section modulus 12.69 cu.in. and RBM 1,015,000 lb-ft/in per rail.	S	S	S	S	S	S	S	S
	FS7	Front axle , 12,000 lbs. (5,450 kg), Dana Spicer E-1204W	S	S	S	S	S	S	S	S
	F26	Front suspension , 12,000 lbs. (5450 kg) tapered leaf semi-elliptical steel alloy. Includes shock absorbers with stabilizer bar	S	S	S	S	S	S	S	S
	HPK	Rear axle , 19,000 lbs. (8618 kg) R050, full-floating single-speed, with oil lubricated rear wheel-bearings, Dana Spicer 19060S	S	S	S	S	S	S	S	S
	GN8	Rear Suspension , 21,000 lbs. (9525 kg), semi-elliptical steel alloy bolted multi-leaf and shock absorbers	S	S	S	S	S	S	S	S
	074	Rear axle , 5.57 ratio	S	S	S	S	S	S	S	S
	MPQ	Transmission Allison 2550RDS 6-speed automatic 2550RDS, with park paw. Includes PTO Gear. Gear and Ratios 3.51, 1.90, 1.44, 1.00, 0.74, 0.64, Rev. 5.09	S	S	S	S	S	S	S	S
	X9K	Warranty , 3-years/unlimited miles (whichever comes first). Covers engine and drive axle.	S	S	S	S	S	S	S	S