

S = Standard Equipment A = Available --(dashes) = Not Available D = ADI Available

■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

* Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Model.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
	AY0	Airbags, Crew Cab: Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front and rear outboard seating positions; Regular Cab: Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front outboard seating positions; Includes airbag deactivation switch for front outboard passenger airbag 1 - Always use seat belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	C99	Airbag deactivation switch, frontal passenger-side 1 - Included and only available with (AY0) airbags.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	C67	Air conditioning, single-zone	S	S	S	S	S	S	S	S
		Assist handle, front passenger and driver on A-pillars	S	S	S	S	S	S	S	S
	IO3	Audio system, 4.2" diagonal color display, AM/FM stereo with USB port and auxiliary jack 1 - Requires (AE7) front 40/20/40 split-bench seat. Not available with (UE1) OnStar or (U2K) SiriusXM Radio.	S ¹	S ¹	S ¹	S ¹	--	--	--	--
	U2J	SiriusXM, delete 1 - Requires Fleet or Government order type and (UE0) OnStar delete.	S	S	S	S	A ¹	A ¹	A ¹	A ¹
	UQ5	Audio system feature, 4-speaker system	S	--	S	--	--	--	--	--
	UQ3	6-speaker audio system 1 - Included and only available with (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment.	A ¹	S	A ¹	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
		Bluetooth for phone , personal cell phone connectivity to vehicle audio system 1 - Included and only available with (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment.	A ¹	A ¹	A ¹	A ¹	S	S	S	S
	K34	Cruise control , steering wheel-mounted	S	S	S	S	S	S	S	S
		Instrumentation , 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure	S	S	S	S	S	S	S	S
	UMN	Speedometer , miles/kilometers	S	S	S	S	S	S	S	S
	UDC	Driver Information Center , 3.5" diagonal monochromatic display, provides warning messages and basic vehicle information	S	S	S	S	--	--	--	--
	AU3	Door locks , power	S	S	S	S	S	S	S	S
	BG9	Floor covering , Graphite-colored rubberized-vinyl	S	S	S	S	S	S	S	S
		Interior trim , Jet Black/Dark Ash 1 - See Color and Trim chart for availability.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
		Mirror , inside rearview manual day/night	S	S	S	S	--	--	--	--
UE0		OnStar , delete 1 - Requires Fleet or Government order type and (U2J) SiriusXM delete or (9D9) inside rearview mirror delete.	S	S	S	S	A ¹	A ¹	A ¹	A ¹
	UVC	Rear Vision Camera , display integrated into Radio 1 - Shipped loose in cab for upfitter installation.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	AE7	Seats , front 40/20/40 split-bench, 3-passenger, driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar.	S	S	S	S	--	--	--	--

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
A52		Seats , front 40/20/40 split-bench, cloth or vinyl 3-passenger. Includes driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Also includes manually adjustable driver lumbar and storage pockets. 1 - Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. Includes (AG1) 10-way power seat.	A ¹	A ¹	A ¹	A ¹	S	S	S	S
	A68	Seat , rear 60/40 folding bench (folds up), 3-passenger, (includes child seat top tether anchor)	--	S	--	S	--	S	--	S
	719	Seat Belt , Black	S	S	S	S	S	S	S	S
	AG1	Seat adjuster , driver 10-way power 1 - Included and only available with (A52) front 40/20/40 split-bench seat.	A ¹	A ¹	A ¹	A ¹	S	S	S	S
	NK5	Steering wheel , urethane	S	S	S	S	--	--	--	--
	N33	Steering column , manual Tilt-Wheel	S	S	S	S	S	S	S	S
	9L7	Upfitter switch kit , provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel	S	S	S	S	S	S	S	S
		Visors , driver and front passenger, vinyl	S	S	S	S	--	--	--	--
		Windows , manual driver and front passenger	S	--	S	--	--	--	--	--
	ZY1	Paint , solid	S	S	S	S	S	S	S	S
	U73	Antenna , fixed mast	S	S	S	S	S	S	S	S
	E01	Assist steps	S	S	S	S	S	S	S	S
	8E8	Bumper , front, Black	S	S	S	S	S	S	S	S
		Capped Fuel Fill	S	S	S	S	S	S	S	S
		Door handles , Black	S	S	S	S	S	S	S	S
	FNP	Front fender extension , painted body color	S	S	S	S	S	S	S	S
	VWX	Grille , base, molded in color, Black	S	S	S	S	S	S	S	S
	P0D	Grille guard screen , insect protection (mounted behind grille)	S	S	S	S	S	S	S	S
	AKP	Glass , solar absorbing, tinted	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
		Daytime Running Lamps , with automatic exterior lamp control	S	S	S	S	S	S	S	S
		Headlamps , halogen projector-beam	S	S	S	S	S	S	S	S
	TR1	Lamps , rear, stop/turn/backup (1-piece assembly) with license plate light	S	S	S	S	S	S	S	S
	U04	Horn , single-note	S	S	S	S	S	S	S	S
	VXT	Incomplete vehicle	S	S	S	S	S	S	S	S
		Lamps , cargo area, cab mounted with switch on center switch bank	S	S	S	S	S	S	S	S
	U01	Lamps , Smoked Amber roof marker	S	S	S	S	S	S	S	S
	DF2	Mirrors , outside high-visibility vertical camper-style, Black with manual folding and extension and lower convex spotter glass	S	S	S	S	--	--	--	--
	9L3	Spare tire delete	S	S	S	S	S	S	S	S
	XDK	Tires , front 225/70R19.5G highway blackwall Goodyear, Max Axle Load: 7,940 lbs. 1 - Requires (YAL) Tires, rear 225/70R19.5G highway blackwall Goodyear, Max Axle Load: 15,000 lbs. or (YMF) Tires, rear 225/70R19.5G traction blackwall Goodyear, Max Axle Load: 15,000 lbs.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	YAL	Tires , rear 225/70R19.5G highway blackwall Goodyear, Max Axle Load: 15,000 lbs.	S	S	S	S	S	S	S	S
	PWQ	Wheels , 19.5" x 6.75", steel, Black painted, 8-holes, hub piloted	S	S	S	S	S	S	S	S
	PD7	Wheel , spare delete	S	S	S	S	S	S	S	S
	KG4	Alternator , 150 amps	S	S	S	S	S	S	S	S
	7Y7	Batteries, heavy-duty dual 1100 cold-cranking amps , includes battery box mounted to left side under cab	S	S	S	S	S	S	S	S
	J48	Brakes , hydraulic, heavy duty Bosch/Meritor/Wabco system with 4-channel (ABS) 1 - Includes (J69) driveline park brake.	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	J69	Brake , parking, driveline park brake system	S	S	S	S	S	S	S	S
	N4E	Emissions , USA 50 State certified	S	S	S	S	S	S	S	S
	N4C	Emissions , 50 state certification	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
	NPR	Exhaust system , right side exit, behind rear wheels 1 - Requires (FQT) 141" wheelbase.	S ¹	--	--	--	S ¹	--	--	--
N12		Exhaust system , rear exit 1 - Not available with (FQT) 141" wheelbase.	A ¹	S	S	S	A ¹	S	S	S
	K40	Exhaust brake	S	S	S	S	S	S	S	S
	L5D	Engine , Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible, 350 hp @ 2700 rpm, 700 lb.-ft. torque @ 1600 rpm	S	S	S	S	S	S	S	S
	FHX	Fuel , diesel B20	S	S	S	S	S	S	S	S
	N2L	Fuel tank , rear only, 40 gallon, mounted between frame side rails and behind rear axle	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
	C7R	<p>GVWR, 16,500 lbs. (7484 kg) 1 - Silverado 4500 HD models with (FQT) 141" wheelbase requires one of the following combinations:</p> <p>(1) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (GL4) 11k rear axle and (GR3) 11k rear suspension. Requires (G68) Rear shock absorbers.</p> <p>(2) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (HD2) 13.5k rear axle and (GR4) 13.5k rear suspension. Requires (G68) Rear shock absorbers.</p> <p>(3) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension. Requires (G68) Rear shock absorbers.</p> <p>(4) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension. Requires (PCJ) Vocational Specific Heavy Suspension Package.</p> <p>(5) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension or (FU7) 15.5k rear suspension. Requires (PCJ) Vocational Specific Heavy Suspension Package.</p> <p>Silverado 4500 HD models without (FQT) 141" wheelbase requires one of the following combinations:</p> <p>(1) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (GL4) 11k rear axle and (GR3) 11k rear suspension and (G68) Rear shock absorbers</p> <p>(2) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (HD2) 13.5k rear axle and (GR4) 13.5k rear suspension and (G68) Rear shock absorbers</p> <p>(3) (FTC) 6.25k front axle and (FTW) 6.25k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension and (G68) Rear shock absorbers</p> <p>(4) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension or (G40) 12K Rear air suspension</p> <p>(5) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension, (FU7) 15.5k rear suspension, (GP1) 13.5K rear air suspension, (GP8) 15.5 rear air suspension, (91B) 13.5k LiquidSpring prep</p>	S ¹	S ²	S ³	S ³	S ¹	S ²	S ³	S ³

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
		single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension 2 - Silverado 4500 HD Crew Cab 2WD models requires one of the following combinations: (1) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension or (G40) 12K Rear air suspension (2) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension, (FU7) 15.5k rear suspension, (GP1) 13.5K rear air suspension, (GP8) 15.5 rear air suspension, (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension 3 - Silverado 4500 HD 4X4 models requires one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension, (FU7) 15.5k rear suspension, (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension								
	066	Rear axle, 4.10 ratio, Max road speed: 79 MPH	S	S	--	--	S	S	--	--
092		Rear axle, 4.30 ratio, Max road speed: 75 MPH	A	A	S	S	A	A	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
	FQT	Wheelbase, 141" (358.1 cm), 60" CA 1 - Requires (F0C) 49" axle to end of frame, (F0D) 63" axle to end of frame, (F0K) 91" axle to end of frame and (NPR) exhaust. Requires (PCJ) Vocational Specific Heavy Suspension Package, when ordering (FTA) 7,000 lbs. Front axle/(FK6) 7,000 lbs. Front suspension or (FTL) 8,000 lbs. Front axle/(FSN) 8,000 lbs. Front suspension and/or (FU7) 15,500 lbs. rear suspension. Not available with rear air suspensions or (91B), (91C), (91D) or (91E) prep for LiquidSpring rear suspension.	S ¹	--	--	--	S ¹	--	--	--
ED9		Wheelbase, 165" (419.1 cm), 84" CA 1 - Requires (F0C) 49" axle to end of frame, (F0D) 63" axle to end of frame, (F0K) 91" axle to end of frame. Requires (PCJ) Vocational Specific Heavy Suspension Package, when ordering (FTA) 7,000 lbs. Front axle/(FK6) 7,000 lbs. Front suspension or (FTL) 8,000 lbs. Front axle/(FSN) 8,000 lbs. Front suspension and/or (FU7) 15,500 lbs. rear suspension.	A ¹	--	S ¹	--	A ¹	--	S ¹	--
	FNV	Wheelbase, 175" (444.5 cm), 60" CA 1 - Requires (F0C) 49" axle to end of frame. Not available with (G40) 12, 000lbs., (GP1) 13,500 lbs. or (GP8) 15,500 lbs. rear air suspension, or (NPK) Exhaust System.	--	S ¹	--	S ¹	--	S ¹	--	S ¹
	F0C	Axle to End of Frame, 49" 1 - Requires wheelbase (ED5) 201", (ED9) 165", (ER2) 189" or (FQT) 141". Not available with (G40), (GP1) or (GP8) rear air suspension. 2 - Requires wheelbase (EM1) 199" or (FNV) 175". Not available with (G40), (GP1) or (GP8) rear air suspension. 3 - Requires wheelbase (ED5) 201", (ED9) 165" or (ER2) 189". Not available with (G40), (GP1) or (GP8) rear air suspension.	S ¹	S ²	S ³	S ²	S ¹	S ²	S ³	S ²
		Steering, power (Bosch S2 8014 Plus)	S	S	S	S	S	S	S	S
	FTC	Front axle, 6,250 lb. (2,835 kg), Dana Spicer D800-N, "I"-beam, non-driving 1 - Requires (FTW) 6,250 lb. front suspension. Includes (G68) rear shock absorbers. Not available with rear air suspensions.	S ¹	--	--	--	S ¹	--	--	--

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
FTA		Front axle , 7,000 lbs, Dana Spicer D800-N, "I"-beam, non-driving 1 - Requires (FK6) 7,000 lb. (3,175 kg) front suspension. Requires (PCJ) Vocational Specific Heavy Suspension Package when ordered with (FQT) 141" Wheelbase or (ED9) 165" Wheelbase. 2 - Requires (FK6) 7,000 lb. (3,175 kg) front suspension.	A ¹	S ²	--	--	A ¹	S ²	--	--
	FTB	Front axle , 7,500 lbs, Dana Spicer 60-256, single-reduction, front driving	--	--	S	S	--	--	S	S
	FTW	Front suspension , 6,250 lbs. (2,835 kg) multi-leaf, includes shock absorbers 1 - Not available with rear air suspensions.	S ¹	--	--	--	S ¹	--	--	--
FK6		Front suspension , 7,000 lbs. (3,175 kg) multi-leaf, includes shock absorbers	A	S	--	--	A	S	--	--
	FTV	Front suspension , 7,500 lbs. (3,402 kg) multi-leaf, includes shock absorbers	--	--	S	S	--	--	S	S
	FTN	Axle lubricant , front, synthetic oil EmGard FE-75W-90	--	--	S	S	--	--	S	S
FN1		Rear axle , 10,000 lb. (4,536 kg) Dana Spicer S14-110, single reduction	A	S	A	A	A	S	A	A
GL4		Rear axle , 11,000 lb. (4,999 kg) Dana Spicer S14-110, single reduction	S	A	S	S	S	A	S	S
		Axle, Open rear axle , non-locking rear	S	S	S	S	S	S	S	S
	GR3	Rear suspension , 11,000 (4,990 kg) multi-leaf, vari-rate 1 - Not available with air suspension.	S ¹	S ¹	S	S	S ¹	S ¹	S	S
	FTO	Axle lubricant , rear, synthetic oil EmGard FE -75W-90	S	S	S	S	S	S	S	S
		Traction control	S	S	S	S	S	S	S	S
		StabiliTrak , Electronic Stability Control System with Traction Control, includes Electronic Trailer Sway Control and Hill Start Assist	S	S	S	S	S	S	S	S
		Neutral-at-Stop , Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop, and remains in neutral until the service brake is released	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description	CC56403	CC56043	CK56403	CK56043	CC56403	CC56043	CK56403	CK56043
			2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab	2WD Reg Cab	2WD Crew Cab	4WD Reg Cab	4WD Crew Cab
			1WT	1WT	1WT	1WT	1LT	1LT	1LT	1LT
	MWA	Highway Service Transmission, Automatic close-ratio 6 SPD with double overdrive, Allison, A1700HS, ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K 1 - Requires (C7Y) 14,001 lbs. GVWR, (C5B) 15,000 lbs. GVWR, (C7P) 16,000 lbs.GVWR, (C7R) 16,500 lbs. GVWR, (GZX) 17,500 lbs. GVWR, (GZJ) 18,000 lbs. GVWR or (GZG) 19,500 lbs. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹	S ¹
	KBK	Transmission shift control calibration, fuel sense Performance	S	S	S	S	S	S	S	S
	JL1	Trailer brake controller, integrated	S	S	S	S	S	S	S	S
	UY7	Trailer provisions, trailering wire harness only, trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.	S	S	S	S	S	S	S	S