



LIST PRICE LIST

January 17, 2022

V202201

Wally's Fire & Safety
(888) 784-2224
wally@wallysfire.com



FIREQUIP





PRIMARY PRICE LIST INDEX

| PAGE | DESCRIPTION |
|------|------------------------|
| 2 | Terms & Conditions |
| 3 | General Warranties (1) |
| 4 | Demo Hose |
| 5 | Coupling Prices |
| 6 | Hose by Application |
| 7 | Hose Cross Reference |
| 8 | Conquest |
| 9 | Gladiator Classic |
| 10 | Gladiator NF |
| 11 | Gladiator FM |
| 12 | Supreme |
| 13 | NP-NDura |
| 14 | DP- Dura Pak |
| 15 | 8D |
| 16 | 8T |
| 17 | DJ800 |
| 18 | Attack lite Poly |
| 19 | Conquest LDH |
| 20 | TD-Triple Duty |
| 21 | DJ600 LDH |
| 22 | TPX |
| 23 | HFX |
| 24 | ATX |
| 25 | UTX |
| 26 | LD |
| 27 | 7F-Forestry |
| 28 | FH-Forestry |
| 29 | Soft Suction |
| 30 | Maxiflex |
| 31 | Fire Engine Booster |
| 32 | Reel Lite |

CUSTOMIZED HOSE STENCILING:

- The standard stenciling of jacketed and rubber covered hose will be per NFPA 1961 Standard on Fire Hose
 - Customized stencils - **No charge for standard alphanumeric custom stencil.**
- "STENCIL KIT" (use as part number) which includes 25 character maximum stencil, and ink marking equipment - **\$18.00 each**

CUSTOMIZED HOSE LENGTHS

- Non standard hose lengths are available by special order - contact customer service for pricing and availability

CUSTOMER SPECIFIED COUPLINGS:

Specific Manufacturers Brands are available by special order only - contact customer service for a price quotation

SPECIAL THREADS:

Threads **OTHER THAN** National Standard (NH or NST), Iron Straight Pipe (NPSH, IPT or SIPT)
or CSA (Canadian Standard Association) add:

- Couplings 1" thru 3" - **\$10.00 per hose (Set)**
- Couplings 3 1/2" thru 6" - **\$20.00 per hose (Set)**

Provided in Sets of One Male/One Female - Same Size & Thread

COUPLING MARKING CHARGES:

*Standard Marking is by Laser Etching - **Hand Stamping is by "Special Order" Only***

Special Marking - Same Description on each Coupling with 10 characters maximum add:

- One End - **\$3.00 each**
- Both Ends - **\$5.00 per set**

Consecutive Numbering - A different number on each coupling or sets of couplings with 10 characters maximum add:

- One End - **\$6.50 each**
- Both Ends - **\$9.50 per set**

ADDITIONAL CHARGES FOR UL/ULC LABEL OR FM APPROVED HOSE (as available):

Note: UL/ULC Approvals are only available in 50' and 100' Lengths

- UL/ULC Underwriters Lab (Canada) **\$20.00 Additional Length**
- FM Factory Mutual **\$10.00 Additional Length**

COUPLING THREAD SIZE OPTION CHART

| | | THREAD SIZE | | | | | | | | | |
|-----------|--------|-------------|--------|----|--------|----|--------|----|--------|----|----|
| | | 1" | 1 1/2" | 2" | 2 1/2" | 3" | 3 1/2" | 4" | 4 1/2" | 5" | 6" |
| HOSE SIZE | 1" | ■ | | | | | | | | | |
| | 1 1/2" | | ■ | | | | | | | | |
| | 1 3/4" | | ■ | | | | | | | | |
| | 2" | | ■ | ■ | | | | | | | |
| | 2 1/2" | | | ■ | ■ | | | | | | |
| | 3" | | | | ■ | ■ | | | | | |
| | 3 1/2" | | | | | ■ | ■ | ■ | | | |
| | 4" | | | | | | | ■ | ■ | | |
| | 5" | | | | | | | | | ■ | |
| | 6" | | | | | | | | | | ■ |



SNAP-TITE HOSE GENERAL WARRANTY POLICY

Under our General Warranty Terms, all double jacket, nitrile rubber and polyurethane fire hose products used in the Municipal fire industry to be free from defects in materials or workmanship over a period of ten (10) years from the original date of shipment.

8T, Dura-Pak (DP) and Forestry products (FH/RL) lines have a one (1) year warranty against defects in materials or workmanship from the date of shipment; all Hard Suction hose (MF,TF) lines have a five (5) year warranty against defects in materials or workmanship from the date of shipment; This warranty shall provide for the repair or replacement of hose and assemblies proven to have failed due to faulty materials or workmanship during normal and reasonable fire ground use, and care of fire hose.

OUR GENERAL WARRANTY IS LIMITED AS FOLLOWS:

All returns must be accompanied by an RMA# (Return Materials Authorization) issued by Snap-tite Hose. RMA form can be found on Snap-tite Hose website at www.snaptitehose.com/rma-form/. Unauthorized returns will be refused. All defective products must be returned freight pre-paid to Snap-tite Hose within thirty (30) days of purchaser's claim. Products or parts must be found to be defective in materials and workmanship upon examination and testing by Snap-tite Hose. If returned goods are found to be defective, inbound freight costs will be refunded.

Total liability is limited to the purchase price of the goods.

Products shall not be considered defective or nonconforming if they substantially fulfill performance requirements and are manufactured in accordance with Snap-tite Hose specifications. This warranty will not extend to goods which have been subject to misuse, improper application, misapplication under conditions not expressly made specifically known to or and approved by Snap-tite Hose in advance of use or which have been repaired or altered by any third party.

For the following selected premium municipal hose products produced by us in our Pennsylvania plants, Snap-tite Hose offers a **Two Year All Hazards Warranty**:

- Ponn Conquest (FC) 1.75" and 2.5" diameter, LDH 4" and 5" diameter
- Ponn Gladiator (FG, FGN, FM) 1.75" and 2.5" diameter (where available)
- Snap-tite Hose (TPX) 1.75", 2.5" diameter, LDH 4" and 5" diameter
- Snap-tite Hose (UTX) LDH 4" and 5" diameter
- Snap-tite Hose (ATX) LDH 4" and 5" diameter
- National Triple Duty (TD) LDH 4" and 5" diameter

Snap-tite Hose will repair or replace, at our option, any accidental damage to these specific products within this two-year warranty period. All hazards damage is limited to accidental occurrences due to fire, cuts, abrasion, or other accidental destruction that occur during an active fire situation.

The following conditions apply:

1. Damaged hose must be returned to the factory freight prepaid for examination upon completion of the Returned Material Authorization (RMA) process and according to the RMA process in effect at the time of the claim.
2. Determination of the applicability of this warranty is at the sole discretion of Snap-tite Hose.
3. Replacement will be like-for-like unless the customer authorizes a change and pays for the price difference; repairs will re-use undamaged couplings from the original hose.

LIFETIME WARRANTY AGAINST DELAMINATION

Snap-tite Hose is committed to providing our customers with safe and reliable products. Our proprietary manufacturing processes allow us to offer a lifetime warranty against delamination for the following product lines:

Ponn Conquest (FC)
Ponn Supreme (FS)
Ponn Gladiator Classic (FG)
Ponn Gladiator Narrow (FGN)
Ponn Gladiator Fire Master (FGM)
National N-Dura (NP)
National Triple Duty (TD)
Snap-tite Hose UTX
Snap-tite Hose TPX
Snap-tite Hose ATX
Snap-tite Hose HFX
Snap-tite Hose LD

DEMO HOSE PROGRAM

Purpose: DEMO HOSE is provided directly to a customer (Distributor or Department) for use at their facility, with prior approval and oversight by the RSM. The DEMO HOSE is issued directly to the customer and the customer is financially responsible for the proper return of the DEMO HOSE

DEMO HOSE Process:

- All Demo Hose requests must be received on a Customer or Distributor purchase order.
- Demo hose requests are entered and invoiced at full value.
- The part number will be the same, adding the suffix "DEMO" at the end of the part number.
- Request for specific hose colors or color stripes on hoses is not permitted. Standard NFPA colors
- Standard thread NH/NPSH (US customers only) on hand lines/ Storz or Standard NH on LDH
- Each length of hose will be stenciled in accordance with NFPA requirements and "DEMO HOSE
- Demo hose will be approved to be out for a total period of 6 weeks.
- Customer Service will notify RSM when demo hose ships.

Hoses out longer than 8 weeks, will be invoiced at full price

NON-STANDARD LENGTH - SHORT / PONY LENGTH POLICY

Municipal Fire Hoses are manufactured in 25, 50 and 100 foot lengths - all other lengths are custom

| Custom Lengths between: | | | Hose Price | Coupling Price | Total Price |
|-------------------------|-----|------|------------|-----------------|------------------------|
| | 1' | 25' | 25' Price | set price below | Sum of Hose & Coupling |
| | 26' | 50' | 50' Price | | |
| | 51' | 100' | 100' Price | | |

Custom orders are non-returnable and will be quoted with lead times based on production schedules

Customer may request remainder of unused hose (uncoupled) to be shipped with order with no additional charge.

COUPLING SET PRICING for Threaded Single/Double Jacket or Rubber Hose

Aluminum Rocker Lug (NH, IPT, or CSA Threads)

| HOSE SIZE | FEMALE/MALE COUPLING SET PRICING | | THREAD SIZE |
|-----------|--|--|----------------|
| | | | |
| 1" | \$26.00 | | 1" |
| 1-1/2" | \$27.00 | | 1-1/2" |
| 1-3/4" | \$34.00 | | 1-1/2" |
| 2" | \$45.00 | | 1 1/2" |
| 2" | \$82.00 | | 2 1/2" |
| 2-1/2" | \$50.00 | | 2-1/2" |
| 3" | \$94.00 | | 2-1/2" |
| 4" | \$157.00 | | 4" |
| 4" | \$197.00 | | 4 1/2" |
| 5" | \$244.00 | | 5" |
| 6" | \$324.00 | | 6" |

Brass Rocker Lug (NH, IPT, or CSA Threads)

| HOSE SIZE | FEMALE/MALE BRASS COUPLING SET PRICING | |
|-----------|--|--|
| | | |
| 1 1/2" | \$63.00 | |
| 2 1/2" | \$171.00 | |

Matching Hose Ends are available as special order:

Male/Male - Same pricing as in Coupling Set Chart(s)

Female/Female - Multiply Coupling Set Price in Chart(s) by 1.32

COUPLING SET PRICING for Storz - Rubber/Jacketed Hose

| HOSE SIZE | COUPLING SET PRICING | | Thread Size |
|-----------|-------------------------|--|----------------|
| | | | |
| 1 1/2" | \$119.00 | | 1 1/2" |
| 1 3/4" | \$127.00 | | 1 1/2" |
| 2" | \$157.00 | | 1 1/2" |
| 2 1/2" | \$200.00 | | 2 1/2" |
| 3" | \$256.00 | | 2 1/2" |
| 3" | \$261.00 | | 3" |
| 4" | \$192.00 | | 4" |
| 5" | \$221.00 | | 5" |
| 6" | \$626.00 | | 6" |
| 8" | \$1,185.00 | | 8" |
| 10" | \$1,800.00 | | 10" |
| 12" | \$2,745.00 | | 12" |

1/4 Turn Coupling Set

| HOSE SIZE | FEMALE/MALE COUPLING SET PRICING | |
|-----------|--|--|
| | | |
| 1" | \$84.00 | |
| 1 1/2" | \$84.00 | |

HOSE BY APPLICATION



ATTACK HOSE

PONN CONQUEST
 PONN GLADIATOR
 PONN GLADIATOR NF
 PONN GLADIATOR FM
 PONN SUPREME
 NATIONAL N-DURA
 NATIONAL DURA-PAK
 NATIONAL TRIPLE-DUTY
 NATIONAL 8D
 NATIONAL 8T
 SNAP-TITE TPX
 SNAP-TITE HFX
 SNAP-TITE ATX
 SNAP-TITE LD
 FIREQUIP DJ800
 FIREQUIP ATTACK LITE POLY



SUPPLY HOSE

SNAP-TITE UTX
 SNAP-TITE TPX
 SNAP-TITE HFX
 SNAP-TITE ATX
 PONN CONQUEST LDH
 NATIONAL TRIPLE-DUTY
 FIREQUIP DJ600



FORESTRY HOSE

NATIONAL 7F
 FIREQUIP FH



BOOSTER HOSE

FIREQUIP FIRE ENGINE HOSE
 FIREQUIP REEL-LITE



HIGH RISE HOSE

PONN CONQUEST
 NATIONAL DURA-PAK
 SNAP-TITE LD



POTABLE WATER

SNAP-TITE UTX
 NATIONAL TRIPLE-DUTY
 PONN CONQUEST LDH
 NATIONAL DURA-PAK
 NATIONAL 8T



LISTED HOSE

PONN CONQUEST (UL,ULC)
 NATIONAL 8D (ULC)
 SNAP-TITE LD (UL,ULC)
 SNAP-TITE HFX (UL,ULC)
 SNAP-TITE TPX (UL,ULC)



C.A.F.S. HOSE

PONN CONQUEST
 PONN SUPREME
 NATIONAL N-DURA
 NATIONAL DURA-PAK
 NATIONAL 7F



SOFT SUCTION HOSE

NATIONAL TRIPLE-DUTY
 NATIONAL 6D
 SNAP-TITE HFX
 SNAP-TITE TPX
 SNAP-TITE UTX



HARD SUCTION HOSE

FIREQUIP MAXIFLEX
 FIREQUIP TANKFLEX

HOSE CROSS REFERENCES

SDH - ATTACK HANDLINES

POLYESTER DOUBLE JACKET LOW FRICTION LOSS – HIGH FLOW

SNAP TITE - *PONN CONQUEST* (FC)
 SNAP TITE – *PONN GLADIATOR* (FG, FN, FM)
 BULLDOG – HI COMBAT & FIRE POWER II
 KEY – COMBAT READY (IMPORTED)
 MERCEDES – AQUAFLOW PLUS & KRAKEN EXO (IMPORTED)
 NIEDNER – ULTRA 2000 (IMPORTED)
 MERCEDES – X STREAM (IMPORTED)
 MERCEDES – X STREAM II (IMPORTED)

HEAVY WEIGHT POLYESTER DOUBLE JACKET THICK RUBBER LINED

SNAP TITE – *PONN SUPREME* (FS)
 KEY- FDNY SPECIAL

POLYESTER DOUBLE JACKET RUBBER LINED TRUE ID

SNAP TITE – *PONN Gladiator FN & FM* (NITRILE RUBBER LINER)
 KEY – TRU ID (EPDM RUBBER LINER)
 NORTH AMERICAN-TRUE DIAMETER 800 (EPDM RUBBER LINER)

NYLON DOUBLE JACKET TPU LINED

SNAP TITE – *NATIONAL -DURA PAK* (DP)
 BULLDOG – PREMIER LITE
 ATI HOSE – JAFLITE (IMPORTED)
 NORTH AMERICAN – DURA FLOW

NITRILE RUBBER/ EXTRUDED THRU-THE-WEAVE

SNAP TITE – *HFX*
 KEY – DURA FLOW (IMPORTED)
 BULLDOG – RED/YELLOW CHIEF
 ATI – JAFRIB (IMPORTED)

NITRILE RUBBER/ 3 PLY DOUBLE VULCANIZED

SNAP TITE – *TPX*
NITRILE RUBBER/ HIGH-RISE EXTRUDED THRU-THE-WEAVE

SNAP TITE – *LD*
 BULLDOG – HIGH POWER

POLYESTER DOUBLE JACKET EPDM RUBBER LINED

NATIONAL 8D
 FIREQUIP – *DJ800* (IMPORTED)
 BULLDOG – ULTIMA
 ATI HOSE – JAFLINE HD (IMPORTED)
 KEY – ECO 10, KEY BIG 10
 NIEDNER – RXL 800 (IMPORTED)
 NORTH AMERICAN – POLY TUFF 800

POLYESTER DOUBLE JACKET TPU LINER

NATIONAL 8T
 FIREQUIP – *ATTACK LITE POLY* (IMPORTED)
 BULLDOG – ULTIMA LITE
 ATI HOSE – JAFLITE (IMPORTED)
 KEY – LITE
 NIEDNER -XL 800/ULTRA 2000 (IMPORTED)
 NORTH AMERICAN – POLY FLOW 800
 MERCEDES – MTFS 800DP/ AQUAFLOW PLUS/
 MERCEDES – MTSS – 800/ CARRY LITE (IMPORTED)

NYLON DOUBLE JACKET EPDM RUBBER LINED

SNAP TITE – *NATIONAL- N DURA* (NP)
 BULLDOG – PREMIER
 ATI – JAFLITE HD (IMPORTED)
 NORTH AMERICA – DURA BUILT
 KEY – MAGNUM

LDH - SUPPLY LINES

POLYESTER DOUBLE JACKET *NON-DELAMINATING" EXTRUDED

SNAP TITE - *PONN CONQUEST* (FC)

NYLON DOUBLE JACKET WOVEN *NON-DELAMINATING"

SNAP TITE- *NATIONAL TRIPLE DUTY* (TD)

POLYESTER DOUBLE JACKET EPDM RUBBER LINED

FIREQUIP – *DJ 600* (IMPORTED)
 KEY-ECO-10
 NORTH AMERICAN- DURA-BUILT 600

POLYESTER DOUBLE JACKET TPU LINED

FIREQUIP – *ATTACK LITE POLY*
 ATI – JAFLINE (4" & 5") (IMPORTED)
 NIEDNER – SUPPLY LINE (IMPORTED)
 MERCEDES – MEGAFLO (IMPORTED)

NYLON DOUBLE JACKET TPU LINED

FIREQUIP -*ATTACK LITE NYLON* (IMPORTED)
 NORTH AMERICAN – TRI FLOW 600
 KEY- MAGNUM LITE

NITRILE RUBBER 3 PLY DOUBLE VULCANIZED

SNAP TITE – *TPX*
 SNAP TITE – *ATX* (300 PSI PRESSURE)

NITRILE RUBBER EXTRUDED THRU-THE-WEAVE

SNAP TITE – *HFX*
 BULLDOG – HI VOL
 NORTH AMERICAN – HI FLOW (IMPORTED)
 KEY – PRO FLOW (IMPORTED)
 MERCEDES – DELUGE (IMPORTED)

POLYURETHANE EXTRUDED THRU-THE-WEAVE

SNAP TITE - *UTX*
 BULLDOG- HI VOL TPU

PONN Conquest Attack (LDH Supply Hose Page 20)



Type "FC" Conquest: Double Jacket Attack Hose

Polyester Double Jacket - Polyurethane lined (Thru-the-Weave) Dura-Cote Treated Hose

LISTED



| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size | Cert Available |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|-------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | | |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 19 | 8.6 | 2-3/16" | UL, ULC |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 21 | 9.5 | 2 5/16" | |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 30 | 13.6 | 2 7/8" | UL, ULC |
| 3" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 35 | 15.9 | 3 9/16" | |

As per NFPA 1961 - Service test pressure is 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FC" - Conquest Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | STRIPE COLOR* | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL | OPTION |
|------|-------------|---|----------------|-------------------------------|-------------------|------------------|----------------|----------------------|---------|
| FC | 17 = 1 3/4" | | 50 = 50' | Y = Yellow | Y = Yellow | 15 = 1 1/2" | N = NH | Blank = | UL= UL |
| | 20 = 2" | | 100 = 100' | R = Red | R = Red | 20 = 2" | I = IPT | Aluminum | Labeled |
| | 25 = 2 1/2" | | | B = Blue | B = Blue | 25 = 2 1/2" | | | |
| | 30 = 3" | | | O = Orange | K = Black | 30 = 3" | | | ULC= UL |
| | | | | G = Green | G = Green | | | | Canada |
| | | | | T = Tan | Blank = No Stripe | | | | Labeled |
| | | | | C = White, Coated | | | | | |

Example: **FC17X50YR15N** = Conquest Hose, 1 3/4" ID by 50' Length, Yellow with Red Stripe, 1 1/2" NH (NST) Aluminum

Note: See page 13 for large diameter Conquest hose pricing.

"FC" - Conquest Attack Hose Pricing

| 25' Lengths, Coated | | | | 50' Lengths, Coated | | | | 100' Lengths, Coated | | | |
|---------------------|--|-------------------------|--------------------------|---------------------|--|-------------------------|--------------------------|----------------------|--|-------------------------|--------------------------|
| I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe |
| 1 3/4" | FC17X25__15N | \$351 | \$327 | 1 3/4" | FC17X50__15N | \$553 | \$504 | 1 3/4" | FC17X100__15N | \$979 | \$881 |
| 2" | FC20X25__15N | \$379 | \$355 | 2" | FC20X50__15N | \$609 | \$560 | 2" | FC20X100__15N | \$1,054 | \$956 |
| 2" | FC20X25__25N | \$429 | \$405 | 2" | FC20X50__25N | \$639 | \$590 | 2" | FC20X100__25N | \$1,084 | \$986 |
| 2 1/2" | FC25X25__25N | \$436 | \$413 | 2 1/2" | FC25X50__25N | \$653 | \$606 | 2 1/2" | FC25X100__25N | \$1,138 | \$1,040 |
| 3" | FC30X25__25N | \$526 | \$502 | 3" | FC30X50__25N | \$798 | \$749 | 3" | FC30X100__25N | \$1,381 | \$1,283 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose
- UL/ULC Underwriters Laboratory (Canada) Listed - see chart above for sizes approved.

CONQUEST STRIPE AND COLOR SELECTION GUIDE

| | | STRIPE COLOR | | | | |
|----------------------|--------|--------------|-----|------|-------|-------|
| | | Yellow | Red | Blue | Black | Green |
| COATING / HOSE COLOR | Yellow | | ■ | ■ | ■ | ■ |
| | Red | | | | ■ | |
| | Blue | | | | ■ | |
| | Orange | | ■ | ■ | ■ | ■ |
| | Purple | | | | ■ | |
| | Green | | | | ■ | |
| | Tan | ■ | ■ | ■ | ■ | ■ |
| | White | ■ | ■ | ■ | ■ | ■ |

PONN Gladiator



Type "FG" Gladiator: Double Jacket Attack Hose

Polyester Double Jacket - Nitrite rubber (Thru-the-Weave) Dura-Cote Treated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size IN |
|--------|--------------|------|------------|------|-------|-------|-------------------------|------|-----------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 3/4" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 22 | 10 | 2-3/16" |
| 2" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 23 | 10.4 | 2-15/16" |
| 2 1/2" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 35 | 15.9 | 2-7/8" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FG"- Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-------------|---|-------------|-------------------|---------------|-------------|-------------------|
| FG | 17 = 1 3/4" | | 50 = 50' | Y = Yellow | 15 = 1 1/2" | N = NH | Blank = Aluminum |
| | 20 = 2" | | 100 = 100' | R = Red | 25 = 2 1/2" | I = IPT | |
| | 25 = 2 1/2" | | | B = Blue | | | |
| | | | | O = Orange | | | |
| | | | | G = Green | | | |
| | | | | T = Tan | | | |
| | | | | C = White, Coated | | | |

Example: **FG17X50Y15N** = Gladiator Hose, 1 3/4" ID by 50' Length, Yellow , 1 1/2" NH Aluminum Couplings

"FG" - Gladiator Attack Hose Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price |
| 1 3/4" | FG17X25__15N | \$332 | 1 3/4" | FG17X50__15N | \$515 | 1 3/4" | FG17X100__15N | \$870 |
| 2" | FG20X25__15N | \$369 | 2" | FG20X50__15N | \$588 | 2" | FG20X100__15N | \$1,005 |
| 2" | FG20X25__25N | \$428 | 2" | FG20X50__25N | \$637 | 2" | FG20X100__25N | \$1,042 |
| 2 1/2" | FG25X25__25N | \$534 | 2 1/2" | FG25X50__25N | \$655 | 2 1/2" | FG25X100__25N | \$1,080 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

PONN Gladiator NF



Type "FGN" Gladiator NF: Double Jacket Attack Hose

Polyester Double Jacket - Nitrile rubber (Thru-the-Weave) Dura-Cote Treated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size IN |
|--------|--------------|------|------------|------|-------|-------|-------------------------|------|--------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 3/4" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 22 | 10 | 2-1/8" |
| 2 1/2" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 35 | 15.9 | 2-7/8" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FGN" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|----------------------------|---|------------------------|--|----------------------------|-------------------|-------------------|
| FGN | 17 = 1 3/4" 25 = 2 1/2" | | 50 = 50' 100 = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White, Coated | 15 = 1 1/2" 25 = 2 1/2" | N = NH I = IPT | Blank = Aluminum |

Example: FGN17X50Y15N = Gladiator NF Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH Aluminum Couplings

"FGN" - Gladiator Attack Hose Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price |
| 1 3/4" | FGN17X25__15N | \$332 | 1 3/4" | FGN17X50__15N | \$515 | 1 3/4" | FGN17X100__15N | \$870 |
| 2 1/2" | FGN25X25__25N | \$438 | 2 1/2" | FGN25X50__25N | \$655 | 2 1/2" | FGN25X100__25N | \$1,080 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

PONN Gladiator FM - Fire Master



Type "FGM" Gladiator FM: Double Jacket Attack Hose

Snap-tite Proprietary Double Jacket - Nitrile rubber lined (Thru-the-Weave) Coated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|-------|-------------------------|-----|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 3/4" | 500 | 3447 | 1000 | 6895 | 1500 | 10342 | 21 | 9.5 | 2-1/8" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FGM"- Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-------------|---|----------------|---------------------------------|------------------|-------------------|----------------------|
| FGM | 17 = 1 3/4" | | 50 = 50' | Natural Proprietary Yarn Red | 15 = 1 1/2" | N = NH I = IPT | Blank = Aluminum |

Example: **FGM17X50R15N** = Gladiator FM Hose, 1 3/4" ID by 50' Length, Red, 1 1/2" NH Aluminum Couplings

"FGM" - Gladiator Attack Hose Pricing

50' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | Coupled Price |
|--------|--|------------------|
| 1 3/4" | FGM17X50__15N | \$487 |

974.776

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose
- Exceeds 15 minutes without failure under UL-19 radiant and conductive testing

PONN Supreme



Type "FS" Supreme: Double Jacket Attack Hose

Polyester Double Jacket - EPDM Rubber Liner with Rubber Backing

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 20 | 9.1 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 21 | 9.5 | 2 1/8" |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 23 | 10.4 | 2 7/16" |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 32 | 14.5 | 3" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 38 | 17.2 | 3 9/16" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FS" - Supreme Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | STRIPE COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|---|---|------------------------|---|--|--|-------------------|----------------------|
| FS | 15 = 1 1/2" 17 = 1 3/4" 20 = 2" 25 = 2 1/2" 30 = 3" | | 50 = 50' 100 = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White, Coated W = White, Uncoated | Y = Yellow R = Red B = Blue K = Black G = Green Blank = No Stripe | 15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3" | N = NH I = IPT | Blank = Aluminum |

Example: FS17X50YR15N = Supreme Hose, 1 3/4" ID by 50' Length, Yellow with Red Stripe, 1 1/2" NH (NST) Aluminum Couplings

"FS" - Supreme Pricing

| 25' Lengths, Coated | | | | 50' Lengths, Coated | | | | 100' Lengths, Coated | | | |
|---------------------|--|-------------------------|--------------------------|---------------------|--|-------------------------|--------------------------|----------------------|--|-------------------------|--------------------------|
| I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add hose and stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe |
| 1 1/2" | FS15X25__15N | \$238 | \$213 | 1 1/2" | FS15X50__15N | \$357 | \$308 | 1 1/2" | FS15X100__15N | \$711 | \$593 |
| 1 3/4" | FS17X25__15N | \$277 | \$252 | 1 3/4" | FS17X50__15N | \$403 | \$354 | 1 3/4" | FS17X100__15N | \$772 | \$664 |
| 2" | FS20X25__15N | \$332 | \$308 | 2" | FS20X50__15N | \$515 | \$466 | 2" | FS20X100__15N | \$962 | \$854 |
| 2" | FS20X25__25N | \$403 | \$378 | 2" | FS20X50__25N | \$585 | \$536 | 2" | FS20X100__25N | \$1,006 | \$898 |
| 2 1/2" | FS25X25__25N | \$386 | \$362 | 2 1/2" | FS25X50__25N | \$553 | \$504 | 2 1/2" | FS25X100__25N | \$1,059 | \$952 |
| 3" | FS30X25__25N | \$574 | \$550 | 3" | FS30X50__25N | \$735 | \$686 | 3" | FS30X100__25N | \$1,383 | \$1,275 |

| 25' Lengths, White/Uncoated | | | | 50' Lengths, White/Uncoated | | | | 100' Lengths, White/Uncoated | | | |
|-----------------------------|---|-------------------------|--------------------------|-----------------------------|---|-------------------------|--------------------------|------------------------------|---|-------------------------|--------------------------|
| I.D. | Part # (add stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe | I.D. | Part # (add stripe color code from matrix above) | Coupled Price w/ Stripe | Coupled Price w/o Stripe |
| 1 1/2" | FS15X25W__15N | \$233 | \$209 | 1 1/2" | FS15X50W__15N | \$347 | \$298 | 1 1/2" | FS15X100W__15N | \$677 | \$569 |
| 1 3/4" | FS17X25W__15N | \$271 | \$246 | 1 3/4" | FS17X50W__15N | \$392 | \$343 | 1 3/4" | FS17X100W__15N | \$718 | \$611 |
| 2" | FS20X25W__15N | \$309 | \$285 | 2" | FS20X50W__15N | \$469 | \$420 | 2" | FS20X100W__15N | \$864 | \$757 |
| 2" | FS20X25W__25N | \$382 | \$357 | 2" | FS20X50W__25N | \$543 | \$494 | 2" | FS20X100W__25N | \$918 | \$811 |
| 2 1/2" | FS25X25W__25N | \$368 | \$343 | 2 1/2" | FS25X50W__25N | \$515 | \$466 | 2 1/2" | FS25X100W__25N | \$947 | \$839 |
| 3" | FS30X25W__25N | \$532 | \$508 | 3" | FS30X50W__25N | \$651 | \$602 | 3" | FS30X100W__25N | \$1,213 | \$1,106 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

SUPREME STRIPE AND COLOR SELECTION GUIDE

| | | STRIPE COLOR | | | | |
|----------------------|--------|--------------|-----|------|-------|-------|
| | | Yellow | Red | Blue | Black | Green |
| COATING / HOSE COLOR | Yellow | | ■ | ■ | ■ | ■ |
| | Red | | | | ■ | |
| | Blue | | | | ■ | |
| | Orange | | ■ | ■ | ■ | ■ |
| | Purple | | | | ■ | |
| | Green | | | | ■ | |
| | Tan | ■ | ■ | ■ | ■ | ■ |
| | White | ■ | ■ | ■ | ■ | ■ |

NATIONAL N-Dura



Type "NP" N-Dura: Double Jacket Attack Hose

Nylon Double Jacket - EPDM Rubber Inner Liner with Rubber Backing

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 19 | 8.6 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 22 | 10 | 2 1/8" |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 23 | 10.4 | 2 1/2" |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 30 | 13.6 | 3" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 40 | 18.1 | 3 9/16" |

As per NFPA 1961 - Service test pressure is 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"NP" - N-Dura Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-------------|---|-------------|-------------------------------|---------------|-------------|-------------------|
| NP | 15 = 1 1/2" | | 50 = 50' | Y = Yellow | 15 = 1 1/2" | N = NH | Blank = Aluminum |
| | 17 = 1 3/4" | | 100 = 100' | R = Red | 20 = 2" | I = IPT | |
| | 20 = 2" | | | B = Blue | 25 = 2 1/2" | | |
| | 25 = 2 1/2" | | | O = Orange | 30 = 3" | | |
| | 30 = 3" | | | G = Green | | | |
| | | | | T = Tan | | | |
| | | | | C = White, Coated | | | |

Example: NP17X50Y15N = N-Dura Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH (NST) Aluminum Couplings

"NP" - N-Dura Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price |
| 1 1/2" | NP15X25__15N | \$207 | 1 1/2" | NP15X50__15N | \$296 | 1 1/2" | NP15X100__15N | \$508 |
| 1 3/4" | NP17X25__15N | \$244 | 1 3/4" | NP17X50__15N | \$338 | 1 3/4" | NP17X100__15N | \$571 |
| 2" | NP20X25__15N | \$279 | 2" | NP20X50__15N | \$408 | 2" | NP20X100__15N | \$662 |
| 2" | NP20X25__25N | \$361 | 2" | NP20X50__25N | \$501 | 2" | NP20X100__25N | \$707 |
| 2 1/2" | NP25X25__25N | \$351 | 2 1/2" | NP25X50__25N | \$483 | 2 1/2" | NP25X100__25N | \$809 |
| 3" | NP30X25__25N | \$530 | 3" | NP30X50__25N | \$646 | 3" | NP30X100__25N | \$1,073 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

NATIONAL Dura-Pak



Type "DP" Dura-Pak: Double Jacket Attack Hose

Nylon Double Jacket - Polyurethane Lined, Dura-Cote Treated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 15 | 6.8 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 17 | 7.7 | 2 1/8" |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 21 | 9.5 | 2 13/32" |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 23 | 10.4 | 2 15/16" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 28 | 12.7 | 3 9/16" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"DP" - Dura-Pak Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|--|---|------------------------|--|--|-------------------|-------------------|
| DP | 15 = 1 1/2" 17 = 1 3/4" 20 = 2 " 25 = 2 1/2" 30 = 3" | | 50 = 50' 100 = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White, Coated | 15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3" | N = NH I = IPT | Blank = Aluminum |

Example: **DP17X50Y15N** = Dura-Pak Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH (NST) Aluminum Couplings

"DP" - Dura-Pak Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price |
| 1 1/2" | DP15X25__15N | \$217 | 1 1/2" | DP15X50__15N | \$315 | 1 1/2" | DP15X100__15N | \$543 |
| 1 3/4" | DP17X25__15N | \$251 | 1 3/4" | DP17X50__15N | \$352 | 1 3/4" | DP17X100__15N | \$620 |
| 2" | DP20X25__15N | \$298 | 2" | DP20X50__15N | \$445 | 2" | DP20X100__15N | \$728 |
| 2" | DP20X25__25N | \$378 | 2" | DP20X50__25N | \$536 | 2" | DP20X100__25N | \$784 |
| 2 1/2" | DP25X25__25N | \$364 | 2 1/2" | DP25X50__25N | \$508 | 2 1/2" | DP25X100__25N | \$842 |
| 3" | DP30X25__25N | \$540 | 3" | DP30X50__25N | \$667 | 3" | DP30X100__25N | \$1,108 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

NATIONAL 8D Hose



Type "8D": Double Jacket Attack Hose

Polyester Double Jacket - Rubber Lined Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size | | Certification Available |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|-----|----------------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | IN | | |
| 1" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 13 | 5.9 | 1 1/2" | | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 15 | 6 | 1 15/16" | | |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 18 | 8.2 | 2 1/8" | ULC | |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 20 | 9.1 | 2 1/2" | | |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 27 | 12.2 | 3" | ULC | |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 33 | 15 | 3 9/16" | | |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"8D" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL | OPTION |
|------|--|---|------------------------|---|---|-------------------|---|-------------------|
| 8D | 10 = 1" 15 = 1 1/2" 17 = 1 3/4" 20 = 2" 25 = 2 1/2" 30 = 3" | | 50 = 50' 100 = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White, Coated W = White, Uncoated | 10 = 1" 15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3" | N = NH I = IPT | Blank = Aluminum BR = Brass Rocker Lug (1 1/2" & 2 1/2" only) | ULC= UL Canada |

Example: 8D17X50Y15N = 8D Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH (NST) Aluminum Couplings

"8D" - Hose Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|-----------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | Uncoupled Price |
| 1" | 8D10X25__10N | \$205 | 1" | 8D10X50__10N | \$296 | 1" | 8D10X100__10N | \$429 | \$378 |
| 1 1/2" | 8D15X25__15N | \$210 | 1 1/2" | 8D15X50__15N | \$301 | 1 1/2" | 8D15X100__15N | \$453 | \$383 |
| | 8D15X25__15NBR | \$248 | | 8D15X50__15NBR | \$359 | | 8D15X100__15NBR | \$510 | |
| 1 3/4" | 8D17X25__15N | \$236 | 1 3/4" | 8D17X50__15N | \$322 | 1 3/4" | 8D17X100__15N | \$532 | \$409 |
| 2" | 8D20X25__15N | \$289 | 2" | 8D20X50__15N | \$429 | 2" | 8D20X100__15N | \$592 | \$510 |
| 2 1/2" | 8D25X25__25N | \$327 | 2 1/2" | 8D25X50__25N | \$434 | 2 1/2" | 8D25X100__25N | \$686 | \$581 |
| | 8D25X25__25NBR | \$554 | | 8D25X50__25NBR | \$606 | | 8D25X100__25NBR | \$869 | |
| 3" | 8D30X25__25N | \$506 | 3" | 8D30X50__25N | \$599 | 3" | 8D30X100__25N | \$889 | \$801 |

| 25' Lengths, White/Uncoated | | | 50' Lengths, White/Uncoated | | | 100' Lengths, White/Uncoated | | | |
|-----------------------------|---------------|---------------|-----------------------------|---------------|---------------|------------------------------|----------------|---------------|-----------------|
| I.D. | Part # | Coupled Price | I.D. | Part # | Coupled Price | I.D. | Part # | Coupled Price | Uncoupled Price |
| 1" | 8D10X25W10N | \$197 | 1" | 8D10X50W10N | \$280 | 1" | 8D10X100W10N | \$381 | \$328 |
| 1 1/2" | 8D15X25W15N | \$198 | 1 1/2" | 8D15X50W15N | \$282 | 1 1/2" | 8D15X100W15N | \$403 | \$339 |
| | 8D15X25W15NBR | \$242 | | 8D15X50W15NBR | \$343 | | 8D15X100W15NBR | \$484 | |
| 1 3/4" | 8D17X25W15N | \$229 | 1 3/4" | 8D17X50W15N | \$308 | 1 3/4" | 8D17X100W15N | \$482 | \$350 |
| 2" | 8D20X25W15N | \$278 | 2" | 8D20X50W15N | \$406 | 2" | 8D20X100W15N | \$543 | \$398 |
| 2 1/2" | 8D25X25W25N | \$315 | 2 1/2" | 8D25X50W25N | \$410 | 2 1/2" | 8D25X100W25N | \$636 | \$475 |
| | 8D25X25W25NBR | \$480 | | 8D25X50W25NBR | \$581 | | 8D25X100W25NBR | \$821 | |
| 3" | 8D30X25W25N | \$488 | 3" | 8D30X50W25N | \$562 | 3" | 8D30X100W25N | \$834 | \$730 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose
- ULC Underwriters Laboratory (Canada) Listed - see chart above for sizes approved.

NATIONAL 8T Hose



Type "8T": Double Jacket Hose

Polyester Double Jacket - Polyurethane Lined Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 14 | 6.4 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 15 | 6.8 | 2 3/16" |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 20 | 9.1 | 2 1/2" |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 28 | 12.7 | 3" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 36 | 16.3 | 3 17/32" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"8T" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-------------|---|-------------|-------------------------------|------------------|----------------|------------------------|
| 8T | 15 = 1 1/2" | | 50 = 50' | Y = Yellow | 15 = 1 1/2" | N = NH | Blank = Aluminum |
| | 17 = 1 3/4" | | 100 = 100' | R = Red | 25 = 2 1/2" | I = IPT | BR = Brass Rocker Lug |
| | 20 = 2" | | | B = Blue | 30 = 3" | | (1 1/2" & 2 1/2" only) |
| | 25 = 2 1/2" | | | O = Orange | | | |
| | 30 = 3" | | | G = Green | | | |
| | | | | T = Tan | | | |
| | | | | C = White, Coated | | | |
| | | | | W = White, Uncoated | | | |

Example: 8T17X50Y15N = 8T Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH (NST) Aluminum Couplings

"8T" - Hose Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | | |
|---------------------|---|---------------|---------------------|---|---------------|----------------------|---|---------------|-----------------|
| I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | I.D. | Part # (add hose color code from matrix above) | Coupled Price | Uncoupled Price |
| 1 1/2" | 8T15X25__15N | \$217 | 1 1/2" | 8T15X50__15N | \$319 | 1 1/2" | 8T15X100__15N | \$462 | \$396 |
| | 8T15X25__15NBR | \$326 | | 8T15X50__15NBR | \$373 | | 8T15X100__15NBR | \$506 | |
| 1 3/4" | 8T17X25__15N | \$245 | 1 3/4" | 8T17X50__15N | \$340 | 1 3/4" | 8T17X100__15N | \$494 | \$420 |
| 2" | 8T20X25__15N | \$291 | 2" | 8T20X50__15N | \$431 | 2" | 8T20X100__15N | \$658 | \$581 |
| 2 1/2" | 8T25X25__25N | \$326 | 2 1/2" | 8T25X50__25N | \$431 | 2 1/2" | 8T25X100__25N | \$707 | \$613 |
| | 8T25X25__25NBR | \$491 | | 8T25X50__25NBR | \$604 | | 8T25X100__25NBR | \$893 | |
| 3" | 8T30X25__25N | \$501 | 3" | 8T30X50__25N | \$588 | 3" | 8T30X100__25N | \$833 | \$737 |

| 25' Lengths, White/Uncoated | | | 50' Lengths, White/Uncoated | | | 100' Lengths, White/Uncoated | | | |
|-----------------------------|---------------|---------------|-----------------------------|---------------|---------------|------------------------------|----------------|---------------|-----------------|
| I.D. | Part # | Coupled Price | I.D. | Part # | Coupled Price | I.D. | Part # | Coupled Price | Uncoupled Price |
| 1 1/2" | 8T15X25W15N | \$209 | 1 1/2" | 8T15X50W15N | \$303 | 1 1/2" | 8T15X100W15N | \$413 | \$338 |
| | 8T15X25W15NBR | \$334 | | 8T15X50W15NBR | \$357 | | 8T15X100W15NBR | \$457 | |
| 1 3/4" | 8T17X25W15N | \$232 | 1 3/4" | 8T17X50W15N | \$315 | 1 3/4" | 8T17X100W15N | \$445 | \$364 |
| 2" | 8T20X25W15N | \$278 | 2" | 8T20X50W15N | \$406 | 2" | 8T20X50W15N | \$609 | \$522 |
| 2 1/2" | 8T25X25W25N | \$313 | 2 1/2" | 8T25X50W25N | \$406 | 2 1/2" | 8T25X100W25N | \$648 | \$555 |
| | 8T25X25W25NBR | \$477 | | 8T25X50W25NBR | \$576 | | 8T25X100W25NBR | \$837 | |
| 3" | 8T30X25W25N | \$482 | 3" | 8T30X50W25N | \$550 | 3" | 8T30X100W25N | \$702 | \$611 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

FIREQUIP DJ800



Type "DJ800": Double Jacket Attack Hose

Polyester Double Jacket - Rubber Lined Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' uncpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|---------------------------|------|--------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | IN |
| 1" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 8.5 | 3.9 | 1 3/8" |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 14.5 | 6.6 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 16.5 | 7.5 | 2 1/16" |
| 2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 21 | 9.5 | 2 7/16" |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 26.5 | 12 | 2 15/16" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 40 | 18.1 | 3 9/16" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"DJ"800 - Part Number Matrix

| TYPE | HOSE I.D. | HOSE LENGTH | COLOR w/ Wear Guard coating | COUPLING SIZE | THREAD TYPE | Coupling Material |
|------|--|--------------------------------|---|---------------------------------------|-------------------|-------------------|
| DJ | 10 = 1" 15 = 1 1/2" 17 = 1 3/4" 20 = 2" 25 = 2 1/2" 30 = 3" | A = 25' B = 50' D = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan W = White, Uncoate | 15 = 1 1/2" 25 = 2 1/2" 30 = 3" | N = NH I = IPT | Blank = Alumi |

Example: DJ17YB = 1.75" 50 ft hose with NST aluminum coupling

"DJ"800 - Hose Pricing

25' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|--------|---|-------------------------|
| 1" | DJ10_A | \$176 |
| 1 1/2" | DJ15_A | \$178 |
| 1 3/4" | DJ17_A | \$202 |
| 2" | DJ20_A | \$301 |
| 2 1/2" | DJ25_A | \$295 |
| 3" | DJ30_A | \$396 |

50' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|--------|---|-------------------------|
| 1" | DJ10_B | \$229 |
| 1 1/2" | DJ15_B | \$242 |
| 1 3/4" | DJ17_B | \$268 |
| 2" | DJ20_B | \$374 |
| 2 1/2" | DJ25_B | \$389 |
| 3" | DJ30_B | \$499 |

100' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price |
|--------|---|--------------------------|
| 1" | DJ10_D | \$420 |
| 1 1/2" | DJ15_D | \$440 |
| 1 3/4" | DJ17_D | \$486 |
| 2" | DJ20_D | \$656 |
| 2 1/2" | DJ25_D | \$708 |
| 3" | DJ30_D | \$880 |

25' White/Uncoated

| I.D. | Part # | 25' Coupled Price |
|--------|--------|-------------------------|
| 1" | DJ10WA | \$158 |
| 1 1/2" | DJ15WA | \$163 |
| 1 3/4" | DJ17WA | \$183 |
| 2" | DJ20WA | \$251 |
| 2 1/2" | DJ25WA | \$271 |
| 3" | DJ30WA | \$367 |

50' White/Uncoated

| I.D. | Part # | 50' Coupled Price |
|--------|--------|-------------------------|
| 1" | DJ10WB | \$196 |
| 1 1/2" | DJ15WB | \$216 |
| 1 3/4" | DJ17WB | \$242 |
| 2" | DJ20WB | \$339 |
| 2 1/2" | DJ25WB | \$348 |
| 3" | DJ30WB | \$455 |

100' White/Uncoated

| I.D. | Part # | 100' Coupled Price |
|--------|--------|--------------------------|
| 1" | DJ10WD | \$367 |
| 1 1/2" | DJ15WD | \$383 |
| 1 3/4" | DJ17WD | \$422 |
| 2" | DJ20WD | \$587 |
| 2 1/2" | DJ25WD | \$620 |
| 3" | DJ30WD | \$790 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

NATIONAL Triple Duty



Type "TD" Triple Duty: Double Jacket, LDH Supply Hose

Nylon Double Jacket, Polyurethane Lined (Thru-the-Weave) Dura-Cote Treated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | IN |
| 4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 47 | 21.3 | 4 17/32" |
| 5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 65 | 29.5 | 5 15/32" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"TD"- Triple Duty Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|--------------------|---|------------------------------------|--|--------------------|--------------------------------|-------------------|
| TD | 40 = 4" 50 = 5" | | 25 = 25' 50 = 50' 100 = 100' | Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White, Coated P = Purple | 40 = 4" 50 = 5" | N = NH I = IPT S = Storz | Blank = Aluminum |

Example: **TD40X50Y40S** = Triple Duty Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Couplings

"TD"- Triple Duty Pricing

| 25' Lengths, Coated | | | 50' Lengths, Coated | | | 100' Lengths, Coated | | | |
|---------------------|---|-------------------------|---------------------|--|-------------------------|----------------------|--|--------------------------|-----------------------------|
| I.D. | Part # (add hose color code matrix above) | 25' Coupled Price | I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price | I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Un-coupled Price |
| 4" NST | TD40X25__40N | \$618 | 4" NST | TD40X50__40N | \$937 | 4" NST | TD40X100__40N | \$1,579 | \$1,288 |
| 4" Storz | TD40X25__40S | \$774 | 4" Storz | TD40X50__40S | \$1,096 | 4" Storz | TD40X100__40S | \$1,726 | |
| 5" NST | TD50X25__50N | \$884 | 5" NST | TD50X50__50N | \$1,325 | 5" NST | TD50X100__50N | \$2,208 | \$1,768 |
| 5" Storz | TD50X25__50S | \$916 | 5" Storz | TD50X50__50S | \$1,357 | 5" Storz | TD50X100__50S | \$2,241 | |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

FIREQUIP ATTACK LITE POLY



Type "AP800": Double Jacket Attack Hose

Polyester Double Jacket - TPU Lined Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' uncpd) | | Bowl Size IN |
|--------|--------------|------|------------|------|-------|------|---------------------------|------|-----------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 13 | 5.9 | 1 15/16" |
| 1 3/4" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 14 | 6.4 | 2 1/8 " |
| 2 1/2" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 24 | 10.9 | 3" |
| 3" | 400 | 2758 | 800 | 5516 | 1200 | 8274 | 29 | 13.2 | 3 1/2" |
| 4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 42 | 19 | 4" |
| 5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 62 | 28.1 | 4 1/2" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"AP/AR/AS" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Wear Guard coating | COUPLING SIZE | THREAD TYPE | Coupling Material |
|------|-------------|---|-------------|--------------------------------|---------------|-------------|-------------------|
| AP | 15 = 1 1/2" | | A = 25' | Y = Yellow | 10 = 1" | N = NH | Blank = Aluminum |
| AR | 17 = 1 3/4" | | B = 50' | R = Red | 15 = 1 1/2" | I = IPT | |
| AS | 25 = 2 1/2" | | D = 100' | B = Blue | 20 = 2" | S = Storz | |
| | 30 = 3" | | | O = Orange | 25 = 2 1/2" | | |
| | 40 = 4" | | | G = Green | 30 = 3" | | |
| | 50 = 5" | | | T = Tan | 40 = 4" | | |
| | | | | W = WhiteUncoated | 50 = 5" | | |

Example: AP17YB = 1.75" 50 ft hose with NST aluminum coupling

"AP" - Hose Pricing

25' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|--------|---|-------------------|
| 1 1/2" | AP15_A | \$238 |
| 1 3/4" | AP17_A | \$277 |
| 2 1/2" | AP25_A | \$370 |
| 3" | AP30_A | \$431 |

50' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|--------|---|-------------------|
| 1 1/2" | AP15_B | \$356 |
| 1 3/4" | AP17_B | \$449 |
| 2 1/2" | AP25_B | \$515 |
| 3" | AP30_B | \$700 |

100' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price |
|--------|---|--------------------|
| 1 1/2" | AP15_D | \$647 |
| 1 3/4" | AP17_D | \$739 |
| 2 1/2" | AP25_D | \$858 |
| 3" | AP30_D | \$1,214 |

LARGE DIAMETER - AR (Threaded RLFxRLM) & AS (Storz)

| | | |
|----|--------|---------|
| 4" | AR40_A | \$667 |
| | AS40_A | \$818 |
| 5" | AR50_A | \$876 |
| | AS50_A | \$1,003 |

| | | |
|----|--------|---------|
| 4" | AR40_B | \$862 |
| | AS40_B | \$922 |
| 5" | AR50_B | \$1,133 |
| | AS50_B | \$1,267 |

| | | |
|----|--------|---------|
| 4" | AR40_D | \$1,386 |
| | AS40_D | \$1,421 |
| 5" | AR50_D | \$1,804 |
| | AS50_D | \$1,848 |

25' Lengths, White/Uncoated

| I.D. | Part # | 25' Coupled Price |
|--------|--------|-------------------|
| 1 1/2" | AP15WA | \$209 |
| 1 3/4" | AP17WA | \$251 |
| 2 1/2" | AP25WA | \$317 |
| 3" | AP30WA | \$405 |

50' Lengths, White/Uncoated

| I.D. | Part # | 50' Coupled Price |
|--------|--------|-------------------|
| 1 1/2" | AP15WB | \$317 |
| 1 3/4" | AP17WB | \$396 |
| 2 1/2" | AP25WB | \$462 |
| 3" | AP30WB | \$594 |

100' Lengths, White/Uncoated

| I.D. | Part # | 100' Coupled Price |
|--------|--------|--------------------|
| 1 1/2" | AP15WD | \$594 |
| 1 3/4" | AP17WD | \$686 |
| 2 1/2" | AP25WD | \$726 |
| 3" | AP30WD | \$977 |

LARGE DIAMETER - AR (Threaded RLFxRLM) & AS (Storz) uncoated (White)

| | | |
|----|--------|-------|
| 4" | AR40WA | \$640 |
| | AS40WA | \$766 |
| 5" | AR50WA | \$812 |
| | AS50WA | \$950 |

| | | |
|----|--------|---------|
| 4" | AR40WB | \$827 |
| | AS40WB | \$882 |
| 5" | AR50WB | \$1,076 |
| | AS50WB | \$1,188 |

| | | |
|----|--------|---------|
| 4" | AR40WD | \$1,313 |
| | AS40WD | \$1,344 |
| 5" | AR50WD | \$1,720 |
| | AS50WD | \$1,756 |

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

PONN Conquest LDH (Attack Hose Page 8)



Type "FC" Conquest: Double Jacket LDH Supply Hose

Polyester Double Jacket - Polyurethane Lined (Thru-the-Weave) Dura-Cote Treated Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size IN |
|------|--------------|------|------------|------|-------|------|-------------------------|------|--------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 50 | 22.7 | 4 17/32" |
| 5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 64.5 | 29.3 | 5 5/16" |
| 6" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 86 | 39.1 | 6 3/4" |

As per NFPA 1961 - Service test pressure is 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"FC" - Conquest Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR w/ Dura-Cote coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-----------|---|-------------|-------------------------------|---------------|-------------|-------------------|
| FC | 40 = 4" | | 25 = 25' | Y = Yellow | 40 = 4" | S = Storz | Blank = Aluminum |
| | 50 = 5" | | 50 = 50' | R = Red | 50 = 5" | | |
| | 60 = 6" | | 100 = 100' | B = Blue | 60 = 6" | | |
| | | | | O = Orange | | | |
| | | | | G = Green | | | |
| | | | | T = Tan | | | |
| | | | | C = White, Coated | | | |
| | | | | P = Purple | | | |

Example: **FC40X50Y40S** = Conquest Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Couplings

Note: See page 9 for smaller diameter Conquest hose pricing.

"FC" - Conquest LDH Supply Hose Pricing

25' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|----------|---|-------------------|
| 4" Storz | FC40X25_40S | \$732 |
| 5" Storz | FC50X25_50S | \$807 |
| 6" Storz | FC60X25_60S | \$1,541 |

50' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|----------|---|-------------------|
| 4" Storz | FC40X50_40S | \$1,031 |
| 5" Storz | FC50X50_50S | \$1,164 |
| 6" Storz | FC60X50_60S | \$2,008 |

100' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Uncoupled Price |
|----------|---|--------------------|----------------------|
| 4" Storz | FC40X100_40S | \$1,632 | \$1,201 |
| 5" Storz | FC50X100_50S | \$1,880 | \$1,430 |
| 6" Storz | FC60X100_60S | \$2,945 | \$1,873 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

FIREQUIP DJ600 LDH



Type "DJ600": Double Jacket, EPDM liner LDH Supply Hose

Polyester Double Jacket, EPDM Lined Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' uncpd) | | Bowl Size |
|------|--------------|------|------------|------|-------|------|---------------------------|------|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 41 | 18.6 | 4 3/8" |
| 5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 65 | 29.5 | 5 3/8" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"DS/DJ" - Part Number Matrix

| TYPE | HOSE I.D. | HOSE LENGTH | COLOR w/ Wear Guard coating | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------------|-----------|-------------|--------------------------------|---------------|-------------|-------------------|
| DS - Storz | A = 25' | 25' | Y = Yellow | 40 = 4" | S = Storz | Blank = Aluminum |
| DJ - NST | B = 50' | 50' | R = Red | 50 = 5" | N = NST | |
| | D = 100' | 100' | O = Orange | | | |
| | | | T = Tan | | | |
| | | | W = White, Uncoated | | | |

Example: DS40YD = DJ600 4" Yellow 100 ft w/ 4" Storz Couplings

"DJ 600"- Pricing

25' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|----------|---|-------------------|
| 4" NST | DJ40_A | \$627 |
| 4" Storz | DS40_A | \$739 |
| 5" NST | DJ40_A | \$805 |
| 5" Storz | DS50_A | \$911 |

50' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|----------|---|-------------------|
| 4" NST | DJ40_B | \$818 |
| 4" Storz | DS40_B | \$911 |
| 5" NST | DJ50_B | \$1,056 |
| 5" Storz | DS50_B | \$1,082 |

100' Lengths, Coated

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price |
|----------|---|--------------------|
| 4" NST | DJ40_D | \$1,392 |
| 4" Storz | DS40_D | \$1,453 |
| 5" NST | DJ50_D | \$2,007 |
| 5" Storz | DS50_D | \$1,809 |

25' Lengths, White/Uncoated

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|----------|---|-------------------|
| 4" NST | DJ40WA | \$603 |
| 4" Storz | DS40WA | \$686 |
| 5" NST | DJ50WA | \$766 |
| 5" Storz | DS50WA | \$858 |

50' Lengths, White/Uncoated

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|----------|---|-------------------|
| 4" NST | DJ40WB | \$779 |
| 4" Storz | DS40WB | \$858 |
| 5" NST | DJ50WB | \$1,003 |
| 5" Storz | DS50WB | \$1,030 |

100' Lengths, White/Uncoated

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price |
|----------|---|--------------------|
| 4" NST | DJ40WD | \$1,332 |
| 4" Storz | DS40WD | \$1,394 |
| 5" NST | DJ50WD | \$1,948 |
| 5" Storz | DS50WD | \$1,750 |

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

Snap-Tite TPX Hose



Type "TPX": Nitrile Rubber Hose

Three-Ply, Double Vulcanized, Heavy Duty - Nitrile Rubber Cover/Liner, Polyester fabric reinforcement



| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size | Certification Available |
|--------|--------------|------|------------|------|-------|------|-------------------------|-------|-----------|----------------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | | |
| 1 3/4" | 400 | 2757 | 800 | 5516 | 1200 | 8274 | 19 | 8.6 | 2 1/16" | |
| 2" | 400 | 2757 | 800 | 5516 | 1200 | 8274 | 24 | 10.9 | 2 5/16" | |
| 2 1/2" | 330 | 2275 | 660 | 4551 | 1000 | 6895 | 33 | 15 | 2 13/16" | |
| 3" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 37 | 16.8 | 3 3/8" | |
| 4" | 250 | 1724 | 500 | 3447 | 750 | 5171 | 50 | 22.7 | 4 5/16" | UL, ULC |
| 5" | 225 | 1551 | 450 | 3103 | 675 | 4654 | 66 | 29.9 | 5 5/16" | UL, ULC |
| 6" | 200 | 1379 | 400 | 2758 | 600 | 4137 | 72 | 32.7* | 6 5/16" | |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"TPX" - Part Number Matrix

| TYPE | HOSE I.D. | X | LENGTH | COLOR | COUPLING SIZE | TYPE | COUPLING MATERIAL | OPTION |
|------|-------------|---|------------|------------|---------------|-----------|-----------------------|----------|
| TPX | 17 = 1 3/4" | | 25 = 25' | Y = Yellow | 15 = 1 1/2" | N = NH | Blank = Aluminum | UL = UL |
| | 20 = 2" | | 50 = 50' | R = Red | 20 = 2" | I = IPT | BR = Brass Rocker Lug | Labeled |
| | 25 = 2 1/2" | | 100 = 100' | O = Orange | 25 = 2 1/2" | S = Storz | BP = Brass Pin Lug | ULC = UL |
| | 30 = 3" | | | | 30 = 3" | | (1 1/2" only) | Canada |
| | 40 = 4" | | | | 35 = 3 1/2" | | | Labeled |
| | 50 = 5" | | | | 40 = 4" | | | |
| | 60 = 6" | | | | 50 = 5" | | | |
| | | | | | 60 = 6" | | | |

Example: TPX40X50Y40S = TPX Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Couplings

NOTE: Brass Couplings are Limited to a Maximum Service Test Pressure of 300 psi (2070 kPa)

3" Storz Couplings are Limited to a Maximum Service Test Pressure of 250 psi (1725 kPa)

"TPX" - Hose Pricing

| 25' Lengths | | |
|-------------|---|----------------------|
| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
| 4" NST | TPX40X25_40N | \$630 |
| 4" Storz | TPX40X25_40S | \$788 |
| 5" NST | TPX50X25_50N | \$784 |
| 5" Storz | TPX50X25_50S | \$816 |
| 6" Storz | TPX60X25_60S | \$1,593 |

| 50' Lengths | | |
|-------------|---|----------------------|
| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
| 1.75" | TPX17X50_15N | \$487 |
| 2" | TPX20X50_15N | \$527 |
| 2 1/2" | TPX25X50_25N | \$609 |
| | TPX25X50_25NBR | \$795 |
| 3" | TPX30X50_25N | \$697 |
| 4" NST | TPX40X50_40N | \$965 |
| 4" Storz | TPX40X50_40S | \$1,124 |
| 5" NST | TPX50X50_50N | \$1,124 |
| 5" Storz | TPX50X50_50S | \$1,157 |
| 6" Storz | TPX60X25_60S | \$2,068 |

| 100' Lengths | | | |
|--------------|---|-----------------------|-------------------------|
| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Uncoupled Price |
| 1.75" | TPX17X100_15N | \$930 | \$876 |
| 2" | TPX20X100_15N | \$1,000 | \$950 |
| 2 1/2" | TPX25X100_25N | \$1,131 | \$1,043 |
| | TPX25X100_25NBR | \$1,318 | |
| 3" | TPX30X100_25N | \$1,308 | \$1,219 |
| 4" NST | TPX40X100_40N | \$1,635 | \$1,342 |
| 4" Storz | TPX40X100_40S | \$1,796 | |
| 5" NST | TPX50X100_50N | \$1,810 | \$1,368 |
| 5" Storz | TPX50X100_50S | \$1,842 | |
| 6" Storz | TPX60X25_60S | \$3,029 | \$1,901 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Brass Pin Lug (BP) pricing is the same as the Brass Rocker Lug (BR option) shown in chart. Replace the "BR" with "BP" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose
- UL/ULC Underwriters Laboratory (Canada) Listed - see chart above for sizes approved.

Snap-Tite HFX Hose



Type "HFX": Nitrile Rubber Hose

Extruded Interlocking Matrix - Thru-the-Weave - Nitrile Rubber Cover/Liner, Polyester/Nylon fabric reinforcement

LISTED



| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size | Certification Available |
|--------|--------------|------|------------|------|-------|------|-------------------------|------|-----------|----------------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | | |
| 1" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 7 | 3.2 | 1 3/16" | |
| 1 1/2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 16 | 7.3 | 1 13/16" | UL, ULC |
| 1 3/4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 19 | 8.6 | 2 1/16" | UL, ULC |
| 2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 21 | 9.5 | 2 5/16" | UL, ULC |
| 2 1/2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 28 | 12.7 | 2 13/16" | UL, ULC |
| 3" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 34 | 15.4 | 3 3/8" | |
| 4" | 230 | 1586 | 460 | 3172 | 700 | 4826 | 48 | 21.8 | 4 5/16" | UL, ULC |
| 5" | 225 | 1551 | 450 | 3103 | 675 | 4654 | 64 | 29 | 5 5/16" | UL, ULC |
| 6" | 225 | 1551 | 450 | 3103 | 675 | 4654 | 69 | 31.3 | 6 5/16" | |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"HFX" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL | OPTION |
|------|-------------|---|-------------|------------|---------------|-------------|--------------------|----------------------|
| HFX | 10 = 1" | | 25 = 25' | Y = Yellow | 10 = 1" | N = NH | Blank = Aluminum | UL = UL Labeled |
| | 15 = 1 1/2" | | 50 = 50' | R = Red | 15 = 1 1/2" | I = IPT | BR = Brass Rocker | UC = ULC (UL Canada) |
| | 17 = 1 3/4" | | 100 = 100' | | 20 = 2" | S = Storz | BP = Brass Pin Lug | Labeled |
| | 20 = 2" | | | | 25 = 2 1/2" | | (1 1/2" only) | |
| | 25 = 2 1/2" | | | | 30 = 3" | | | |
| | 30 = 3" | | | | 35 = 3 1/2" | | | |
| | 40 = 4" | | | | 40 = 4" | | | |
| | 50 = 5" | | | | 45 = 4 1/2" | | | |
| | 60 = 6" | | | | 50 = 5" | | | |
| | | | | | 60 = 6" | | | |

Example: HFX40X50Y40S = HFX Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Couplings

NOTE: Brass Couplings are Limited to a Maximum Service Test Pressure of 300 psi (2070 kPa)

3" Storz Couplings are Limited to a Maximum Service Test Pressure of 250 psi (1725 kPa)

"HFX" - Hose Pricing

25' Lengths

| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
|----------|---|-------------------|
| | | |
| | | |
| | | |
| | | |
| | | |
| 4" NST | HFX40X25__40N | \$525 |
| 4" Storz | HFX40X25__40S | \$674 |
| 5" NST | HFX50X25__50N | \$704 |
| 5" Storz | HFX50X25__50S | \$728 |
| 6" Storz | HFX60X25__60S | \$1,367 |

50' Lengths

| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
|----------|---|-------------------|
| 1" | HFX10X50__10N | \$266 |
| 1 1/2" | HFX15X50__15N | \$315 |
| | HFX15X50__15NBR | \$378 |
| 1 3/4" | HFX17X50__15N | \$373 |
| | HFX17X50__15NBR | \$436 |
| 2" | HFX20X50__15N | \$392 |
| 2 1/2" | HFX25X50__25N | \$434 |
| | HFX25X50__25NBR | \$618 |
| 3" | HFX30X50__25N | \$506 |
| 4" NST | HFX40X50__40N | \$753 |
| 4" Storz | HFX40X50__40S | \$914 |
| 5" NST | HFX50X50__50N | \$970 |
| 5" Storz | HFX50X50__50S | \$986 |
| 6" Storz | HFX60X50__60S | \$1,866 |

100' Lengths

| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Un-coupled Price |
|----------|---|--------------------|-----------------------|
| 1" | HFX10X100__10N | \$483 | \$436 |
| 1 1/2" | HFX15X100__15N | \$578 | \$528 |
| | HFX15X100__15NBR | \$641 | |
| 1 3/4" | HFX17X100__15N | \$695 | \$644 |
| | HFX17X100__15NBR | \$758 | |
| 2" | HFX20X100__15N | \$709 | \$660 |
| 2 1/2" | HFX25X100__25N | \$774 | \$688 |
| | HFX25X100__25NBR | \$961 | |
| 3" | HFX30X100__25N | \$886 | \$770 |
| 4" NST | HFX40X100__40N | \$1,213 | |
| 4" Storz | HFX40X100__40S | \$1,367 | \$920 |
| 5" NST | HFX50X100__50N | \$1,497 | |
| 5" Storz | HFX50X100__50S | \$1,437 | \$1,056 |
| 6" Storz | HFX60X100__60S | \$2,605 | \$1,478 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Brass Pin Lug (BP) pricing is the same as the Brass Rocker Lug (BR option) shown in chart. Replace the "BR" with "BP" to order.

Hose Approvals, Certifications, and/or Standards

- UL/ULC: Underwriters Laboratory (Canada) Listed - see chart above for sizes approved.

- Meets NFPA 1961 Standard on Fire Hose

Snap-Tite ATX Hose



Type "ATX": High Pressure, Large Diameter Nitrile Rubber Hose

Large Diameter Attack Hose - Three-Ply, Double Vulcanized, High Pressure - Nitrile Rubber Cover/Liner, Polyester fabric reinforcement

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size IN |
|------|--------------|------|------------|------|-------|------|-------------------------|------|--------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 60 | 27.2 | 4 7/16" |
| 5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 66.5 | 30.2 | 5 5/16" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"ATX"- Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLIN G | THREAD TYPE | COUPLING MATERIAL |
|------|--------------------|---|------------------------------------|-------------------------------------|--------------------|--------------------------------|-------------------|
| ATX | 40 = 4" 50 = 5" | | 25 = 25' 50 = 50' 100 = 100' | Y = Yellow R = Red O = Orange | 40 = 4" 50 = 5" | N = NH I = IPT S = Storz | Blank = Aluminum |

Example: ATX40X50YM40S = ATX Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Couplings

"ATX" - Hose Pricing

| 25' Lengths | | |
|-------------|--|-------------------------|
| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
| 4" NST | ATX40X25__M40N | \$620 |
| 4" Storz | ATX40X25__M40S | \$779 |
| 5" NST | ATX50X25__M50N | \$847 |
| 5" Storz | ATX50X25__M50S | \$879 |

| 50' Lengths | | |
|-------------|--|-------------------------|
| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
| 4" NST | ATX40X50__M40N | \$944 |
| 4" Storz | ATX40X50__M40S | \$1,105 |
| 5" NST | ATX50X50__M50N | \$1,252 |
| 5" Storz | ATX50X50__M50S | \$1,283 |

| 100' Lengths | | | |
|--------------|--|--------------------------|----------------------------|
| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Uncoupled Price |
| 4" NST | ATX40X100__M40N | \$1,595 | \$1,300 |
| 4" Storz | ATX40X100__M40S | \$1,754 | |
| 5" NST | ATX50X100__M50N | \$2,061 | \$1,622 |
| 5" Storz | ATX50X100__M50S | \$2,094 | |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

SNAP-TITE UTX



Type "UTX" : Large Diameter Supply Hose

Polyurethane Thru-the-Weave, Polyester Fabric Reinforcement

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|------|--------------|------|------------|------|-------|------|-------------------------|------|--------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 4" | 200 | 1379 | 400 | 2758 | 600 | 4137 | 40 | 18.1 | 4-5/16" |
| 5" | 200 | 1379 | 400 | 2758 | 600 | 4137 | 52 | 23.6 | 5-5/16" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"UTX"- Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL |
|------|-----------|---------|-------------|------------------|------------------|----------------|-------------------|
| UTX | 40 = 4" | 50 = 5" | 25 = 25' | G = Hi-Viz Green | 40 = 4" | N = NH | Blank = Aluminum |
| | | | 50 = 50' | O = Blaze Orange | 50 = 5" | I = IPT | |
| | | | 100 = 100' | Y = Yellow | | S = Storz | |
| | | | | R = Red | | | |

Example: UTX50X100G50S = Hose, 5" ID by 100' Length, Hi-Viz Green, 5" Storz Aluminum Couplings

"UTX"- Pricing

| 25' Lengths | | |
|-------------|---|-------------------|
| I.D. | Part # (add hose color code from matrix above) | 25' Coupled Price |
| 4" NST | UTX40X25__40N | \$515 |
| 4" Storz | UTX40X25__40S | \$667 |
| 5" NST | UTX50X25__50N | \$721 |
| 5" Storz | UTX50X25__50S | \$751 |

| 50' Lengths | | |
|-------------|---|-------------------|
| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
| 4" NST | UTX40X50__40N | \$749 |
| 4" Storz | UTX40X50__40S | \$900 |
| 5" NST | UTX50X50__50N | \$1,024 |
| 5" Storz | UTX50X50__50S | \$1,054 |

| 100' Lengths | | | |
|--------------|---|--------------------|----------------------|
| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Uncoupled Price |
| 4" NST | UTX40X100__40N | \$1,158 | \$937 |
| 4" Storz | UTX40X100__40S | \$1,295 | |
| 5" NST | UTX50X100__50N | \$1,543 | \$1,206 |
| 5" Storz | UTX50X100__50S | \$1,571 | |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose

Snap-Tite LD Hose



Type "LD": Nitrile Rubber Covered Thru-the-Weave Hose

Extruded Interlocking Matrix - Thru-the-Weave - Nitrile Rubber Cover/Liner, Nylon fabric reinforcement

LISTED



| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size IN | Certification Available |
|--------|--------------|------|------------|------|-------|------|-------------------------|-----|-----------------|----------------------------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | | |
| 1" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 7 | 3.2 | 1 3/16" | |
| 1 1/2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 10 | 4.5 | 1 13/16" | |
| 1 3/4" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 13 | 5.9 | 2 1/16" | |
| 2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 15 | 6.8 | 2 3/16" | |
| 2 1/2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 20 | 9.1 | 2 13/16" | UL, ULC |

The service test pressure is 10% greater than the "normal highest operating pressure" at which the hose is designed to be used.

"LD" - Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR | COUPLING SIZE | THREAD TYPE | COUPLING MATERIAL | OPTION |
|------|---|---|---|-----------------------------------|--|--|--|---|
| LD | 10 = 1" 15 = 1 1/2" 17 = 1 3/4" 20 = 2" 25 = 2 1/2" | | 50 = 50' 100 = 100' 75 = 75' (1 3/4" only) | Y = Yellow R = Red B = Blue | 10 = 1" 15 = 1 1/2" 20 = 2" 25 = 2 1/2" | N = NH I = IPT BW = British Instantaneous | Blank = Aluminum BR = Brass Rocker Lug BP = Brass Pin Lug (1 1/2") G = Gunmetal (BW Thread Only) | UL = UL Labeled ULC = UL Canada Labeled |

Example: LD17X50R15N = LD Hose, 1 3/4" ID by 50' Length, Red, 1 1/2" Aluminum Rocker Lug - NH/NST Couplings

"LD" - Hose Pricing

| 50' Lengths | | |
|-------------|---|-------------------------|
| I.D. | Part # (add hose color code from matrix above) | 50' Coupled Price |
| 1" | LD10X50__10N | \$278 |
| 1 1/2" | LD15X50__15N | \$289 |
| | LD15X50__15NBR | \$352 |
| 1 3/4" | LD17X50__15N | \$301 |
| | LD17X50__15NBR | \$364 |
| 2" | LD20X50__15N | \$324 |
| | LD20X50__25N | \$364 |
| 2 1/2" | LD25X50__25N | \$399 |
| | LD25X50__25NBR | \$585 |

| 100' Lengths | | | |
|--------------|---|--------------------------|----------------------------|
| I.D. | Part # (add hose color code from matrix above) | 100' Coupled Price | 100' Uncoupled Price |
| 1" | LD10X100__10N | \$494 | \$460 |
| 1 1/2" | LD15X100__15N | \$515 | \$477 |
| | LD15X100__15NBR | \$576 | |
| 1 3/4" | LD17X100__15N | \$539 | \$502 |
| | LD17X100__15NBR | \$599 | |
| 2" | LD20X100__15N | \$585 | \$550 |
| | LD20X100__25N | \$623 | |
| 2 1/2" | LD25X100__25N | \$693 | \$620 |
| | LD25X100__25NBR | \$875 | |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Brass Pin Lug (BP) pricing is the same as the Brass Rocker Lug (BR option) shown in chart. Replace the "BR" with "BP" to order.

| 75' Hi-Rise Length | | |
|--------------------|---|-------------------------|
| I.D. | Part # (add hose color code from matrix above) | 75' Coupled Price |
| 2" | LD20X75__25N | \$554 |

Hose Approvals, Certifications, and/or Standards

- Meets NFPA 1961 Standard on Fire Hose
- UL/ULC Underwriters Laboratory (Canada) Listed - see chart above for sizes approved.

NATIONAL 7F Hose



Type "7F": Forestry Hose WHITE Uncoated

Polyester Single Jacket - Polyurethane Lined - White Uncoated Forestry Hose

| Size | Service Test | | Proof Test | | Burst | | Weight (for 50' cpd) | | Bowl Size |
|--------|--------------|------|------------|------|-------|------|-------------------------|-----|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 1" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 5 | 2.3 | 1 5/32" |
| 1 1/2" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 7 | 3.2 | 1 3/4" |

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

"7F" - Forestry Hose Part Number Matrix

| <u>TYPE</u> | <u>HOSE I.D.</u> | <u>X</u> | <u>HOSE LENGTH</u> | <u>COLOR</u> w/ Dura-Cote coating | <u>COUPLING SIZE</u> | <u>THREAD TYPE</u> | <u>COUPLING MATERIAL</u> |
|-------------|------------------------|----------|------------------------|--------------------------------------|------------------------|--|--------------------------|
| 7F | 10 = 1" 15 = 1 1/2" | | 50 = 50' 100 = 100' | W = White Uncoated | 10 = 1" 15 = 1 1/2" | N = NH I = IPT QT = Quarter Turn | Blank = Aluminum |

Example: **7F10X50W10N** = 7F Forestry Hose, 1" ID by 50' Length, White, 1" Aluminum NH (NST) Couplings

"7F" - Forestry Hose Pricing

| 50' Lengths, White Uncoated | | |
|-----------------------------|-------------|-------------------|
| I.D. | Part # | 50' Coupled Price |
| 1" | 7F10X50W10N | \$149 |
| 1 1/2" | 7F15X50W15N | \$196 |

| 100' Lengths, White Uncoated | | |
|------------------------------|--------------|--------------------|
| I.D. | Part # | 100' Coupled Price |
| 1" | 7F10X100W10N | \$254 |
| 1 1/2" | 7F15X100W15N | \$336 |

IPT pricing is the same as the NH ("N" option) shown in chart. Replace the "N" with "I" to order.

Hose Approvals, Certifications, and/or Standards

- Meets requirements of U.S. Forest Service
- Meets NFPA 1961 Standard on Fire Hose

FIREQUIP Wildland Ultra Forestry Hose



Type "FH": Small Diameter Forestry Hose

Polyester Single Jacket - Polyurethane Lined, Forestry Hose

USDA FSS 5100 TYPE 1 = White

USDA FSS 5100 TYPE 2 = Yellow

| Size | Service PSI | | Proof PSI | | Burst PSI | | Weight (for 50' cpd) | | Bowl Size |
|------|-------------|------|-----------|------|-----------|------|-------------------------|-----|-----------|
| | PSI | kPa | PSI | kPa | PSI | kPa | LBS | KG | |
| 5/8" | 200 | 1379 | 400 | 2758 | 600 | 4137 | 1.25 | 0.6 | Coupled |
| 3/4" | 200 | 1379 | 400 | 2758 | 600 | 4137 | 2 | 0.9 | Coupled |
| 1" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 4 | 1.8 | 1 3/16" |
| 1.5" | 300 | 2068 | 600 | 4137 | 900 | 6205 | 7 | 3.1 | 1 3/4" |

"FH"- Wildland Ultra Part Number Matrix

| TYPE | HOSE I.D. | X | HOSE LENGTH | COLOR coating | Coupling size | THREAD TYPE | COUPLING MATERIAL |
|------|-------------|---|-------------|---------------------|---------------|-------------|---------------------|
| FH | FH75 = 3/4" | | A = 25' | W = White, Uncoated | 3/4" | Garden Hose | Brass = Garden Hose |
| | FH10 = 1" | | B = 50' | Y = Yellow, Coated | 10 = 1.0" | N = NH | Blank = Aluminium |
| | FH15 = 1.5" | | D = 100' | | 15 = 1.5" | | |

Example: FH58WB = FH Forestry Hose, 5/8" ID by 50' Length, White, 3/4" Garden Hose Brass Couplings

Type "FH"- Wildland Ultra Forestry Hose Pricing

25' Length, Coated

| I.D. | Part # | 25' Coupled Price |
|------|--------|-------------------|
| 1" | FH10YA | \$119 |
| 1.5" | FH15YA | \$185 |

50' Length, Coated

| I.D. | Part # | 50' Coupled Price |
|------|--------|-------------------|
| 3/4" | FH75YB | \$152 |
| 1" | FH10YB | \$185 |
| 1.5" | FH15YB | \$244 |

100' Length, Coated

| I.D. | Part # | 100' Coupled Price |
|------|--------|--------------------|
| 3/4" | FH75YD | \$264 |
| 1" | FH10YD | \$315 |
| 1.5" | FH15YD | \$420 |

25' Length, White / Uncoated

| I.D. | Part # | 25' Coupled |
|------|--------|-------------|
| 1" | FH10WA | \$110 |
| 1.5" | FH15WA | \$172 |

50' Length, White / Uncoated

| I.D. | Part # | 50' Coupled Price |
|------|--------|-------------------|
| 5/8" | FH58WB | \$143 |
| 1" | FH10WB | \$222 |
| 1.5" | FH15WB | \$222 |

100' Length, White / Uncoated

| I.D. | Part # | 100' Coupled |
|------|--------|--------------|
| 5/8" | FH58WD | \$238 |
| 1" | FH10WD | \$290 |
| 1.5" | FH15WD | \$383 |

Hose Approvals, Certifications, and/or Standards

- Meets requirements of U.S. Forest Service

Determine your part number while you build a price for all available types of Soft Sleeve Suction Hose. The example below the matrix shows how the part number and price are built per item ordered.

Soft-Sleeve Suction Hose Pricing Instructions

Hose Types Available: (See additional technical specifications on product page)

TD - Triple Duty: Double Jacket, Dura-Cote Treated Nylon Outer Jacket, PU Extruded-thru-the-weave Hose (4" & 5" only)

FC - Ponn Conquest LDH: Double Jacket, Dura-Cote Treated Polyester Outer Jacket, PU Extruded-thru-the-weave Hose (4" & 5" only)

6D - Double Jacket, Polyester Outer Jacket, Rubber Lined Hose

HFX - Extruded Thru-the-Weave Nitrile Rubber Cover/Liner, Polyester/Nylon Fabric Reinforcement

TPX - Three-Ply, Double Vulcanized, Heavy Duty Nitrile Rubber Cover/Liner, Polyester Fabric Reinforcement

UTX - Extruded Thru-the-Weave Polyurethane Cover/Liner. Polyester Fabric Reinforcement (4" & 5" only)

2 - SELECT LENGTH OF HOSE

StD hose lengths are 10', 15', 20', & 25'.

10 = 10 feet long

15 = 15 feet long

20 = 20 feet long

25 = 25 feet long (max length)

Y = Yellow = Available on TD HFX TPX

W = White (Uncoated) = Available on 6D

G = Hi-Viz Green = Available on UTX only

O = Blaze Orange = Available on UTX only

NFL = Female Long Handle, Lightweight - High Strength Hardcoated Aluminum, NH (NST) Threads

NF = Female Rocker Lug, Lightweight - High Strength Hardcoated Aluminum, NH (NST) Threads

NM = Male Rocker Lug, Lightweight - High Strength Hardcoated Aluminum, NH (NST) Threads

S = STORZ, Lightweight - High Strength Hardcoated Aluminum

| CPLNG | STORZ Connection to Hose Size: | |
|-------|--------------------------------|-------|
| Size | | |
| 40 | = | \$191 |
| 50 | = | \$264 |
| 60 | = | \$601 |

The part numbers and information above is considered "Special". **ALL SALES ARE FINAL AND MAY NOT BE RETURNED.**

MAXI-FLEX HARD SUCTION



Light, Flexible PVC Hard Suction Hose For Drafting



FIREQUIP MAXIFLEX PERFORMANCE AND WEIGHT CHART

| Hose Size | Working Pressure psi 70 °F | Bend Radius (Inches) | Vacuum (Inches) | Nominal Outside Diameter (Inches) | Weight per 10ft Length(uncoupled) |
|-----------|----------------------------------|-------------------------|--------------------|--------------------------------------|--------------------------------------|
| 1.5" | 70 | 5 | 29.8 | 1.82 | 5 |
| 2" | 65 | 7 | 29.8 | 2.32 | 8 |
| 3" | 50 | 12 | 29 | 3.57 | 12 |
| 4" | 68 | 15 | 29 | 4.67 | 20 |
| 4.5" | 50 | 16 | 29 | 5.79 | 25 |
| 5" | 50 | 16 | 29 | 5.79 | 25 |
| 6" | 47 | 19 | 29 | 6.83 | 45 |

"MF" Maxi-Flex Hose Pricing

Rocker Lug Female X Rocker Lug Male

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|--------|--------|---------|-------|---|
| 1 1/2" | MF15R1 | 10 feet | \$143 | MAXIFLEX HARD: 1.5" X 10' / 1.5" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 1 1/2" | MF15R2 | 20 feet | \$260 | MAXIFLEX HARD: 1.5" X 20' / 1.5" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 2" | MF20R1 | 10 feet | \$178 | MAXIFLEX HARD: 2.0" X 10' / 2.0" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 2" | MF20R2 | 20 feet | \$326 | MAXIFLEX HARD: 2.0" X 20' / 2.0" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 3" | MF25R1 | 10 feet | \$370 | MAXIFLEX HARD: 3" X 10' / 2.5" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 3" | MF25R2 | 20 feet | \$660 | MAXIFLEX HARD: 3" X 20' / 2.5" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 3" | MF30R1 | 10 feet | \$449 | MAXIFLEX HARD: 3" X 10' / 3" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |
| 3" | MF30R2 | 20 feet | \$739 | MAXIFLEX HARD: 3" X 20' / 3" NH Aluminum Coupling Rocker Lug Female X Rocker Lug Male |

Long Handle Female X Rocker Lug Male

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|--------|--------|---------|---------|--|
| 3" | MF25L1 | 10 feet | \$488 | MAXIFLEX HARD: 3" X 10' / 2.5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 3" | MF25L2 | 20 feet | \$594 | MAXIFLEX HARD: 3" X 20' / 2.5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 3" | MF30L1 | 10 feet | \$554 | MAXIFLEX HARD: 3" X 10' / 3" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 3" | MF30L2 | 20 feet | \$812 | MAXIFLEX HARD: 3" X 20' / 3" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 4" | MF40L1 | 10 feet | \$924 | MAXIFLEX HARD: 4" X 10' / 4" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 4" | MF40L2 | 20 feet | \$1,122 | MAXIFLEX HARD: 4" X 20' / 4" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 4 1/2" | MF45L1 | 10 feet | \$1,214 | MAXIFLEX HARD: 5" X 10' / 4.5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 4 1/2" | MF45L2 | 20 feet | \$1,386 | MAXIFLEX HARD: 5" X 20' / 4.5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 5" | MF50L1 | 10 feet | \$1,188 | MAXIFLEX HARD: 5" X 10' / 5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 5" | MF50L2 | 20 feet | \$1,584 | MAXIFLEX HARD: 5" X 20' / 5" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 6" | MF60L1 | 10 feet | \$1,346 | MAXIFLEX HARD: 6" X 10' / 6" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |
| 6" | MF60L2 | 20 feet | \$1,769 | MAXIFLEX HARD: 6" X 20' / 6" NH Aluminum Coupling Long Handle Female X Rocker Lug Male |

Storz Couplings

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|------|---------|---------|---------|------------------------------------|
| 4" | MF40S1 | 10 feet | \$1,267 | MAXIFLEX HARD: 4" X 10' / 4" Storz |
| 4" | MF40S2 | 20 feet | \$1,650 | MAXIFLEX HARD: 4" X 20' / 4" Storz |
| 5" | MF50S1 | 10 feet | \$1,452 | MAXIFLEX HARD: 5" X 10' / 5" Storz |
| 5" | MF50S2 | 20 feet | \$1,762 | MAXIFLEX HARD: 5" X 20' / 5" Storz |
| 6" | MF60S1 | 10 feet | \$2,178 | MAXIFLEX HARD: 6" X 10' / 6" Storz |
| 6" | MF60S2 | 20 feet | \$2,706 | MAXIFLEX HARD: 6" X 20' / 6" Storz |
| 6" | MF60S15 | 10 feet | \$1,896 | MAXIFLEX HARD: 6" X 10' / 5" Storz |
| 6" | MF60S25 | 20 feet | \$2,979 | MAXIFLEX HARD: 6" X 20' / 5" Storz |

FIRE ENGINE BOOSTER HOSE



Light, Flexible PVC Hard Suction Hose For Drafting

| SIZE | WORKING PRESSURE | BURST | WEIGHT (FOR 50' UNCOUPLED) | WEIGHT (FOR 100' UNCOUPLED) | BOWL SIZE |
|--------|------------------|--------------|-------------------------------|--------------------------------|-----------|
| IN | PSI (kPa) | PSI (kPa) | LBS (KG) | LBS (KG) | IN |
| 3/4" | 800 (5155) | 3200 (22060) | 21 (9.5) | 42 (19) | 1 1/4" |
| 1" | 800 (5155) | 3200 (22060) | 30 (13.6) | 60 (27.2) | 1 1/2" |
| 1 1/2" | 200 (1380) | 600 (4140) | 50 (22.7) | 100 (45.4) | 2" |



Fire Engine Booster Hose Pricing

Hard Coated Aluminum

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|------|--------|----------|---------|--|
| 3/4" | BH75RA | 25 feet | \$449 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 25' / 1" NH Aluminum coupling |
| 3/4" | BH75RB | 50 feet | \$726 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 50' / 1" NH Aluminum coupling |
| 3/4" | BH75RD | 100 feet | \$1,228 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 100' / 1" NH Aluminum coupling |
| 3/4" | BH75RE | 150 feet | \$1,742 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 150' / 1" NH Aluminum coupling |
| 3/4" | BH75RG | 200 feet | \$2,270 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 200' / 1" NH Aluminum coupling |
| 1" | BH10RA | 25 feet | \$528 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 25' / 1" NH Aluminum coupling |
| 1" | BH10RB | 50 feet | \$858 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 50' / 1" NH Aluminum coupling |
| 1" | BH10RD | 100 feet | \$1,478 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 100' / 1" NH Aluminum coupling |
| 1" | BH10RE | 150 feet | \$2,099 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 150' / 1" NH Aluminum coupling |
| 1" | BH10RG | 200 feet | \$2,772 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 200' / 1" NH Aluminum coupling |

Barway Brass

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|------|--------|----------|---------|--|
| 3/4" | BB75RA | 25 feet | \$528 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 25' / 1" NH Barway Brass coupling |
| 3/4" | BB75RB | 50 feet | \$805 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 50' / 1" NH Barway Brass coupling |
| 3/4" | BB75RD | 100 feet | \$1,294 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 100' / 1" NH Barway Brass coupling |
| 3/4" | BB75RE | 150 feet | \$1,795 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 150' / 1" NH Barway Brass coupling |
| 3/4" | BB75RG | 200 feet | \$2,323 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 200' / 1" NH Barway Brass coupling |
| 1" | BB10RA | 25 feet | \$660 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 25' / 1" NH Barway Brass coupling |
| 1" | BB10RB | 50 feet | \$924 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 50' / 1" NH Barway Brass coupling |
| 1" | BB10RD | 100 feet | \$1,584 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 100' / 1" NH Barway Brass coupling |
| 1" | BB10RE | 150 feet | \$2,178 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 150' / 1" NH Barway Brass coupling |
| 1" | BB10RG | 200 feet | \$2,798 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 200' / 1" NH Barway Brass coupling |

Barway Chrome / Brass

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|------|--------|----------|---------|---|
| 3/4" | BC75RA | 25 feet | \$605 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 25' / 1" NH Barway Chrome/Brass coupling |
| 3/4" | BC75RB | 50 feet | \$858 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 50' / 1" NH Barway Chrome/Brass coupling |
| 3/4" | BC75RD | 100 feet | \$1,386 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 100' / 1" NH Barway Chrome/Brass coupling |
| 3/4" | BC75RE | 150 feet | \$1,914 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 150' / 1" NH Barway Chrome/Brass coupling |
| 3/4" | BC75RG | 200 feet | \$2,442 | BOOSTER HOSE: Red, 800 psi working pressure, .75" X 200' / 1" NH Barway Chrome/Brass coupling |
| 1" | BC10RA | 25 feet | \$818 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 25' / 1" NH Barway Chrome/Brass coupling |
| 1" | BC10RB | 50 feet | \$1,109 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 50' / 1" NH Barway Chrome/Brass coupling |
| 1" | BC10RD | 100 feet | \$1,703 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 100' / 1" NH Barway Chrome/Brass coupling |
| 1" | BC10RE | 150 feet | \$2,376 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 150' / 1" NH Barway Chrome/Brass coupling |
| 1" | BC10RG | 200 feet | \$2,904 | BOOSTER HOSE: Red, 800 psi working pressure, 1" X 200' / 1" NH Barway Chrome/Brass coupling |

AAH Alarm Hose - Rigid, Red, for Reels

| I.D. | PART # | LENGTH | PRICE | DESCRIPTION |
|--------|--------|----------|---------|--|
| 1 1/2" | BH15RA | 25 feet | \$422 | BOOSTER HOSE: Red, 200 psi working pressure, 1.5" X 25' / 1.5" NH Aluminum coupling |
| 1 1/2" | BH15RB | 50 feet | \$660 | BOOSTER HOSE: Red, 200 psi working pressure, 1.5" X 50' / 1.5" NH Aluminum coupling |
| 1 1/2" | BH15RD | 100 feet | \$1,320 | BOOSTER HOSE: Red, 200 psi working pressure, 1.5" X 100' / 1.5" NH Aluminum coupling |
| 1 1/2" | BH15RE | 150 feet | \$1,954 | BOOSTER HOSE: Red, 200 psi working pressure, 1.5" X 150' / 1.5" NH Aluminum coupling |
| 1 1/2" | BH15RG | 200 feet | \$2,640 | BOOSTER HOSE: Red, 200 psi working pressure, 1.5" X 200' / 1.5" NH Aluminum coupling |

REEL-LITE BOOSTER HOSE




Lightweight Woven TPU Single and Double Jacket Forestry Reel-Lite Hose

| SIZE | SERVICE TEST | PROOF TEST | BURST | WEIGHT (FOR 50' UNCOUPLED) | BOWL SIZE |
|------|--------------|------------|------------|-------------------------------|-----------|
| IN | PSI (kPa) | PSI (kPa) | PSI (kPa) | LBS (KG) | IN |
| 1" | 300 (2070) | 600 (4140) | 900 (6200) | 5 (2.3) | 1 3/16" |

As per NFPA 1961 – The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

HOSE COLORS

Yellow Red




"RL" Single Jacket Reel-Lite Hose Pricing

NH ALUMINUM COUPLING

| I.D. | PART # | LENGTH | PRICE | SINGLE JACKET DESCRIPTION |
|------|--------|----------|-------|---|
| 1" | RL10RA | 25 feet | \$251 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 25' / 1" NH Aluminum coupling |
| 1" | RL10YA | 25 feet | \$251 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 25' / 1" NH Aluminum coupling |
| 1" | RL10RB | 50 feet | \$367 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 50' / 1" NH Aluminum coupling |
| 1" | RL10YB | 50 feet | \$367 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 50' / 1" NH Aluminum coupling |
| 1" | RL10RD | 100 feet | \$704 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 100' / 1" NH Aluminum coupling |
| 1" | RL10YD | 100 feet | \$704 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 100' / 1" NH Aluminum coupling |

NH ALUMINUM REATTACHABLE COUPLING

| I.D. | PART # | LENGTH | PRICE | SINGLE JACKET DESCRIPTION |
|------|---------|----------|-------|--|
| 1" | RL10RAR | 25 feet | \$361 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 25' / 1" NH Aluminum Reattachable coupling |
| 1" | RL10YAR | 25 feet | \$361 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 25' / 1" NH Aluminum Reattachable coupling |
| 1" | RL10RBR | 50 feet | \$436 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 50' / 1" NH Aluminum Reattachable coupling |
| 1" | RL10YBR | 50 feet | \$436 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 50' / 1" NH Aluminum Reattachable coupling |
| 1" | RL10RDR | 100 feet | \$770 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 100' / 1" NH Aluminum Reattachable coupling |
| 1" | RL10YDR | 100 feet | \$770 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 100' / 1" NH Aluminum Reattachable coupling |

"RD" Double Jacket Reel-Lite Hose Pricing

NH ALUMINUM COUPLING

| I.D. | PART # | LENGTH | PRICE | DOUBLE JACKET DESCRIPTION |
|------|--------|----------|-------|---|
| 1" | RD10RA | 25 feet | \$348 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 25' / 1" NH Aluminum coupling |
| 1" | RD10YA | 25 feet | \$348 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 25' / 1" NH Aluminum coupling |
| 1" | RD10RB | 50 feet | \$431 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 50' / 1" NH Aluminum coupling |
| 1" | RD10YB | 50 feet | \$431 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 50' / 1" NH Aluminum coupling |
| 1" | RD10RD | 100 feet | \$766 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 100' / 1" NH Aluminum coupling |
| 1" | RD10YD | 100 feet | \$766 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 100' / 1" NH Aluminum coupling |

NH ALUMINUM REATTACHABLE COUPLING

| I.D. | PART # | LENGTH | PRICE | DOUBLE JACKET DESCRIPTION |
|------|---------|----------|-------|--|
| 1" | RD10RAR | 25 feet | \$416 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 25' / 1" NH Aluminum Reattachable coupling |
| 1" | RD10YAR | 25 feet | \$416 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 25' / 1" NH Aluminum Reattachable coupling |
| 1" | RD10RBR | 50 feet | \$532 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 50' / 1" NH Aluminum Reattachable coupling |
| 1" | RD10YBR | 50 feet | \$532 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 50' / 1" NH Aluminum Reattachable coupling |
| 1" | RD10RDR | 100 feet | \$812 | REEL-LITE BOOSTER HOSE: Red, 600 psi working pressure, 1" X 100' / 1" NH Aluminum Reattachable coupling |
| 1" | RD10YDR | 100 feet | \$812 | REEL-LITE BOOSTER HOSE: Yellow, 600 psi working pressure, 1" X 100' / 1" NH Aluminum Reattachable coupling |