Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

SPECIFICATION PROPOSAL

Data Code	Description	Weight Front	Weight Rear	
Price Level				
PRL-27D	SD PRL-27D (EFF:MY24 ORDERS)			
Data Version				
DRL-016	SPECPRO21 DATA RELEASE VER 016			
Vehicle Configurat	ion			
001-177	114SD CONVENTIONAL CHASSIS	7,934	6,476	
004-224	2024 MODEL YEAR SPECIFIED			
002-004	SET BACK AXLE - TRUCK	480	-480	
019-002	STRAIGHT TRUCK PROVISION			
003-001	LH PRIMARY STEERING LOCATION			
General Service				
AA1-002	TRUCK CONFIGURATION			
AA6-002	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)			
A85-020	FIRE SERVICE			
A84-1EV	EMERGENCY VEHICLES BUSINESS SEGMENT			
AA4-011	FIXED LOAD COMMODITY			
AA5-006	TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS			
AB1-008	MAXIMUM 8% EXPECTED GRADE			
AB5-003	MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			
995-1AE	FREIGHTLINER LEVEL II WARRANTY			
A66-99D	EXPECTED FRONT AXLE(S) LOAD: 14600.0 lbs.			
A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD: 27000.0 lbs.			
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 41600.0 lbs.			
Truck Service				
AA3-031	FIRE TANK - NO MAIN DRIVELINE DRIVEN SPLIT- SHAFT PTO/PUMP			
A88-99D	EXPECTED TRUCK BODY LENGTH: 16.0 ft			



	Data Code	Description	Weight Front	Weight Rear	
	AF6-99D	EXP EMPTY BODY CG LOC FROM BODY FRT(A89): 8.0 ft			
	A89-99D	BRAKING-EXPECTED CAB TO BODY CLEARANCE: 40.0 in			
	AF3-357	TBD			
	RTK-1AA	APPROVAL TO SHARE SPEC WITH TEM			
	AF7-99D	EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES: 32.0 in			
Engine	•				
	101-25T	CUMMINS X12 500EV HP @ 1900 RPM, 1700 LB- FT @ 1000 RPM, 2000 GOV RPM, R/F/E	-390	-45	
Electro	nic Paramete	ers			
	79A-060	60 MPH ROAD SPEED LIMIT			
	79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT			
	79F-004	CUMMINS TRIP INFORMATION REPORTS ENABLED; LEVEL 1: 4 MPH, LEVEL 2: 7 MPH ABOVE ROAD SPEED LIMIT			
	80C-004	ENGINE BRAKE WITH CRUISE CONTROL ENABLED AT 2 MPH ABOVE SET SPEED, 1 MPH INCREMENT BETWEEN BRAKING LEVELS			
	80E-001	ENGINE FAN ENABLED WITH RETARDER			
	80F-001	AUTOMATIC MAINTENANCE MONITOR WITH ALERT AT 5% OF INTERVAL REMAINING			
	80J-002	REGEN INHIBIT SPEED THRESHOLD - 5 MPH			
Engine	Equipment				
	99C-021	2010 EPA/CARB/GHG21 CONFIGURATION			
	99D-010	NO 2008 CARB EMISSION CERTIFICATION			
	13E-001	STANDARD OIL PAN			
	105-001	ENGINE MOUNTED OIL CHECK AND FILL			
	014-1BX	SIDE OF HOOD AIR INTAKE WITH NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER			
	124-1E7	DR 12V 275 AMP 40-SI BRUSHLESS PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE	10		
	292-236	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES			
	290-017	BATTERY BOX FRAME MOUNTED			
	281-004	BATTERY JUMPERS WITH MEGA FUSE JUNCTION BLOCK (MFJB)	4		
	282-001	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB			



Data	a Code	Description	Weight Front	Weight Rear	
291-	017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
289-	001	NON-POLISHED BATTERY BOX COVER			
293-	060	POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH WITH LOCKING PROVISION MOUNTED OUTBOARD DRIVER SEAT	2		
295-	029	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2		
107-	048	CUMMINS NATURALLY ASPIRATED 25.9 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE			
152-	039	GVG, FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING			
128-	004	CUMMINS INTEBRAKE BRAKE WITH HIGH MED LOW BRAKE			
016-	1DC	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES	10	5	
28F-	-007	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND DASH MOUNTED SINGLE REGENERATION REQUEST/INHIBIT SWITCH			
239-	001	STANDARD EXHAUST SYSTEM LENGTH			
237-	022	RH HORIZONTAL TAILPIPE, EXIT FORWARD OF REAR TIRES	20	20	
23U-	-001	6 GALLON DIESEL EXHAUST FLUID TANK	-35	-10	
30N-	-003	100 PERCENT DIESEL EXHAUST FLUID FILL			
23Y-	-001	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			
43X-	-002	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
43Y-	-001	STANDARD DIESEL EXHAUST FLUID TANK CAP			
273-	048	HORTON 2-SPEED DRIVEMASTER ADVANTAGE POLAREXTREME FAN DRIVE			
276-	002	AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED			
110-	003	CUMMINS SPIN ON FUEL FILTER			
118-	800	COMBINATION FULL FLOW/BYPASS OIL FILTER			
266-	057	1500 SQUARE INCH ALUMINUM RADIATOR			
103-	039	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			



Data	Code	Description	Weight Front	Weight Rear	
171-0	007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
172-0	001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES			
270-0	016	RADIATOR DRAIN VALVE			
168-0	002	LOWER RADIATOR GUARD	6		
155-0	055	DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	-45		
Transmissio	n				
342-1	IKH	ALLISON 4000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION	260	100	
Transmissio	n Equip	oment			
343-3	331	ALLISON VOCATIONAL PACKAGE 198 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL EVS			
84B-0	003	ALLISON VOCATIONAL RATING FOR FIRE TRUCK/EMERGENCY VEHICLE APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES			
84C-	023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84D-	023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84E-0	013	S1 PERFORMANCE PRIMARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84F-0	012	S1 PERFORMANCE SECONDARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84G-	012	2000 RPM PRIMARY MODE SHIFT SPEED			
84H-	012	2000 RPM SECONDARY MODE SHIFT SPEED			
84N-2	200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED			
84U-	000	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES			
84M-	001	PUMP MODE INPUT ENABLED 3RD/4TH LOCKUP WIRED ON TCM INPUT AJ/BQ - ALLISON 5TH GEN TRANSMISSIONS			
85B-0	004	4TH RANGE INDICATION ON TCM OUTPUT C - ALLISON 5TH GEN TRANSMISSIONS			
85Q-	998	NO AMT DEFAULT START GEAR			
353-0	065	VEHICLE INTERFACE WIRING CONNECTOR WITH BLUNT CUTS, AT BACK OF CAB			



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

Data Code	Description	Weight Front	Weight Rear			
34C-002	ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR MOUNTED BACK OF CAB					
362-2FH	CHELSEA PTO - CHL870XDFJP B5XV					
363-001	PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON					
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN					
345-003	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED					
97G-004	TRANSMISSION PROGNOSTICS - ENABLED 2013					
370-011	WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED					
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK					
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)					
Front Axle and Equ	uipment					
400-1A9	DETROIT DA-F-16.0-5 16,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	190				
402-1A3	MERITOR EX-H AIR DISC FRONT BRAKES					
403-026	FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT LINING					
419-004	FRONT DISC BRAKE ROTORS					
409-006	FRONT OIL SEALS					
408-001	VENTED FRONT HUB CAPS WITH WINDOW, CENTER, AND SIDE PLUGS - OIL					
416-022	STANDARD SPINDLE NUTS FOR ALL AXLES					
405-030	FRONT AIR DISC BRAKE INTERNAL ADJUSTERS					
406-001	STANDARD KING PIN BUSHINGS					
536-012	TRW TAS-85 POWER STEERING	40				
539-003	POWER STEERING PUMP					
534-003	4 QUART POWER STEERING RESERVOIR	5				
40T-004	GUARANTEED NAME BRAND "ROADRANGER SYNTHETIC" FE 75W-90 FRONT AXLE LUBE					
Front Suspension						
620-004	16,000# FLAT LEAF FRONT SUSPENSION	260				
619-004	GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION					
410-001	FRONT SHOCK ABSORBERS					
Rear Axle and Equ	Rear Axle and Equipment					



Data Code	Description	Weight Front	Weight Rear	
420-1DR	RS-25-160 27,000# R-SERIES FIRE/EMERGENCY SERVICE SINGLE REAR AXLE		60	
421-563	5.63 REAR AXLE RATIO			
424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			
386-094	RPL14 MERITOR SERVICE-FREE MAIN DRIVELINE WITH HALF ROUND (17T) YOKES	20	20	
452-001	DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20	
878-018	(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE			
87B-005	BUZZER AND BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH			
423-1A3	MERITOR EX-H AIR DISC REAR BRAKES			
433-025	FIRE AND EMERGENCY SEVERE SERVICE NON- ASBESTOS REAR BRAKE LINING			
434-012	BRAKE CAMS AND CHAMBERS ON REAR SIDE OF DRIVE AXLE(S)			
451-005	REAR DISC BRAKE ROTORS			
440-006	REAR OIL SEALS			
426-1AH	AIR DISC LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS			
428-030	REAR AIR DISC BRAKE INTERNAL ADJUSTERS			
41T-003	GUARANTEED NAME BRAND "ROADRANGER SYNTHETIC" FE 75W-90 REAR AXLE LUBE			
42T-001	STANDARD REAR AXLE BREATHER(S)			
Rear Suspension				
622-1DE	27,000# FLAT LEAF SPRING REAR SUSPENSION WITH RADIUS ROD AND HELPER FOR FIRE/EMERGENCY SERVICE		80	
\	WITH HELPER			
621-001	SPRING SUSPENSION - NO AXLE SPACERS			
431-007	STANDARD U-BOLT PAD WITH U-BOLTS EXTENDED 1.00" LONGER THAN STANDARD			
623-005	FORE/AFT CONTROL RODS			
Brake System				
490-101	WABCO 4S/4M ABS WITH TRACTION CONTROL, WITH ATC OFF-ROAD SWITCH			
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
904-001	FIBER BRAID PARKING BRAKE HOSE			
412-001	STANDARD BRAKE SYSTEM VALVES			



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

Data Code	Description	Weight Front	Weight Rear	
46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM			
413-002	STD U.S. FRONT BRAKE VALVE			
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
480-088	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER			
483-004	WABCO OIL COALESCING FILTER FOR AIR DRYER			
479-003	AIR DRYER MOUNTED INBOARD ON LH RAIL			
A	T LEAST 60 INCHES BOC FOR PUMP CLEARANCE			
460-1AM	STEEL AIR BRAKE RESERVOIRS MOUNTED INSIDE RAIL; CUSTOMER ACCEPTS TANKS MOUNTED IN REAR OVERHANG/REAR SUSPENSION			
477-006	BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)			
Trailer Connections				
335-004	UPGRADED CHASSIS MULTIPLEXING UNIT			
Wheelbase & Frame				
545-542	5425MM (214 INCH) WHEELBASE			
546-102	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	470	120	
548-803	TEM TO EVALUATE AND INSTALL FRAME RAIL REINFORCEMENT AS NEEDED FOR FRONT FRAME MOUNTED EQUIPMENT			
552-039	1825MM (72 INCH) REAR FRAME OVERHANG			
55W-007	FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-20	100	
AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 148.03 in			
AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 108.03 in			
AE4-99D	CALC'D FRAME LENGTH - OVERALL: 315.6 in			
FSS-0LH	CALCULATED FRAME SPACE LH SIDE: 111.35 in			
FSS-0RH	CALCULATED FRAME SPACE RH SIDE: 54.52 in			
553-001	SQUARE END OF FRAME			
550-001	FRONT CLOSING CROSSMEMBER			
559-001	STANDARD WEIGHT ENGINE CROSSMEMBER			
562-055	STANDARD MIDSHIP #1 CROSSMEMBER(S); FIRST MIDSHIP MOUNTED 36.0 INCHES BACK OF CAB			



ı	Data Code	Description	Weight Front	Weight Rear
	572-038	REARMOST CROSSMEMBER MOUNTED WITH LAST CROSSMEMBER 13 INCHES FROM END OF FRAME		
	565-001	STANDARD SUSPENSION CROSSMEMBER		
Chassis	Equipment			
	556-1E6	14 INCH CHROMED STEEL BUMPER		
ţ	558-070	REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME	15	
Ę	574-001	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
ŧ	551-002	HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS		
(605-103	D15-28195-000 CENTER PUNCH TO MARK CENTERLINE OF REAR SUSPENSION ON TOP FLANGE OF FRAME		
(970-039	TANK BODY 1501 TO 3000 GALLONS		
6	607-029	CLEAR FRAME RAIL FROM TRANSMISSION PTO OPENING TO 36 INCHES BACK OF CAB OUTBOARD/INSIDE/BELOW LH RAIL		
	TH	EN 607-001 ENTIRE WAY		
Fuel Tan	ks			
2	204-215	50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH	-10	
2	218-005	RECTANGULAR FUEL TANK(S)		
2	215-004	POLISHING OF FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
2	212-007	FUEL TANK(S) FORWARD		
(664-004	POLISHED STAINLESS STEEL STEP FINISH		
2	205-002	CHROME FUEL TANK CAP(S)		
•	122-1H3	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	10	
2	216-020	EQUIFLO INBOARD FUEL SYSTEM		
	202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires				
(093-994	MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES	50	
(094-994	MICHELIN XZE 12R22.5 16 PLY RADIAL REAR TIRES		100
Hubs				
	418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS	1	



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

	Data Code	Description	Weight Front	Weight Rear	
	450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS			
Wheels	;				
	502-735	ACCURIDE 43644 ACCU-LITE 22.5X8.25 10-HUB PILOT 5.79 INSET ALUMINUM DISC FRONT WHEELS	-64		
	505-736	ACCURIDE 43644 ACCU-LITE 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-128	
	496-011	FRONT WHEEL MOUNTING NUTS			
	497-011	REAR WHEEL MOUNTING NUTS			
	498-019	ALLIGATOR/V2B DUAL SEAL INFLATOR CAPS, FRONT AND REAR			
Cab Ex	terior				
	829-1A2	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB			
	650-008	AIR CAB MOUNTING			
	648-002	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE			
	667-004	FRONT FENDERS SET-BACK AXLE			
	678-067	SAFETY YELLOW LH AND RH INTERIOR GRAB HANDLES AND LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT			
	645-002	BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL			
	646-042	STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS			
	65X-003	CHROME HOOD MOUNTED AIR INTAKE GRILLE			
	644-004	FIBERGLASS HOOD			
	690-017	HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5		
	727-802	FACTORY PREP DUAL 25 INCH ROUND STUTTER TONE HOOD MOUNTED AIR HORNS WITH DUAL LANYARDS HORNS SHIP LOOSE FOR PDI INSTALL	4		
	726-002	DUAL ELECTRIC HORNS			
	728-002	DUAL HORN SHIELDS			
	575-001	REAR LICENSE PLATE MOUNT END OF FRAME			
	312-067	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS			
	302-047	LED AERODYNAMIC MARKER LIGHTS			
	311-025	HEADLIGHTS ON WITH WIPERS, WITH LOW BEAM DAYTIME RUNNING LIGHTS			



Data Code	Description	Weight Front	Weight Rear	
294-094	OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TAIL WIRES TO 7 FEET BEYOND END OF FRAME		-5	
300-015	STANDARD FRONT TURN SIGNAL LAMPS			
469-014	AUTOMATIC ON/OFF, ENGINE COMPARTMENT, HOOD ACTIVATED WORK LIGHT WITH MANUAL OVERRIDE	1		
744-103	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LED LIGHTS AND LH AND RH REMOTE			
797-001	DOOR MOUNTED MIRRORS			
796-001	102 INCH EQUIPMENT WIDTH			
743-204	LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS			
74A-001	RH DOWN VIEW MIRROR			
729-001	STANDARD SIDE/REAR REFLECTORS			
677-055	RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER			
275-061	PARK BRAKE REMINDER WARNING SYSTEM			
764-010	COMPOSITE EXTERIOR SUN VISOR	10		
768-998	NO REAR WINDOW			
661-003	TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS			
654-027	RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S)	4		
663-013	1-PIECE SOLAR GREEN GLASS WINDSHELD			
659-019	2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED			
Cab Interior				
707-1AK	OPAL GRAY VINYL INTERIOR			
706-026	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR			
708-026	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR			
772-006	BLACK MATS WITH SINGLE INSULATION			
785-998	NO DASH MOUNTED ASH TRAYS AND LIGHTER			
691-014	FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS AND ADDITIONAL CENTER COMPARTMENT WITHOUT NETTING			



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

Data Code	Description	Weight Front	Weight Rear	
694-010	IN DASH STORAGE BIN			
742-007	(2) CUP HOLDERS LH AND RH DASH			
680-006	GRAY/CHARCOAL FLAT DASH			
860-004	SMART SWITCH EXPANSION MODULE			
700-002	HEATER, DEFROSTER AND AIR CONDITIONER			
701-008	STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE			
703-005	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH			
170-019	STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES			
130-041	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR			
702-002	BINARY CONTROL, R-134A			
739-034	PREMIUM INSULATION			
285-027	SOLID-STATE CIRCUIT PROTECTION AND FUSES WITH SPARE FUSE KIT			
280-007	12V NEGATIVE GROUND ELECTRICAL SYSTEM			
324-011	DOME DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF			
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
78G-004	KEY QUANTITY OF 4			
655-005	LH AND RH ELECTRIC DOOR LOCKS			
284-101	(1) 12V POWER SUPPLY (1) DUAL 2.1 AMP USB CHARGER IN DASH			
756-1G7	H.O. BOSTROM SIERRA AIR-30 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH ADJUSTABLE RECLINE, FIXED LUMBAR AND NFPA 1901- 2009/2016 COMPLIANT SEAT SENSOR			
760-1G7	H.O.BOSTROM SIERRA AIR-30 HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH ADJUSTABLE RECLINE, FIXED LUMBAR AND NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR			
759-009	INBOARD DRIVER SEAT ARMREST, NO PASSENGER SEAT ARMREST			
711-004	LH AND RH INTEGRAL DOOR PANEL ARMRESTS			
758-081	GRAY AND BLACK DURAWEAR FABRIC DRIVER SEAT COVER, SEAT BOLSTER AND INSERT			
761-081	GRAY AND BLACK DURAWEAR FABRIC PASSENGER SEAT COVER, SEAT BOLSTER AND INSERT			
763-105	NFPA 1901-2009 HIGH VISIBILITY ORANGE SEAT BELTS	1		



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

Data Code	Description	Weight Front	Weight Rear	
532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10		
540-015	4-SPOKE 18 INCH (450MM) STEERING WHEEL			
765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS			
67E-006	INTERFACE CONNECTORS AND WIRING FOR CUSTOMER PROVIDED LED STEP LIGHTING			
Instruments & Cont	rols			
732-004	GRAY DRIVER INSTRUMENT PANEL			
734-004	GRAY CENTER INSTRUMENT PANEL			
870-001	BLACK GAUGE BEZELS			
486-006	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM WITH (1) ADDITIONAL PARK SWITCH FOR CUSTOMER USE			
840-002	2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES			
198-034	INTAKE MOUNTED AIR RESTRICTION INDICATOR W/ COLOR LED WARNING LIGHT, 18 INCH AND 20 INCH LIMITS	1		
721-003	87 DECIBELS TO 112 DECIBELS AUTOMATIC SELF-ADJUSTING BACKUP ALARM		3	
149-013	ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL			
156-020	IGNITION SWITCH WITH NON REMOVABLE KEY			
811-042	ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED			
160-038	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH			
844-001	2 INCH ELECTRIC FUEL GAUGE			
856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			
854-001	ENGINE OIL TEMPERATURE GAUGE			
864-001	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			
830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
372-035	(1) DASH MOUNTED PTO SWITCH WITH INDICATOR LAMP	11		
49B-004	ELECTRONIC STABILITY CONTROL			
852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE			
679-998	NO OVERHEAD INSTRUMENT PANEL			
786-119	NFPA VEHICLE DATA RECORDER AND SEATBELT DISPLAY			



	Data Code	Description	Weight Front	Weight Rear
	746-136	AM/FM/WB WORLD TUNER RADIO WITH AUXILIARY INPUT, J1939	10	
	747-001	DASH MOUNTED RADIO		
	750-002	(2) RADIO SPEAKERS IN CAB		
	753-008	AM/FM ANTENNA MOUNTED ON LH SIDE MIRROR		
	74D-002	RADIO WIRING WITH POWER CUTOFF WHEN VEHICLE IN REVERSE GEAR		
	810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
	817-001	STANDARD VEHICLE SPEED SENSOR		
	812-001	ELECTRONIC 3000 RPM TACHOMETER		
	813-998	NO VEHICLE PERFORMANCE MONITOR	-5	
	162-002	IGNITION SWITCH CONTROLLED ENGINE STOP		
	81Y-001	PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH		
	264-032	(2) OVERHEAD MOUNTED LANYARD CONTROLS: (1) OFFICER AIR HORN AND (1) DRIVER AIR HORN		
	836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
	660-025	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY PROGRAMMED TO SLOWEST SPEED WITH PARK BRAKE SET		
	304-001	MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH		
	27D-012	ALTERNATING FLASHING LOW BEAM HEADLAMPS WITH DASH SWITCH, WITH PARK BRAKE RELEASED		
	882-018	ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		
	299-013	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER, AND HAZARD IN HANDLE		
	298-039	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS		
Design	ı			
	065-000	PAINT: ONE SOLID COLOR		
Color				
	980-6A7	CAB COLOR A: L3007EY OSHA RED ELITE EY		
	230 0/11	3. 15 3313. (7.1 E000) E1 301 (1.1 E5 EE1 E E1		



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

Data Code	Description	Weight Front	Weight Rear		
986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT				
976-995	SUNVISOR PAINTED SAME AS CAB COLOR A				
963-003	STANDARD E COAT/UNDERCOATING				
Certification / Compliance					
996-001	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS				
Secondary Factory Options					
998-033	CORPORATE PDI CENTER IN-SERVICE AND OPTION INSTALLATION/MODIFICATION				



Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

DIMENSIONS




TABLE SUMMARY - DIMENSIONS

Dimensions	Inches
Bumper to Back of Cab (BBC)	113.4
Bumper to Centerline of Front Axle (BA)	47.9
Front Axle to Back of Cab (AC)	65.6
Min. Cab to Body Clearance (CB)	40.0
Back of Cab to Centerline of Rear Axle(s) (CA)	148.0
Effective Back of Cab to Centerline of Rear Axle(s) (Effective CA)	108.0
Back of Cab Protrusions (Exhaust/Intake) (CP)	2.0
Back of Cab Protrusions (Side Extenders/Trim Tab) (CP)	0.0
Back of Cab Protrusions (CNG Tank)	0.0
Back of Cab Clearance (CL)	40.0
Back of Cab to End of Frame	219.9
Cab Height (CH)	71.8
Wheelbase (WB)	213.6
Frame Overhang (OH)	71.9
Overall Frame Length	315.6
Overall Length (OAL)	333.4
Rear Axle Spacing	0.0
Unladen Frame Height at Centerline of Rear Axle	41.9

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.



Prepared for: Jason Bennett NC SHERIFFS ASSOCIATION PO BOX 20049

RALEIGH, NC 27619

Prepared by: Terry Keith Excel Truck Group 4633 Equipment Drive Charlotte, NC 28269

