REMOUNT PRICING Version 22.0

EXCELLANCE, Inc

453 Lanier Road, Madison, Alabama 35758 1-800-882-9799 NCSA FIRE/EMS/LAW ENFORCEMENT SPECIALTY VEHICLES PROCUREMENT BID 23-03-0524

REMOUNT BUILD SHEET - TYPE I-EHD INTERNATIONAL CV-515

ENTER MODEL YEAR FOR NEW CHASSIS: 2023	120	<u>CHASSIS</u>	
ENTER MODEL YEAR FOR NEW CHASSIS: 2023 ENTER MODEL OF NEW CHASSIS: CV-515 ENTER MAKE OF NEW CHASSIS: INTERNATIONAL ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: 104" ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: 171" CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis high idle system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)		(1) Excellance Supplied Chassis	
ENTER MODEL YEAR FOR NEW CHASSIS: 2023 130 ENTER MODEL OF NEW CHASSIS: CV-515 131 ENTER MAKE OF NEW CHASSIS: INTERNATIONAL 132 ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: 104" 133 ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" 134 135 136 THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: 171" 137 CHASSIS INSPECTION 138 Inspected for damage and defects upon delivery 139 Test Drive 140 the customer/ dealer. 141 All loose equipment received with the chassis shall be inventoried and stored. 142 All loose equipment received with the chassis shall be inventoried and stored. 143 All conditioner, gauges, dome lights, turn signals, parking lights, etc.). 144 CHASSIS WORK TO BE PERFORMED 145 Heat Shields shall be installed above the exhaust system. 146 Chassis shall have undercoating applied. 147 Exhaust modifications shall be performed as necessary. 148 Air valve extensions shall be installed on the rear inner tires. 149 New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) 150 New mounting hardware shall be connected and operational. 151 Chassis high idle system shall be connected to the module electrical system. 152 Chassis electrical charging/ battery system shall be connected to the module electrical system. 153 New Chassis emergency light wiring shall be connected to the module electrical system. 154 New Chassis emergency light wiring shall be connected to the module electrical system.	124		
ENTER MODEL YEAR FOR NEW CHASSIS: 2023 130 ENTER MODEL OF NEW CHASSIS: CV-515 131 ENTER MAKE OF NEW CHASSIS: INTERNATIONAL 132 ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: 104" 133 ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" 134 135 136 THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: 171" 137 CHASSIS INSPECTION 138 Inspected for damage and defects upon delivery 139 Test Drive 140 the customer/ dealer. 141 All loose equipment received with the chassis shall be inventoried and stored. 142 All loose equipment received with the chassis shall be inventoried and stored. 143 All conditioner, gauges, dome lights, turn signals, parking lights, etc.). 144 CHASSIS WORK TO BE PERFORMED 145 Heat Shields shall be installed above the exhaust system. 146 Chassis shall have undercoating applied. 147 Exhaust modifications shall be performed as necessary. 148 Air valve extensions shall be installed on the rear inner tires. 149 New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) 150 New mounting hardware shall be connected and operational. 151 Chassis high idle system shall be connected to the module electrical system. 152 Chassis electrical charging/ battery system shall be connected to the module electrical system. 153 New Chassis emergency light wiring shall be connected to the module electrical system. 154 New Chassis emergency light wiring shall be connected to the module electrical system.			
ENTER MODEL OF NEW CHASSIS: CV-515 ENTER MAKE OF NEW CHASSIS: INTERNATIONAL ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: INTERNATIONAL ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 104" ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loase equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be connected to the module electrical system.	125		
ENTER MAKE OF NEW CHASSIS: INTERNATIONAL ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: 104" ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" IMPLICATION OF NEW CHASSIS: 171"	129	ENTER MODELYEAR FOR NEW CHASSIS:	2023
ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS: 104" ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" 171" 172 173 THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, intersection lights, etc.)	130	ENTER MODEL OF NEW CHASSIS:	CV-515
ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS: 171" 1734 1735 1736 1737 1738 1739 1740 1750 177 178 179 179 179 179 179 179 179 179 179 179	131	ENTER MAKE OF NEW CHASSIS:	INTERNATIONAL
THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	132	ENTER CAB TO AXLE MEASUREMENT OF NEW CHASSIS:	104"
THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	133	ENTER WHEELBASE MEASUREMENT OF NEW CHASSIS:	171"
THE REMOUNT WILL HAVE THE FOLLOWING WORK INCLUDED IN THE STANDARD BASE CONVERSION: CHASSIS INSPECTION Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	134	·	
Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	135		
Inspected for damage and defects upon delivery Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis high idle system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	136		
Test Drive The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)			
The chassis shall be inspected against (A) Excellance's Chassis order, and (B) the specifications supplied by the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	138		
the customer/ dealer. All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Chassis shall have undercoating applied. Air valve extensions shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	139		
All loose equipment received with the chassis shall be inventoried and stored. All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)			
All chassis functions shall be tested for proper operation (accelerator, brakes, headlights, wipers, horn, radio, air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)			
air conditioner, gauges, dome lights, turn signals, parking lights, etc.). CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	141		
144 CHASSIS WORK TO BE PERFORMED 145 Heat Shields shall be installed above the exhaust system. 146 Chassis shall have undercoating applied. 147 Exhaust modifications shall be performed as necessary. 148 Air valve extensions shall be installed on the rear inner tires. 149 New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) 150 New mounting bracket for the rear bumper shall be installed to the chassis frame. 151 Chassis high idle system shall be connected and operational. 152 Chassis electrical charging/ battery system shall be connected to the module electrical system. 153 New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)			
CHASSIS WORK TO BE PERFORMED Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	142	air conditioner, gauges, dome lights, turn signals, parking lights, etc.).	
Heat Shields shall be installed above the exhaust system. Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	143		
Chassis shall have undercoating applied. Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	144	CHASSIS WORK TO BE PERFORMED	
Exhaust modifications shall be performed as necessary. Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	145	Heat Shields shall be installed above the exhaust system.	
Air valve extensions shall be installed on the rear inner tires. New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	146	Chassis shall have undercoating applied.	
New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outriggers (Type I units only) New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	147	Exhaust modifications shall be performed as necessary.	
New mounting bracket for the rear bumper shall be installed to the chassis frame. Chassis high idle system shall be connected and operational. Chassis electrical charging/ battery system shall be connected to the module electrical system. New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	148	Air valve extensions shall be installed on the rear inner tires.	
151 Chassis high idle system shall be connected and operational. 152 Chassis electrical charging/ battery system shall be connected to the module electrical system. 153 New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	149	New mounting hardware shall be installed including: Grade 8 bolts, washers, nylon lock-nuts, spacers, outrigge	rs (Type I units only)
152 Chassis electrical charging/ battery system shall be connected to the module electrical system. 153 New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	150	New mounting bracket for the rear bumper shall be installed to the chassis frame.	
New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	151	Chassis high idle system shall be connected and operational.	
	152		
All power cables connecting the chassis electrical system to the modular electrical system shall be replaced.	153	New Chassis emergency light wiring shall be installed (Grille, Intersection lights, etc.)	
	154	All power cables connecting the chassis electrical system to the modular electrical system shall be replaced.	

REMOUNT PRICING Version 22.0

155	The chassis fuel fill shall be installed in accordance with current QVM standards.
	Modular Air conditioning system shall have a vacuum performed and shall be recharged with 134A Freon with
156	ultra-violet leak identification air conditioning oil dye installed into the system.
157	The module to chassis heater valves and pump shall be replaced.
	Chassis to module attachment shall be finished off via Excellance fabricated close out panels and a rubber
	seal on a Type III units. A cab to module rubber accordion style boot shall be installed on EHD and Type I
158	units.
159	New Front module mounted stone guards.
160	New back-up alarm Reattach all existing Radio wiring disconnected from the chassis by Excellance during the remount process.
	THIS IS LIMITED TO TWO (2) RADIO SYSTEMS - ADDITIONAL PRICING WILL BE ADDED FOR VEHICLES WITH
161	MORE THAN TWO RADIO SYSTEMS - ADDITIONAL PRICING WILL BE ADDED FOR VEHICLES WITH
161	"No Smoking" Fasten Your Seatbelt" sticker shall be installed in the chassis cab.
162	NO SHIOKING T ASIEN TOUR Sealbert. Sticker shall be installed in the chassis cab.
163	APPITIONAL ITEMS TO BE PROVIDED
164	ADDITIONAL ITEMS TO BE PROVIDED
165	A professional Front End Alignment shall be performed on the chassis upon completion of the remount process.
166	The Fuel tank shall be full of fuel upon completion of the remount process.
167	All chassis engine fluid levels shall be inspected and adjusted as necessary.
168	Chassis tire pressure shall be inspected and adjusted as needed.
169	All hinges, latches, locks, door hold open devices etc. shall be lubricated.
170	Headlights shall be adjusted to the proper level.
171	The interior and exterior of the ambulance body and chassis cab shall be professionally washed and detailed.
173	
174	DOCUMENTS AND CERTIFICATIONS TO BE PROVIDED
175	Excellance shall provide electrical diagrams for all circuits added during the remount process.
176	Vehicle shall have a weight certificate documented and installed on the unit.
177	Air Conditioning shall have a certificate documenting Freon capacity.
178	Oxygen leak test and verification sticker shall be installed on the unit.
179	Upon full payment a "Bill of Sale", "Odometer Statement" and receipt shall be provided.
180 181	UNLESS OTHERWISE SPECIFIED IN THIS ORDER, ITEMS THAT ARE REMOVED DURING THE REMOUNT PROCESS SHALL BE REINSTALLED
101	
100	IN THE SAME MANNER WITH WHICH THEY WERE ORIGINALLY INSTALLED ONTO THE NEW CHASSIS AND MODULE BODY. VEHICLES WITH EXCESSIVE
182	EQUIPMENT MAY INCUR ADDED CHARGES FOR EQUIPMENT TO BE TRANSFERRED.
183	ALSO INCLUDED IN THE BASE PRICE FOR "REMOUNTING" AN AMBULANCE:
184	EXCELLANCE WILL PERFORM THE FOLLOWING TASKS UPON THE UNIT ARRIVING AT THE FACTORY:
185 186	Physical Inspection of the Exterior body to include:
187	Structural Damage
188	Condition of paint
189	Condition of striping and lettering
190	light housings
191	Door hardware (handles, hinges & door frames)
	· · · · · · · · · · · · · · · · · · ·

Window Frames

192

REMOUNT PRICING Version 22.0

193			Walk- Through or Pass-Through rubber boots (if applicable)
194			Bumper step (hinges, screws, rivets, rubber dock bumpers)
195			Compartment doors (handles, hinges, skins, drains, venting, etc.)
196			
197			Physical inspection of the Interior Patient Compartment to include:
198			Floor Covering
199			Formica
200			IV hangers
201			Cot Hardware
202			02 outlets
203			Trim (upholstery, aluminum and Trim Lock")
204			Cabinetry (hinges, slides, unistrut, shelves, Plexiglas)
205			Upholstery (seats, head-knockers, arm-rests, etc.)
206			Countertops
207			Attendant Seat and seat base
208			Drawers (slides, latches, etc.)
209			Lighting (lenses, switches, outlets, etc.)
210			Electrical Cabinet (blown fuses, loose wiring, wire chafing, missing components, etc.)
211			
212 213			ALL LOOSE EQUIPMENT ARRIVING WITH THE VEHICLE SHALL BE INVENTORIED, DOCUMENTED AND STORED UPON THE UNIT ARRIVAL TO THE FACTORY. EXCELLANCE SHALL NOT BE RESPONSIBLE FOR UNDOCUMENTED LOOSE EQUIPMENT LEFT IN THE VEHICLE.
214			PHOTOGRAPHS TO DOCUMENT THE CONDITION OF THE UNIT SHALL BE TAKEN UPON THE UNIT ARRIVAL TO THE FACTORY.
215			
216			ANY ADDITIONAL COSTS DUE TO WORK DEEMED NECESSARY BY EXCELLANCE TO THE MODULAR BODY OR CUSTOMER/ DEALER SUPPLIED
217			CHASSIS SHALL BE ASSESSED AS EARLY AS POSSIBLE DURING THE REMOUNT PROCESS. THE CUSTOMER/ DEALER SHALL BE NOTIFIED OF
218			THE NECESSARY WORK AND ASSOCIATED COSTS FOR THEIR WRITTEN APPROVAL.
219			
234			
235			BASE REMOUNT
236			IF CHOOSING THE SAME BRAND AND MODEL CHASSIS
240	(1) Excellance EHD
245	(•	
272			EXCELLANCE CAB & CHASSIS
273 280			EXCELLANCE LITERATURE
281	(1) Wiring diagram of all conversion circuits and Excellance changes & additions
284			SUSPENSION / DRIVE TRAIN
335			CHASSIS WHEEL COVER
390 393	(1) DELETION CREDIT- Do not paint the outer rims of the chassis with white Krylon paint.
JJJ	(1	DELETION ONED 17- DO NOT paint the outer time of the onassis with white fitylon paint.

<u>REMOUNT PRICING</u> <u>Version 22.0</u>

404 707 MODULAR BOD 708 L-1 COMPARTMENT 709 No additional work to be done to this compartment 773 L-3 Compartment 774 No additional work to be done to this compartment 838 L-4 Compartment 839 No additional work to be done to this compartment 903 R-1 Compartment 904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment 1033 R-4 Compartment		
708 L-1 COMPARTMENT 709 No additional work to be done to this compartment 773 L-3 Compartment 774 No additional work to be done to this compartment 838 L-4 Compartment 839 No additional work to be done to this compartment 903 R-1 Compartment 904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment	404	
No additional work to be done to this compartment L-3 Compartment No additional work to be done to this compartment L-4 Compartment No additional work to be done to this compartment R-1 Compartment No additional work to be done to this compartment R-2 Compartment No additional work to be done to this compartment R-2 Compartment No additional work to be done to this compartment	707	MODULAR BODY:
773 L-3 Compartment 774 No additional work to be done to this compartment 838 L-4 Compartment 839 No additional work to be done to this compartment 903 R-1 Compartment 904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment	708	<u>L-1 COMPARTMENT</u>
No additional work to be done to this compartment L-4 Compartment No additional work to be done to this compartment R-1 Compartment No additional work to be done to this compartment R-2 Compartment No additional work to be done to this compartment No additional work to be done to this compartment No additional work to be done to this compartment	709	No additional work to be done to this compartment
838 L-4 Compartment 839 No additional work to be done to this compartment 903 R-1 Compartment 904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment	773	<u>L-3 Compartment</u>
No additional work to be done to this compartment R-1 Compartment No additional work to be done to this compartment R-2 Compartment No additional work to be done to this compartment No additional work to be done to this compartment	774	No additional work to be done to this compartment
903 R-1 Compartment 904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment	838	<u>L-4 Compartment</u>
904 No additional work to be done to this compartment 968 R-2 Compartment 969 No additional work to be done to this compartment	839	No additional work to be done to this compartment
968 <u>R-2 Compartment</u> 969 No additional work to be done to this compartment	903	R-1 Compartment
No additional work to be done to this compartment	904	No additional work to be done to this compartment
	968	R-2 Compartment
1033 R-4 Compartment	969	No additional work to be done to this compartment
	1033	R-4 Compartment

No additional work to be done to this compartment

1034