

## **NEW BUILD SHEET - TYPE III CHEVROLET G3500 GAS**

- 239 The chassis model year shall be: 2023
- 240
- 241 The chassis engine shall be a GAS - powered engine.
- 242 ( 1 ) The cab for the chassis will be ordered "**standard OEM white**" from the chassis manufacturer.
- 252 ( 1 ) The chassis will be SUPPLIED BY EXCELLANCE.
- 253 **Note: Excellence is entitled to OEM concessions on any chassis supplied by Excellence.**
- 299 **CHEVROLET / GMC C/K SERIES (AMBULANCE PREP PKG.)**
- 302
- 309 ( 1 ) **G3500 Short Type III** 96" x 146" box  
310 CA = 80"
- 335
- 347 The vehicle will be ready for delivery w/ electrical diagrams, cleaned, inspected, fuel tanks full,  
348 vehicle serviced, certified weight ticket, and copies of all warranties and owners manuals.  
349 Air tanks installed by Excellence will have manual moisture relief valves.
- 355 ( 1 ) \* Chevrolet/GMC Chassis service manuals: gmupfitter.com
- 361 ( 1 ) \* Running Boards, Diamond Plate with grating and Excellence logo welded  
362 into step area for Type III
- 442 **CUSTOMER NOTES / SPECIAL REQUESTS**
- 443 \*\* Install an engraved aluminum plate with "EXCELLANCE", Unit #, and date of manufacture  
444 on the inside door panel of the L4 compartment. Place either above or below the  
445 standard label. (CAAS Req.)
- 446 \*\* Install an engraved aluminum plate in the cab with the maximum height capacity. (CAAS Req.)
- 451
- 453 **CHASSIS: TIRE / WHEEL**
- 454
- 455 OEM Steel-belted All-Weather Radial tires per chassis specifications
- 456
- 457 ( 1 ) \* There is no spare tire for this ambulance chassis.
- 459
- 471 ( 1 ) \* Wheel Inserts for G-series, "Phoenix" stainless steel w/ rear air valve extension
- 551
- 552 **CHASSIS: EXTERIOR**
- 553
- 607 ( 1 ) \* Mud Flaps, 2 Rear
- 622
- 625 **CHASSIS: INTERIOR CAB**
- 626
- 632 ( 1 ) GM light duty: gray interior cab color
- 640
- 641 ( 1 ) Cab floorboard to have rubber matting
- 657
- 660 **CHASSIS ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**
- 661
- 663 Module disconnect power switch
- 664 ( 1 ) This GM chassis will NOT have the automatic high-idle module in lieu of  
665 the OEM manual activation.
- 667 ( 1 ) Type III light duty includes addition of exterior battery compartment in R4-2  
668 OEM alternator(s) with internal regulator  
671 Back-up alarm, reverse activated
- 685
- 687 **CHASSIS ELECTRICAL SYSTEM: INTERIOR CAB**
- 688

- 689 ( 1 ) Engine cover mounted console on Type III units  
 700 ( 1 ) Map Light, Flex-head Littlelite with red lens (12" shaft) located on front console  
 708 ( 1 ) Volt Meter with Dual USB port installed on console switch panel.  
 710  
 719 ( 1 ) \* Ignition security system, anti-theft device, Kussmaul Safety Lock 3 (CAAS Req.)  
 724 ( 1 ) \* Pro-Vision TV-205 rear camera system with 5" LCD flat screen  
 725 monitor on the cab console. (CAAS Req.)

**MODULAR BODY: STANDARD SPECIFICATIONS**

- 746  
 747  
 748 All aluminum modular ambulance body with 1/4-inch thick aluminum corner extrusions  
 749 ( 1 ) Module headroom shall be 69 inches for this non-EHD unit.  
 753 All aluminum framework with special anti-corrosion barrier applied to all fasteners, hinges, and components  
 754 Aluminum exterior skin shall be .125" thick, attached by continuous welds at all seams and corners  
 755 Aluminum exterior roof skin shall be .125" thick aluminum  
 757 3/4-inch thick composite floor with .063" aluminum subfloor insulated with Polystyrene foam planking  
 758 Install .125" thick Aluminum overlay to the top of the Coosa Board floor  
 762 3 module entry doors and all exterior compartment doors insulated with 2" Styrofoam planking  
 763 ( 1 ) Left rear door shall close with an automatic "slam latch"  
 764 2 key locking module entry door handles all keyed alike  
 765 ( 1 ) Curbside entry door equipped with gas shock and nylon restraint strap to reduce opening and closing force  
 769 Number of grabber / hold-open devices with gaskets: 2  
 770 Polished extruded aluminum drip rails over all module entry doors and exterior compartment doors  
 772 ( 1 ) Fuel fill housing for chassis to be: recessed cast aluminum housing(s)  
 776 1 set aluminum diamondplate stone guards for front of unit  
 778 1 set diamondplate rub rails with aluminum tubular support & plastic spacers off body  
 779 2 aluminum wheelwells  
 780 ( 1 ) 1 set polished cast aluminum module fenderettes  
 783 1 diamondplate rear kick panel  
 784 ( 1 ) 8 body mounting 5/8" diameter Grade 8 bolts w/ heavy duty wear point spacers  
 788 1 custom-made aluminum diamondplate rear bumper with the following features:  
 789 

angled	rear corners
folding	step built into bumper
1	dock bumper(s) each side of bumper

  
 792 All windows installed in the patient compartment come with "privacy glass"  
 793 Fixed window for each rear entry door. Specify size: 12" x 36"  
 795 ( 1 ) Fixed curbside entry door window. Specify size: 18" x 24"

**MODULAR BODY:**

- 812  
 814  
 815  
 819 ( 1 ) Type III: Walk-thru between cab and module with sliding lockable door  
 832 ( 1 ) \* Modify roof structure to add additional tubing allowing module ceiling to be a flat  
 833 surface. Center trough pad will be replaced with a painted cover panel. The roof  
 834 of the module will be double insulated.  
 835 ( 1 ) \* Modify L4 compartment into an upper and lower compartment. The Upper L4/1  
 836 compartment will house the HVAC system facing forward with lines being routed  
 837 around the front of the module to be ducted through the ceiling and at the front bulkhead.  
 838 ( 1 ) \* Cabinet B and Cabinet D above the CPR seat shall be angled.

**CAB / MODULE PAINT AND LETTERING: STANDARD SPECIFICATIONS**

- 870  
 871  
 874 ( 1 ) \* DELETION CREDIT: Do not paint the 4 outer wheels  
 875 Include one touch up paint kit for each color used  
 880 ( 1 ) \* DELETION CREDIT: Delete Federal ambulance markings

**PAINT**

- 881  
 882  
 883  
 884 The cab for the chassis will be ordered and painted standard OEM white.  
 885 ( 1 ) The module shall be painted the same color to match the chassis.

898 ( 1 ) \* Metallic paint will not be used anywhere on this unit.

911

**BELTLINE**

914 ( 1 ) \* DELETE standard 11" reflective beltline stripe

959

**PINSTRIPES**

964 ( 1 ) \* DELETION: No pinstripe tape AND no painted beltline to be applied by factory

970

**LETTERING**

1031

1032

1033 ( 1 ) Excellence supplied/installed lettering is not included but can be provided

1034

**EXTERIOR COMPARTMENTS: STANDARD SPECIFICATIONS**

1053

1054

All exterior compartment doors insulated with 2" styrofoam  
206 latch w/ key locking stainless steel 9000 series D-ring handles with gaskets (where possible)

1055

1058 ( 1 ) Doors equipped with gas shocks to reduce opening and closing force

1065 Machine louvered or plastic venting, as needed, in all exterior compartments

1066 ( 1 ) Battery storage compartment below R4, WITH sliding tray (standard only on Type III)

1074 Note: Battery storage compartment R4-2 to have 52C door latch in lieu of 206 latch

1087

**EXTERIOR COMPARTMENTS:**

1088 All aluminum unistruts to be welded into exterior compartments (no screws or rivets)

1089 \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)

1090

**Compartment L1: (Streetside Rear)**

1091

1092

1093 ( 1 ) Tall L1 version - standard for 146" & 166" modules

1094 ( 1 ) \* Backboard storage in L1 will have 2 adjustable vertical dividers

Type of shelves in L1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	3	0.125"
Fixed shelves	0	0.125"

1096

1097

1098

1100 ( 1 ) Inside / Outside access with interior cabinet door

1106 ( 1 ) One standard LED light in compartment - to be door activated

1127

**Compartment L3/1: (Outside electrical compartment for power distribution panel)**

1128

1135 ( 1 ) One standard LED light in compartment - to be door activated

1144

**Compartment L3/2: (Streetside Intermediate)**

Type of shelves in L3/2:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	1	0.125"
Fixed shelves	0	0.125"

1147

1148

1149

1156 ( 1 ) One standard LED light in compartment - to be door activated

1177

**Compartment L4: (Streetside Forward)**

Type of shelves in L4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

1181

1182

1183

1185 ( 1 ) One standard LED light in compartment - to be door activated

1203

**Compartment R1: (Curbside Rear)**

1205

1206 ( 1 ) Short R1 - standard for 146" module

1208 ( 1 ) Inside / Outside access for Short R1

Type of shelves in Short R1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

1217

1218

1219

1235 ( 1 ) One standard LED light in R1 compartment - to be door activated

1279

**Compartment R4: (Curbside Forward)**

1280

1281 ( 1 ) Inside / Outside access for full height of R4 compartment

1295 ( 1 ) Drug box storage in R4 shall have a locking Painted Aluminum

1296 ( 1 ) Cabinet beside the drug box storage in R4 will have inside / outside

1297 access with a non-locking Painted Aluminum  
 1298 The vertically-hinged doors will be individually latching doors

Type of shelves in R4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	2	0.125"
Fixed shelves	0	0.125"

1308  
 1309  
 1310  
 1311  
 1318 ( 1 ) One standard LED light in compartment - to be door activated  
 1334  
 1417 ( 4 ) Number of exterior compartment(s) to be finished in Excellence texturized paint.  
 1418 Specify each compartment here: ALL - EXCEPT R4 which is to be finished white

**PATIENT COMPARTMENT: STANDARD SPECIFICATIONS**

1491  
 1492  
 1493 Install clear polycarbonate throughout the unit.  
 1497 Full seam-welded NFPA-compliant anti-skid aluminum diamondplate stepwell with flush sweep-out design  
 1498 Door-activated flush-mounted stepwell light, LED  
 1499 3 interior entry door panels, aluminum painted white  
 1500 ( 1 ) Alternating red/white 10" reflective diagonal stripes on each Personnel Door  
 1505 Grab handles for module doors to be: 1.25" diameter seamless stainless steel  
 1506 ( 1 ) Grab handle(s) for the inside of the side entry door: 18" long  
 1508 ( 1 ) Grab handle(s) on each rear door inside the module: "L" shape 33" x 17.5"  
 1509 Aluminum walls painted white  
 1510 Aluminum ceiling finish painted white  
 1511 ( 1 ) Insulation in the module walls and ceiling  
 1513 Welded tubular aluminum cabinet framework with cabinet tubular faces painted white  
 1514 Sliding medical cabinet doors of 1/4" polycarbonate with full height extruded aluminum handles  
 1515 All cabinet interiors are to be painted white  
 1516 Cabinets have Austin latches on hinged cabinet doors and Safety Pins on sliding doors (KKK compliant)  
 1517 Cabinets will be labeled with their rated weight capacity  
 1518 Streetside action area with solid surface counter top  
 1519 The color for all counter tops will be: light gray w/ white & charcoal speckles  
 1527 Action area shelf to have lip  
 1528 Oxygen compartment shall have one polycarbonate hinged access door for "M" & "H" size cylinders  
 1529 Squad bench w/vinyl covered padded split seat cushion and with a hinged lid  
 1530 two 6-point seat belt harnesses: red  
 1531 sets of patient restraint straps: 3 red  
 1532 Squad bench to have a solid vinyl covered padded back rest and head rest  
 1533 2 "No smoking oxygen equipped / Fasten your seatbelt" decals, one in cab and one in module  
 1534 Removable wiring access panels, vinyl padded down the center of the ceiling w/ 1" x 2" tubular supports  
 1535 ( 1 ) # of 72" x 1.25" diameter stainless steel overhead grab rails on 146" module: 2  
 1539 1 CPR seat with vinyl covered padded seat and head protectors  
 1540 CPR seat to have 6-point seat belt harness

**PATIENT COMPARTMENT:**

1563  
 1564  
 1565 Painted white aluminum interior  
 1570 \* High back EMT Captains Chair (Bucket Seat) at Action Area w/ these features:  
 1571 Built-in Child-Safety Seat? No  
 1572 # of seat belt harness points: 6  
 1573 # of arm rests: 0 no arm rests

1577 ( 1 ) \* Sewn upholstery  
 1579 ( 1 ) \* WISE brand

Type of IV holder	Quantity	Mounting location for IV holders:
Rubber shaft fold-down w/ velcro	1	head of primary cot
Rubber shaft fold-down w/ velcro	1	head of squad bench

1619  
 1620 Cabinet over Action Area to have...  
 1621 ( 1 ) Sliding doors that are made of polycarbonate

**BIO-HAZARD / TRASH CONTAINERS:**

- 1689  
 1691 ( 1 ) **Two wall mounted Maxim kits - each kit has one sharpes container and one trash container**  
 1694 ( 1 ) **Maxxim kit(s) to be mounted by Excellence when customer picks up unit**  
 1697 ( 1 ) \* Compartment in top of action area (L3/2 access) for sharpes and trash - (CAAS Req.)  
 1698 Trash with hinged, spring loaded polycarbonate lid; Sharpes to be without lid.

**SEATING / UPHOLSTERY:**

- 1753  
 1754  
 1755 Padded vinyl head protectors over module entryways, color coordinated to match interior  
 1759 ( 1 ) **Gray** color for upholstery (Gray)  
 1768 ( 1 ) **Net at head of Squad Bench, standard 58" x 17" (Red unless specified in Customer Notes)**

**FLOOR COVERING:**

- 1784  
 1785  
 1786  
 1787 Heavy duty vinyl floor covering will be installed inside patient compartment  
 1788 ( 1 ) \* **Lonseal / Lonplate II flooring (this flooring will extend up the side walls)**

Type of floor selected above:	Floor color	Curbside wall covered in:
* Lonseal / Lonplate II flooring	421 Mica	Floor covering

Streetside wall covered in:
Floor covering

**HANDRAILS / MOUNTING BRACKETS:**

- 1807  
 1808  
 1809  
 1810 ( 1 ) All handrails will be stainless steel, knurled, antimicrobial rails painted (powder coated) yellow.

**COT / LITTER MOUNT:**

- 1826 ( Brand ) ( Model )  
 1827 The cot used in this unit will be a: **TBD** | **TBD**  
 1828 The cot will be supplied by: **Customer**  
 1829 The retention system will be supplied by: **Customer**

*Purchaser / Customer agrees to idemnify and hold Excellence harmless for the installation of any cot retention system specified by the Customer that is not compliant with any governmental authority.*

The mounting position for the cot shall be:

- 1833  
 1834 ( 1 ) \* Center mount for one cot  
 1836  
 1838 ( 1 ) **Post and wheel cups will NOT be installed in the patient compartment.**

**THE COT WILL BE SUPPLIED BY CUSTOMER**

**THE RETENTION SYSTEM WILL BE SUPPLIED BY CUSTOMER**

**\*\* Install customer-supplied cot retention system. Excellence can supply upon request.**

**MODULE ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**

- 1869  
 1870 12 VDC electrical distribution system  
 1871 Color and function coded wiring  
 1872 GXL high temperature wiring insulation  
 1873 Automatic reset circuit breakers  
 1874 Heat shrink tubing on all terminals  
 1875 Lighted rocker switches  
 1876 Engraved backlit switch labels  
 1877 1 labeled power distribution panel will be located in the exterior L3/1 compartment  
 1879 Patient compartment control console with hinged access panels in action area  
 1880 12 VDC Medical outlets to be installed as follows:

Type of outlet:	Quantity	Location for outlet(s):
Cigarette	2	Action Area

- 1889  
 1890 Magnetically controlled, hermetically sealed door switches  
 1891 "Module Entry Door Open" warning circuit w/ warning light in cab console  
 1895 Door activated exterior compartment lighting  
 1896 All of the dome lights located on the **curbside** to turn on to low intensity when  
 1897 module entry doors are opened and/or switch on cab console is activated

1898 All switches, indicators and control devices shall be labeled in accordance w/ current KKK-A-1822

1900

1901

**MODULE ELECTRICAL SYSTEM:**

1902

1903

1 Kussmaul #091-32 Load Manager / Sequencer.

1904

Load Manager and status indicator to be located in cab console.

1905 ( 1 )

Excellance will determine load manager circuits and sequence of priority.

1914

1927

2 #RG58U coax antenna cables from center wiring trough to behind driver's seat

1929

\* Location for origination of first "std" coax cable: module center trough

1930

\* Location for termination of first "std" coax cable: behind the cab seat

1931

\* Location for origination of 2nd "std" coax cable: module center trough

1932

\* Location for termination of 2nd "std" coax cable: behind the cab seat

1977 ( 1 )

TruckLite LEDs # 80162C EMT ("Standard" in action area)

1983

1985 ( 1 )

Four Whelen 8-inch LED dome lights mounted in ceiling on streetside

1986 ( 1 )

Four Whelen 8-inch LED dome lights mounted in ceiling on curbside

1996 ( 1 )

\* All ceiling lights to operate with two switches (one for streetside & one for curbside lights).

2048

2049

**125 VAC ELECTRICAL: STANDARD SPECIFICATIONS**

2050

Location for each 125 VAC duplex receptacle (interior to be lighted; exterior to be weatherproof):

2052 ( 1 )

in Action Area

2053 ( 1 )

lower section of the R-4 ALS cabinet

2060

GFI circuit breaker box to be located: mounted in GFI box in electrical panel

2061

First GFI circuit breaker to be wired to: the engine block heater

2062

Second GFI circuit breaker wired to: the 125V electrical system

2077

**SHORELINE**

2078

2079

2080 ( 1 )

One 30 amp / 125 volt Twist Lock Shoreline Plug with weatherproof lift cover (with female Shoreline Input Adapter)

2081

2114

2125 ( 1 )

\* **Shoreline to be mounted :** Side of module forward of L4 hinge

2140

2142

**125 VAC ELECTRICAL EQUIPMENT:**

2143

2147

On-board 15-amp battery charger activated via the shoreline

2166 ( 1 )

\* Pre-wire with switch at EMT panel for inverter to be installed by customer

2167

\* Specify brand & model number of the inverter here: TBD. Excellance can supply & install an inverter.

2200

2202

**SCENE AND EXTERIOR LIGHTS: STANDARD SPECIFICATIONS**

2203

2204

2 backup lights wired to operate with rear scene / load lights

2205

Rear license plate bracket shall be surface mounted on rear of unit with light

2206

1 set of red rear turn marker lights on each side of module using:

2207 ( 1 )

L.E.D. 4" round turn marker lights (part # 44350R)

2211

2212

**WORKLIGHTS / FLOODLIGHTS / SPOTLIGHT:**

2213

2214

The hand-held spotlight will be: recess-mounted on passenger side of front console

2215 ( 1 )

Minimum 100,000 CP lamp handheld spotlight w/ momentary switch (Standard)

2225

2229 ( 1 )

\* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome

2230

flange) on each side of module (in lieu of halogen lights).

2234 ( 1 )

\* DELETE "standard" Whelen 900 side scene lights on each side of module.

2241 ( 1 )

\* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome

2242

flange) on rear wall of module.

2244 ( 1 )

\* DELETE "standard" Whelen 900 rear scene lights.

2245

Note: Scene lights on rear of module will be deleted when rear light bar has scene light option.

2283

2284  
2285  
2286  
2287  
2288  
2289  
2290  
2291  
2417  
2419  
2435  
2436  
2437  
2439  
2440  
2441  
2442  
2455  
2456  
2479  
2480  
2481  
2482  
2484  
2485  
2486  
2487  
2489  
2490  
2491  
2492  
2493  
2494  
2500  
2501  
2502  
2504  
2505  
2506  
2507  
2509  
2510  
2511  
2512  
2513  
2514  
2515  
2516  
2518  
2540  
2541  
2543  
2544  
2549  
2551  
2552  
2555  
2592  
2593  
2594

**TURN SIGNAL / TAIL LIGHTS:**

**Primary brake, turn signal & backup lighting**

The Primary brake, turn signal, and backup lights on the rear of the module will be:  
600 series L.E.D. lights as turn signals set in a triple Horizontal Casting  
600 series L.E.D. lights as brake lights set in a triple Horizontal Casting  
600 series L.E.D. lights as backup lights set in a triple Horizontal Casting

**GRILLE LIGHTS / INTERSECTION LIGHTS**

**Grille Lights** shall be:

( 705 ) Whelen 700 Red L.E.D. w/o flange Lens color: clear

( 705 ) **Intersection Lights** on the driver's side shall be: Whelen 700 Red L.E.D. w/o flange  
( 705 ) **Intersection Lights** on passenger's side shall be: Whelen 700 Red L.E.D. w/o flange

Lens color:  
clear  
clear

**OTHER VISUAL WARNING LIGHTS: STANDARD SPECIFICATIONS**

Flashing light installed at the top center of front module wall shall be:

( 904 ) Whelen 900 series White LED with flange  
The color of the lens for this light is: clear

Flashing lights in each upper corner of the front module wall (2 total) shall be:

( 901 ) Whelen 900 series Red LED w/ flange  
The color of the lens for this light is: clear

\* Install one additional flashing light on the side of the front wall of module.

( 901 ) This curbside light shall be: Whelen 900 series Red LED w/ flange  
( 901 ) This streetside light shall be: Whelen 900 series Red LED w/ flange  
Color of curbside lens shall be: clear Color of streetside lens shall be: clear

Flashing lights in each upper corner of the curbside module wall (2 total) are:

( 901 ) Whelen 900 series Red LED w/ flange  
The color of the lens for this light is: clear

Flashing lights in each upper corner of streetside module wall (2 total) are:

( 901 ) Whelen 900 series Red LED w/ flange  
The color of the lens for this light is: clear

\* **Wheel well lights** on each side of module (2 total) shall be:

( 701 ) Whelen 700 series Red LED w/ flange  
The wheel well light lens color is: clear

Flashing lights in the upper corners of module rear wall (2 total) shall be:

( 901 ) Whelen 900 series Red LED w/ flange  
The color of the lens for this light is: clear

Flashing light installed at the top center of rear module wall shall be:

( 702 ) Whelen 700 series Amber LED w/ flange  
Color for this lens shall be: clear

( 1 ) 1 Whelen AFM-1660 solid state flasher (Standard)  
( 1 ) The flash pattern for the emergency lights shall be programmed as specified by KKK.

**EMERGENCY AUDIBLE WARNING SYSTEM:**

( 1 ) 1 Whelen hands free electronic siren with cab console mounted controls w/ PA microphone

2595 Siren tones to be programmed in "default" mode.  
2599  
2618 **Speaker**  
2619  
2620 ( 1 ) Two through-the-bumper mounted speakers ("standard" on E-350, E-450, G3500, G4500).  
2651  
2653 **OXYGEN AND SUCTION SYSTEMS: STANDARD SPECIFICATIONS**  
2654  
2655 Oxygen system plumbing with cylinder wrench chained in oxygen compartment  
2656  
2657 **Tank Brackets:**  
2658  
2659 ( 1 ) \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)  
2662  
2663 ( 1 ) \* Zico "MultiVersal" restraint system with adjustable bracket for a "M" tank  
2674 1 oxygen regulator, 50 PSI  
2677  
2678 **Oxygen Systems:**  
2693 Ohio-Diamond type oxygen outlets.  
2694 ( 1 ) \* 2 oxygen outlets located at EMT panel, 1 at curbside  
2722  
2742 **Vacuum System:**  
2743  
2744 Sscor suction system with 1 canister and lid, on-off power switch, 5-foot exhaust hose,  
2745 vacuum gauge and internal regulator (no vacuum outlet needed) - to be installed...  
2746 ( 1 ) ... aft of action area control panel on the streetside interior wall.  
2780  
2782 **HVAC SYSTEMS: STANDARD SPECIFICATIONS**  
2783  
2784 12 VDC multi-speed exhaust fan at rear of module  
2785 1 static air intake at front curbside of module  
2786 Floor-level return air plenum with replaceable filter for A/C-heat unit  
2787  
2788 **HVAC SYSTEMS:**  
2789  
2792 ( 1 ) \* Discharge the HVAC system down the length of the patient compartment in  
2793 the ceiling via the "center trough".  
2820 **Ford E-series and Chevy G-series Type III Chassis**  
2821 12 Volt HVAC systems:  
2822 ( 1 ) Heavy duty combination heater / air conditioner system w / digital  
2823 electronic thermostat with digital temperature display.  
2824 ( 1 ) \* Add under-body-mounted auxiliary A/C condenser  
2908  
2910 **FIRE EXTINGUISHER:**  
2911  
2912 ( 2 ) 5# ABC fire extinguishers  
2914 \* Extinguisher mounting instructions: Ship Loose