

## **NEW BUILD SHEET - TYPE III CHEVROLET G4500 GAS**

- 239 The chassis model year shall be: 2023  
240  
241 The chassis engine shall be a GAS - powered engine.  
242 ( 1 ) The cab for the chassis will be ordered "**standard OEM white**" from the chassis manufacturer.  
252 ( 1 ) The chassis will be SUPPLIED BY EXCELLANCE.  
253 **Note: Excellence is entitled to OEM concessions on any chassis supplied by Excellence.**  
299 **CHEVROLET / GMC C/K SERIES (AMBULANCE PREP PKG.)**  
302  
315 ( 1 ) **G4500** **Type III L** 96" x 166" box  
316 CA = 100"  
346  
347 The vehicle will be ready for delivery w/ electrical diagrams, cleaned, inspected, fuel tanks full,  
348 vehicle serviced, certified weight ticket, and copies of all warranties and owners manuals.  
349 Air tanks installed by Excellence will have manual moisture relief valves.  
355 ( 1 ) \* Chevrolet/GMC Chassis service manuals: gmupfitter.com  
361 ( 1 ) \* Running Boards, Diamond Plate with grating and Excellance logo welded  
362 into step area for Type III  
442 **CUSTOMER NOTES / SPECIAL REQUESTS**  
443 **\*\* Install an engraved aluminum plate with "EXCELLANCE", Unit #, and date of manufacture**  
444 **on the inside door panel of the L4 compartment. Place either above or below the**  
445 **standard label. (CAAS Req.)**  
446 **\*\* Install an engraved aluminum plate in the cab with the maximum height capacity. (CAAS Req.)**  
451  
453 **CHASSIS: TIRE / WHEEL**  
454  
455 OEM Steel-belted All-Weather Radial tires per chassis specifications  
456  
457 ( 1 ) \* There is no spare tire for this ambulance chassis.  
459  
471 ( 1 ) \* Wheel Inserts for G-series, "Phoenix" stainless steel w/ rear air valve extension  
551  
552 **CHASSIS: EXTERIOR**  
553  
607 ( 1 ) \* Mud Flaps, 2 Rear  
622  
625 **CHASSIS: INTERIOR CAB**  
626  
632 ( 1 ) GM light duty: gray interior cab color  
640  
641 ( 1 ) Cab floorboard to have rubber matting  
657  
660 **CHASSIS ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**  
661  
663 Module disconnect power switch  
664 ( 1 ) This GM chassis will NOT have the automatic high-idle module in lieu of  
665 the OEM manual activation.  
667 ( 1 ) Type III light duty includes addition of exterior battery compartment in R4-2  
668 OEM alternator(s) with internal regulator  
671 Back-up alarm, reverse activated  
685  
687 **CHASSIS ELECTRICAL SYSTEM: INTERIOR CAB**  
688

- 689 ( 1 ) Engine cover mounted console on Type III units
- 700 ( 1 ) Map Light, Flex-head Littlelite with red lens (12" shaft) located on front console
- 708 ( 1 ) Volt Meter with Dual USB port installed on console switch panel.
- 710
- 719 ( 1 ) \* Ignition security system, anti-theft device, Kussmaul Safety Lock 3 (CAAS Req.)
- 724 ( 1 ) \* Pro-Vision TV-205 rear camera system with 5" LCD flat screen
- 725 monitor on the cab console. (CAAS Req.)

**MODULAR BODY: STANDARD SPECIFICATIONS**

- 745
- 746
- 747
- 748 All aluminum modular ambulance body with 1/4-inch thick aluminum corner extrusions
- 749 ( 1 ) Module headroom shall be 69 inches for this non-EHD unit.
- 753 All aluminum framework with special anti-corrosion barrier applied to all fasteners, hinges, and components
- 754 Aluminum exterior skin shall be .125" thick, attached by continuous welds at all seams and corners
- 755 Aluminum exterior roof skin shall be .125" thick aluminum
- 757 3/4-inch thick composite floor with .063" aluminum subfloor insulated with Polystyrene foam planking
- 758 Install .125" thick Aluminum overlay to the top of the Coosa Board floor
- 762 3 module entry doors and all exterior compartment doors insulated with 2" Styrofoam planking
- 763 ( 1 ) Left rear door shall close with an automatic "slam latch"
- 764 2 key locking module entry door handles all keyed alike
- 765 ( 1 ) Curbside entry door equipped with gas shock and nylon restraint strap to reduce opening and closing force
- 769 Number of grabber / hold-open devices with gaskets: 2
- 770 Polished extruded aluminum drip rails over all module entry doors and exterior compartment doors
- 772 ( 1 ) Fuel fill housing for chassis to be: recessed cast aluminum housing(s)
- 776 1 set aluminum diamondplate stone guards for front of unit
- 778 1 set diamondplate rub rails with aluminum tubular support & plastic spacers off body
- 779 2 aluminum wheelwells
- 780 ( 1 ) 1 set polished cast aluminum module fenderettes
- 783 1 diamondplate rear kick panel
- 785 ( 1 ) 10 body mounting 5/8" diameter Grade 8 bolts w/ heavy duty wear point spacers
- 788 1 custom-made aluminum diamondplate rear bumper with the following features:
- 789 

angled	rear corners
folding	step built into bumper
1	dock bumper(s) each side of bumper
- 790
- 791
- 792 All windows installed in the patient compartment come with "privacy glass"
- 793 Fixed window for each rear entry door. Specify size: 12" x 36"
- 795 ( 1 ) Fixed curbside entry door window. Specify size: 18" x 24"

**MODULAR BODY:**

- 812
- 814
- 815
- 819 ( 1 ) Type III: Walk-thru between cab and module with sliding lockable door
- 832 ( 1 ) \* Modify roof structure to add additional tubing allowing module ceiling to be a flat
- 833 surface. Center trough pad will be replaced with a painted cover panel. The roof
- 834 of the module will be double insulated.
- 835 ( 1 ) \* Modify L4 compartment into an upper and lower compartment. The Upper L4/1
- 836 compartment will house the HVAC system facing forward with lines being routed
- 837 around the front of the module to be ducted through the ceiling and at the front bulkhead.
- 838 ( 1 ) \* Cabinet B and Cabinet D above the CPR seat shall be angled.
- 868

**CAB / MODULE PAINT AND LETTERING: STANDARD SPECIFICATIONS**

- 870
- 871
- 874 ( 1 ) \* DELETION CREDIT: Do not paint the 4 outer wheels
- 875 Include one touch up paint kit for each color used
- 880 ( 1 ) \* DELETION CREDIT: Delete Federal ambulance markings
- 881

**PAINT**

- 882
- 883
- 884 The cab for the chassis will be ordered and painted standard OEM white.
- 885 ( 1 ) The module shall be painted the same color to match the chassis.

898 ( 1 ) \* Metallic paint will not be used anywhere on this unit.

911

**BELTLINE**

914 ( 1 ) \* DELETE standard 11" reflective beltline stripe

959

**PINSTRIPES**

964 ( 1 ) \* DELETION: No pinstripe tape AND no painted beltline to be applied by factory

970

**LETTERING**

1031

1032

1033 ( 1 ) Excellence supplied/installed lettering is not included but can be provided

1052

**EXTERIOR COMPARTMENTS: STANDARD SPECIFICATIONS**

1053

1054

All exterior compartment doors insulated with 2" styrofoam  
206 latch w/ key locking stainless steel 9000 series D-ring handles with gaskets (where possible)

1058 ( 1 ) Doors equipped with gas shocks to reduce opening and closing force

1065 Machine louvered or plastic venting, as needed, in all exterior compartments

1066 ( 1 ) Battery storage compartment below R4, WITH sliding tray (standard only on Type III)

1074 Note: Battery storage compartment R4-2 to have 52C door latch in lieu of 206 latch

1087

**EXTERIOR COMPARTMENTS:**

1088 All aluminum unistruts to be welded into exterior compartments (no screws or rivets)

1089 \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)

1090

1091

**Compartment L1: (Streetside Rear)**

1092 ( 1 ) Tall L1 version - standard for 146" & 166" modules

1093 ( 1 ) \* Backboard storage in L1 will have 2 adjustable vertical dividers

Type of shelves in L1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	3	0.125"
Fixed shelves	0	0.125"

1096 ( 1 ) Inside / Outside access with interior cabinet door

1106 ( 1 ) One standard LED light in compartment - to be door activated

1127

**Compartment L3/1: (Outside electrical compartment for power distribution panel)**

1128 ( 1 ) One standard LED light in compartment - to be door activated

1144

**Compartment L3/2: (Streetside Intermediate)**

Type of shelves in L3/2:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	1	0.125"
Fixed shelves	0	0.125"

1147 ( 1 ) One standard LED light in compartment - to be door activated

1177

**Compartment L4: (Streetside Forward)**

Type of shelves in L4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

1181 ( 1 ) One standard LED light in compartment - to be door activated

1203

**Compartment R1: (Curbside Rear)**

1222 ( 1 ) Tall R1 - standard on 166" & over boxes - includes short R2 unless deleted at

1225 ( 1 ) \* Backboard storage in Tall R1. # of adjust. dividers: 0

Type of shelves in Tall R1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

1227 ( 1 ) Outside access for Tall R1

1228 ( 1 ) One standard LED light in R1 compartment - to be door activated

1252

**Compartment Short R2: (Curbside Rear) Only available if Tall R1 is selected.**

1253 ( 1 ) Inside / Outside access for Short R2

Type of shelves in R2:	Quantity	Thickness of aluminum
------------------------	----------	-----------------------

1260	Adjustable shelves with unistrut	1	0.125"
1261	Fixed shelves	0	0.125"

1263 ( 1 ) One standard LED light in compartment - to be door activated

1279

1280 **Compartment R4: (Curbside Forward)**

1281 ( 1 ) Inside / Outside access for full height of R4 compartment

1295 ( 1 ) Drug box storage in R4 shall have a locking Painted Aluminum

1296 ( 1 ) Cabinet beside the drug box storage in R4 will have inside / outside

1297 access with a non-locking Painted Aluminum

1298 The vertically-hinged doors will be individually latching doors

1308

Type of shelves in R4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	2	0.125"
Fixed shelves	0	0.125"

1318 ( 1 ) One standard LED light in compartment - to be door activated

1334

1417 ( 5 ) Number of exterior compartment(s) to be finished in Excellence texturized paint.

1418 Specify each compartment here: ALL - EXCEPT R4 which is to be finished white

1489

1491 **PATIENT COMPARTMENT: STANDARD SPECIFICATIONS**

1492

1493 Install clear polycarbonate throughout the unit.

1497 Full seam-welded NFPA-compliant anti-skid aluminum diamondplate stepwell with flush sweep-out design

1498 Door-activated flush-mounted stepwell light, LED

1499 3 interior entry door panels, aluminum painted white

1500 ( 1 ) Alternating red/white 10" reflective diagonal stripes on each Personnel Door

1505 Grab handles for module doors to be: 1.25" diameter seamless stainless steel

1506 ( 1 ) Grab handle(s) for the inside of the side entry door: 18" long

1508 ( 1 ) Grab handle(s) on each rear door inside the module: "L" shape 33" x 17.5"

1509 Aluminum walls painted white

1510 Aluminum ceiling finish painted white

1511 ( 1 ) Insulation in the module walls and ceiling

1513 Welded tubular aluminum cabinet framework with cabinet tubular faces painted white

1514 Sliding medical cabinet doors of 1/4" polycarbonate with full height extruded aluminum handles

1515 All cabinet interiors are to be painted white

1516 Cabinets have Austin latches on hinged cabinet doors and Safety Pins on sliding doors (KKK compliant)

1517 Cabinets will be labeled with their rated weight capacity

1518 Streetside action area with solid surface counter top

1519 The color for all counter tops will be: light gray w/ white & charcoal speckles

1527 Action area shelf to have lip

1528 Oxygen compartment shall have one polycarbonate hinged access door for "M" & "H" size cylinders

1529 Squad bench w/vinyl covered padded split seat cushion and with a hinged lid

1530 two 6-point seat belt harnesses: red

1531 sets of patient restraint straps: 3 red

1532 Squad bench to have a solid vinyl covered padded back rest and head rest

1533 2 "No smoking oxygen equipped / Fasten your seatbelt" decals, one in cab and one in module

1534 Removable wiring access panels, vinyl padded down the center of the ceiling w/ 1" x 2" tubular supports

1536 ( 1 ) # of 96" x 1.25" diameter stainless steel overhead grab rails on 166" module: 1

1539 1 CPR seat with vinyl covered padded seat and head protectors

1540 CPR seat to have 6-point seat belt harness

1550

1563 **PATIENT COMPARTMENT:**

1564

1565 Painted white aluminum interior

1570 \* High back EMT Captains Chair (Bucket Seat) at Action Area w/ these features:

1571 Built-in Child-Safety Seat? No

1572 # of seat belt harness points: 6

1573 # of arm rests: 0 no arm rests

1577 ( 1 ) \* Sewn upholstery

1579 ( 1 ) \* WISE brand

1581

1583  
1584  
1585  
1619  
1620  
1621 ( 1 )  
1687  
1688  
1689  
1691 ( 1 )  
1694 ( 1 )  
1697 ( 1 )  
1698  
1753  
1754  
1755  
1756  
1759 ( 1 )  
1768 ( 1 )  
1784  
1785  
1786  
1787  
1788 ( 1 )  
1797  
1798  
1807  
1808  
1809  
1810 ( 1 )  
1823  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834 ( 1 )  
1836  
1838 ( 1 )  
1844  
1845  
1849  
1850  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1879  
1880

Type of IV holder	Quantity	Mounting location for IV holders:
Rubber shaft fold-down w/ velcro	1	head of primary cot
Rubber shaft fold-down w/ velcro	1	head of squad bench

Cabinet over Action Area to have...

Sliding doors that are made of polycarbonate

**BIO-HAZARD / TRASH CONTAINERS:**

Two wall mounted Maxim kits - each kit has one sharpes container and one trash container

Maxim kit(s) to be mounted by Excellence when customer picks up unit

\* Compartment in top of action area (L3/2 access) for sharpes and trash - (CAAS Req.)

Trash with hinged, spring loaded polycarbonate lid; Sharpes to be without lid.

**SEATING / UPHOLSTERY:**

Padded vinyl head protectors over module entryways, color coordinated to match interior

Gray color for upholstery (Gray)

Net at head of Squad Bench, standard 58" x 17" (Red unless specified in Customer Notes)

**FLOOR COVERING:**

Heavy duty vinyl floor covering will be installed inside patient compartment

\* Lonseal / Lonplate II flooring (this flooring will extend up the side walls)

Type of floor selected above:	Floor color	Curbside wall covered in:
* Lonseal / Lonplate II flooring	421 Mica	Floor covering

Streetside wall covered in:
Floor covering

**HANDRAILS / MOUNTING BRACKETS:**

All handrails will be stainless steel, knurled, antimicrobial rails painted (powder coated) yellow.

**COT / LITTER MOUNT:**

The cot used in this unit will be a: ( Brand ) ( Model )  
 TBD | TBD

The cot will be supplied by: Customer

The retention system will be supplied by: Customer

*Purchaser / Customer agrees to idemnify and hold Excellence harmless for the installation of any cot retention system specified by the Customer that is not compliant with any governmental authority.*

The mounting position for the cot shall be:

\* Center mount for one cot

Post and wheel cups will NOT be installed in the patient compartment.

**THE COT WILL BE SUPPLIED BY CUSTOMER**

**THE RETENTION SYSTEM WILL BE SUPPLIED BY CUSTOMER**

**\*\* Install customer-supplied cot retention system. Excellence can supply upon request.**

**MODULE ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**

12 VDC electrical distribution system

Color and function coded wiring

GXL high temperature wiring insulation

Automatic reset circuit breakers

Heat shrink tubing on all terminals

Lighted rocker switches

Engraved backlit switch labels

1 labeled power distribution panel will be located in the exterior L3/1 compartment

Patient compartment control console with hinged access panels in action area

12 VDC Medical outlets to be installed as follows:

1883  
1884  
1889  
1890  
1891  
1895  
1896  
1897  
1898  
1900  
1901  
1902  
1903  
1904  
1905 ( 1 )  
1914  
1927  
1929  
1930  
1931  
1932  
1977 ( 1 )  
1983  
1985 ( 1 )  
1986 ( 1 )  
1996 ( 1 )  
2048  
2049  
2050  
2051  
2052 ( 1 )  
2053 ( 1 )  
2060  
2061  
2062  
2068  
2078  
2079  
2080 ( 1 )  
2081  
2114  
2125 ( 1 )  
2140  
2142  
2143  
2147  
2166 ( 1 )  
2167  
2200  
2202  
2203  
2204  
2205  
2206  
2207 ( 1 )  
2211  
2212  
2213  
2214  
2215 ( 1 )  
2225

Type of outlet:	Quantity	Location for outlet(s):
Cigarette	2	Action Area

Magnetically controlled, hermetically sealed door switches  
 "Module Entry Door Open" warning circuit w/ warning light in cab console  
 Door activated exterior compartment lighting  
 All of the dome lights located on the curbside to turn on to low intensity when  
 module entry doors are opened and/or switch on cab console is activated  
 All switches, indicators and control devices shall be labeled in accordance w/ current KKK-A-1822

**MODULE ELECTRICAL SYSTEM:**

1 Kussmaul #091-32 Load Manager / Sequencer.  
 Load Manager and status indicator to be located in cab console.  
 Excellance will determine load manager circuits and sequence of priority.

2 #RG58U coax antenna cables from center wiring trough to behind driver's seat  
 \* Location for origination of first "std" coax cable: module center trough  
 \* Location for termination of first "std" coax cable: behind the cab seat  
 \* Location for origination of 2nd "std" coax cable: module center trough  
 \* Location for termination of 2nd "std" coax cable: behind the cab seat

TruckLite LEDs # 80162C EMT ("Standard" in action area)  
 Four Whelen 8-inch LED dome lights mounted in ceiling on streetside  
 Four Whelen 8-inch LED dome lights mounted in ceiling on curbside  
 \* All ceiling lights to operate with two switches (one for streetside & one for curbside lights).

**125 VAC ELECTRICAL: STANDARD SPECIFICATIONS**

Location for each 125 VAC duplex receptacle (interior to be lighted; exterior to be weatherproof):

( 1 )	<u>in Action Area</u>
( 1 )	<u>lower section of the R-4 ALS cabinet</u>
	GFI circuit breaker <u>box</u> to be located: <u>mounted in GFI box in electrical panel</u>
	First GFI circuit breaker to be wired to: <u>the engine block heater</u>
	Second GFI circuit breaker wired to: <u>the 125V electrical system</u>

**SHORELINE**

One 30 amp / 125 volt Twist Lock Shoreline Plug with  
 weatherproof lift cover (with female Shoreline Input Adapter)  
 \* **Shoreline to be mounted :** Side of module forward of L4 hinge

**125 VAC ELECTRICAL EQUIPMENT:**

On-board 15-amp battery charger activated via the shoreline  
 \* Pre-wire with switch at EMT panel for inverter to be installed by customer  
 \* Specify brand & model number of the inverter here: TBD. Excellance can supply & install an inverter.

**SCENE AND EXTERIOR LIGHTS: STANDARD SPECIFICATIONS**

2 backup lights wired to operate with rear scene / load lights  
 Rear license plate bracket shall be surface mounted on rear of unit with light  
 1 set of red rear turn marker lights on each side of module using:  
 L.E.D. 4" round turn marker lights (part # 44350R)

**WORKLIGHTS / FLOODLIGHTS / SPOTLIGHT:**

The hand-held spotlight will be: recess-mounted on passenger side of front console  
 Minimum 100,000 CP lamp handheld spotlight w/ momentary switch (Standard)

- 2229 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome
- 2230 flange) on each side of module (in lieu of halogen lights).
- 2234 ( 1 ) \* DELETE "standard" Whelen 900 side scene lights on each side of module.
- 2241 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome
- 2242 flange) on rear wall of module.
- 2244 ( 1 ) \* DELETE "standard" Whelen 900 rear scene lights.
- 2245 **Note: Scene lights on rear of module will be deleted when rear light bar has scene light option.**

2283  
2284

**TURN SIGNAL / TAIL LIGHTS:**

2285  
2286

**Primary brake, turn signal & backup lighting**

2287  
2288

The Primary brake, turn signal, and backup lights on the rear of the module will be:

2289  
2290  
2291  
2361

- 600 series L.E.D. lights as turn signals set in a triple Horizontal Casting
- 600 series L.E.D. lights as brake lights set in a triple Horizontal Casting
- 600 series L.E.D. lights as backup lights set in a triple Horizontal Casting

2419  
2435

**GRILLE LIGHTS / INTERSECTION LIGHTS**

2436  
2437

**Grille Lights shall be:**

( 705 )

Whelen 700 Red L.E.D. w/o flange      Lens color: clear

2439  
2440

Lens color:

( 705 )

**Intersection Lights** on the driver's side shall be:      Whelen 700 Red L.E.D. w/o flange

clear

( 705 )

**Intersection Lights** on passenger's side shall be:      Whelen 700 Red L.E.D. w/o flange

clear

2455  
2456

**OTHER VISUAL WARNING LIGHTS: STANDARD SPECIFICATIONS**

2479  
2480

Flashing light installed at the top center of front module wall shall be:

( 904 )

Whelen 900 series White LED with flange

2482  
2484

The color of the lens for this light is: clear

2485  
2486

Flashing lights in each upper corner of the front module wall (2 total) shall be:

( 901 )

Whelen 900 series Red LED w/ flange

2487  
2489

The color of the lens for this light is: clear

2490  
2491

\* Install one additional flashing light on the side of the front wall of module.

( 901 )

This curbside light shall be: Whelen 900 series Red LED w/ flange

( 901 )

This streetside light shall be: Whelen 900 series Red LED w/ flange

2493  
2494

Color of curbside lens shall be: clear

Color of streetside lens shall be: clear

2500  
2501

Flashing lights in each upper corner of the curbside module wall (2 total) are:

( 901 )

Whelen 900 series Red LED w/ flange

2502  
2504

The color of the lens for this light is: clear

2505  
2506

Flashing lights in each upper corner of streetside module wall (2 total) are:

( 901 )

Whelen 900 series Red LED w/ flange

2507  
2509

The color of the lens for this light is: clear

2510  
2511

\* **Wheel well lights** on each side of module (2 total) shall be:

( 701 )

Whelen 700 series Red LED w/ flange

2512  
2513

The wheel well light lens color is: clear

2514  
2515

Flashing lights in the upper corners of module rear wall (2 total) shall be:

( 901 )

Whelen 900 series Red LED w/ flange

2516  
2518

The color of the lens for this light is: clear

2540  
2541

Flashing light installed at the top center of rear module wall shall be:

( 702 )

Whelen 700 series Amber LED w/ flange

Color for this lens shall be: clear

2544  
2549 ( 1 ) 1 Whelen AFM-1660 solid state flasher (Standard)  
2551  
2552 ( 1 ) The flash pattern for the emergency lights shall be programmed as specified by KKK.  
2555  
2592 **EMERGENCY AUDIBLE WARNING SYSTEM:**  
2593  
2594 ( 1 ) 1 Whelen hands free electronic siren with cab console mounted controls w/ PA microphone  
2595 Siren tones to be programmed in "default" mode.  
2599  
2618 **Speaker**  
2619  
2620 ( 1 ) Two through-the-bumper mounted speakers ("standard" on E-350, E-450, G3500, G4500).  
2651  
2653 **OXYGEN AND SUCTION SYSTEMS: STANDARD SPECIFICATIONS**  
2654  
2655 Oxygen system plumbing with cylinder wrench chained in oxygen compartment  
2656  
2657 **Tank Brackets:**  
2658  
2659 ( 1 ) \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)  
2662  
2663 ( 1 ) \* Zico "MultiVersal" restraint system with adjustable bracket for a "M" tank  
2674 1 oxygen regulator, 50 PSI  
2677  
2678 **Oxygen Systems:**  
2693 Ohio-Diamond type oxygen outlets.  
2694 ( 1 ) \* 2 oxygen outlets located at EMT panel, 1 at curbside  
2722  
2742 **Vacuum System:**  
2743  
2744 Sscor suction system with 1 canister and lid, on-off power switch, 5-foot exhaust hose,  
2745 vacuum gauge and internal regulator (no vacuum outlet needed) - to be installed...  
2746 ( 1 ) ... aft of action area control panel on the streetside interior wall.  
2780  
2782 **HVAC SYSTEMS: STANDARD SPECIFICATIONS**  
2783  
2784 12 VDC multi-speed exhaust fan at rear of module  
2785 1 static air intake at front curbside of module  
2786 Floor-level return air plenum with replaceable filter for A/C-heat unit  
2787  
2788 **HVAC SYSTEMS:**  
2789  
2792 ( 1 ) \* Discharge the HVAC system down the length of the patient compartment in  
2793 the ceiling via the "center trough".  
2820 **Ford E-series and Chevy G-series Type III Chassis**  
2821 12 Volt HVAC systems:  
2822 ( 1 ) Heavy duty combination heater / air conditioner system w / digital  
2823 electronic thermostat with digital temperature display.  
2824 ( 1 ) \* Add under-body-mounted auxiliary A/C condenser  
2908  
2910 **FIRE EXTINGUISHER:**  
2911  
2912 ( 2 ) 5# ABC fire extinguishers  
2914 \* Extinguisher mounting instructions: Ship Loose