

## **NEW BUILD SHEET - TYPE I DODGE RAM 4500 4X2 DIESEL**

239 The chassis model year shall be: 2023

240

241 The chassis engine shall be a DIESEL - powered engine.

242 ( 1 ) The cab for the chassis will be ordered "**standard OEM white**" from the chassis manufacturer.

252 ( 1 ) The chassis will be SUPPLIED BY EXCELLANCE.

253 **Note: Excellence is entitled to OEM concessions on any chassis supplied by Excellence.**

275

276 **DODGE SERIES (AMBULANCE PREP PKG.)**

278

283 ( 1 ) **Dodge 4500 Long Type I** 96" x 172" box

285 2-wheel drive CA = 108"

335

347 The vehicle will be ready for delivery w/ electrical diagrams, cleaned, inspected, fuel tanks full,  
348 vehicle serviced, certified weight ticket, and copies of all warranties and owners manuals.

349 Air tanks installed by Excellence will have manual moisture relief valves.

357 ( 1 ) \* Dodge Chassis service manuals: [rambodybuilder.com](http://rambodybuilder.com)

381

382 **CHASSIS: SUSPENSION**

388

397 ( 1 ) \* Rear LiquidSpring Suspension for Dodge \*\* (see NOTE below)

409 **\*\* WEIGHT ADVISORY: This item affects GVW and payload availability.**

417 ( 1 ) \* Activate "dump" feature automatically when left rear door is open

418 ( 1 ) Override switch at rear of module on curbside door.

426 \* Suspension System installation includes "down" indicator light on front console.

442 **CUSTOMER NOTES / SPECIAL REQUESTS**

443 \*\* Install an engraved aluminum plate with "EXCELLANCE", Unit #, and date of manufacture

444 on the inside door panel of the L4 compartment. Place either above or below the

445 standard label. (CAAS Req.)

446 \*\* Install an engraved aluminum plate in the cab with the maximum height capacity. (CAAS Req.)

451

453 **CHASSIS: TIRE / WHEEL**

454

455 **OEM Steel-belted All-Weather Radial tires per chassis specifications**

456

457 ( 1 ) \* There is no spare tire for this ambulance chassis.

459

469 ( 1 ) \* Wheel Inserts for Dodge 4500, "Phoenix" stainless steel w/ rear valve extension

551

552 **CHASSIS: EXTERIOR**

553

607 ( 1 ) \* **Mud Flaps, 2 Rear**

622

625 **CHASSIS: INTERIOR CAB**

626

636 ( 1 ) Dodge: black/diesel gray interior cab color is the only choice available

640

641 ( 1 ) **Cab floorboard to have rubber matting**

657

660 **CHASSIS ELECTRICAL SYSTEM:**

661

663 **Module disconnect power switch**

- 668 OEM alternator(s) with internal regulator  
671 Back-up alarm, reverse activated  
685  
687 **CHASSIS ELECTRICAL SYSTEM: INTERIOR CAB**  
688  
690 ( 1 ) Floor mounted console on Type I and EHD units  
700 ( 1 ) Map Light, Flex-head Littlelite with red lens (12" shaft) located on front console  
708 ( 1 ) Volt Meter with Dual USB port installed on console switch panel.  
710  
719 ( 1 ) \* Ignition security system, anti-theft device, Kussmaul Safety Lock 3 (CAAS Req.)  
724 ( 1 ) \* Pro-Vision TV-205 rear camera system with 5" LCD flat screen  
725 monitor on the cab console. (CAAS Req.)  
745  
746 **MODULAR BODY:**  
747  
748 All aluminum modular ambulance body with 1/4-inch thick aluminum corner extrusions  
751 ( 1 ) Module headroom shall be 72 inches for this unit.  
753 All aluminum framework with special anti-corrosion barrier applied to all fasteners, hinges, and components  
754 Aluminum exterior skin shall be .125" thick, attached by continuous welds at all seams and corners  
755 Aluminum exterior roof skin shall be .125" thick aluminum  
757 3/4-inch thick composite floor with .063" aluminum subfloor insulated with Polystyrene foam planking  
758 Install .125" thick Aluminum overlay to the top of the Coosa Board floor  
762 3 module entry doors and all exterior compartment doors insulated with 2" Styrofoam planking  
763 ( 1 ) Left rear door shall close with an automatic "slam latch"  
764 2 key locking module entry door handles all keyed alike  
765 ( 1 ) Curbside entry door equipped with gas shock and nylon restraint strap to reduce opening and closing force  
769 Number of grabber / hold-open devices with gaskets: 2  
770 Polished extruded aluminum drip rails over all module entry doors and exterior compartment doors  
772 ( 1 ) Fuel fill housing for chassis to be: recessed cast aluminum housing(s)  
776 1 set aluminum diamondplate stone guards for front of unit  
778 1 set diamondplate rub rails with aluminum tubular support & plastic spacers off body  
779 2 aluminum wheelwells  
780 ( 1 ) 1 set polished cast aluminum module fenderettes  
783 1 diamondplate rear kick panel  
786 ( 1 ) 10 body mounting 5/8" diameter Grade 8 bolts w/ heavy duty wear point spacers & outrigger supports  
788 1 custom-made aluminum diamondplate rear bumper with the following features:  
789 angled rear corners  
790 folding step built into bumper  
791 1 dock bumper(s) each side of bumper  
792 All windows installed in the patient compartment come with "privacy glass"  
793 Fixed window for each rear entry door. Specify size: 12" x 36"  
795 ( 1 ) Fixed curbside entry door window. Specify size: 18" x 24"  
812  
814 **MODULAR BODY:**  
815  
824 ( 1 ) \* Type I: Cabinet below pass-thru window to have dual hinged painted aluminum-faced doors  
832 ( 1 ) \* Modify roof structure to add additional tubing allowing module ceiling to be a flat  
833 surface. Center trough pad will be replaced with a painted cover panel. The roof  
834 of the module will be double insulated.  
835 ( 1 ) \* Modify L4 compartment into an upper and lower compartment. The Upper L4/1  
836 compartment will house the HVAC system facing forward with lines being routed  
837 around the front of the module to be ducted through the ceiling and at the front bulkhead.  
838 ( 1 ) \* Cabinet B and Cabinet D above the CPR seat shall be angled.  
868  
870 **CAB / MODULE PAINT AND LETTERING:**  
871  
874 ( 1 ) \* DELETION CREDIT: Do not paint the 4 outer wheels  
875 Include one touch up paint kit for each color used  
880 ( 1 ) \* DELETION CREDIT: Delete Federal ambulance markings

881  
882  
883  
884  
885  
898  
911  
912  
914  
959  
960  
964  
970  
1031  
1032  
1033  
1034  
1053  
1054  
1055  
1056  
1058  
1065  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1096  
1097  
1098  
1100  
1106  
1127  
1128  
1135  
1144  
1145  
1147  
1148  
1149  
1156  
1177  
1178  
1181  
1182  
1183  
1185  
1203  
1205  
1222  
1225  
1227  
1228  
1229  
1232  
1235  
1252

**PAINT**

The cab for the chassis will be ordered and painted standard OEM white.  
( 1 ) The module shall be painted the same color to match the chassis.  
( 1 ) \* Metallic paint will not be used anywhere on this unit.

**BELTLINE**

( 1 ) \* DELETE standard 11" reflective beltline stripe

**PINSTRIPES**

( 1 ) \* DELETION: No pinstripe tape AND no painted beltline to be applied by factory

**LETTERING**

( 1 ) Excellence supplied/installed lettering is not included but can be provided

**EXTERIOR COMPARTMENTS: STANDARD SPECIFICATIONS**

All exterior compartment doors insulated with 2" styrofoam  
206 latch w/ key locking stainless steel 9000 series D-ring handles with gaskets (where possible)  
( 1 ) Doors equipped with gas shocks to reduce opening and closing force  
Machine louvered or plastic venting, as needed, in all exterior compartments

**EXTERIOR COMPARTMENTS:**

All aluminum unistruts to be welded into exterior compartments (no screws or rivets)  
\* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)

Compartment L1: (Streetside Rear)

( 1 ) Tall L1 version - standard for 146" & 166" modules

( 1 ) \* Backboard storage in L1 will have 2 adjustable vertical dividers

Type of shelves in L1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	3	0.125"
Fixed shelves	0	0.125"

( 1 ) Inside / Outside access with interior cabinet door

( 1 ) One standard LED light in compartment - to be door activated

Compartment L3/1: (Outside electrical compartment for power distribution panel)

( 1 ) One standard LED light in compartment - to be door activated

Compartment L3/2: (Streetside Intermediate)

Type of shelves in L3/2:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	1	0.125"
Fixed shelves	0	0.125"

( 1 ) One standard LED light in compartment - to be door activated

Compartment L4: (Streetside Forward)

Type of shelves in L4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

( 1 ) One standard LED light in compartment - to be door activated

Compartment R1: (Curbside Rear)

( 1 ) Tall R1 - standard on 166" & over boxes - includes short R2 unless deleted at

( 1 ) \* Backboard storage in Tall R1. # of adjust. dividers: 0

Type of shelves in Tall R1:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	0	0.125"
Fixed shelves	0	0.125"

( 1 ) Outside access for Tall R1

( 1 ) One standard LED light in R1 compartment - to be door activated

1253 ( 1 ) Compartment Short R2: (Curbside Rear) Only available if Tall R1 is selected.

1255 ( 1 ) Inside / Outside access for Short R2

Type of shelves in R2:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	1	0.125"
Fixed shelves	0	0.125"

1263 ( 1 ) One standard LED light in compartment - to be door activated

1279

1280 Compartment R4: (Curbside Forward)

1281 ( 1 ) Inside / Outside access for full height of R4 compartment

1295 ( 1 ) Drug box storage in R4 shall have a locking Painted Aluminum

1296 ( 1 ) Cabinet beside the drug box storage in R4 will have inside / outside

1297 access with a non-locking Painted Aluminum

1298 The vertically-hinged doors will be individually latching doors

1308

Type of shelves in R4:	Quantity	Thickness of aluminum
Adjustable shelves with unistrut	2	0.125"
Fixed shelves	0	0.125"

1318 ( 1 ) One standard LED light in compartment - to be door activated

1334

1417 ( 5 ) Number of exterior compartment(s) to be finished in Excellance texturized paint.

1418 Specify each compartment here: ALL - EXCEPT R4 which is to be finished white

1489

### 1491 **PATIENT COMPARTMENT: STANDARD SPECIFICATIONS**

1492

1493 Install clear polycarbonate throughout the unit.

1497 Full seam-welded NFPA-compliant anti-skid aluminum diamondplate stepwell with flush sweep-out design

1498 Door-activated flush-mounted stepwell light, LED

1499 3 interior entry door panels, aluminum painted white

1500 ( 1 ) Alternating red/white 10" reflective diagonal stripes on each Personnel Door

1505 Grab handles for module doors to be: 1.25" diameter seamless stainless steel

1506 ( 1 ) Grab handle(s) for the inside of the side entry door: 18" long

1508 ( 1 ) Grab handle(s) on each rear door inside the module: "L" shape 33" x 17.5"

1509 Aluminum walls painted white

1510 Aluminum ceiling finish painted white

1511 ( 1 ) Insulation in the module walls and ceiling

1513 Welded tubular aluminum cabinet framework with cabinet tubular faces painted white

1514 Sliding medical cabinet doors of 1/4" polycarbonate with full height extruded aluminum handles

1515 All cabinet interiors are to be painted white

1516 Cabinets have Austin latches on hinged cabinet doors and Safety Pins on sliding doors (KKK compliant)

1517 Cabinets will be labeled with their rated weight capacity

1518 Streetside action area with solid surface counter top

1519 The color for all counter tops will be: light gray w/ white & charcoal speckles

1527 Action area shelf to have lip

1528 Oxygen compartment shall have one polycarbonate hinged access door for "M" & "H" size cylinders

1529 Squad bench w/vinyl covered padded split seat cushion and with a hinged lid

1530 two 6-point seat belt harnesses: red

1531 sets of patient restraint straps: 3 red

1532 Squad bench to have a solid vinyl covered padded back rest and head rest

1533 2 "No smoking oxygen equipped / Fasten your seatbelt" decals, one in cab and one in module

1534 Removable wiring access panels, vinyl padded down the center of the ceiling w/ 1" x 2" tubular supports

1536 ( 1 ) # of 96" x 1.25" diameter stainless steel overhead grab rails on 166" module: 1

1539 1 CPR seat with vinyl covered padded seat and head protectors

1540 CPR seat to have 6-point seat belt harness

1550

1565 Painted white aluminum interior

1570 \* High back EMT Captains Chair (Bucket Seat) at Action Area w/ these features:

1571 Built-in Child-Safety Seat? No

1572 # of seat belt harness points: 6

1573 # of arm rests: 0 no arm rests

1577 ( 1 ) \* Sewn upholstery

1579 ( 1 ) \* WISE brand

1581  
 1583  
 1584  
 1585  
 1619  
 1620  
 1621 ( 1 )  
 1687  
 1688  
 1689  
 1691 ( 1 )  
 1694 ( 1 )  
 1697 ( 1 )  
 1698  
 1753  
 1754  
 1755  
 1756  
 1759 ( 1 )  
 1768 ( 1 )  
 1784  
 1785  
 1786  
 1787  
 1788 ( 1 )  
 1797  
 1798  
 1807  
 1808  
 1809  
 1810 ( 1 )  
 1823  
 1825  
 1826  
 1827  
 1828  
 1829  
 1830  
 1831  
 1832  
 1833  
 1834 ( 1 )  
 1836  
 1838 ( 1 )  
 1844  
 1845  
 1849  
 1850  
 1867  
 1868  
 1869  
 1870  
 1871  
 1872  
 1873  
 1874  
 1875  
 1876  
 1877  
 1879

Type of IV holder	Quantity	Mounting location for IV holders:
Rubber shaft fold-down w/ velcro	1	head of primary cot
Rubber shaft fold-down w/ velcro	1	head of squad bench

Cabinet over Action Area to have...

( 1 ) Sliding doors that are made of polycarbonate

**BIO-HAZARD / TRASH CONTAINERS:**

( 1 ) Two wall mounted Maxxim kits - each kit has one sharpes container and one trash container

( 1 ) Maxxim kit(s) to be mounted by Excellence when customer picks up unit

( 1 ) \* Compartment in top of action area (L3/2 access) for sharpes and trash - (CAAS Req.)

Trash with hinged, spring loaded polycarbonate lid; Sharpes to be without lid.

**SEATING / UPHOLSTERY:**

Padded vinyl head protectors over module entryways, color coordinated to match interior

( 1 ) Gray color for upholstery (Gray)

( 1 ) Net at head of Squad Bench, standard 58" x 17" (Red unless specified in Customer Notes)

**FLOOR COVERING:**

Heavy duty vinyl floor covering will be installed inside patient compartment

( 1 ) \* Lonseal / Lonplate II flooring (this flooring will extend up the side walls)

Type of floor selected above:	Floor color	Curbside wall covered in:
* Lonseal / Lonplate II flooring	421 Mica	Floor covering

Streetside wall covered in:
Floor covering

**HANDRAILS / MOUNTING BRACKETS:**

( 1 ) All handrails will be stainless steel, knurled, antimicrobial rails painted (powder coated) yellow.

**COT / LITTER MOUNT:**

The cot used in this unit will be a: ( Brand ) ( Model )  
 TBD | TBD

The cot will be supplied by: Customer

The retention system will be supplied by: Customer

*Purchaser / Customer agrees to idemnify and hold Excellence harmless for the installation of any cot retention system specified by the Customer that is not compliant with any governmental authority.*

The mounting position for the cot shall be:

( 1 ) \* Center mount for one cot

( 1 ) Post and wheel cups will NOT be installed in the patient compartment.

**THE COT WILL BE SUPPLIED BY CUSTOMER**

**THE RETENTION SYSTEM WILL BE SUPPLIED BY CUSTOMER**

\*\* Install customer-supplied cot retention system. Excellence can supply upon request.

**MODULE ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**

12 VDC electrical distribution system

Color and function coded wiring

GXL high temperature wiring insulation

Automatic reset circuit breakers

Heat shrink tubing on all terminals

Lighted rocker switches

Engraved backlit switch labels

1 labeled power distribution panel will be located in the exterior L3/1 compartment

Patient compartment control console with hinged access panels in action area

1880  
1883  
1884  
1889  
1890  
1891  
1895  
1896  
1897  
1898  
1900  
1901  
1902  
1903  
1904  
1905 ( 1 )  
1914  
1927  
1929  
1930  
1931  
1932  
1977 ( 1 )  
1983  
1985 ( 1 )  
1986 ( 1 )  
1996 ( 1 )  
2048  
2049  
2050  
2051  
2052 ( 1 )  
2053 ( 1 )  
2060  
2061  
2062  
2068  
2078  
2079  
2080 ( 1 )  
2081  
2114  
2125 ( 1 )  
2140  
2142  
2143  
2147  
2166 ( 1 )  
2167  
2200  
2202  
2203  
2204  
2205  
2206  
2207 ( 1 )  
2211  
2212  
2213  
2214  
2215 ( 1 )

12 VDC Medical outlets to be installed as follows:

Type of outlet:	Quantity	Location for outlet(s):
Cigarette	2	Action Area

Magnetically controlled, hermetically sealed door switches  
 "Module Entry Door Open" warning circuit w/ warning light in cab console  
 Door activated exterior compartment lighting  
 All of the dome lights located on the curbside to turn on to low intensity when module entry doors are opened and/or switch on cab console is activated  
 All switches, indicators and control devices shall be labeled in accordance w/ current KKK-A-1822

**MODULE ELECTRICAL SYSTEM:**

1 Kussmaul #091-32 Load Manager / Sequencer.  
 Load Manager and status indicator to be located in cab console.  
 Excellance will determine load manager circuits and sequence of priority.

2 #RG58U coax antenna cables from center wiring trough to behind driver's seat  
 \* Location for origination of first "std" coax cable: module center trough  
 \* Location for termination of first "std" coax cable: behind the cab seat  
 \* Location for origination of 2nd "std" coax cable: module center trough  
 \* Location for termination of 2nd "std" coax cable: behind the cab seat

TruckLite LEDs # 80162C EMT ("Standard" in action area)  
 Four Whelen 8-inch LED dome lights mounted in ceiling on streetside  
 Four Whelen 8-inch LED dome lights mounted in ceiling on curbside  
 \* All ceiling lights to operate with two switches (one for streetside & one for curbside lights).

**125 VAC ELECTRICAL: STANDARD SPECIFICATIONS**

Location for each 125 VAC duplex receptacle (interior to be lighted; exterior to be weatherproof):

( 1 )	<u>in Action Area</u>
( 1 )	<u>lower section of the R-4 ALS cabinet</u>
	GFI circuit breaker <u>box</u> to be located: <u>mounted in GFI box in electrical panel</u>
	First GFI circuit breaker to be wired to: <u>the engine block heater</u>
	Second GFI circuit breaker wired to: <u>the 125V electrical system</u>

**SHORELINE**

One 30 amp / 125 volt Twist Lock Shoreline Plug with weatherproof lift cover (with female Shoreline Input Adapter)  
 \* **Shoreline to be mounted :** Side of module forward of L4 hinge

**125 VAC ELECTRICAL EQUIPMENT:**

On-board 15-amp battery charger activated via the shoreline  
 \* Pre-wire with switch at EMT panel for inverter to be installed by customer  
 \* Specify brand & model number of the inverter here: TBD. Excellance can supply & install an inverter.

**SCENE AND EXTERIOR LIGHTS: STANDARD SPECIFICATIONS**

2 backup lights wired to operate with rear scene / load lights  
 Rear license plate bracket shall be surface mounted on rear of unit with light  
 1 set of red rear turn marker lights on each side of module using:  
 L.E.D. 4" round turn marker lights (part # 44350R)

**WORKLIGHTS / FLOODLIGHTS / SPOTLIGHT:**

The hand-held spotlight will be: recess-mounted on passenger side of front console  
 Minimum 100,000 CP lamp handheld spotlight w/ momentary switch (Standard)

- 2225
- 2229 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome flange) on each side of module (in lieu of halogen lights).
- 2230
- 2234 ( 1 ) \* DELETE "standard" Whelen 900 side scene lights on each side of module.
- 2241 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome flange) on rear wall of module.
- 2242
- 2244 ( 1 ) \* DELETE "standard" Whelen 900 rear scene lights.
- 2245 Note: Scene lights on rear of module will be deleted when rear light bar has scene light option.
- 2283

**TURN SIGNAL / TAIL LIGHTS:**

**Primary brake, turn signal & backup lighting**

The Primary brake, turn signal, and backup lights on the rear of the module will be:  
 600 series L.E.D. lights as turn signals set in a triple Horizontal Casting  
 600 series L.E.D. lights as brake lights set in a triple Horizontal Casting  
 600 series L.E.D. lights as backup lights set in a triple Horizontal Casting

**GRILLE LIGHTS / INTERSECTION LIGHTS**

**Grille Lights** shall be:

- 2435
- 2436
- 2437 ( 705 ) Whelen 700 Red L.E.D. w/o flange      Lens color: clear
- 2439
- 2440
- 2441 ( 705 ) **Intersection Lights** on the driver's side shall be:      Whelen 700 Red L.E.D. w/o flange      Lens color: clear
- 2442 ( 705 ) **Intersection Lights** on passenger's side shall be:      Whelen 700 Red L.E.D. w/o flange      clear
- 2455

**OTHER VISUAL WARNING LIGHTS: STANDARD SPECIFICATIONS**

Flashing light installed at the top center of front module wall shall be:

- 2480
- 2481 ( 904 ) Whelen 900 series White LED with flange
- 2482 The color of the lens for this light is: clear
- 2484

Flashing lights in each upper corner of the front module wall (2 total) shall be:

- 2485
- 2486 ( 901 ) Whelen 900 series Red LED w/ flange
- 2487 The color of the lens for this light is: clear
- 2489

\* Install one additional flashing light on the side of the **front wall** of module.

- 2490
- 2491 ( 901 )      This curbside light shall be:      Whelen 900 series Red LED w/ flange
- 2492 ( 901 )      This streetside light shall be:      Whelen 900 series Red LED w/ flange
- 2493      Color of curbside lens shall be:      clear      Color of streetside lens shall be:      clear
- 2494

Flashing lights in each upper corner of the curbside module wall (2 total) are:

- 2500
- 2501 ( 901 ) Whelen 900 series Red LED w/ flange
- 2502 The color of the lens for this light is: clear
- 2504

Flashing lights in each upper corner of streetside module wall (2 total) are:

- 2505
- 2506 ( 901 ) Whelen 900 series Red LED w/ flange
- 2507 The color of the lens for this light is: clear
- 2509

\* **Wheel well lights** on each side of module (2 total) shall be:

- 2510
- 2511 ( 701 ) Whelen 700 series Red LED w/ flange
- 2512      The wheel well light lens color is:      clear
- 2513

Flashing lights in the upper corners of module rear wall (2 total) shall be:

- 2514
- 2515 ( 901 ) Whelen 900 series Red LED w/ flange
- 2516 The color of the lens for this light is: clear
- 2518

Flashing light installed at the top center of rear module wall shall be:

- 2540
- 2541 ( 702 ) Whelen 700 series Amber LED w/ flange

2543 Color for this lens shall be: clear

2544

2549 ( 1 ) 1 Whelen AFM-1660 solid state flasher (Standard)

2551

2552 ( 1 ) The flash pattern for the emergency lights shall be programmed as specified by KKK.

2555

2592 **EMERGENCY AUDIBLE WARNING SYSTEM:**

2593

2594 ( 1 ) 1 Whelen hands free electronic siren with cab console mounted controls w/ PA microphone

2595 Siren tones to be programmed in "default" mode.

2599

2618 **Speaker**

2619

2626 ( 1 ) Two through-the-bumper speakers ("standard" on Dodge RAM chassis)

2651

2653 **OXYGEN AND SUCTION SYSTEMS: STANDARD SPECIFICATIONS**

2654

2655 Oxygen system plumbing with cylinder wrench chained in oxygen compartment

2656

2657 **Tank Brackets:**

2658

2659 ( 1 ) \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)

2662

2663 ( 1 ) \* Zico "MultiVersal" restraint system with adjustable bracket for a "M" tank

2674 1 oxygen regulator, 50 PSI

2677

2678 **Oxygen Systems:**

2693 Ohio-Diamond type oxygen outlets.

2694 ( 1 ) \* 2 oxygen outlets located at EMT panel, 1 at curbside

2722

2742 **Vacuum System:**

2743

2744 Scsor suction system with 1 canister and lid, on-off power switch, 5-foot exhaust hose,

2745 vacuum gauge and internal regulator (no vacuum outlet needed) - to be installed...

2746 ( 1 ) ... aft of action area control panel on the streetside interior wall.

2780

2782 **HVAC SYSTEMS: STANDARD SPECIFICATIONS**

2783

2784 12 VDC multi-speed exhaust fan at rear of module

2785 1 static air intake at front curbside of module

2786 Floor-level return air plenum with replaceable filter for A/C-heat unit

2787

2788 **HVAC SYSTEMS:**

2789

2792 ( 1 ) \* Discharge the HVAC system down the length of the patient compartment in

2793 the ceiling via the "center trough".

2795 **Dodge Type I Chassis**

2796 12 Volt HVAC systems:

2797 ( 1 ) Heavy duty combination heater / air conditioner system w / digital electronic thermostat with

2798 digital temperature display.

2799 ( 1 ) \* Add a second 12 VDC engine mounted compressor for dual independent

2800 12 VDC compressors for cooling the cab and module individually.

2801 ( 1 ) \* Add an under-body-mounted auxiliary A/C condenser

2908

2910 **FIRE EXTINGUISHER:**

2911

2912 ( 2 ) 5# ABC fire extinguishers

2914 \* Extinguisher mounting instructions: Ship Loose