



Key Specifications

Gas
Fuel Type

2,075
lbs Payload

100-Hr
Maintenance
Interval

Engine & Drivetrain

Air Intake	Front Air Intake with Donaldson® Cyclonic Air Filter
Cooling	Liquid
Cylinders Displacement	1,000 cc
Drive System Type	On-Demand 4x4
Engine Type	ProStar 1,000 cc Gas
Fuel System/Battery	Electronic Fuel Injection
Horsepower	39.5 HP
Maintenance Interval	100 Hours (25 Hour initial)
Top Speed	Adjustable up to 40 mph (64 km/h)
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

Dimensions

Bed Box Dimensions (L x W x H)	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,913 lb (868 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	11 in (27.9 cm)
Hitch Towing Rating	2,500 lbs (1,133.9 kg)
Overall Vehicle Size (L x W x H)	157 x 62.5 x 75 in (399 x 159 x 191 cm)
Payload Capacity	2,075 lb (941 kg)
Person Capacity	4
Turning Radius	18.25 ft (5.6 m)
Wheelbase	117 in (297.2 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride
Hitch Type	Standard 2 in (5.08 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Diff lock indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator
Lighting	55W low/ 60W high, LED Tail
Other Standard Features	Horn, Backup Alarm, Password protected, electronically adjustable speed limiting
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

Tires / Wheels

Electronic Power Steering	Standard
Front Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Hubs	Front: Steel; Rear: Ductile Iron
Rear Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Wheels	12 x 6 HD Steel - Gloss Black

Suspension

Front Suspension	9 in (22.9 cm)
Rear Suspension	9 in (22.9 cm)