# Pro XD Full-Size Diesel Crew



### Engine & Drivetrain

Air IntakeFront Air Intake with Donaldson® Cyclonic Air FilterCoolingLiquidCylinders Displacement898 ccDrive System TypeOn-Demand 4x4Engine Type3-Cylinder Kubota® DieselFuel System/BatteryMechanical InjectionHorsepower24.5 HPMaintenance Interval200 Hours (50 Hour initial)Top SpeedAutomatic PVT H/L/N/R/P; Shaft		
Cylinders Displacement898 ccDrive System TypeOn-Demand 4x4Engine Type3-Cylinder Kubota® DieselFuel System/BatteryMechanical InjectionHorsepower24.5 HPMaintenance Interval200 Hours (50 Hour initial)Top Speed26 mph (41 km/h)	Air Intake	Front Air Intake with Donaldson® Cyclonic Air Filter
Drive System TypeOn-Demand 4x4Engine Type3-Cylinder Kubota® DieselFuel System/BatteryMechanical InjectionHorsepower24.5 HPMaintenance Interval200 Hours (50 Hour initial)Top Speed26 mph (41 km/h)	Cooling	Liquid
Engine Type 3-Cylinder Kubota® Diesel   Fuel System/Battery Mechanical Injection   Horsepower 24.5 HP   Maintenance Interval 200 Hours (50 Hour initial)   Top Speed 26 mph (41 km/h)	Cylinders Displacement	898 cc
Fuel System/Battery Mechanical Injection   Horsepower 24.5 HP   Maintenance Interval 200 Hours (50 Hour initial)   Top Speed 26 mph (41 km/h)	Drive System Type	On-Demand 4x4
Horsepower 24.5 HP   Maintenance Interval 200 Hours (50 Hour initial)   Top Speed 26 mph (41 km/h)	Engine Type	3-Cylinder Kubota® Diesel
Maintenance Interval 200 Hours (50 Hour initial)   Top Speed 26 mph (41 km/h)	Fuel System/Battery	Mechanical Injection
Top Speed     26 mph (41 km/h)	Horsepower	24.5 HP
	Maintenance Interval	200 Hours (50 Hour initial)
Transmission/Final Drive Automatic PVT H/L/N/R/P; Shaft	Top Speed	26 mph (41 km/h)
	Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

### Dimensions

Bed Box Dimensions (L x W x H)	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,904 lb (864 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	11 in (27.9 cm)
Hitch Towing Rating	2,500 lbs (1,133.9 kg)
Overall Vehicle Size (L x W x H)	157 x 62.5 x 75 in (399 x 159 x 191 cm)
Payload Capacity	2,075 lb (941 kg)
Person Capacity	4
Turning Radius	18.25 ft ( 5.6 m)
Wheelbase	117 in (297.2 cm)
2	

#### **Brakes**

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park in Transmission + Separate Mechanical Parking Brake Standard

## Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride
Hitch Type	Standard 2 in (5.08 cm) Receiver
Instrumentation	All Digital Gauge, Speedomoter, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Engaged Alarm
Lighting	55W low/ 60W high, LED Tail
Other Standard Features	Horn, Backup Alarm
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

### Tires / Wheels

Electronic Power Steering	Standard
Front Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Hubs	Front: Steel; Rear: Ductile Iron
Rear Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Wheels	12 x 6 HD Steel - Gloss Black

## Suspension

Front Suspension	9 in (22.9 cm)
Rear Suspension	9 in (22.9 cm)