

2000 Double Stack Transport Trailer Technical Specifications

Designed to transport (2) ONE Boat 1660 R ONE Series® boats but can be modified by the department for personal watercraft, R ONE iSeries® inflatable rescue boats and/or other rescue equipment.

Dimensions

| Length | 25' | 7.6 m |
|--|-----------|----------|
| Width | 7' 4" | 2.2 m |
| Height (Trailer Only) | 8' 7" | 2.6 m |
| Height With "R ONE Series®" Boat On Top Rack | 10' 1" | 3 m |
| Weight of Empty Trailer | 1,250 lbs | 567 kg |
| Weight Capacity | 4,000 lbs | 1,814 kg |
| Inside Runner Width | 37.25" | 94.62 cm |
| Axles | 2 | 2 |

Top Rack Lowered Via Electric Winch

- Each rack supports up to a 16' craft(s).
- Includes a *Warn Industries* "VR-10,000" electric winch with a 10,000lb capacity and remote control switch for automated raising/lowering of top rack.
- Surge Brakes on both axles with safety cable
- (2) Spare tires and enclosed battery tray included
- Optional galvanized coating for brackish water
- Allows user to load and unload boats without physically lifting boats higher than 36" off the ground
- Upper rack can be lowered and raised to load/unload boat, locks positively in up-transport position
- Runners are made of SteelPOLY polyethylene material which requires virtually no maintenance



