

OB-380-R Specifications:

- Length 12' 6"
- Beam 6' 5"
- Weight w/ floor: 220 lbs.
- Weight capacity: 6 persons / 1,750 lbs.
- Max HP / Weight: 30 HP / 175 lbs. / Long shaft (20")
- Tube diameter 20"
- Air chambers: 5 chambers with individual inflation valves & pressure relief valves + Keel chamber.
- Seams: RF welded
- Material: Kevlon, synthetic PVC, 1.2 mm 2,222 Dtx.
- Transom 20"
- Factory warranty: 2 Years
- Self-bailing drain

Standard Features:

- Non-skid EVA foam padded aluminum panel floor with anodized aluminum stringers
- Marine-grade plywood transom with Epoxy coating
- Transom splash guards
- Aluminum engine mounting plate
- Transom glued to tubes and bolted for reinforcement
- Black rub strake around perimeter of boat
- Rubbing strakes on keel and tubes
- 6 nylon carrying handles w/ neoprene cover
- Stainless bow handle
- Exterior/Interior lifeline ropes
- 11 Stainless steel interior D-ring tie downs
- 2 Stainless steel heavy-duty tow rings on bow
- 4 Stainless steel heavy-duty tow rings on rear tubes

- (2) Foot pumps with hose & gauge
- (1) Repair kit included
- Bow bag
- Set of Paddles
- Storage bags, (1) for floor panels & (1) for hull
- Optional High-flow Scuppers can be added to boat