# **SPORTSTER**<sup>®</sup>





## **HIGHLIGHTS**

- Limited 3 year, 60,000 mile factory warranty
- -Police Duty Use only
- -Fully Transferable
- -Expires at 3 years or 60,000 miles, whichever comes first

#### **DIMENSIONS**

Length	<b>86 in.</b> (2185 mm)
Overall Width	<b>33.5 in.</b> (850 mm)
Overall Height	<b>44.9 in.</b> (1140 mm)
Seat Height	<b>Laden¹ 25.7 in.</b> (653 mm) <b>Unladen 29.9 in.</b> (760 mm)
Ground Clearance	<b>5.5 in.</b> (140 mm)
Rake (Steering Head)	300
Fork Angle	300
Trail	<b>4.6 in.</b> (117 mm)
Wheelbase	<b>59.6 in.</b> (1515 mm)
Fuel Capacity	-

(warning light at approximately 1 gal.) 3.3 gal. (12.5 L)

# Weight

 As Shipped **545 lb.** (247 kg) • In Running Order **564 lb.** (256 kg) Gross Vehicle Weight Rating 1000 lb. (454 kg) • Gross Axle Weight Rating

- Front

**335 lb.** (152 kg) - Rear **665 lb.** (302 kg)

#### **ENGINE**

Engine		Air-Cooled, Evolution®
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder	
Bore x Stroke		3 in. x 3.811 in.
		(76.2 mm x 96.8 mm)
Displacen	nent	<b>53.9 cu. in.</b> (883 cc)
Compress	sion Ratio	9:1

## **PERFORMANCE**

Engine Torque<sup>2</sup> (per J1349):

 North America 54 ft. lb. @ 3750 RPM (73 Nm @ 3750 RPM)

Lean Angle (per J1168):

• Right 27° • Left

Fuel Economy<sup>3</sup> **51 mpg** (4.6 L/100 km) (EPA estimate - combined MPG)

## **CHASSIS**

Frame

Frame	Mild steel, tubular frame; circular sections; cast junctions
Swingarm	Mild steel, rectangular tube section, stamped junctions; MIG welded
Front Fork	39 mm
Rear Shocks	Coil-over; preload dual-adjustable
WheelsBlac	k 9-Spoke with Machined Highlights
<ul><li>Front</li></ul>	<b>19 in. x 2.15 in.</b> (483 mm x 55 mm)
• Rear	<b>16 in. x 3 in.</b> (406 mm x 76 mm)
Brakes	

Dual-piston front; • Caliper Type dual-piston rear

• Rotor Type (diameter x width): - Front

(300 mm x 5 mm) 10.24 in. x 0.28 in. - Rear (260 mm x 7.1 mm)

• Anti-lock Braking System

Optional

11.8 in. x 0.2 in.

Suspension Travel

• Front Wheel 3.6 in. (92 mm) Rear Wheel 1.6 in. (41 mm)

1 Measurement reflects 180 lb. (81.7 kg) operator weight.

2 Values shown are nominal.
3 The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

Visit H-D.com/Police for additional specifications and available color options.