

S = Standard Equipment A = Available --(dashes) = Not Available D = ADI Available

■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

\* Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Model.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
	R6S	<b>NEW! Interim Model Year Standard Equipment Package</b> , includes (T4L) LED headlamps, (TIJ) Radiator grille, Silver, (JL9) Power front and rear antilock disc brakes with stability control, (NH4) 30 Gal fuel tank - Stainless Steel, and (H72) Medium Ash Gray interior 1 - Standard option content effective with July 2021 Production.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
	C60	<b>Air conditioning</b> , single-zone manual, integral in-dash mounted	S	S	S	S	S	S	S	S
	K34	<b>Cruise control</b> , electronic, automatic	S	S	S	S	S	S	S	S
		<b>Cup holders</b>	S	S	S	S	S	S	S	S
	UIZ	<b>Audio System</b> , AM/FM stereo with CD player, auxiliary jack, USB port and Bluetooth	S	S	S	S	S	S	S	S
	UAD	<b>Audio system feature</b> , 2 speakers	S	S	S	S	S	S	S	S
	AU3	<b>Door locks</b> , power	S	S	S	S	S	S	S	S
	UDH	<b>Driver Information Center</b> , (DIC) (monitors vital functions including diesel exhaust fluid levels (DEF), particulate matter emissions level in the diesel particulate filter (DPF), diesel particulate filter regeneration, service reminders for engine oil, transmission oil, differential oil, power steering fluid, engine oil filter, and fuel filters. The DIC provides fuel economy reporting by average, instant, and trip.)	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
		<b>Floor mats</b>	S	S	S	S	S	S	S	S
		<b>Lighting</b> , interior dome	S	S	S	S	S	S	S	S
	A1F	<b>Seat</b> , front high back bucket driver and passenger, tricot cloth covered reclining high back driver seat with single two-occupant fold down passenger seat	S	S	S	S	S	S	S	S
	N3R	<b>Steering wheel</b> , urethane	S	S	S	S	S	S	S	S
	N33	<b>Steering wheel</b> , tilt and telescopic	S	S	S	S	S	S	S	S
		<b>Storage</b> , door pockets	S	S	S	S	S	S	S	S
		<b>Storage</b> , seatback pockets	S	S	S	S	S	S	S	S
	A31	<b>Windows</b> , power	S	S	S	S	S	S	S	S
		<b>Windshield washer bottle access</b> , on passenger side dash when passenger-side door is open	S	S	S	S	S	S	S	S
	T4L	<b>NEW! LED Headlamps</b> 1 - Included and only available with (R6S) Interim Model Year Standard Equipment Package. Standard option content effective with July 2021 Production.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
	TIJ	<b>NEW! Grille</b> , Silver 1 - Included and only available with (R6S) Interim Model Year Standard Equipment Package. Standard option content effective with July 2021 Production.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
		<b>Daytime Running Lamps</b>	S	S	S	S	S	S	S	S
		<b>Glass</b> , tinted	S	S	S	S	S	S	S	S
	DB5	<b>Mirror</b> , outside left-hand and right-hand dual cab-mounted with integral convex mirror	S	S	S	S	S	S	S	S
	E01	<b>Assist steps</b>	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
	2TA	<b>Tires</b> , front, LT215/85R16 E 115/112 L BW ALS VAR1 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	3TA	<b>Tires</b> , rear, LT215/85R16 E 115/112 L BW ALS VAR1 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	PWJ	<b>Wheels</b> , 16" x 6, K. steel 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	2TB	<b>Tires</b> , front, 225/70R19.5 F 125/123 L BW HWY VAR1 1 - Standard on 4500XD, 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	3TB	<b>Tires</b> , rear, 225/70R19.5 F 125/123 L BW HWY VAR1 1 - Standard on 4500XD, 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	PWK	<b>Wheels</b> , 19.5" x 6", K steel 1 - Standard on 4500XD, 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	CD7	<b>Windshield wiper</b> , pulse, wet arm	S	S	S	S	S	S	S	S
	RQ2	<b>Vehicle Application Truck</b>	S	S	S	S	S	S	S	S
	VXT	<b>Incomplete vehicle certification</b>	S	S	S	S	S	S	S	S
	K45	<b>Air cleaner</b> , heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.	S	S	S	S	S	S	S	S
	TP7	<b>Battery</b> , dual 750 cold-cranking amps, 12-volt, maintenance free	S	S	S	S	S	S	S	S
	JL9	<b>NEW! Brake</b> , 4-wheel antilock, front and rear disc with traction control and stability control 1 - Included and only available with (R6S) Interim Model Year Standard Equipment Package. Standard option content effective with July 2021 Production.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
	JE5	<b>Brakes</b> , 4-wheel antilock, front disc, rear drum, dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system. <b>1 - Not available with (R6S) Interim Model Year Standard Equipment Package.</b>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
	J69	<b>Brake</b> , parking, cable actuated, internal expanding drum type, transmission-mounted	S	S	S	S	S	S	S	S
	I1B	<b>Engine</b> , Diesel 5.2L 4 cylinder, 215 hp [160.3 kW] @2500 rpm, 452 lb-ft of torque [612.8 Nm] @ 1850-2750 rpm (Governed). 16 valve, four cycle, chain-driven dual overhead camshaft valve train, a cast iron cylinder block, and a cast aluminum cylinder head. Turbocharged, inter-cooled, water cooled EGR, direct injection, electronically controlled common rail fuel system and engine cruise control. Oil level check switch and light. Engine warning system with audible warning for low oil pressure, high coolant temperature, and a protection system that will reduce fueling if excessive coolant temperature is detected	S	S	S	S	S	S	S	S
	K40	<b>Exhaust brake</b>	S	S	S	S	S	S	S	S
	N4C	<b>Emissions</b> , 50 state certification	S	S	S	S	S	S	S	S
	NC2	<b>Exhaust</b> , single horizontal outlet	S	S	S	S	S	S	S	S

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
	NH2	<b>Fuel tank</b> , 30 Gallon, (113L), rectangular fuel tank. mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill 1 - Not available with (R6S) Interim Model Year Standard Equipment Package.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
	NH4	<b>NEW! Fuel tank</b> , 30 Gallon, (113L), stainless steel, includes 2 auxiliary fuel ports 1 - Included and only available with (R6S) Interim Model Year Standard Equipment Package. Standard option content effective with July 2021 Production.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>
	KG9	<b>Alternator</b> , 140 amps	S	S	S	S	S	S	S	S
	C7S	<b>GVWR</b> , 14,500 lbs. (6577 kg) 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	C7P	<b>GVWR</b> , 16,000 lbs. (7257 kg) 1 - Standard on 4500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	C7X	<b>GVWR</b> , 17,950 lbs. (8142 kg) 1 - Standard on 5500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	S <sup>1</sup>	S <sup>1</sup>
	GZG	<b>GVWR</b> , 19,500 lbs. (8845 kg) 1 - Standard on 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S <sup>1</sup>	S <sup>1</sup>
	EB4	<b>Wheelbase</b> , 109" (276.9 cm)	S	--	--	--	--	--	--	--
	FNJ	<b>Wheelbase</b> , 132.5" (336.6 cm)	--	S	--	--	--	--	--	--
	FWH	<b>Wheelbase</b> , 150" (381.0 cm)	--	--	S	--	--	--	S	--
	FNW	<b>Wheelbase</b> , 176" (447.0 cm)	--	--	--	S	--	--	--	S
	EM2	<b>Wheelbase</b> , 200" (508 cm) 1 - Only available with exterior color (16U) Arc White. Vehicle build will require additional lead time.	--	--	--	--	S <sup>1</sup>	--	--	--
	EL5	<b>Wheelbase</b> , 212" (538.5 cm) 1 - Only available with exterior color (16U) Arc White. Vehicle build will require additional lead time.	--	--	--	--	--	S <sup>1</sup>	--	--

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
		<b>Frame</b> , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 7.20 cu.in. and RBM 316,800 lb-ft/in per rail.	S	S	S	S	S	S	--	--
		<b>Frame</b> , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 11.89 cu.in. and RBM 523,160 lb-ft/in per rail.	--	--	--	--	--	--	S	S
	FL5	<b>Front axle</b> , 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering. ratio 18.8-20.9:1 1 - Standard on 4500HD, 4500XD and 5500HD only. 2 - Standard on 5500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>2</sup>	--	S	S
	FL9	<b>Front suspension</b> , 6,830 lbs. (3098 kg) tapered leaf, semi-elliptical steel alloy. Includes shock absorbers and stabilizer bar. 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	FL6	<b>Front axle</b> , 7275 lbs. (3300 kg), reverse Elliot "I"-beam 1 - Standard on 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S <sup>1</sup>	S <sup>1</sup>
	FM2	<b>Front suspension</b> , 8,440 lbs. (3828 kg) tapered leaf 1 - Standard on 4500XD, 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	HS6	<b>Rear axle</b> , 11,020 lbs. (4998 kg) R050, full-floating single-speed, with oil lubricated rear wheel-bearings 1 - Standard on 4500HD and 4500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	FU3	<b>Rear Suspension</b> , 12,900 lbs. (5851 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>

Free Flow RPO Code	Ref. Only RPO Code	Description 1 - Available on CT*1003 models (all vehicles). 2 - Available on CT*2003 models (all vehicles). 3 - Available on CT*3003 models (all vehicles). 4 - Available on CT*4003 models (all vehicles). 5 - Available on CT*5003 models (5500HD and 5500XD only). Vehicle build will require additional lead time. 6 - Available on CT66003 model (5500XD only). Vehicle build will require additional lead time. 7 - Available on CT*4043 models (all vehicles).	Reg. Cab						Crew Cab	
			1WT 109" WB <sup>1</sup>	1WT 132.5" WB <sup>2</sup>	1WT 150" WB <sup>3</sup>	1WT 176" WB <sup>4</sup>	1WT 200" WB <sup>5</sup>	1WT 212" WB <sup>6</sup>	1WT 150" WB <sup>7</sup>	1WT 176" WB <sup>8</sup>
	FU5	<b>Rear Suspension</b> , 14,308 lbs. (6490 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers 1 - Standard on 4500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	HS9	<b>Rear axle</b> , 14,550 lbs. (6600 kg) 1 - Standard on 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	FU6	<b>Rear Suspension</b> , 14,550 lbs. (6599 kg) 1 - Standard on 5500HD and 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S	S <sup>1</sup>	S <sup>1</sup>
	005	<b>Rear axle</b> , 4.56 ratio 1 - Standard on 4500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	029	<b>Rear axle</b> , 4.77 ratio 1 - Standard on 4500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	--	S <sup>1</sup>	S <sup>1</sup>
	062	<b>Rear axle</b> , 5.12 ratio 1 - Standard on 5500HD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	--	S <sup>1</sup>	S <sup>1</sup>
	011	<b>Rear axle</b> , 5.57 ratio 1 - Standard on 5500XD only.	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S <sup>1</sup>	S	S <sup>1</sup>	S <sup>1</sup>
	IR7	<b>Transmission</b> , 6-speed automatic Aisin A465 transmission with fifth and sixth gear overdrive with lock up in 2nd, 3rd, 4th, 5th and 6th, PTO capability automatic torque converter lockup in stationary PTO mode.	S	S	S	S	S	S	S	S