

# 300G SERIES AIR-COOLED MIDMOUNT™

Powerful. Fuel Efficient.  
Economical.



Model 337G5

LIMITED WARRANTY†

**3 YEAR**

— G4 – 1000 HOURS —  
— G5 – 1250 HOURS —

COMMERCIAL

**4 YEAR**

— 800 HRS —  
RESIDENTIAL

The 300G Series models are equipped with the Vanguard EFI engine, with closed-loop electronic fuel injection. EFI technology provides a wide range of benefits including better fuel economy, reliable hot and cold weather starts, reduced engine exhaust emissions and fewer fuel-related service issues.

Hydro-Gear transmissions feature self-contained, heavy-duty commercial transaxles that provide powerful, Grasshopper-smooth response, while integrated cooling fans and 1-3/8-inch axles extend service life. Enjoy best-in-class transmission fluid change intervals, reducing costs and maintenance.

5.5-inch deep DuraMax® decks, with anvil-edged design for exceptional durability, easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional Mulching Kits and PowerVac™ Collection Systems are available.

The Premium Comfort Seat on the G4 model provides 2-inch fore and aft adjustment and is covered with breathable, CoolTemp Cordura® fabric that dissipates heat and won't tear or crack with extended use. Iso-mounting absorbs and reduces vibration before it reaches the seat. Coil-spring suspension and foldable, padded armrests add up to all-day comfort for the operator.

The G5 model features a Grammer Premier Suspension Seat covered with exclusive CoolTemp Cordura. This seat offers the ultimate in customized operator fit. It adjusts to the individual operator's weight and slides fore and aft. The backrest tilts and includes adjustable lumbar support. Adjustable, foldable, padded armrests complete the comfort features of this seat.

QuikAjust Tilt™ dual steering levers on all 300G models provide 9 inches of "no tools" adjustment for maximum comfort and fit while maintaining natural arm and wrist positions. The hydraulically dampened levers deliver a smooth, responsive ride and return to neutral when released from both forward and reverse.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

The 13.0 gal/49.2 L single-fill fuel tank location lowers the center of gravity, providing more traction and stability for an enhanced ride. The rear bumper protects the rear of the mower while preserving easy access and removal of the service shield.

**328G4**  
EFI

52 61

810cc, V-Twin Vanguard,  
Delphi®-based closed-loop,  
Electronic Fuel Injection  
gasoline engine

**337G5**  
EFI

61 72

993cc, V-Twin Vanguard,  
Delphi®-based closed-loop,  
Electronic Fuel Injection  
gasoline engine

Increase your productivity with speeds  
up to 11.0 mph and 7.20 acres per hour  
with a 72-inch cutting deck.\*



## OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (see page 8)
- » Down Discharge™ mulching packages (see page 7)
- » Speed-Trimming™ heavy-duty anti-scalp roller for 61" and 72" decks (see page 7)
- » TrimAide™ anti-scalp roller for 52" deck (see page 7)
- » DuraFlex™ suspension forks (see page 9)
- » LED work lights (Standard G5 models)
- » Extended steering levers
- » Big Boy wide-seat conversion kit
- » Premier Suspension Seat (see page 3) (Standard on G5 models)
- » Premium Comfort Seat (see page 3) (Standard on G4 models)
- » Footrest Riser (see page 3)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® Airless Turf Tire (24 x 12-12) (see page 9)
- » Michelin® X® Tweel® Airless Front Tires (13 x 6.5-6) (see page 9)
- » Flat-proof front tires (see page 9)
- » Edge-EZE™ edger
- » Shielded sprayer
- » Sunshade Canopy (for ROPS) (see page 9)
- » Yellow beacon light
- » Filter minder (see page 9)
- » Side discharge control kit (see page 7)
- » Air Dam Kit (see page 8)

# AIR-COOLED 300G SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	328G4 52	328G4 61	337G5 61	337G5 72
<b>ENGINE</b>				
<b>Type/Displacement/Cylinders</b>				
B&S Vanguard EFI/49.4 cu. in. (810cc)/V-twin	•	•		
B&S Vanguard EFI/60.6 cu. in. (993cc)/V-twin			•	•
<b>Lubrication System</b>				
Pressure Lube, Filter				
<b>Crankshaft / Cooling System</b>				
Vertical / Air				
<b>Fuel / Capacity</b>				
Gasoline - unleaded / 13 U.S. Gal (49.2 L)				
<b>Air Cleaner</b>				
Heavy-duty, cyclonic, remote-mounted engine dual cleaner with replaceable element				
<b>Muffler</b>				
Ultra-quiet, single, industrial type				
<b>MOWING DECKS</b>				
<b>Construction (Robotic-welded steel)</b>				
Double-layered 10-gauge plus 7-gauge formed steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength.				
Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.				
<b>Blades (MARBAIN®, 1/4-in.)</b>				
(3) 18 in. (45.7 cm)	•			
(3) 21 in. (53.3 cm)		•	•	
(3) 25 in. (63.5 cm)				•
<b>Spindle Assemblies</b>				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Spindle cone designed to eliminate fiber wrap. Double bearings, non-greasable.				
<b>Spindle Housing</b>				
8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern.				
<b>Spindle Cones</b>				
Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.				
<b>QuikAjust™ DropPin™ Height Adjustment</b>				
Foot-controlled height adjustment pedal with pin				
<b>Cutting Height Range</b>				
1.0 – 5.0 in. (2.5 – 12.7 cm) in 1/4-inch increments				
<b>Blade Drive</b>				
Belt drive with single Kevlar V-belt & idler arm tensioning				
<b>STARTER &amp; ELECTRICAL SYSTEM</b>				
<b>Maintenance-Free Battery/Charging Capacity/Starter</b>				
12 Volt/20 amp/solenoid shift	•	•	•	•
12 Volt/25 amp/solenoid shift				
<b>Ignition</b>				
Breakerless				
<b>Interlock System</b>				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.				
<b>ULTIMATE OPERATOR STATION™</b>				
<b>Operator Seat</b>				
Premium Comfort Seat with sliding function	•	•	○	○
Premier Suspension (Grammer) Seat – slides fore and aft and adjusts to operator's size and weight	○	○	•	•
<b>Suspension</b>				
Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™).				
<b>Console-Mounted Instruments</b>				
Low engine oil pressure, combination electronic fuel gauge/hour meter, engine code light and parking brake warning lights, ignition and push/pull PTO switches.				
<b>Work Lights (Pre-wired)</b>				
LED	○	○	•	•

• Standard ○ Option

MODEL - CUTTING WIDTH	328G4 52	328G4 61	337G5 61	337G5 72
<b>TRANSMISSION &amp; STEERING</b>				
<b>Type</b>				
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans. Integrated transaxles with 12cc piston pumps and gear reduction, internal disc brakes, and 1-3/8 inch axles.	•	•		
Heavy-duty Hydro-Gear ZT-5400 hydrostatic transmissions with cooling fans. Integrated transaxles with 16cc piston pumps and gear reduction, internal disc brakes, and 1-3/8 inch axles.			•	•
<b>Filtration/Hydro Fluid</b>				
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change.				
<b>Speed</b>				
0 – 10.5 mph (0 – 16.9 kph) forward	•	•		
0 – 11.0 mph (0 – 17.7 kph) forward			•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•
<b>Turning Radius</b>				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.				
<b>Steering</b>				
One- or two-handed operation with QuikAjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position.				
<b>Brakes</b>				
Dynamic braking through hydrostatic transmission				
<b>Parking Brake</b>				
Internal disc brake in transmission.				
<b>TIRE SIZES</b>				
<b>Drive Wheels – Standard (5-bolt pattern)</b>				
24 x 12-12 turf type, 4-ply rated	•	•		
26 x 12-12 turf type, 6-ply rated			•	•
24 x 12-12 Airless Turf Tweel Drive Wheel	○	○	○	○
<b>Front Casters</b>				
13 x 6.5-6; rib tread, pneumatic with double-sealed bearings to protect from grass wrap				
13 x 6.5-6; Airless Tweel Caster Wheel	○	○	○	○
<b>DIMENSIONS (Mower &amp; Deck)</b>				
<b>Mulch Width/Length</b> (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)				
53.5 in. (135.9 cm)/84.0 in. (213.4 cm)	•			
62.5 in. (158.8 cm)/85.0 in. (215.9 cm)		•	•	
73.5 in. (186.7 cm)/89.0 in. (226.9 cm)				•
<b>Height (Seat back)</b>				
49.5 in. (125.7 cm)	•	•		
49.0 in. (124.5 cm)			•	•
<b>Height (Seat cushion)</b>				
33.0 in. (83.8 cm)	•	•		
35.0 in. (88.9 cm)			•	•
<b>Height (ROPS)</b>				
70.0 in. (177.8 cm)	•	•		
72.0 in. (182.9 cm)			•	•
<b>Drive Tire Track Width (outside edge to outside edge)</b>				
53.0 in. (134.6 cm)	•	•		
54.5 in. (138.4 cm)			•	•
<b>WEIGHT</b>				
Uncrated*: (Mower & Deck) 1140 lbs. (517.1 kg)	•			
Uncrated*: (Mower & Deck) 1190 lbs. (539.8 kg)		•		
Uncrated*: (Mower & Deck) 1260 lbs. (571.2 kg)			•	
Uncrated*: (Mower & Deck) 1340 lbs. (607.8 kg)				•

\*DuraMax® deck mulching package kit weights with high-low mulching blades:  
52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)