| Specifications                                |                           |  |
|---|---------------------------|--|
|   | DX140LC-5                 |  |
| Configuration                                 | US20 US40                 |  |
| Engine  |                           |  |
| Model   | DX140LC-5                 |  |
| Rated Flywheel Power (Gross)                  | 115.2 hp @ 2,000 rpm      |  |
| Rated Horse Power (Net)                       | 109.4 hp @ 2,000 rpm      |  |
| Max. Torque (Net)                             | 369 lbf·ft @ 1,400 rpm    |  |
| Engine Emissions Tier (EPA)                   | T4                        |  |
| Engine After Treatment                        | CEGR+DOC+SCR with DEF     |  |
| Engine Make                                   | Perkins                   |  |
| Engine Name                                   | Perkins 1204F             |  |
| Engine Number of Cylinders                    | 4                         |  |
| Engine Displacement                           | 269 in <sup>3</sup>       |  |
| Hydraulic System                              | 200 111                   |  |
| Main Pump: Displacement                       | 3.48 in <sup>3</sup> /rev |  |
|   | 3.46 m /164               |  |
| Control Valve: Relief Valve Pressure (Normal) | 4,694 psi                 |  |
| Control Valve: Relief Valve Pressure (Boost)  | 4,978 psi                 |  |
| Main Pump: Max. Flow Rate (each)              | 30.12 gal/min             |  |
| Main Pump: Quantity                           | 2                         |  |
| Main Pump: Main Relief Pressure               | 1,294 psi                 |  |
| Undercarriage                                 |                           |  |
| Upper Rollers: Quantity Per Side              | 1                         |  |
| Lower Rollers: Quantity Per Side              | 7                         |  |
| Track Length                                  | 12' 3"                    |  |
| Track Link: Track Gauge                       | 6' 6"                     |  |
| Ground Clearance                              | 1' 4"                     |  |
| Ground Pressure                               | 5.26 psi                  |  |
| Swing Mechanism                               | 5.20 ps.                  |  |
| Swing Performance: Max Swing Torque           | 34718 lbf·ft              |  |
| Swing Performance: Max Swing Speed (At        | 0 11 20 101 10            |  |
| Efficiency)                                   | 10.7 rpm                  |  |
| Travel System/Drive Mechanism                 |                           |  |
| Travel performance: Traction Force (Highest   |                           |  |
| Value)  | 35935 lbf·ft @ 100 %      |  |
| Travel performance: Traveling Speed - Low     |                           |  |
| (XXX/)  | 1.84 mph                  |  |
| Travel performance: Traveling Speed - High    |                           |  |
| (/XXX)  | 3.08 mph                  |  |
| Travel performance: Gradeability              | 70°                       |  |
| Weights                                       | I                         |  |
| Operating Weight                              | 32,783 lb 34,987 lb       |  |
| Standard Boom Length                          | 15.09 ft                  |  |
| Standard Arm Length                           | 9.84 ft                   |  |

| Standard Bucket Size                      | 0.59 yd³          |                   |  |
|---|-------------------|-------------------|--|
| Shoe Width                                | 1' 11"            |                   |  |
| Dimensions                                |                   |                   |  |
| Shipping Height - Hose (With Attachment)  | 10' 5"            |                   |  |
| Shipping Length (Without Attachment)      | 25' 0"            |                   |  |
| Shipping Width (Standard)                 | 8' 5"             |                   |  |
| Overall Height Over Cab                   | 9' 1"             |                   |  |
| Working Range                             |                   |                   |  |
| Max Digging Reach (Ground)                | 27' 11"           |                   |  |
| Max Digging Height                        | 28' 8"            |                   |  |
| Max Digging Depth                         | 20' 1"            |                   |  |
| Max Loading Height                        | 21' 1"            |                   |  |
| Digging Force (ISO)                       |                   |                   |  |
| Arm Digging Force - Pressure up           | 13,228 lb         |                   |  |
| Bucket Digging Force - Pressure up        | 24,471 lb         |                   |  |
| Arm Digging Force - Normal                | 12,346 lb         |                   |  |
| Refill Capacities                         |                   |                   |  |
| Fuel Tank                                 | 70.01 gal         |                   |  |
| Hydraulic System                          | 44.91 gal         |                   |  |
| Engine Coolant                            | 7.13 gal          |                   |  |
| Engine Oil                                | 2.64 gal          |                   |  |
| Hydraulic Tank                            | 38.3 gal          |                   |  |
| Environment                               |                   |                   |  |
| Noise Level: Guaranteed Sound Power Level | 101 dBA           |                   |  |
| Noise Level: Operator                     | 70 dBA            |                   |  |
| Lift Capacity                             |                   |                   |  |
| Lifting Capacity over front @ Horizontal  |                   |                   |  |
| Distance - 10 ft Above Ground             | 9,500 lb @ 15 ft  | 9,500 lb @ 15 ft  |  |
| Lifting Capacity over front @ Horizontal  |                   |                   |  |
| Distance - Ground Level                   | 11,180 lb @ 15 ft | 12,770 lb @ 15 ft |  |
| Lifting Capacity over front @ Horizontal  |                   |                   |  |
| Distance - 10 ft Below Ground             | 10,990 lb @ 15 ft | 12,570 lb @ 15 ft |  |
| Lifting Capacity over front @ Horizontal  |                   |                   |  |
| Distance - 3m Above Ground                |                   |                   |  |
| Lifting Capacity over front @ Horizontal  |                   |                   |  |
| Distance - 3m Below Ground                |                   |                   |  |