# **Dynapac F80W**

## Mini pavers





### **Technical data**

Masses	
Tractor weight (incl. standard screed)	2,500 lbs
Dimensions	
Basic width	33 in

33 in
99 in
10 in
65 in

Capacity	
Paving thickness (max/min)	0.2 -3.9 in
Theoretical placement capacity	38 t/h

Undercarriage	
Final drive	Hydrostatic
Front wheels (Qty x W x D)	1x 13 /6
Rear wheels	2x 17 /5
Turning radius (inside)	37 in

Propulsion	
Paving speed	0-82 ft/min
Transport speed	0-3 mph

Engine	
Manufacturer/Model	Hatz 1B40
Rated power	8.5 HP
Туре	Air cooled
Electrical system	12 V
Fuel tank capacity	1.3 gal

Material hopper	
Capacity	21 cu ft

<b>E</b> Conveyor	
Conveyor control	Automatic with limit switch and flow gates
Conveyor type	One conveyor, reversible


FFC Auger	
Auger control	Automatic with limit switch
Auger diameter	4.72 in


## **Dynapac F80W**

### Mini pavers



### **Technical data**





Dimensions	
B. Width	33 in
H1. Height	60 in
H2. Height, operator platform	16.5 in
L1. Length	112.5 in
L2. Length, transport	99 in
L3. Length, hopper	65.5 in



### Optional equipment

- Mechanical extensions (2x 7 in) till 65 in

- Twin wheels
  Hopper filling help
  Additional auger LED light
  Front wheel scraper

Suitable screeds					
Model	Basic width	Working width, hydraulic extendable	Working width, max.	Compacting elements	Heating system
Dynapac V1300V	2.62 ft	4.27 ft	5.41 ft	Vibration	Propane (LPG)