

Dynapac MF2500CS

Mobile feeders



Technical data



Masses

Transport mass	44,092.68 lbs
----------------	---------------



Dimensions

Transport length	30 ft
Transport width	8 ft
Transport height	10 in
Front ramp angle	10°



Material hopper

Dumping height, center	20.59 in
------------------------	----------



Propulsion

Operating speed, max	82 ft/min
Transport speed, max	2.5 mph



Engine

Manufacturer/Model	Cummins QSB 6.7-C220
Rated power, SAE J1995	220 hp
Electrical system	24 V
Emissions according to	Stage 3A /Tier 3
Fuel tank capacity	79 gal



Engine

Manufacturer/Model	Cummins QSB 6.7-C225
Rated power, SAE J1995	168 kW (225 hp) @ 2,200 rpm
Electrical system	24V
Emissions according to	Stage 4 /Tier 4f



Conveyor

Conveyor type	Rubber belt on two chains mounted with metal stiffeners.
Conveyor speed	Constantly variable
Conveyor width	47.24 in
Feeding height	85.83 in
Feeding height (max/min)	110 in /86 in
Feed capacity	4000 t/h
Feed capacity, optional swing conveyor	2000 t/h

Find us locally at www.dynapac.us

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.
The above information is a general description only, all informations are supplied without liability.



dynapac_mf2500cs_us-20180504.101028.pdf 2018-05-04 10:10

Dynapac MF2500CS

Mobile feeders



Technical data



Dimensions	
A. Axle track	154 in
B1. Width, max.	100 in
B2. Width, standard	8 ft
B3. Width, wheel track	82 in
C1. Track width	13 in
H1. Height, max.	157 in
H2. Height, transport	10 in
H3. Height	22.44 in
H4. Height, max.	16 ft
L1. Length	30 ft
L3. Length, hopper	90.16 in

Find us locally at www.dynapac.us

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.
The above information is a general description only, all informations are supplied without liability.