Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471

A proposal for NC SHERIFFS ASSOCIATION

Prepared by **PIEDMONT TRUCK CENTER, INC.** Todd Lenhart

Apr 14, 2022

Western Star 47X

Components shown may not reflect all spec'd options and are not to scale

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis 04/14/2022 10:33 AM

Page 1 of 14

SPECIFICATION PROPOSAL

	Description
Price Level	
	WST 47X/49X PRL-26X (EFF:07/26/21)
DetaManstan	
Data Version	
	SPECPRO21 DATA RELEASE VER 043
Vehicle Configuration	on
	WESTERN STAR 47X
	2023 MODEL YEAR SPECIFIED
	SET BACK AXLE - TRUCK
	TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560
	LH PRIMARY STEERING LOCATION
General Service	
	TRUCK/TRAILER CONFIGURATION
	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	CONSTRUCTION SERVICE
	GOVERNMENT BUSINESS SEGMENT
	DIRT/SAND/ROCK COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	WESTERN STAR VOCATIONAL WARRANTY
	EXPECTED FRONT AXLE(S) LOAD: 12000.0 lbs
	EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs

	Description
	EXPECTED GROSS COMBINATION WEIGHT :
	52000.0 lbs
Truck Service	
	END DUMP BODY
	GODWIN MANUFACTURING COMPANY
Engine	
	CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT @ 1200 RPM
Electronic Paramete	ers
	75 MPH ROAD SPEED LIMIT
Engine Equipment	
	2010 EPA/CARB/GHG21 CONFIGURATION
	NO 2008 CARB EMISSION CERTIFICATION
	STANDARD OIL PAN
	ENGINE MOUNTED OIL CHECK AND FILL
	SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER
	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES
	BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL
	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB
	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN
	UNPOLISHED ALUMINUM WST BATTERY BOX COVER
	CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE
	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM
	CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS
	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH

STANDARD EXHAUST SYSTEM LENGTH

RH STANDARD HORIZONTAL TAILPIPE

8 GALLON DIESEL EXHAUST FLUID TANK

UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

AIR POWERED ON/OFF ENGINE FAN CLUTCH

AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

1400 SQUARE INCH VOCATIONAL RADIATOR

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

RADIATOR DRAIN VALVE

LOWER RADIATOR GUARD

NO REPTO, EXTENDED FLYWHEEL HOUSING, CUML9 REQUIRED FOR PACKGING

ELECTRIC GRID AIR INTAKE WARMER

DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH

Transmission

EATON FULLER FRO-16210C TRANSMISSION

Transmission Equipment

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP EATON ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH TORQUE LIMITING CLUTCH BRAKE

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING

HYDRAULIC CLUTCH CONTROL

ALUMINUM CLUTCH HOUSING

NO PTO MOUNTING LOCATION SPECIFIED

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND

DRAIN

PAINTED SHIFT LEVER, SOLID LINKAGE

AIR TO OIL TRANSMISSION COOLER

SYNTHETIC TRANSMISSION LUBE

Front Axle and Equipment

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

CONMET PRESET PLUS PREMIUM ALUMINUM FRONT HUBS

MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

SINGLE POWER STEERING GEAR, BENDIX, 12-13.3K

2 QUART SEE THROUGH POWER STEERING RESERVOIR

CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

12,000# DUAL TAPERLEAF FRONT SUSPENSION MAINTENANCE FREE RUBBER BUSHINGS -FRONT SUSPENSION FRONT SHOCK ABSORBERS

Rear Axle and Equipment

MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

Page 5 of 14

	Description
	CONMET PRESET PLUS PREMIUM ALUMINUM
	REAR HUBS
	4.11 REAR AXLE RATIO
	IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING
	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES
	(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
	NON-ASBESTOS REAR BRAKE LINING
	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)
	GUNITE CAST IRON REAR BRAKE DRUMS
	REAR BRAKE DUST SHIELDS
	REAR OIL SEALS
	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS
	HALDEX AUTOMATIC REAR SLACK ADJUSTERS
	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE
	STANDARD REAR AXLE BREATHER(S)
Rear Suspension	
	TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION
	9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)
	AXLE CLAMPING GROUP
	55 INCH AXLE SPACING
	FORE/AFT AND TRANSVERSE CONTROL RODS
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)
Brake System	
	WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH

WITH ATC SHUT OFF SWITCH

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES

RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE

WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE

WABCO OIL COALESCING FILTER FOR AIR

DRYER

AIR DRYER MOUNTED UNDER HOOD

STEEL AIR BRAKE RESERVOIRS

PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS

PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION

SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME

Wheelbase & Frame

5275MM (208 INCH) WHEELBASE

9.5MM X 89.0MM X 304.0MM STEEL FRAME (0.37X3.50X11.97 INCH) 120 KSI

1825MM (72 INCH) REAR FRAME OVERHANG FRAME OVERHANG RANGE: 71 INCH TO 80 INCH

CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 142.52 in

CALC'D FRAME LENGTH - OVERALL : 324.73 in FRAME HEIGHT TOP FRONT UNLADEN : 41.07 in FRAME HEIGHT TOP FRONT LADEN : 39.05 in FRAME HEIGHT TOP REAR UNLADEN : 42.96 in FRAME HEIGHT TOP REAR LADEN : 40.45 in SQUARE END OF FRAME

STANDARD WEIGHT ENGINE CROSSMEMBER

STANDARD CROSSMEMBER BACK OF

TRANSMISSION

HEAVY DUTY MIDSHIP #1 CROSSMEMBER STANDARD CAST ALUMINUM REARMOST CROSSMEMBER

	Description	
	STANDARD SUSPENSION CROSSMEMBER	
	STANDARD WEIGHT REAR SUSPENSION	
	CROSSMEMBER	
Chassis Equipment		
	UNPOLISHED ALUMINUM WST EQUIPMENT COVERS	
	BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER	
	REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME	
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE	
	CLASS 10.9 THREADED METRIC FASTENERS; REAR SUSPENSION HANGER TO BE HUCK-SPIN	
	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE	
Fuel Tanks		
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH	
	25 INCH DIAMETER FUEL TANK(S)	
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS	
	FUEL TANK(S) FORWARD	
	PLAIN STEP FINISH	
	FUEL TANK CAP(S)	
	EQUIFLO INBOARD FUEL SYSTEM	
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	
Tires		
	CONTINENTAL HSR2 11R22.5 14 PLY RADIAL FRONT TIRES	
	CONTINENTAL HSR2 11R22.5 14 PLY RADIAL REAR TIRES	
Wheels		
	ALCOA LVL ONE 88267X 22.5X8.25 10-HUB PILOT 5.80 INSET ALUMINUM DISC FRONT WHEELS	
	ACCURIDE 29169 22.5X8.25 10-HUB PILOT 5- HAND HD STEEL DISC REAR WHEELS	
	FRONT WHEEL MOUNTING NUTS	
	REAR WHEEL MOUNTING NUTS	
Application Version 11.7.		04/14/2022 10:33 AM

	Description
Cab Exterior	
	111 INCH BBC CONVENTIONAL ALUMINUM CAB
	STAINLESS STEEL CAB ACCENT MOLDING
	FRONT FENDERS
	INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES
	BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN
	X-SERIES STEEL REINFORCED ALUMINUM CAB
	X-SERIES VOCATIONAL HOOD
	HOOD OPENING ASSIST WITH LOCKING STRUT
	WESTERN STAR NAMEPLATES
	DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
	SINGLE ELECTRIC HORN
	REAR LICENSE PLATE MOUNT END OF FRAME
	DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM
	ROOF MOUNTED LED MARKER LIGHTS
	DAYTIME RUNNING LIGHTS
	INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
	LED SIDE TURN SIGNAL
	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
	102 INCH EQUIPMENT WIDTH
	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
	RH DOWN VIEW MIRROR
	STANDARD SIDE/REAR REFLECTORS
	REAR REFLECTIVE DEVICE
	UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER
	SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH
	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

	Description
	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior	
	X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE
	CHARCOAL BLACK VINYL BASE LEVEL INTERIOR
	CARBON WITH BASE BLACK ACCENT
	BLACK MATS
	(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY
	FORWARD ROOF MOUNTED CONSOLE
	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS
	(2) COAT HOOKS ON BACKWALL OF CAB
	DIGITAL ALARM CLOCK IN DRIVER DISPLAY
	STANDARD HEATER PLUMBING
	RADIATOR MOUNTED AIR CONDITIONER CONDENSER
	STANDARD INSULATION
	STANDARD LED CAB LIGHTING
	REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS
	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME
	KEY QUANTITY OF 2
	LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION
	BLACK DOOR HANDLES
	BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT
	BASIC 2.0 HIGH BACK NON SUSPENSION PASSENGER SEAT
	NO SEAT ARMREST
	BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO
	BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH EMBROIDERED LOGO

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN 4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

STOCK TRUCK/UPFIT PACKAGE LVL 1

EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS

ELECTRONIC ACCELERATOR CONTROL

BLACK GAUGE BEZELS

STANDARD CENTER INSTRUMENT PANEL

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

NO ENGINE OIL TEMPERATURE GAUGE

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER

ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

NO PTO CONTROLS

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

NO AM/FM RADIO ANTENNA

POWER AND GROUND WIRING PROVISION OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY RADIO

SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD

HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

ELECTRONIC 2500 RPM TACHOMETER

DETROIT CONNECT PLATFORM HARDWARE

IGNITION SWITCH CONTROLLED ENGINE STOP

FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, CAPPED

HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #3,0N/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #4,ON/OFF LATCHING, 10 AMPS BATTERY POWER

PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY

BW TRACTOR PROTECTION VALVE

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis

	Description	
	TRAILER HAND CONTROL BRAKE VALVE	
	2 INCH TURBO AIR PRESSURE GAUGE	
	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY	
	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS	
	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR	
	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT	
Design		
	PAINT: ONE SOLID COLOR	
Color		
	CAB COLOR A: L0006EY WHITE ELITE EY	
	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT	
	POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)	
Certification / Compliance		
	U.S. FMVSS CERTIFICATION, EXCEPT SALES	

CABS AND GLIDER KITS

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471 Prepared by: Todd Lenhart PIEDMONT TRUCK CENTER, INC. 412 SOUTH REGIONAL ROAD GREENSBORO, NC 27409 Phone: 3366682401

QUOTATION

WESTERN STAR 47X

SET BACK AXLE - TRUCK CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT @ 1200 RPM EATON FULLER FRO-16210C TRANSMISSION MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE 12,000# DUAL TAPERLEAF FRONT SUSPENSION 111 INCH BBC CONVENTIONAL ALUMINUM CAB 5275MM (208 INCH) WHEELBASE 9.5MM X 89.0MM X 304.0MM STEEL FRAME (0.37X3.50X11.97 INCH) 120 KSI 1825MM (72 INCH) REAR FRAME OVERHANG

			PER UNIT	TOTAL
VEHICLE PRICE	TOTAL # OF UNITS (1)	\$	107,547	\$ 107,547
EXTENDED WARRANTY		\$	0	\$ 0
DEALER INSTALLED OPTIONS		\$	0	\$ 0
CUSTOMER PRICE BEFORE TAX		\$	107,547	\$ 107,547
TAXES AND FEES				
TAXES AND FEES		\$	0	\$ 0
OTHER CHARGES		\$	0	\$ 0
TRADE-IN				
TRADE-IN ALLOWANCE		\$	(0)	\$ (0)
BALANCE DUE	(LOCAL CURRENCY)	\$	107,547	\$ 107,547
COMMENTS:				
Projected delivery on / provided the ord	er is received before _	//	·	

APPROVAL:

Please indicate your acceptance of this quotation by signing below:

Customer: X

_ Date: ___ / ___ / ____.

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at <u>www.daimler-truckfinancial.com</u>.

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSB Chassis