Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471

# A proposal for NC SHERIFFS ASSOCIATION

Prepared by **PIEDMONT TRUCK CENTER, INC.** Todd Lenhart

Apr 14, 2022

Western Star 47X

Components shown may not reflect all spec'd options and are not to scale

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis 04/14/2022 10:38 AM

Page 1 of 14

# SPECIFICATION PROPOSAL

	Description
Price Level	
	WST 47X/49X PRL-26X (EFF:07/26/21)
Data Version	
	SPECPRO21 DATA RELEASE VER 043
Vehicle Configurati	on
	WESTERN STAR 47X
	2023 MODEL YEAR SPECIFIED
	SET FORWARD AXLE - TRUCK
	STRAIGHT TRUCK PROVISION, NON-TOWING
	LH PRIMARY STEERING LOCATION
General Service	
	TRUCK CONFIGURATION
	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	PICKUP AND DELIVERY/SHORT HAUL SERVICE
	GOVERNMENT BUSINESS SEGMENT
	GENERAL FREIGHT COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	WESTERN STAR ON-HIGHWAY WARRANTY
	EXPECTED FRONT AXLE(S) LOAD: 12000.0 lbs
	EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs
Truck Service	

#### Truck Service

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

GODWIN MANUFACTURING COMPANY

### Engine

CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT @ 1200 RPM

#### **Electronic Parameters**

75 MPH ROAD SPEED LIMIT

#### **Engine Equipment**

2010 EPA/CARB/GHG21 CONFIGURATION NO 2008 CARB EMISSION CERTIFICATION

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES

BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL

SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB

WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN

UNPOLISHED ALUMINUM WST BATTERY BOX COVER

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM

CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS

RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH

STANDARD EXHAUST SYSTEM LENGTH

RH STANDARD HORIZONTAL TAILPIPE

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

8 GALLON DIESEL EXHAUST FLUID TANK
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR
CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
NO REPTO, EXTENDED FLYWHEEL HOUSING, CUML9 REQUIRED FOR PACKGING
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH

DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH

## Transmission

EATON FULLER FRO-14210C TRANSMISSION

# **Transmission Equipment**

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP EATON ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH TORQUE LIMITING CLUTCH BRAKE

ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING

HYDRAULIC CLUTCH CONTROL

ALUMINUM CLUTCH HOUSING

NO PTO MOUNTING LOCATION SPECIFIED

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

	Description
	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
	PAINTED SHIFT LEVER, SOLID LINKAGE
	AIR TO OIL TRANSMISSION COOLER
	SYNTHETIC TRANSMISSION LUBE
Front Axle and Equip	pment
	DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE
	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS
	MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
	NON-ASBESTOS FRONT BRAKE LINING
	CONMET CAST IRON FRONT BRAKE DRUMS
	FRONT BRAKE DUST SHIELDS
	FRONT OIL SEALS
	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS
	SINGLE POWER STEERING GEAR, BENDIX, 12- 13.3K
	2 QUART SEE THROUGH POWER STEERING RESERVOIR
	CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE
Front Suspension	
	12,000# DUAL TAPERLEAF FRONT SUSPENSION
	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION
	FRONT SHOCK ABSORBERS
Rear Axle and Equip	oment
	MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE
	CONMET PRESET PLUS PREMIUM ALUMINUM REAR HUBS
	4.11 REAR AXLE RATIO
	IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

	Description	
	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES	
	(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES	
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH	
	MERITOR 16.5X7 Q+ CAST SPIDER HEAVY DUTY CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	
	NON-ASBESTOS REAR BRAKE LINING	
	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)	
	GUNITE CAST IRON REAR BRAKE DRUMS	
	REAR BRAKE DUST SHIELDS	
	REAR OIL SEALS	
	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS	
	HALDEX AUTOMATIC REAR SLACK ADJUSTERS	
	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE	
	STANDARD REAR AXLE BREATHER(S)	
Rear Suspension		
	TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION	
	9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)	
	AXLE CLAMPING GROUP	
	55 INCH AXLE SPACING	
	FORE/AFT AND TRANSVERSE CONTROL RODS	
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)	
Brake System		
	WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH	
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES	
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE	
	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER	
Application Version 11	7 206	04/14/2022 10:38 AM

	Description	
	WABCO OIL COALESCING FILTER FOR AIR DRYER	
	AIR DRYER FRAME MOUNTED	
	STEEL AIR BRAKE RESERVOIRS	
	PULL CABLES ON ALL AIR RESERVOIR(S)	
Wheelbase & Frame		
	5490MM (216 INCH) WHEELBASE, SFA ONLY	
	9.5MM X 89.0MM X 304.0MM STEEL FRAME (0.37X3.50X11.97 INCH) 120 KSI	
	1650MM (65 INCH) REAR FRAME OVERHANG	
	FRAME OVERHANG RANGE: 61 INCH TO 70 INCH	
	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 134.65 in	
	CALC'D FRAME LENGTH - OVERALL: 309.96 in	
	FRAME HEIGHT TOP FRONT UNLADEN : 41.14 in	
	FRAME HEIGHT TOP FRONT LADEN: 39.05 in	
	FRAME HEIGHT TOP REAR UNLADEN : 42.96 in	
	FRAME HEIGHT TOP REAR LADEN: 40.45 in	
	SQUARE END OF FRAME	
	STANDARD WEIGHT ENGINE CROSSMEMBER	
	STANDARD CROSSMEMBER BACK OF TRANSMISSION	
	HEAVY DUTY MIDSHIP #1 CROSSMEMBER	
	STANDARD CAST ALUMINUM REARMOST CROSSMEMBER	
	STANDARD SUSPENSION CROSSMEMBER	
	STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER	
<b>Chassis Equipment</b>		
	UNPOLISHED ALUMINUM WST EQUIPMENT COVERS	
	BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER	
	REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME	
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE	
	CLASS 10.9 THREADED METRIC FASTENERS; REAR SUSPENSION HANGER TO BE HUCK-SPIN	
	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE	
Application Version 11.7.	.206	04/14/2022 10:38 AM

Data Version PRL-26X.043 2023 47XSF Chassis

Page 7 of 14

	Description	
Fuel Tanks		
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH	
	25 INCH DIAMETER FUEL TANK(S)	
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS	
	FUEL TANK(S) FORWARD	
	PLAIN STEP FINISH	
	FUEL TANK CAP(S)	
	EQUIFLO INBOARD FUEL SYSTEM	
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	
Tires		
	CONTINENTAL HSR2 11R22.5 14 PLY RADIAL FRONT TIRES	
	CONTINENTAL HSR2 11R22.5 14 PLY RADIAL REAR TIRES	
Wheels		
	ACCURIDE 29169 22.5X8.25 10-HUB PILOT 5- HAND HD STEEL DISC FRONT WHEELS	
	ACCURIDE 51487 ACCU-LITE 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS	
	FRONT WHEEL MOUNTING NUTS	
	REAR WHEEL MOUNTING NUTS	
Cab Exterior		
	111 INCH BBC CONVENTIONAL ALUMINUM CAB	
	STAINLESS STEEL CAB ACCENT MOLDING	
	FRONT FENDERS	
	INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES	
	BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN	
	X-SERIES STEEL REINFORCED ALUMINUM CAB	
	X-SERIES VOCATIONAL HOOD	
	HOOD OPENING ASSIST WITH LOCKING STRUT	
	WESTERN STAR NAMEPLATES	
	DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS	
Application Version 11.7	.206	04/14/2022 10:38 AM
Data Version PRL-26X.0	43	<b>_</b>

2023 47XSF Chassis

	Description
	SINGLE ELECTRIC HORN
	REAR LICENSE PLATE MOUNT END OF FRAME
	DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM
	ROOF MOUNTED LED MARKER LIGHTS
	DAYTIME RUNNING LIGHTS
	INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
	LED SIDE TURN SIGNAL
	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
	102 INCH EQUIPMENT WIDTH
	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
	RH DOWN VIEW MIRROR
	STANDARD SIDE/REAR REFLECTORS
	REAR REFLECTIVE DEVICE
	UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER
	SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH
	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD
	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior	
	X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE
	CHARCOAL BLACK VINYL BASE LEVEL INTERIOR
	CARBON WITH BASE BLACK ACCENT
	BLACK MATS
	(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY
	FORWARD ROOF MOUNTED CONSOLE
	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS
	(2) COAT HOOKS ON BACKWALL OF CAB
	DIGITAL ALARM CLOCK IN DRIVER DISPLAY
	STANDARD HEATER PLUMBING

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

RADIATOR MOUNTED AIR CONDITIONER CONDENSER STANDARD INSULATION STANDARD LED CAB LIGHTING

REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS

DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME

**KEY QUANTITY OF 2** 

LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION

#### BLACK DOOR HANDLES

BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT

BASIC 2.0 HIGH BACK NON SUSPENSION PASSENGER SEAT

NO SEAT ARMREST

BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH EMBROIDERED LOGO

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES

DRIVER AND PASSENGER INTERIOR SUN VISORS

## **Instruments & Controls**

STOCK TRUCK/UPFIT PACKAGE LVL 1 EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS

ELECTRONIC ACCELERATOR CONTROL

BLACK GAUGE BEZELS

STANDARD CENTER INSTRUMENT PANEL

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

NO ENGINE OIL TEMPERATURE GAUGE

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER

ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

NO PTO CONTROLS

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

NO AM/FM RADIO ANTENNA

POWER AND GROUND WIRING PROVISION OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY RADIO

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis

Description
SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #3,ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #4,ON/OFF LATCHING, 10 AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS
ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT

#### PAINT: ONE SOLID COLOR

# Color

Design

CAB COLOR A: L0006EY WHITE ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis 04/14/2022 10:38 AM

Page 12 of 14

Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471

Description

POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

# **Certification / Compliance**

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

04/14/2022 10:38 AM

Page 13 of 14

Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471 Prepared by: Todd Lenhart PIEDMONT TRUCK CENTER, INC. 412 SOUTH REGIONAL ROAD GREENSBORO, NC 27409 Phone: 3366682401

# QUOTATION

## WESTERN STAR 47X

SET FORWARD AXLE - TRUCK CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT @ 1200 RPM EATON FULLER FRO-14210C TRANSMISSION MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE 12,000# DUAL TAPERLEAF FRONT SUSPENSION 111 INCH BBC CONVENTIONAL ALUMINUM CAB 5490MM (216 INCH) WHEELBASE, SFA ONLY 9.5MM X 89.0MM X 304.0MM STEEL FRAME (0.37X3.50X11.97 INCH) 120 KSI 1650MM (65 INCH) REAR FRAME OVERHANG

			PER UNIT	TOTAL
VEHICLE PRICE	TOTAL # OF UNITS (1)	\$	106,527	\$ 106,527
EXTENDED WARRANTY		\$	0	\$ 0
DEALER INSTALLED OPTIONS		\$	0	\$ 0
CUSTOMER PRICE BEFORE TAX		\$	106,527	\$ 106,527
TAXES AND FEES				
TAXES AND FEES		\$	0	\$ 0
OTHER CHARGES		\$	0	\$ 0
TRADE-IN				
TRADE-IN ALLOWANCE		\$	(0)	\$ (0)
BALANCE DUE	(LOCAL CURRENCY)	\$	106,527	\$ 106,527
COMMENTS:				
Projected delivery on / / provid	ded the order is received before	/	/	

APPROVAL:

Please indicate your acceptance of this quotation by signing below:

Customer: X

Date: \_\_\_ / \_\_\_ / \_\_\_.

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at <u>www.daimler-truckfinancial.com</u>.

Application Version 11.7.206 Data Version PRL-26X.043 2023 47XSF Chassis