Prepared for: Kaylyn Mitman NC SHERIFFS ASSOCIATION PO BOX 20049 RALEIGH, NC 27619 Phone: 919-459-6471 Prepared by: Todd Lenhart PIEDMONT TRUCK CENTER, INC. 412 SOUTH REGIONAL ROAD GREENSBORO, NC 27409 Phone: 3366682401

# A proposal for NC SHERIFFS ASSOCIATION

Prepared by **PIEDMONT TRUCK CENTER, INC.** Todd Lenhart

Apr 22, 2021

# Western Star 49X



Components shown may not reflect all spec'd options and are not to scale

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis 04/22/2021 11:38 AM

Page 1 of 15

# SPECIFICATION PROPOSAL

	Description
Price Level	
	WST 49X STAR PRL-24X (EFF:01/19/21)
Data Version	
	SPECPRO21 DATA RELEASE VER 009
Vehicle Configuration	on
	WESTERN STAR 49X
	2022 MODEL YEAR SPECIFIED
	SET BACK AXLE - TRACTOR
	TRAILER TOWING PROVISION FORWARD OF FIFTH WHEEL
	LH PRIMARY STEERING LOCATION
General Service	
	TRACTOR/TRAILER CONFIGURATION
	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	PICKUP AND DELIVERY/SHORT HAUL SERVICE
	GOVERNMENT BUSINESS SEGMENT
	GENERAL FREIGHT COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	WESTERN STAR ON-HIGHWAY WARRANTY
	EXPECTED FRONT AXLE(S) LOAD: 12000.0 lbs
	EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

	Description
Truck Service	
	NO MFR'S/BODY TYPE IDENTIFICATION
Tractor Service	
	VAN TRAILER
	SINGLE (1) TRAILER
Engine	
	CUM X12 350 HP @ 1800 RPM, 1350 LB-FT @ 1000 RPM, 1800 GOV RPM
Engine Equipment	
	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG21 CONFIGURATION
	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)
	ENGINE MOUNTED OIL CHECK AND FILL
	SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER
	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
	(3) DTNA GENUINE, HIGH TEMP AGM STARTING AND CYCLING, MIN 2775CCA, 570RC, THREADED STUD BATTERIES
	PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE OF CAB
	BATTERY BOX MOUNTED UNDER PASSENGER SEAT
	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN
	PLASTIC BATTERY BOX COVER
	CUMMINS NATURALLY ASPIRATED 25.9 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE
	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM
	CUMMINS INTEBRAKE BRAKE WITH HIGH MED LOW BRAKE
	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP
23 GALLON DIESEL EXHAUST FLUID TANK
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD
AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR
CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
NO AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED

# Transmission

# EATON FULLER FRO-16210C TRANSMISSION

MAGNETIC SWITCH

# **Transmission Equipment**

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP EATON ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis 04/22/2021 11:38 AM

Page 4 of 15

TORQUE LIMITING CLUTCH BRAKE ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING HYDRAULIC CLUTCH CONTROL ALUMINUM CLUTCH HOUSING

NO PTO MOUNTING LOCATION SPECIFIED

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

PAINTED SHIFT LEVER, SOLID LINKAGE

AIR TO OIL TRANSMISSION COOLER

SYNTHETIC TRANSMISSION LUBE

## **Front Axle and Equipment**

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

CONMET PRESET PLUS PREMIUM ALUMINUM FRONT HUBS

MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

2011/2013-FMVSS 121 RSD FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

SINGLE POWER STEERING GEAR, BENDIX, 12-13.3K

2 QUART SEE THROUGH POWER STEERING RESERVOIR

CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE

# **Front Suspension**

12,000# DUAL TAPERLEAF FRONT SUSPENSION MAINTENANCE FREE RUBBER BUSHINGS -FRONT SUSPENSION FRONT SHOCK ABSORBERS

# **Rear Axle and Equipment**

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

	DETROIT DA-RT-40.0-4S HH 40,000# R-SERIES TANDEM REAR AXLE
	CONMET PRESET PLUS PREMIUM ALUMINUM REAR HUBS
	3.58 REAR AXLE RATIO
	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING
	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES
	(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH WITH IAD FEEDBACK
	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
	2011/2013-FMVSS 121 RSD REAR BRAKE LININGS
	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS
	GUNITE CAST IRON REAR BRAKE DRUMS
	REAR BRAKE DUST SHIELDS
	REAR OIL SEALS
	WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS
	MERITOR AUTOMATIC REAR SLACK ADJUSTERS
	FE 75W-85 REAR AXLE LUBE
	STANDARD REAR AXLE BREATHER(S)
• • • •	

# **Rear Suspension**

AIRLINER 40,000# REAR SUSPENSION

7.9 INCH NOMINAL RIDE HEIGHT (415MM GLOBAL REFERENCE HEIGHT)

STANDARD AXLE SEATS IN AXLE CLAMP GROUP

51 INCH AXLE SPACING

IGNITION CONTROLLED ELECTRIC DUMP SWITCH FOR AIR SUSPENSION WITH STATE RETENTION AND GAUGE

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

	Description
	Description REAR AIR SUSPENSION DUMP VALVE AUTOFILL
	>5 MPH WITH INDICATOR LIGHT
	SINGLE AIR REAR SUSPENSION LEVELING VALVE
	TRANSVERSE CONTROL RODS
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)
Brake System	
	WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
	WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE
	WABCO OIL COALESCING FILTER FOR AIR DRYER
	AIR DRYER MOUNTED UNDER HOOD
	STEEL AIR BRAKE RESERVOIRS
	PULL CABLES ON ALL AIR RESERVOIR(S)
<b>Trailer Connections</b>	
	12 FOOT STRAIGHT TRAILER AIR HOSE
	36 INCH STAINLESS STEEL SLIDE BAR WITH SPRING TYPE AIR HOSE HANGER
	COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER MOUNTED LH BACK OF CAB WITH GROUND ACCESS
	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED BACK OF CAB/BACK OF SLEEPER
	NO ADDITIONAL TRAILER CABLE RECEPTACLE
	INBOARD FLAG BRACKET LOCATED AT BACK OF CAB/BACK OF SLEEPER
	12 FOOT DETACHABLE STRAIGHT PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR
Wheelbase & Frame	
	4575MM (180 INCH) WHEELBASE

4575MM (180 INCH) WHEELBASE

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

8.0MM X 82.0MM X 281.0MM STEEL FRAME (0.32X3.23X11.06 INCH) 120 KSI 1475MM (58 INCH) REAR FRAME OVERHANG FRAME OVERHANG RANGE: 51 INCH TO 60 INCH CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 105.12 in CALC'D FRAME LENGTH - OVERALL: 282.78 FRAME HEIGHT TOP FRONT UNLADEN: 40.69 in FRAME HEIGHT TOP FRONT LADEN: 38.73 in FRAME HEIGHT TOP REAR UNLADEN: 40.05 in FRAME HEIGHT TOP REAR LADEN: 38.48 in FLANGE TAPERED END OF FRAME, GRIND AND POLISH WELDS STANDARD CROSSMEMBER BACK OF TRANSMISSION STANDARD MIDSHIP #1 CROSSMEMBER(S) STANDARD REARMOST CROSSMEMBER STANDARD SUSPENSION CROSSMEMBER

STANDARD WEIGHT REAR SUSPENSION

CROSSMEMBER

### **Chassis Equipment**

UNPOLISHED ALUMINUM WST EQUIPMENT COVERS

LH BACK OF CAB ACCESS, GRAB HANDLES WITH SINGLE RUBBER INSERT

14 INCH (350MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS

BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER

REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME

BUMPER MOUNTING FOR SINGLE LICENSE PLATE

BETTS B-23 PAINTED COILED MUDFLAP BRACKETS

WESTERN STAR LOGO BLACK MUDFLAPS

CLASS 10.9 THREADED METRIC FASTENERS; REAR SUSPENSION HANGER TO BE HUCK-SPIN

EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE NO TOOL/STORAGE BOX #1 MOUNTING LOCATION

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

	Description
	NO TOOL/STORAGE BOX #2 MOUNTING
	LOCATION
	NO TIRE PRESSURE CONTROL/SENSOR
	CHASSIS,MISC CUSTOM REQUIREMENTS-NONE
	NO ADDITIONAL LH MID-CHASSIS ROUTING & CLIPPING BRACKETS
	NO ADDITIONAL RH MID-CHAS ROUTING & CLIPPING BRACKETS
Fifth Wheel	
	FONTAINE 6000 SERIES 6NWB 24.0 INCH AIR SLIDE FIFTH WHEEL
	FIFTH WHEEL 305MM (12.0 INCHES) AHEAD OF SUSPENSION CENTERLINE
	197MM (7.75 INCH) FIFTH WHEEL HEIGHT
	STEEL OUTBOARD ANGLE - FIFTH WHEEL MOUNTING
	DASH MOUNTED CONTROL AND PLUMBING FOR FIFTH WHEEL
	SIDE LEFT FIFTH WHEEL RELEASE
	NO FIFTH WHEEL RAMP
Fuel Tanks	
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
	25 INCH DIAMETER FUEL TANK(S)
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS
	FUEL TANK(S) FORWARD
	PLAIN STEP FINISH
	FUEL TANK CAP(S)
	EQUIFLO INBOARD FUEL SYSTEM
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
	NO FUEL COOLER
Tires	
	BRIDGESTONE R284 ECOPIA 11R22.5 14 PLY RADIAL FRONT TIRES
	CONTINENTAL HDL2 11R22.5 14 PLY RADIAL REAR TIRES
Wheels	

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

ALCOA LVL ONE 88267X 22.5X8.25 10-HUB PILOT 5.80 INSET ALUMINUM DISC FRONT WHEELS
ACCURIDE 51487 ACCU-LITE 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS
NO SPARE WHEEL
NO ADDITIONAL SPARE WHEEL

NO POLISHED, BRIGHT STANDARD POLISH, BRUSHED OR BRIGHT LVL ONE SPARE WHEEL

# **Cab Exterior**

121 INCH BBC ALUMINUM CONVENTIONAL CAB

STAINLESS STEEL CAB ACCENT MOLDING

NO BAGGAGE DOOR

NO SLEEPER DOOR

FRONT FENDERS

INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES

BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN

X-SERIES STEEL REINFORCED ALUMINUM CAB

X-SERIES VOCATIONAL HOOD

HOOD OPENING ASSIST WITH LOCKING STRUT

WESTERN STAR NAMEPLATES

DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS

SINGLE ELECTRIC HORN

DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME

**KEY QUANTITY OF 2** 

REAR LICENSE PLATE MOUNT END OF FRAME

DUAL STAGE INTELLIGENT LED HEADLIGHTS ROOF MOUNTED LED MARKER LIGHTS

DAYTIME RUNNING LIGHTS

INTEGRAL LED STOP/TAIL/BACKUP LIGHTS

LED SIDE TURN SIGNAL

NO LOAD LOCK CARRIERS

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

	Description
	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
	102 INCH EQUIPMENT WIDTH
	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
	RH DOWN VIEW MIRROR
	STANDARD SIDE/REAR REFLECTORS
	REAR REFLECTIVE DEVICE
	REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS
	UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER
	NO SLEEPER VENT
	SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH
	NO SIDE SLEEPER CAP WINDOWS
	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD
	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior	
	X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE
	CHARCOAL BLACK VINYL BASE LEVEL INTERIOR
	CARBON WITH BASE BLACK ACCENT
	BLACK MATS
	(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY
	FORWARD ROOF MOUNTED CONSOLE
	NO AUX ELECTRICAL VAULT CLEAR SPACE REQUEST
	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS
	(2) COAT HOOKS ON BACKWALL OF CAB
	DIGITAL ALARM CLOCK IN DRIVER DISPLAY
	NO CUP/THERMOS HOLDER
	NO FIRE EXTINGUISHER
	STANDARD HEATER PLUMBING

RADIATOR MOUNTED AIR CONDITIONER CONDENSER

STANDARD INSULATION

NO BAGGAGE COMPARTMENT LIGHT

STANDARD LED CAB LIGHTING

### NO SLEEPER INTERIOR LAMP

LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION

# BLACK DOOR HANDLES

NO AC 120V CAB WIRING AND AC OUTLET

BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT

BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT

NO SEAT ARMREST

BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH EMBROIDERED LOGO

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS

NO SUPPLEMENTAL RESTRAINT SYSTEM

4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES DRIVER AND PASSENGER INTERIOR SUN

VISORS

## **Instruments & Controls**

STOCK TRUCK/UPFIT PACKAGE LVL 1

DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY

EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS

ELECTRONIC ACCELERATOR CONTROL

STANDARD CENTER INSTRUMENT PANEL

BLACK GAUGE BEZELS

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH CAPS

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

ENGINE OIL TEMPERATURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER

ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

NO PTO CONTROLS

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

ELECTRIC ENGINE OIL PRESSURE GAUGE

BLUETOOTH, USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

AM/FM ANTENNA MOUNTED ON RH SIDE MIRROR

POWER AND GROUND WIRING PROVISION OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY RADIO

SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD NO ANTENNA-RADIO,UHF/VHF

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

NO TELEVISION ANTENNA/PROVISION ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

ELECTRONIC 2500 RPM TACHOMETER

DETROIT CONNECT PLATFORM HARDWARE

TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL IGNITION SWITCH CONTROLLED ENGINE STOP

FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, CAPPED

HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #3,0N/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #4,ON/OFF LATCHING, 10 AMPS BATTERY POWER

NO SW RCPTS & WRG, ALTN CSL LOC PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY

BW TRACTOR PROTECTION VALVE

TRAILER HAND CONTROL BRAKE VALVE

2 INCH TURBO AIR PRESSURE GAUGE

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY

SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY

ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS

TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR

SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT

### Design

PAINT: ONE SOLID COLOR

#### Color

CAB COLOR A: L0006EY WHITE ELITE EY

Application Version 11.6.103 Data Version PRL-24X.009 2021 49XSB Chassis

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

**Certification / Compliance** 

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.